

Package ‘SQLove’

April 17, 2025

Title Execute 'SQL' Scripts in 'R' Containing Multiple Queries

Version 1.0.2

Description The nature of working with structured query language ('SQL') scripts efficiently often requires the creation of temporary tables and there are few clean and simple 'R' 'SQL' execution approaches that allow you to complete this kind of work with the 'R' environment. This package seeks to give 'SQL' implementations in 'R' a little love by deploying functions that allow you to deploy complex 'SQL' scripts within a typical 'R' workflow.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.3

Imports DBI, readr, RJDBC, odbc

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Kerns Sam [aut, cre]

Maintainer Kerns Sam <samwkerns@gmail.com>

Repository CRAN

Date/Publication 2025-04-17 06:40:01 UTC

Contents

dbGetMultiQuery	2
dbSendMultiUpdate	2
Index	4

dbGetMultiQuery	<i>Query a database with multiple query actions and one, final, select statement.</i>
-----------------	---

Description

Requires a DBI workflow that creates a connection with a relational database per DBI: <https://dbi.r-dbi.org/>. This function is an extension of the `DBI::dbGetQuery` and `RJDBC::dbSendUpdate` functions.

Usage

```
dbGetMultiQuery(conn, conn_type = "JDBC", sql_path, pattern = NULL, replacement = NULL)
```

Arguments

conn	A database connection object
conn_type	A string indicating if the connection type is a JDBC or ODBC connection - accepts "JDBC" or "ODBC" as arguments, defaults to "JDBC"
sql_path	Character vector pointing to SQL script
pattern	A character object you would like to substitute in the SQL script - this is not required and defaults to NULL. Calls <code>gsub</code> under the hood, so use regex for pattern identification. You may provide a single string or a vector of strings equal in length to the vector of strings in the replacement field.
replacement	A character vector replacing the pattern specified - this is not required and defaults to NULL. Calls <code>gsub</code> under the hood, so use regex for pattern identification. You may provide a single string or a vector of strings equal in length to the vector of strings in the replacement field.

Value

A data object

dbSendMultiUpdate	<i>Run multiple SQL query actions within the DB environment.</i>
-------------------	--

Description

Requires a DBI workflow that creates a connection with a relational database per DBI: <https://dbi.r-dbi.org/>. This function is an extension of the `RJDBC::dbSendUpdate` function.

Usage

```
dbSendMultiUpdate(conn, conn_type = "JDBC", sql_path)
```

Arguments

conn	A database connection object
conn_type	A string indicating if the connection type is a JDBC or ODBC connection - accepts "JDBC" or "ODBC" as arguments, defaults to "JDBC"
sql_path	Character vector pointing to SQL script

Value

No object returned - for production automation

Index

dbGetMultiQuery, [2](#)
dbSendMultiUpdate, [2](#)