

# Package ‘TensorComplete’

May 11, 2021

**Type** Package

**Title** Tensor Noise Reduction and Completion Methods

**Version** 0.1.0

**Author** Chanwoo Lee <chanwoo.lee@wisc.edu>, Miaoyan Wang <miaoyan.wang@wisc.edu>

**Maintainer** Chanwoo Lee <chanwoo.lee@wisc.edu>

**Imports** pracma, methods, utils, tensorregress, MASS

**Description** Efficient algorithms for tensor noise reduction and completion. This package includes a suite of parametric and nonparametric tools for estimating tensor signals from noisy, possibly incomplete observations. The methods allow a broad range of data types, including continuous, binary, and ordinal-valued tensor entries. The algorithms employ the alternating optimization. The detailed algorithm description can be found in the following three references.

**URL** Chanwoo Lee and Miaoyan Wang. Tensor denoising and completion based on ordinal observations. ICML, 2020.

<http://proceedings.mlr.press/v119/lee20i.html> Chanwoo Lee and Miaoyan Wang. Beyond the Signs: Nonparametric tensor completion via sign series. 2021. <https://arxiv.org/abs/2102.00384>  
Chanwoo Lee, Lexin Li, Hao Helen Zhang, and Miaoyan Wang. Nonparametric trace regression in high dimensions via sign series representation. 2021. <https://arxiv.org/abs/2105.01783>

**License** GPL (>= 2)

**Encoding** UTF-8

**RoxygenNote** 7.1.1

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2021-05-11 14:52:15 UTC

## R topics documented:

Altopt . . . . .	2
bic . . . . .	3
fit_continuous_cp . . . . .	4

fit_continuous_tucker . . . . .	5
fit_nonparaT . . . . .	6
fit_ordinal . . . . .	7
likelihood . . . . .	8
predict_ordinal . . . . .	9
realization . . . . .	10

<b>Index</b>	<b>11</b>
--------------	-----------

---

Altopt	<i>Alternating optimization of the weighted classification loss</i>
--------	---

---

### Description

Optimize the weighted classification loss given a weight tensor, an observed data tensor, and a large margin loss. This function is used as a subroutine in the main function `fit_nonparaT`.

### Usage

```
Altopt(Ybar,W,r,type = c("logistic","hinge"),start = "linear")
```

### Arguments

<code>Ybar</code>	A given (possibly noisy and incomplete) data tensor.
<code>W</code>	A weight tensor used in the weighted classification loss.
<code>r</code>	A rank to be fitted (CP rank).
<code>type</code>	A large margin loss to be used. Logistic or hinge loss is available.
<code>start</code>	Choice of initialization method. Use random initialization if <code>start = "random"</code> ; Use the initialization based on low rank approximation if <code>start = "linear"</code> . Linear initialization is default.

### Value

The returned object is a list of components.

`binary_obj` - Trajectory of binary loss values over iterations.

`obj` - Trajectory of weighted classification loss values over iterations.

`iter` - The number of iterations.

`error` - Trajectory of errors over iterations.

`fitted` - A tensor that optimizes the weighted classification loss.

### References

C. Lee and M. Wang. Beyond the Signs: Nonparametric Tensor Completion via Sign Series. *arXiv preprint arXiv:2102.00384*, 2021.

**Examples**

```

library(tensorregress)
indices = c(2,3,4)
noise = rand_tensor(indices)@data
Theta = array(runif(prod(indices),min=-3,max = 3),indices)

# The signal plus noise model
Y = Theta + noise

# Optimize the weighted classification for given a sign tensor sign(Y) and a weight tensor abs(Y)
result = Altopt(sign(Y),abs(Y),r = 3,type = "hinge",start = "linear")
signTheta = sign(result$fitted)

```

---

**bic**
*Bayesian Information Criterion (BIC) value.*


---

**Description**

Compute Bayesian Information Criterion (BIC) given a parameter tensor, an observed tensor, the dimension, and the rank based on cumulative logistic model. This BIC function is designed for selecting rank in the `fit_ordinal` function.

**Usage**

```
bic(ttnsr, theta, omega, d, r)
```

**Arguments**

<code>ttnsr</code>	An observed tensor.
<code>theta</code>	A continuous-valued tensor (latent parameters).
<code>omega</code>	The cut-off points.
<code>d</code>	Dimension of the tensor.
<code>r</code>	Rank of the tensor.

**Value**

BIC value at given inputs based on cumulative logistic model.

---

fit_continuous_cp	<i>Signal tensor estimation from a noisy and incomplete data tensor based on CP low rank tensor method.</i>
-------------------	---

---

## Description

Estimate a signal tensor from a noisy and incomplete data tensor using CP low rank tensor method.

## Usage

```
fit_continuous_cp(data,r)
```

## Arguments

data	A given (possibly noisy and incomplete) data tensor.
r	A rank to be fitted (CP rank).

## Value

The returned object is a list of components.

est - An estimated signal tensor based on CP low rank tensor method.

U - A list of factor matrices.

lambda - A vector of tensor singular values.

## Examples

```
library(tensorregress)
indices = c(2,3,4)
noise = rand_tensor(indices)@data
Theta = array(runif(prod(indices),min=-3,max = 3),indices)

# The signal plus noise model
Y = Theta + noise

# Estimate Theta from CP low rank tensor method
hatTheta = fit_continuous_cp(Y,3)
print(hatTheta$est)
```

---

fit\_continuous\_tucker *Signal tensor estimation from a noisy and incomplete data tensor based on the Tucker model.*

---

### Description

Estimate a signal tensor from a noisy and incomplete data tensor using the Tucker model.

### Usage

```
fit_continuous_tucker(ttnsr,r,alpha = TRUE)
```

### Arguments

ttnsr	A given (possibly noisy and incomplete) data tensor.
r	A rank to be fitted (Tucker rank).
alpha	A signal level
	alpha = TRUE If the signal level is unknown.

### Value

A list containing the following:

- C - An estimated core tensor.
- A - Estimated factor matrices.
- iteration - The number of iterations.
- cost - Log-likelihood value at each iteration.

### Examples

```
# Latent parameters
library(tensorregress)
alpha = 10
A_1 = matrix(runif(15*2,min=-1,max=1),nrow = 15)
A_2 = matrix(runif(15*2,min=-1,max=1),nrow = 15)
A_3 = matrix(runif(15*2,min=-1,max=1),nrow = 15)
C = as.tensor(array(runif(2^3,min=-1,max=1),dim = c(2,2,2)))
theta = ttm(ttm(ttm(C,A_1,1),A_2,2),A_3,3)@data
theta = alpha*theta/max(abs(theta))
adj = mean(theta)
theta = theta-adj
omega = c(-0.2,0.2)+adj

# Observed tensor
ttnsr <- realization(theta,omega)@data

# Estimation of parameters
continuous_est = fit_continuous_tucker(ttnsr,c(2,2,2),alpha = 10)
```

---

fit_nonparaT	<i>Main function for nonparametric tensor estimation and completion based on low sign rank model.</i>
--------------	---

---

### Description

Estimate a signal tensor from a noisy and incomplete data tensor using nonparametric tensor method via sign series.

### Usage

```
fit_nonparaT(Y, truer, H, Lmin, Lmax, option = 2)
```

### Arguments

Y	A given (possibly noisy and incomplete) data tensor. The function allows both continuous- and binary-valued tensors. Missing value should be encoded as NA.
truer	Sign rank of the signal tensor.
H	Resolution parameter.
Lmin	Minimum value of the signal tensor (or minimum value of the tensor Y).
Lmax	Maximum value of the signal tensor (or maximum value of the tensor Y).
option	A large margin loss to be used. Use logistic loss if option = 1, hinge loss if option = 2. Hinge loss is default.

### Value

The returned object is a list of components.

fitted - A series of optimizers that minimize the weighted classification loss at each level.

est - An estimated signal tensor based on nonparametric tensor method via sign series.

### References

C. Lee and M. Wang. Beyond the Signs: Nonparametric Tensor Completion via Sign Series. *arXiv preprint arXiv:2102.00384*, 2021.

### Examples

```
library(tensorregress)
indices = c(2,2,2)
noise = rand_tensor(indices)@data
Theta = array(runif(prod(indices),min=-2,max = 2),indices)

# The signal plus noise model
Y = Theta + noise

# Estimate Theta from nonparametric completion method via sign series
```

```
hatTheta = fit_nonparaT(Y,truer = 2,H = 2,Lmin = -2,Lmax = 2, option =2)
print(hatTheta$est)
```

---

fit_ordinal	<i>Main function for parametric tensor estimation and completion based on ordinal observations.</i>
-------------	---

---

## Description

Estimate a signal tensor from a noisy and incomplete ordinal-valued tensor using the cumulative logistic model.

## Usage

```
fit_ordinal(ttnsr,r,omega=TRUE,alpha = TRUE)
```

## Arguments

ttnsr	A given (possibly noisy and incomplete) data tensor. The function allows binary- and ordinal-valued tensors. Missing value should be encoded as NA.
r	A rank to be fitted (Tucker rank).
omega	The cut-off points if known, omega = TRUE if unknown.
alpha	A signal level alpha = TRUE if the signal level is unknown.

## Value

A list containing the following:

- C - An estimated core tensor.
- A - Estimated factor matrices.
- theta - An estimated latent parameter tensor.
- iteration - The number of iterations.
- cost - Log-likelihood value at each iteration.
- omega - Estimated cut-off points.

## References

C. Lee and M. Wang. Tensor denoising and completion based on ordinal observations. *International Conference on Machine Learning (ICML)*, 2020.

**Examples**

```

# Latent parameters
library(tensorregress)
alpha = 10
A_1 = matrix(runif(15*2,min=-1,max=1),nrow = 15)
A_2 = matrix(runif(15*2,min=-1,max=1),nrow = 15)
A_3 = matrix(runif(15*2,min=-1,max=1),nrow = 15)
C = as.tensor(array(runif(2^3,min=-1,max=1),dim = c(2,2,2)))
theta = ttm(ttm(ttm(C,A_1,1),A_2,2),A_3,3)@data
theta = alpha*theta/max(abs(theta))
adj = mean(theta)
theta = theta-adj
omega = c(-0.2,0.2)+adj

# Observed tensor
ttnsr <- realization(theta,omega)@data

# Estimation of parameters
ordinal_est = fit_ordinal(ttnsr,c(2,2,2),omega = TRUE,alpha = 10)

```

likelihood

*Log-likelihood function (cost function).***Description**

Return log-likelihood function (cost function) value evaluated at a given parameter tensor, an observed tensor, and cut-off points.

**Usage**

```
likelihood(ttnsr,theta,omega,type = c("ordinal","Gaussian"))
```

**Arguments**

ttnsr	An observed tensor data.
theta	A continuous-valued tensor (latent parameters).
omega	The cut-off points.
type	Types of log-likelihood function. "ordinal" specifies log-likelihood function based on the cumulative logistic model. "Gaussian" specifies log-likelihood function based on the Gaussian model.

**Value**

Log-likelihood value at given inputs.



---

predict_ordinal	<i>Predict ordinal-valued tensor entries from the cumulative logistic model.</i>
-----------------	--

---

### Description

Predict ordinal-valued tensor entries given latent parameters and a type of estimations.

### Usage

```
predict_ordinal(theta,omega,type = c("mode","mean","median"))
```

### Arguments

theta	A continuous-valued tensor (latent parameters).
omega	The cut-off points.
type	Type of estimations: "mode" specifies argmax based label estimation. "mean" specifies mean based label estimation. "median" specifies median based label estimation.

### Value

A predicted ordinal-valued tensor given latent parameters and a type of estimations.

### References

C. Lee and M. Wang. Tensor denoising and completion based on ordinal observations. *International Conference on Machine Learning (ICML)*, 2020.

### Examples

```
indices <- c(10,20,30)
arr <- array(runif(prod(indices),-2,2),dim = indices)
b <- c(-1.5,0,1.5)
r_predict <- predict_ordinal(arr,b,type = "mode");r_predict
```

---

realization	<i>An ordinal-valued tensor randomly simulated from the cumulative model.</i>
-------------	---

---

**Description**

Simulate an ordinal-valued tensor from the cumulative logistic model with the parameter tensor and the cut-off points.

**Usage**

```
realization(theta,omega)
```

**Arguments**

theta	A continuous-valued tensor (latent parameters).
omega	The cut-off points.

**Value**

An ordinal-valued tensor randomly simulated from the cumulative logistic model.

**References**

C. Lee and M. Wang. Tensor denoising and completion based on ordinal observations. *International Conference on Machine Learning (ICML)*, 2020.

**Examples**

```
indices <- c(10,20,30)
arr <- array(runif(prod(indices)),dim = indices)
b <- qnorm((1:3)/4)
r_sample <- realization(arr,b);r_sample
```

# Index

Altopt, [2](#)

bic, [3](#)

fit\_continuous\_cp, [4](#)

fit\_continuous\_tucker, [5](#)

fit\_nonparaT, [6](#)

fit\_ordinal, [7](#)

likelihood, [8](#)

predict\_ordinal, [9](#)

realization, [10](#)