

Package ‘pkgmaker’

October 20, 2020

Type Package

Title Development Utilities for R Packages

Version 0.32.2

Date 2020-10-20

Description Provides some low-level utilities to use for package development. It currently provides managers for multiple package specific options and registries, vignette, unit test and bibtex related utilities. It serves as a base package for packages like NMF, RcppOctave, doRNG, and as an incubator package for other general purposes utilities, that will eventually be packaged separately. It is still under heavy development and changes in the interface(s) are more than likely to happen.

License GPL (>= 2)

URL <https://renozao.github.io/pkgmaker/>

BugReports <https://github.com/renozao/pkgmaker/issues>

LazyLoad yes

Encoding UTF-8

Depends R (>= 3.0.0), methods, stats, registry

Imports tools, grDevices, utils, graphics, codetools, digest, stringr, xtable, withr, assertthat

Suggests devtools (>= 0.8), roxygen2, RUnit, testthat, knitr, rmarkdown, markdown, yaml, Biobase, datasets, rbibutils (>= 1.3)

Collate 'bibtex.R' 'colors.R' 'data.R' 'namespace.R' 'utils.R' 'devutils.R' 'files.R' 'graphics.R' 'options.R' 'logging.R' 'unitTests.R' 'is.R' 'knitr.R' 'registry.R' 'package-extra.R' 'package.R' 'packages.R' 'project.R' 'rd.R' 'user.R' 'vignette.R' 'with.r'

RoxygenNote 7.1.0

NeedsCompilation no

Author Renaud Gaujoux [aut, cre]

Maintainer Renaud Gaujoux <renozao@protonmail.com>

Repository CRAN

Date/Publication 2020-10-20 21:20:02 UTC

R topics documented:

.silenceF	4
addnames	5
addToLogger	6
add_lib	6
alphacol	7
askUser	8
bibtex	9
cgetAnywhere	10
charmap	10
checkWarning	11
citecmd	11
compile_src	12
CRAN	12
digest_function	13
exitCheck	13
expand_list	14
ExposeAttribute	16
extractLocalFun	17
factor2character	17
file_extension	18
find_devpackage	18
getLoadingNamespace	19
gfile	20
graphics-utils	20
hasArg2	21
hasEnvar	22
inSweave	22
irequire	23
isCRANcheck	24
is_package_path	25
is_something	26
iterCount	27
knit_ex	28
latex_preamble	30
list.data	32
list.libs	33
load_all_file	34
load_project	34
lverbose	35
makeFakeVignette	37

makeUnitVignette	37
make_vignette_auxfiles	38
messagef	38
mkoptions	39
new2	40
oneoffVariable	41
onLoad	42
option_symlink	43
orderVersion	44
packageData	45
packageEnv	46
packageReference	48
packageRegistry	48
packageTestEnv	51
parsePackageCitation	51
pkgmaker-deprecated	52
postponeAction	52
quickinstall	53
R.exec	54
RdSection2latex	54
read.yaml_section	55
regfetch	56
render_notes	57
reorder_columns	58
require.quiet	59
requireRUnit	60
rnw	60
Rversion	62
setBiocMirror	63
setClassRegistry	63
setPackageExtraHandler	64
setupPackageOptions	66
simpleRegistry	66
source_files	67
str_diff	67
str_out	68
sVariable	70
Sys.getenv_value	71
sys_call_stack	72
testRversion	72
unit.test	73
unlist_	74
unlist_with_sep	75
userData	75
userIs	76
using_something	77
utest	78
utestFramework	79

utestPath	80
winbuild	80
write.bib	81
write.pkgbib	81
writeUnitVignette	83
Index	84

.silenceF	<i>Silencing Functions</i>
-----------	----------------------------

Description

Generates a wrapper function that silences the output, messages, and/or warnings of a given function.

Usage

```
.silenceF(f, level = 7L)
```

Arguments

- | | |
|-------|--|
| f | function to silence |
| level | a single numeric (integer) that indicates the silencing level, which encodes the set of output to be silenced.
It is interpreted like unix permission bit system, where each bit of the binary expression of the silencing level corresponds to a given type of output: <ul style="list-style-type: none"> • 0: nothing silenced; • 1: <i>stdout</i>; • 2: <i>stderr</i> messages; • 4: <i>stderr</i> warnings. |

For example, level 3 = 2 + 1 means silencing *stdout* and *stderr*, while 5 = 3 + 2 means silencing *stderr* messages and warnings, but not outputs to *stdout*. The default value is 7 = 4 + 2 + 1, which silences all output.

Negative values are supported and mean "*silence everything except the corresponding type*", e.g., level = -1 silences all except *stdout* (computed as the binary complementary of 7, i.e. $7 - 1 = 5 = 3 + 2$). See examples.

Value

a function

Examples

```
f <- function(){
  cat("stdout message\n")
  message("stderr message")
  warning("stderr warning", immediate. = TRUE)
}

# example of generated wrapper
g <- .silenceF(f)
g

# use of silencing level
for(l in 7:-7){ message("\nLevel: ", l); .silenceF(f, l)() }

# inline functions
ifun <- .silenceF(function(){ f(); invisible(1) })
ifun()
ifun <- .silenceF(function(){ f(); 1 })
ifun()
ifun <- .silenceF(function(){ f(); 1 }, 2L)
ifun()
```

addnames

Generating Names

Description

Generates names or dimnames for objects.

Usage

```
addnames(x, ...)
```

Default S3 method:
addnames(x, ...)

S3 method for class 'vector'
addnames(x, prefix = "x", sep = "", ...)

S3 method for class 'array'
addnames(x, prefix = letters[1:length(dim(x))], sep = "", ...)

S3 method for class 'matrix'
addnames(x, prefix = c("row", "col"), ...)

Arguments

x	object whose names are generated.
...	extra arguments to allow extension and passed to the next method.
prefix	prefix string to use. A vector can be used to specify a prefix for each dimension of x. Names are build as <prefix><sep><index>.
sep	separator used between the prefix and the numeric index.

 addToLogger

Enhancing RUnit Logger

Description

Adds a function or a local variable to RUnit global logger.

Usage

```
addToLogger(name, value, logger = NULL)
```

Arguments

name	name of the function or variable to add
value	object to append to the logger. If value is a function it is added to the list and is accessible via <code>.testLogger\$name</code> . If value is a variable it is added to the local environment and is therefore accessible in all logging functions.
logger	an optional RUnit logger object. If missing or NULL, the object <code>.testLogger</code> is searched in <code>.GlobalEnv</code> – and an error is thrown if it does not exist.

Value

the modified logger object. Note that the global object is also modified if logger is NULL.

 add_lib

Adding Package Libraries

Description

Prepend/append paths to the library path list, using `.libPaths`.

Usage

```
add_lib(..., append = FALSE)
```

Arguments

... paths to add to `.libPath`
append logical that indicates that the paths should be appended rather than prepended.

Details

This function is meant to be more convenient than `.libPaths`, which requires more writing if one wants to:

- sequentially add libraries;
- append and not prepend new path(s);
- keep the standard user library in the search path.

Examples

```
ol <- .libPaths()
# called sequentially, .libPaths only add the last library
show( .libPaths('.') )
show( .libPaths(tempdir()) )
# restore
.libPaths(ol)

# .libPaths does not keep the standard user library
show( .libPaths() )
show( .libPaths('.') )
# restore
.libPaths(ol)

# with add_lib
show( add_lib('.') )
show( add_lib(tempdir()) )
show( add_lib('..', append=TRUE) )

# restore
.libPaths(ol)
```

alphacol

Colour utilities

Description

alphacol adds an alpha value to a colour specification and convert to a hexadecimal colour string.

Usage

```
alphacol(col, alpha = FALSE)
```

Arguments

col	vector of any of the three kinds of R color specifications, i.e., either a color name (as listed by <code>colors()</code>), a hexadecimal string of the form "#rrggbb" or "#rrggbbaa" (see <code>rgb</code>), or a positive integer <code>i</code> meaning <code>palette()[i]</code> .
alpha	logical value indicating whether the alpha channel (opacity) values should be returned.

Examples

```
# Alphas
alphacol('red') # do nothing
alphacol('red', 10)
alphacol('#aabbcc', 5)
alphacol(4, 5)
```

askUser

User Queries

Description

This function is an improved version of `userQuery` from Bioconductor **Biobase** package, which asks the user about some task that needs her intervention to proceed, e.g., ask if one should perform a computation, install a package, etc..

Usage

```
askUser(
  msg,
  allowed = c("y", "n"),
  idefault = "n",
  default = "n",
  case.sensitive = FALSE
)
```

Arguments

msg	The output message
allowed	Allowed input from the user
idefault	default response in interactive mode. This answer will be in upper case in the question and will be the one returned if the user simply hits return.
default	default response in non-interactive mode. If NA, then the user is forced to provide an answer, even in non-interactive mode (e.g., when run through <code>Rscript</code>).
case.sensitive	Is the response case sensitive? Defaults to FALSE

Value

the character string typed/agreed by the user or directly the default answer in non-interactive mode.

bibtex

Bibtex Utilities

Description

Utility functions to work with BiBTeX files.

Usage

```
packageReferenceFile(PACKAGE = NULL, check = FALSE)
```

```
package_bibliography(PACKAGE = NULL, action = c("path", "copy", "load"))
```

Arguments

PACKAGE	package name. If NULL, then the name of the calling package is used.
check	logical that indicates if the result should be an empty string if the bibliography file (or package) does not exist.
action	single character string that specifies the action to be performed: <ul style="list-style-type: none">• 'path': return the path to the bibliography file. It returns an empty character string if the file does not exist.• 'copy': copy the bibliography file to the current directory, overwriting any existing REFERENCES.bib file.• 'load': load the bibliography file and return a list of utils::bibentry objects. It returns NULL if the file does not exist.

Functions

- `packageReferenceFile`: returns the path to a package REFERENCES.bib file.
- `package_bibliography`: returns the bibliography associated with a package. This can

Examples

```
packageReferenceFile('pkgmaker')  
packageReferenceFile('pkgmaker', check = TRUE)
```

cgetAnywhere	<i>Get Anywhere</i>
--------------	---------------------

Description

Similar to [getAnywhere](#), but looks for the value of its argument.

Usage

```
cgetAnywhere(x)
```

Arguments

x	a single character string
---	---------------------------

charmap	<i>Substituting Strings Against a Mapping Table</i>
---------	---

Description

Match the elements of a character vectors against a mapping table, that can specify multiple exact or partial matches.

Usage

```
charmap(x, maps, nomatch = NULL, partial = FALSE, rev = FALSE)
```

Arguments

x	character vector to match
maps	mapping tables. May be a character vector, a list of character vectors or a function.
nomatch	character string to be used for non-matched elements of x. If NULL, these elements are left unchanged.
partial	logical that indicates if partial matches are allowed, in which case mappings are used as regular expressions.
rev	logical that indicates if the mapping should be interpreted in the reverse way.

checkWarning	<i>Extra Check Functions for RUnit</i>
--------------	--

Description

checkWarning checks if a warning is generated by an expression, and optionally follows an expected regular expression pattern.

Usage

```
checkWarning(expr, expected = TRUE, msg = NULL)
```

Arguments

expr	an R expression
expected	expected value as regular expression pattern. If a logical, then it specifies if a warning is expected or not. For backward compatibility, a NULL value is equivalent to TRUE.
msg	informative message to add to the error in case of failure

Examples

```
# check warnings
checkWarning({ warning('ah ah'); 3})
checkWarning({ warning('ah oh ah'); 3}, 'oh')
try( checkWarning(3) )
try( checkWarning({ warning('ah ah'); 3}, 'warn you') )
```

citecmd	<i>Citing Package References</i>
---------	----------------------------------

Description

Create a citation command from package specific BibTeX entries, suitable to be used in Rd files or Latex documents. The entries are looked in a file named REFERENCES.bib in the package's root directory (i.e. inst/ in development mode).

Usage

```
citecmd(key, ..., REFERENCES = NULL)
```

Arguments

key character vector of BibTeX keys
 ... extra arguments passed to `format.bibentry`.
 REFERENCES package or bibentry specification

Value

a character string containing the text formatted BibTeX entries

<code>compile_src</code>	<i>Compile Source Files from a Development Package</i>
--------------------------	--

Description

Compile Source Files from a Development Package

Usage

```
compile_src(pkg = NULL, load = TRUE)
```

Arguments

pkg the name of the package to compile
 load a logical indicating whether the compiled library should be loaded after the compilation (default) or not.

Value

None

CRAN	<i>Main CRAN Mirror URL</i>
------	-----------------------------

Description

CRAN simply contains the url of CRAN main mirror (<https://cran.r-project.org>), and aims at simplifying its use, e.g., in calls to `install.packages`.

Usage

```
CRAN
```

Format

An object of class character of length 1.

Examples

```
## Not run:
install.packages('pkgmaker', repos=CRAN)

## End(Not run)
```

digest_function	<i>Compute Function Digest Hash</i>
-----------------	-------------------------------------

Description

Computes a digest hash of the body and signature of a function. Note that the hash is not affected by attributes or the function's environment.

Usage

```
digest_function(fun, n = Inf)
```

Arguments

fun	a function
n	a single numeric that indicates the length of the hash.

Details

The hash itself is computed using [digest::digest](#).

Value

a character string

exitCheck	<i>Exit Error Checks</i>
-----------	--------------------------

Description

exitCheck provides a mechanism to distinguish the exit status in [on.exit](#) expressions.

Usage

```
exitCheck()
```

Details

It generates a function that is used within a function's body to "flag" normal exits and in its [on.exit](#) expression to check the exit status of a function. Note that it will correctly detect errors only if all normal exit are wrapped into a call to it.

Examples

```

# define some function
f <- function(err){

  # initialise an error checker
  success <- exitCheck()

  # do something on exit that depends on the error status
  on.exit({
    if(success()) cat("Exit with no error: do nothing\n")
    else cat("Exit with error: cleaning up the mess ...\n")
  })

  # throw an error here
  if( err ) stop('There is an error')

  success(1+1)
}

# without error
f(FALSE)
# with error
try( f(TRUE) )

```

 expand_list

Expanding Lists

Description

expand_list expands a named list with a given set of default items, if these are not already in the list, partially matching their names.

Usage

```
expand_list(x, ..., .exact = TRUE, .names = !.exact)
```

```
expand_dots(..., .exclude = NULL)
```

Arguments

x	input list
...	extra named arguments defining the default items. A list of default values can also be passed as a single unnamed argument.
.exact	logical that indicates if the names in x should be partially matched against the defaults.

.names logical that only used when .exact=FALSE and indicates that the names of items in x that partially match some defaults should be expanded in the returned list.

.exclude optional character vector of argument names to exclude from expansion.

Value

a list

Functions

- expand_dots: expands the ... arguments of the function in which it is called with default values, using expand_list. It can **only** be called from inside a function.

Examples

```
expand_list(list(a=1, b=2), c=3)
expand_list(list(a=1, b=2, c=4), c=3)
# with a list
expand_list(list(a=1, b=2), list(c=3, d=10))
# no partial match
expand_list(list(a=1, b=2, c=5), cd=3)
# partial match with names expanded
expand_list(list(a=1, b=2, c=5), cd=3, .exact=FALSE)
# partial match without expanding names
expand_list(list(a=1, b=2, c=5), cd=3, .exact=FALSE, .names=FALSE)

# works also inside a function to expand a call with default arguments
f <- function(...){
  cl <- match.call()
  expand_list(cl, list(a=3, b=4), .exact=FALSE)
}
f()
f(c=1)
f(a=2)
f(c=1, a=2)

# expanding dot arguments

f <- function(...){
  expand_dots(list(a=2, bcd='a', xxx=20), .exclude='xxx')
}

# add default value for all arguments
f()
# add default value for `bcd` only
f(a=10)
# expand names
f(a=10, b=4)
```

ExposeAttribute *Exposing Object Attributes*

Description

The function `ExposeAttribute` creates an S3 object that exposes all attributes of any R object, by making them accessible via methods `$` and/or `$<-`.

Usage

```
ExposeAttribute(object, ..., .MODE = "rw", .VALUE = FALSE)
```

```
attr_mode(x)
```

```
attr_mode(x) <- value
```

Arguments

<code>object</code>	any R object whose attributes need to be exposed
<code>...</code>	attributes, and optionally their respective values or access permissions. See argument value of <code>attr_mode</code> for details on the way of specifying these.
<code>.MODE</code>	access mode: “r” : (read-only) only method <code>\$</code> is defined “w” : (write-only) only method <code>\$<-</code> is defined “rw” : (read-write) both methods <code>\$</code> and <code>\$<-</code> are defined
<code>.VALUE</code>	logical that indicates if the values of named arguments in <code>...</code> should be considered as attribute assignments, i.e. that the result object has these attributes set with the specified values. In this case all these attributes will have the access permission as defined by argument <code>.MODE</code> .
<code>x</code>	an <code>ExposeAttribute</code> object
<code>value</code>	replacement value for mode. It can be <code>NULL</code> to remove the <code>ExposeAttribute</code> wrapper, a single character string to define a permission for all attributes (e.g., <code>'rw'</code> or <code>'r'</code>), or a list specifying access permission for specific attributes or classes of attributes defined by regular expressions. For example, <code>list(a='r',b='w','blabla.*'='rw')</code> set attribute <code>'a'</code> as read-only, attribute <code>'b'</code> as write-only, all attributes that start with <code>'blabla'</code> in read-write access.

extractLocalFun	<i>Extracting Local Function Definition</i>
-----------------	---

Description

extractLocalFun Extracts local function from wrapper functions of the following type, typically used in S4 methods: `'function(a,b,...){ .local <-function(a,b,c,d,...){} .local(a,b,...) }'`

Works for methods that are created (setMethod) as a wrapper function to an internal function named .local.

Usage

```
extractLocalFun(f)
```

```
allFormals(f)
```

Arguments

f definition of the wrapper function

Value

a function

a paired list like the one returned by [formals](#).

factor2character	<i>Converting Factors to Character Vectors</i>
------------------	--

Description

Converts all factor variables to character vectors in a data.frame or phenotypic data.

Usage

```
factor2character(x)
```

Arguments

x data.frame or ExpressionSet object

Value

an object of the same class as x.

file_extension *Extract File Extension*

Description

Extract File Extension

Usage

```
file_extension(x, ext = NULL)
```

Arguments

x	path as a character vector.
ext	extension to append instead of the original extension.

Examples

```
file_extension('alpha.txt')
file_extension(paste('aa.tt', 1:5, sep=''))
# change extension
file_extension(paste('aa.tt', 1:5, sep=''), 'pdf')
file_extension(paste('aatt', 1:5, sep=''), 'pdf')
```

find_devpackage *Find Path to Development Package Root Directory*

Description

Development packages are looked-up according to rules defined in a file .Rpackages in the user's home directory.

Usage

```
find_devpackage(x, error = TRUE)
```

Arguments

x	name of the development package to lookup.
error	logical that indicates if an error is thrown when the project root directory could not be found.

Specification of package path

Package paths are specified in a list with:

- unnamed elements: character strings give path to directories to lookup for sub-directories that match exactly the package's name;
- named element containing character strings: these are paths that are looked up only for packages that match the element name. If the element name contains any of the characters `*?()$^\\[]`, then it is matched using regular expression.

getLoadingNamespace *Namespace Development Functions*

Description

getLoadingNamespace returns information about the loading namespace. It is a wrapper to [loadingNamespaceInfo](#), that does not throw an error.

Usage

```
getLoadingNamespace(env = FALSE, info = FALSE, nodev = FALSE)
```

```
isLoadingNamespace(ns, nodev = FALSE)
```

```
isNamespaceLoaded2(ns)
```

```
isDevNamespace(ns)
```

```
addNamespaceExport(x)
```

```
ns_get(x, ns = NULL, ...)
```

Arguments

env	logical that indicates that the namespace's environment (i.e. the namespace itself) should be returned.
info	logical that indicates that the complete information list should be returned
nodev	logical that indicates if loading devtools namespace should be discarded.
ns	the name of a namespace or a namespace whose loading state is tested. If missing isLoadingNamespace test if any namespace is being loaded.
x	character vector containing the names of R objects to export in the loading namespace.
...	extra arguments passed to get0 .

Value

the name of the loading namespace if env and info are FALSE, an environment if env=TRUE, a list with elements pkgname and libname if info=TRUE.

Functions

- `isLoadingNamespace`: Tests if a namespace is being loaded.
- `isNamespaceLoaded2`: tests if a given namespace is loaded, without loading it, contrary to `isNamespace`. It is similar to `isNamespaceLoaded` – which it uses – but also accepts environments.
- `isDevNamespace`: tests the – current – namespace is a devtools namespace.
- `addNamespaceExport`: Dynamically adds exported objects into the loading namespace.
- `ns_get`: gets an object from a given namespace.

`gfile`*Open a File Graphic Device*

Description

Opens a graphic device depending on the file extension.

Usage

```
gfile(filename, width, height, ...)
```

Arguments

<code>filename</code>	path to the image file to create.
<code>width</code>	output width
<code>height</code>	output height
<code>...</code>	other arguments passed to the relevant device function such as png or pdf . <code>importFrom grDevices bmp jpeg pdf png svg tiff</code>

`graphics-utils`*Utility Functions for Graphics*

Description

Utility Functions for Graphics

`mfrow` returns a 2-long numeric vector suitable to use in `par(mfrow=x)`, that will arrange `n` panels in a single plot.

Usage

```
mfrow(n)
```

Arguments

`n` number of plots to be arranged.

Examples

```
mfrow(1)
mfrow(2)
mfrow(3)
mfrow(4)
mfrow(10)
```

`hasArg2`*Checking for Missing Arguments*

Description

This function is identical to [hasArg](#), except that it accepts the argument name as a character string. This avoids to have a check NOTE about invisible binding variable.

Usage

```
hasArg2(name)
```

Arguments

`name` the name of an argument as a character string.

Examples

```
f <- function(...){ hasArg2('abc') }
f(a=1)
f(abc=1)
f(b=1)
```

hasEnvar

Check Environment Variables

Description

Tells if some environment variable(s) are defined.

Usage

```
hasEnvar(x)
```

Arguments

x environment variable name, as a character vector.

Examples

```
hasEnvar('_R_CHECK_TIMINGS_')  
hasEnvar('ABCD')
```

inSweave

Identifying Sweave Run

Description

Tells if the current code is being executed within a Sweave document.

Usage

```
inSweave()
```

Value

TRUE or FALSE

Examples

```
# Not in a Sweave document  
inSweave()  
  
# Within a Sweave document
```

irequire	<i>Require a Package with User Interaction</i>
----------	--

Description

Like base `require`, `irequire` tries to find and load a package, but in an interactive way, i.e. offering the user to install it if not found.

Usage

```
irequire(
  package,
  lib = NULL,
  ...,
  load = TRUE,
  msg = NULL,
  quiet = TRUE,
  prependLF = FALSE,
  ptype = c("CRAN-like", "BioC", "BioCsoft", "BioCann"),
  autoinstall = !interactive()
)
```

Arguments

<code>package</code>	name of the package
<code>lib</code>	path to the directory (library) where the package is to be looked for and installed if agreed by the user.
<code>...</code>	extra arguments passed to <code>install.packages</code> .
<code>load</code>	a logical that indicates if the package should be loaded, possibly after installation.
<code>msg</code>	message to display in case the package is not found when first trying to load/find it. This message is appended to the string "Package '<packagename>' is required".
<code>quiet</code>	logical that indicates if loading a package should be done quietly with <code>require.quiet</code> or normally with <code>require</code> .
<code>prependLF</code>	logical that indicates if the message should start at a new line.
<code>ptype</code>	type of package: from CRAN-like repositories, Bioconductor, Bioconductor software, Bioconductor annotation. Bioconductor packages are installed using <code>biocLite</code> from the BiocInstaller package or fetched on line at http://bioconductor.org/biocLite.R .
<code>autoinstall</code>	logical that indicates if missing packages should just be installed without asking with the user, which is the default in non-interactive sessions.

Value

TRUE if the package was successfully loaded/found (installed), FALSE otherwise.

See Also

Other require: [require.quiet\(\)](#)

isCRANcheck

Package Check Utils

Description

isCRANcheck **tries** to identify if one is running CRAN-like checks.

Usage

```
isCRANcheck(...)
```

```
isCRAN_timing()
```

```
isCHECK()
```

Arguments

... each argument specifies a set of tests to do using an AND operator. The final result tests if any of the test set is true. Possible values are:

- 'timing' Check if the environment variable `_R_CHECK_TIMINGS_` is set, as with the flag `'--timing'` was set.
- 'cran' Check if the environment variable `_R_CHECK_CRAN_INCOMING_` is set, as with the flag `'--as-cran'` was set.

Details

Currently isCRANcheck returns TRUE if the check is run with either environment variable `_R_CHECK_TIMINGS_` (as set by flag `'--timings'`) or `_R_CHECK_CRAN_INCOMINGS_` (as set by flag `'--as-cran'`).

Warning: the checks performed on CRAN check machines are on purpose not always run with such flags, so that users cannot effectively "trick" the checks. As a result, there is no guarantee this function effectively identifies such checks. If really needed for honest reasons, CRAN recommends users rely on custom dedicated environment variables to enable specific tests or examples.

Functions

- `isCRAN_timing`: tells if one is running CRAN check with flag `'--timing'`.
- `isCHECK`: tries harder to test if running under R CMD check. It will definitely identifies check runs for:
 - unit tests that use the unified unit test framework defined by **pkgmaker** (see [utest](#));
 - examples that are run with option `R_CHECK_RUNNING_EXAMPLES_ = TRUE`, which is automatically set for man pages generated with a fork of **roxygen2** (see *References*).

Currently, isCHECK checks both CRAN expected flags, the value of environment variable `_R_CHECK_RUNNING_UTESTS_`, and the value of option `R_CHECK_RUNNING_EXAMPLES_`. It will return TRUE if any of these environment variables is set to anything not equivalent to FALSE, or if the option is TRUE. For example, the function `utest` sets it to the name of the package being checked (`_R_CHECK_RUNNING_UTESTS_=<pkgname>`), but unit tests run as part of unit tests vignettes are run with `_R_CHECK_RUNNING_UTESTS_=FALSE`, so that all tests are run and reported when generating them.

References

Adapted from the function CRAN in the **fda** package.

<https://github.com/renozao/roxygen>

Examples

```
isCHECK()
```

is_package_path	<i>Test for Package Root Directory</i>
-----------------	--

Description

Tells if a directory is a package directory, i.e. that it contains a DESCRIPTION file.

Usage

```
is_package_path(x, error = FALSE)
```

Arguments

x	path to the directory to test
error	logical that indicates if an error should be raised if the directory is not a package directory.

`is_something`*Testing Object Type*

Description

Testing Object Type

`is_NA` tests if a variable is exactly NA (logical, character, numeric or integer)

`isFALSE` Tests if a variable is exactly FALSE.

`isNumber` tests if a variable is a single number

`isReal` tests if a variable is a single real number

`isInteger` tests if an object is a single integer

`isString` tests if an object is a character string.

`is.dir` tests if a filename is a directory.

`is.file` tests if a filename is a file.

`hasNames` tests if an object has names.

Usage

`is_NA(x)`

`isFALSE(x)`

`isNumber(x)`

`isReal(x)`

`isInteger(x)`

`isString(x, y, ignore.case = FALSE)`

`is.dir(x)`

`is.file(x)`

`hasNames(x, all = FALSE)`

Arguments

`x` an R object

`y` character string to compare with.

`ignore.case` logical that indicates if the comparison should be case sensitive.

`all` logical that indicates if the object needs all names non empty

Value

TRUE or FALSE

See Also

[isTRUE](#)

iterCount	<i>Simple Text Iteration Counter</i>
-----------	--------------------------------------

Description

Simple Text Iteration Counter

Usage

```
iterCount(n = 100, i0 = 0L, title = "Iterations", extra = NULL, verbose = TRUE)
```

Arguments

n	number of total steps
i0	starting step
title	character string to use as title
extra	character vector providing extra text to add at each step
verbose	logical that toggles the counter

Examples

```
progress <- iterCount(LETTERS)
res <- sapply(LETTERS, function(x){
  Sys.sleep(.1)
  progress()
})
# terminate counter
i_end <- progress(NULL)
i_end
```

Description

`knit_ex` is a utility function for running small knitr examples, e.g., to illustrate functionalities or issues.

`hook_backspace` is a chunk hook that enables the use of backspace characters in the output (e.g., as used in progress bars), and still obtain a final output as in the console.

Usage

```
knit_ex(x, ..., quiet = TRUE, open = FALSE)
```

```
hook_try(before, options, envir)
```

```
hook_backspace()
```

```
hook_toggle()
```

Arguments

<code>x</code>	text to knit as a character vector
<code>...</code>	arguments passed to <code>knit2html</code> or <code>knit</code>
<code>quiet</code>	logical that indicates if knitting should be quiet (no progress bars etc..).
<code>open</code>	logical, only used when <code>x</code> is in <code>.Rmd</code> format, that indicates if the generated document result should be open in a browser, instead of being printed on screen. Not that a browser will not open in non-interactive sessions, and the result will be returned invisibly.
<code>before</code>	logical that indicates when the hook is being called: before or after the chunk is processed.
<code>options</code>	list of current knitr chunk options
<code>envir</code>	environment where the chunk is evaluated

Value

`knit_ex` returns the generated code, although invisibly when `open=TRUE`.

Functions

- `hook_try`: is a knitr hook to enable showing error messages thrown by `try`. The function is not meant to be called directly, but only registered using `knitr::knit_hooks` (see details on this dedicated man page).
This simply defines a function `try` in `envir` that prints the error message if any, and is called instead of base `try`.
- `hook_toggle`: is a chunk hook that adds clickable elements to toggle *individual* code chunks in HTML documents generated from `.Rmd` files.

Examples

```

library(knitr)
knit_ex("1 + 1")

library(knitr)

# standard error message is caught
knit_ex("stop('ah ah')")

# with try the error is output on stderr but not caught by knitr
knit_ex("try( stop('ah ah') )")

# no message caught
knit_ex("
^^^{r, include = FALSE}
knit_hooks$set(try = pkgmaker::hook_try)
^^^

^^^{r, try=TRUE}
try( stop('ah ah') )
^^^")

# Correctly formatting backspaces in chunk outputs
tmp <- tempfile(fileext = '.Rmd')
cat(file = tmp, "
^^^{r, include = FALSE}
library(knitr)
knit_hooks$set(backspace = pkgmaker::hook_backspace())
^^^
Default knitr does not handle backspace and adds a special character:
^^^{r}
cat('abc\bd')
^^^

Using the hook backspace solves the issue:
^^^{r, backspace=TRUE}
cat('abc\bd')
^^^
")

# knit
out <- knitr::knit2html(tmp, fragment.only = TRUE)
# look at output
## Not run:
  browseURL(out)
  edit( file = out)

## End(Not run)
# cleanup

```

```
out_files <- list.files(dirname(out), full.names = TRUE,
                       pattern = paste0("^", tools::file_path_sans_ext(out)))
unlink(c(tmp, out_files))
```

```
knit_ex("
```

```
Declare chunk hook:
```

```
^^^{r, setup}
library(knitr)
knit_hooks$set(toggle = hook_toggle())
^^^
```

```
The R code of this chunk can be toggled on/off, and starts visible:
```

```
^^^{r, toggle=TRUE}
print(1:10)
^^^
```

```
The R code of this chunk can be toggled on/off, and starts hidden:
```

```
^^^{r, toggle=FALSE}
print(1:10)
^^^
```

```
This is a plain chunk that cannot be toggled on/off:
```

```
^^^{r}
print(1:10)
^^^
```

```
Now all chunks can be toggled and start visible:
```

```
^^^{r, toggle_all}
opts_chunk$set(toggle = TRUE)
^^^
```

```
^^^{r}
sample(5)
^^^
```

```
To disable the toggle link, one can pass anything except TRUE/FALSE:
```

```
^^^{r, toggle = NA}
sample(5)
^^^
```

```
", open = TRUE)
```

Description

latex_preamble outputs/returns command definition LaTeX commands to be put in the preamble of vignettes.

Usage

```
latex_preamble(  
  PACKAGE,  
  R = TRUE,  
  CRAN = TRUE,  
  Bioconductor = TRUE,  
  GEO = TRUE,  
  ArrayExpress = TRUE,  
  biblatex = FALSE,  
  only = FALSE,  
  file = ""  
)  
  
latex_bibliography(PACKAGE, file = "")
```

Arguments

PACKAGE	package name
R	logical that indicate if general R commands should be added (e.g. package names, inline R code format commands)
CRAN	logical that indicate if general CRAN commands should be added (e.g. CRAN package citations)
Bioconductor	logical that indicate if general Bioconductor commands should be added (e.g. Bioc package citations)
GEO	logical that indicate if general GEOmnibus commands should be added (e.g. urls to GEO datasets)
ArrayExpress	logical that indicate if general ArrayExpress commands should be added (e.g. urls to ArrayExpress datasets)
biblatex	logical that indicates if a \bibliography command should be added to include references from the package's REFERENCES.bib file.
only	a logical that indicates if the only the commands whose dedicated argument is not missing should be considered.
file	connection where to print. If NULL the result is returned silently.

Details

Argument PACKAGE is not required for latex_preamble, but must be correctly specified to ensure biblatex=TRUE generates the correct bibliography command.

Functions

- latex_bibliography: latex_bibliography prints or return a LaTeX command that includes a package bibliography file if it exists.

Examples

```
latex_preamble()
latex_preamble(R=TRUE, only=TRUE)
latex_preamble(R=FALSE, CRAN=FALSE, GEO=FALSE)
latex_preamble(GEO=TRUE, only=TRUE)
```

list.data

List Package Data Objects

Description

Lists data objects that are shipped within package(s).

Usage

```
list.data(package = NULL)
```

Arguments

package a single character string that specifies the name of a particular package where to look for data objects.

Value

a data.frame object with columns:

- package: name of the package that holds the data object.
- data: name of the key to use in `utils::data` or `ldata` to load the data object.
- object: name of the (sub-)object that is contained in the data object.

See Also

[utils::data](#), [ldata](#)

Examples

```
# list all data objects
head(list.data())

# list all data objects in package 'datasets'
subset(list.data("datasets"), data %in% "beavers")
```

list.libs	<i>Library Files Utilities</i>
-----------	--------------------------------

Description

Lists binary library files in a directory

Usage

```
list.libs(dir, ..., all.platforms = FALSE)
```

```
libname(x)
```

Arguments

dir	directory
...	extra arguments passed to list.files .
all.platforms	a logical that indicates whether to list library files for the current platform only (default) or all platforms (Unix, Windows, Mac).
x	a filename

Value

a character vector

Functions

- `libname`: extracts library names from a path, removing the directory part of the path, as well as the platform specific library extension.

Examples

```
libname('mylib.so')  
libname('/some/path/somewhere/mylib.dll')
```

load_all_file	<i>Generate a Loading Script for Development Packages</i>
---------------	---

Description

Writes a script file that contains code that loads a given development package.

Usage

```
load_all_file(path = path.package(package), package, dest = NULL)
```

Arguments

path	a character string that contains the path to the development package.
package	the name of the package for which the loading script must be generated. It must be a package that has already been loaded with <code>devtools::load_all</code> in the current session, so that its path can be retrieved.
dest	the path to script file to create (as a character string). If not provided, then the script is written in a temporary .R file with prefix "load_all_<pkgname>_".

Details

This is useful when we want to load a development package in batchtools registries:

```
library(devtools)
library(batchtools)

load_all("path/to/pkgA")
makeRegistry(..., source = load_all_file("pkgA"))
```

Value

a character string that contains the path to the script file.

load_project	<i>Load Development Package</i>
--------------	---------------------------------

Description

Load Development Package

Usage

```
load_project(
  pkg,
  reset = FALSE,
  ...,
  utests = TRUE,
  verbose = FALSE,
  addlib = TRUE,
  character.only = FALSE,
  try.library = FALSE
)

library_project(...)
```

Arguments

<code>pkg</code>	name of the package/project to load.
<code>reset</code>	logical that indicates if the package should be reloaded (passed to <code>load_all</code>).
<code>...</code>	other arguments passed to <code>load_all</code> .
<code>utests</code>	logical that indicates if an environment containing the unit test functions should be created. If TRUE this environment is accessible at <code>pkgname::UnitTests\$test.filename.r\$function</code> .
<code>verbose</code>	logical that indicates if log messages should be printed.
<code>addlib</code>	logical that indicates if the <code>lib/</code> sub-directory, if it exists, should be prepended to the library path. This enables to control the version of the loaded dependencies.
<code>character.only</code>	logical that indicates if argument <code>pkg</code> should be evaluated or taken literal.
<code>try.library</code>	logical that indicates if projects that could not be found should be looked up in the installed packages.

Functions

- `library_project`: shortcut for `load_project(..., try.library = TRUE)`, to load project code from installed library if not found as a development project. All its arguments are passed to `load_project`.

Iverbose

Logging Feature

Description

Iverbose returns/sets the current verbosity level.

Usage

```
lverbose(val, global = FALSE)

lsilent()

is.verbose()

lmessage(level, ..., appendLF = TRUE, sep = "", force = FALSE)

vmessage(...)

log_append(...)
```

Arguments

<code>val</code>	logical/numeric value that sets the verbosity level.
<code>global</code>	logical that indicates if the verbose level of all log handlers should be set to <code>val</code> .
<code>level</code>	verbosity level threshold (numeric value) above which the message should be printed out. This threshold is compared with the current verbosity level as returned by <code>lverbose</code> .
<code>...</code>	parts of a character message that are concatenated and passed to the current logger's write function.
<code>appendLF</code>	logical indicating if an newline character should be appended at the end of the message.
<code>sep</code>	separation character, used when concatenating all arguments in <code>...</code>
<code>force</code>	logical that indicates if one should output messages or return a non null logger, even if the verbose mode is not high enough.

Value

the old verbose level

Functions

- `lsilent`: tells if all verbose messages are silenced.
- `is.verbose`: tells if verbosity is on, i.e. at level greater than 0.
- `lmessage`: prints out a message (on `stdout`) if the verbosity level is greater than a given value.
- `vmessage`: prints out a log message (at level 1) using the current logger, typically on `stdout`. It is a shortcut for `lmessage(1L, ...)`.
- `log_append`: directly appends some message to the current log line.

makeFakeVignette	<i>Generate a Fake Vignette</i>
------------------	---------------------------------

Description

Generate a Fake Vignette

Usage

```
makeFakeVignette(src, out, PACKAGE = NULL)
```

Arguments

src	original Sweave file
out	output file
PACKAGE	package name where to look the source vignette

makeUnitVignette	<i>Make Vignette for Unit Tests</i>
------------------	-------------------------------------

Description

Builds a vignette for unit tests in a package using the [utest](#) and a template vignette file.

Usage

```
makeUnitVignette(
  pkg,
  file = paste(pkg, "-unitTests.pdf", sep = ""),
  ...,
  check = FALSE
)
```

Arguments

pkg	Package name
file	Output file (.Rnw, .tex, or .pdf)
...	extra arguments passed to utest .
check	logical that indicates the vignette was made from R CMD check, in which case the vignette is updated only if results of unit tests can be found in the unit test output directory, where they would have been generated by utest .

Value

Result of running unit test suite

```
make_vignette_auxfiles
```

Generate RMarkdown Vignette Auxiliary Files

Description

Generate RMarkdown Vignette Auxiliary Files

Usage

```
make_vignette_auxfiles(
  PACKAGE,
  input = NULL,
  bibfile = "library.bib",
  Rpkg.prefix = "Rpackage_",
  ...
)
```

Arguments

PACKAGE	package name
input	vignette source file. If NULL then the current file is obtained via a call to knitr::current_input .
bibfile	output file for R package citations.
Rpkg.prefix	prefix to use when generating the bibtex entries of cited R packages. If Rpkg.prefix = 'Rpackage_', then Rmarkdown citations should be @Rpackage_mypkg.
...	other arguments passed to latex_preamble

Details

To use this feature add the following in your YAML header:

```
header-includes:
  - \input{"`r pkgmaker::make_vignette_auxfiles('pkgmaker')`}
bibliography: library.bib
```

```
messagef
```

General Log Formatting

Description

Generate a formatted diagnostic message. This function is a shortcut for `message(sprintf(...))`.

Usage

```
messagef(fmt, ..., domain = NULL, appendLF = TRUE)
```

```
wnote(..., immediate. = TRUE)
```

Arguments

fmt	a character vector of format strings, each of up to 8192 bytes.
...	values to be passed into fmt. Only logical, integer, real and character vectors are supported, but some coercion will be done: see the ‘Details’ section. Up to 100.
domain	see gettext .
appendLF	logical: should messages given as a character string have a newline appended?
immediate.	logical, indicating if the call should be output immediately, even if getOption("warn") <= 0.

Functions

- `wnote`: throws a simple note as an immediate warning. It is a shortcut for `warning(..., immediate. = TRUE, call. = FALSE)`.

See Also

[sprintf](#), [message](#)

Examples

```
messagef("Hello %s number %i", 'world', 4)
```

mkoptions

Quick Option-like Feature

Description

`mkoptions` is a function that returns a function that behaves like [options](#), with an attached internal/local list of key-value pairs.

Usage

```
mkoptions(...)
```

```
.options(..., .DATA)
```

Arguments

- ... list of keys or key-value pairs. For `mkoptions` these define initial/default key-value pairs.
- `.DATA` a list or an environment with an element `.options`.

Functions

- `.options`: is a low-level function that mimics the behaviour of the base function `options`, given a set of key-value pairs. It is the workhorse function used in `mkoptions` and package-specific option sets (see [setupPackageOptions](#))

See Also

[setupPackageOptions](#)

Examples

```
f <- mkoptions(a=3, b=list(1,2,3))
str(f())
f('a')
f('b')
str(old <- f(a = 10))
str(f())
f(old)
str(f())
```

new2

Alternative S4 Constructor

Description

An alternative version of `new` to create objects based on a list of values.

Usage

```
new2(class, ...)
```

Arguments

- `class` Class name to instantiate
- ... extra arguments from which slot values are extracted by exact matching of names.

Examples

```

setClass('A', contain='character', representation(x='numeric', y='character'))

# identical behaviour with standard calls
identical(new('A'), new2('A'))
identical(new('A', x=1), new2('A', x=1))

# but if passing that are names not slots
identical(new('A'), new2('A', b=1))
identical(new('A', x=1), new2('A', x=1, b=3))
identical(new('A', x=1), new2('A', x=1, b=3))

# standard `new` would coerce first unnamed argument into parent of 'A' (i.e. 'character')
new('A', list(x=1))
new('A', list(x=1, y='other'))
# `new2` rather use it to initialise the slots it can find in the list
identical(new('A', x=1), new2('A', list(x=1)))
identical(new('A', x=1, y='other'), new2('A', list(x=1, y='other')))

```

oneoffVariable

One-off Global Variables

Description

Defines a function that allow to get/assign a global variable whose value is ensured to be reset after each access.

Usage

```
oneoffVariable(default = NULL)
```

Arguments

default	default value to which the global variable is reset after each access. Default is NULL.
---------	---

Value

a function with one argument (value) that provides get/set access to a global variable. If called with a value, it assigns this value to the global variable. If called with no argument, it returns the current value of the global variable and reset it to its default value – as defined at its creation.

Examples

```
x <- oneoffVariable(0)
# returns default value
x()
# assign a value
x(3)
# get the value
x()
# second call returns default value again
x()
```

onLoad

Default Load/Unload Functions

Description

Default Load/Unload Functions

Usage

```
onLoad(libname = NULL, pkgname, chname = packageName())
```

```
onUnload(libpath)
```

Arguments

libname	a character string giving the library directory where the package defining the namespace was found.
pkgname	a character string giving the name of the package.
chname	a character string naming a DLL (also known as a dynamic shared object or library) to load.
libpath	a character string giving the complete path to the package.

Examples

```
# in a package namespace:
.onLoad <- function(libname=NULL, pkgname){

pkgmaker::.onLoad(libname, pkgname)

}

# in a package namespace:
.onUnload <- function(libpath){
```

```

    pkgmaker::onUnload(libpath)
  }

```

option_symlink	option_symlink creates a symbolic link to option x.
----------------	---

Description

option_symlink creates a symbolic link to option x.

is_option_symlink tests if x is a symbolic link option.

option_symlink_target returns the end target option of a symbolic link option x.

as.package_options creates an object such as the ones used to stores package specific options.

The method `[[` is equivalent to `options()` or `getOption(...)`: e.g. `obj[[]]` returns the list of options defined in `obj`, and `obj[['abc']]` returns the value of option 'abc'.

packageOptions provides access to package specific options from a given package that were defined with `setupPackageOptions`, and behaves as the base function [options](#).

listPackageOptions returns the names of all option currently defined with `setupPackageOptions`.

Usage

```

option_symlink(x)

is_option_symlink(x, opts)

option_symlink_target(x, opts)

as.package_options(..., defaults = NULL)

## S3 method for class 'package_options'
x[[...]]

packageOptions(..., PACKAGE = packageName())

listPackageOptions()

```

Arguments

x	a character string, a list or an object of class <code>package_options</code> .
opts	a list of options
...	arguments passed to <code>getOption</code> (only first one is used).
defaults	NULL or a list of default options with their values.
PACKAGE	a package name

Value

a character vector (possibly empty).

Examples

```
listPackageOptions()
```

orderVersion	<i>Ordering Version Numbers</i>
--------------	---------------------------------

Description

Orders a vector of version numbers, in natural order.

Usage

```
orderVersion(x, ..., decreasing = FALSE)
```

```
sortVersion(x, ...)
```

Arguments

x	a character vector of version numbers
...	extra parameters passed to <code>orderVersion</code> and <code>order</code>
decreasing	a logical that indicates if the ordering should be decreasing

Examples

```
v <- c('1.0', '1.03', '1.2')
order(v)
orderVersion(v)
```

```
sort(v)
sortVersion(v)
```

packageData	<i>Loading Package Data</i>
-------------	-----------------------------

Description

Loads package data using `data`, but allows the user to avoid NOTEs for a ‘non visible binding variable’ to be thrown when checking a package. This is possible because this function returns the loaded data.

Usage

```
packageData(
  list,
  envir = .GlobalEnv,
  ...,
  options = NULL,
  stringsAsFactors = getOption("stringsAsFactors")
)

ldata(list, ..., package = NULL, error = TRUE, simplify = TRUE)
```

Arguments

<code>list</code>	character vector containing the names of the data to load.
<code>envir</code>	the environment where the data should be loaded.
<code>...</code>	other arguments eventually passed to <code>data</code> .
<code>options</code>	list of R options to set before calling <code>data</code> . This may be useful the data is shipped as an R script.
<code>stringsAsFactors</code>	logical that indicates if character columns of tabular data should be converted into factors.
<code>package</code>	a character vector giving the package(s) to look in for data sets, or NULL. By default, all packages in the search path are used, then the ‘data’ subdirectory (if present) of the current working directory.
<code>error</code>	a logical that indicates whether an error should be thrown if the requested data cannot be found.
<code>simplify</code>	logical that indicates if queries of one object only (i.e. argument <code>list</code> is of length one) should return the data object itself.

Value

the loaded data.

Functions

- `ldata`: loads a package data in the parent frame. It is a shortcut for `packageData(list, ..., envir=parent.frame())`

Examples

```
## Not run: mydata <- packageData('mydata')
```

```
## Not run:  
# in a package' source => won't issue a NOTE  
myfunction function(){  
  mydata <- ldata('mydata')  
}
```

```
## End(Not run)
```

packageEnv

Package Development Utilities

Description

packageEnv is a slight modification from [topenv](#), which returns the top environment, which in the case of development packages is the environment into which the source files are loaded by [load_all](#).

Usage

```
packageEnv(pkg, skip = FALSE, verbose = FALSE)
```

```
topns_name(n = 1L, strict = TRUE, unique = TRUE)
```

```
topns(strict = TRUE)
```

```
packageName(envir = packageEnv(), .Global = FALSE, rm.prefix = TRUE)
```

```
str_ns(envir = packageEnv())
```

```
packagePath(..., package = NULL, lib.loc = NULL, check = TRUE)
```

```
isPackageInstalled(..., lib.loc = NULL)
```

```
as_package(x, ..., quiet = FALSE, extract = FALSE)
```

Arguments

pkg	package name. If missing the environment of the runtime caller package is returned.
skip	a logical that indicates if the calling namespace should be skipped.
verbose	logical that toggles verbosity

n	number of namespaces to return
strict	a logical that indicates if the global environment should be considered as a valid namespace.
unique	logical that indicates if the result should be reduced to contain only one occurrence of each namespace.
envir	environment where to start looking for a package name. The default is to use the runtime calling package environment.
.Global	a logical that indicates if calls from the global environment should throw an error (FALSE: default) or the string 'R_GlobalEnv'.
rm.prefix	logical that indicates if an eventual prefix 'package:' should be removed from the returned string.
...	arguments passed to file.path .
package	optional name of an installed package
lib.loc	path to a library of R packages where to search the package
check	logical that indicates if an error should be thrown if the path to the package root directory cannot be found. If this is the case and check = FALSE, then the function returns NULL.
x	package specified by its installation/development path or its name as 'package:*'.
quiet	a logical that indicate if an error should be thrown if a package is not found. It is also passed to find.package .
extract	logical that indicates if DESCRIPTION of package source files should be extracted. In this case there will be no valid path.

Value

packageEnv returns an environment
 a character string
 a character string

Functions

- `topns_name`: returns the name of the runtime sequence of top namespace(s), i.e. the name of the top calling package(s), from top to bottom.
 The top namespace is not necessarily the namespace where `topns_name` is effectively called. This is useful for packages that define functions that need to access the calling namespace, even from calls nested into calls to another function from the same package – in which case `topenv` would not give the desired environment.
- `topns`: returns the runtime top namespace, i.e. the namespace of the top calling package, possibly skipping the namespace where `topns` is effectively called. This is useful for packages that define functions that need to access the calling namespace, even from calls nested into calls to another function from the same package – in which case `topenv` would not give the desired environment.
- `packageName`: returns the current package's name. It was made internal from version 0.16, since the package **utils** exported its own `packageName` function in R-3.0.0.

- `str_ns`: formats a package environment/namespace for log/info messages.
- `packagePath`: returns the current package's root directory, which is its installation/loading directory in the case of an installed package, or its source directory served by devtools.
- `isPackageInstalled`: checks if a package is installed.
- `as_package`: an enhanced version of [as.package](#), that is not exported not to mask the original function. It could eventually be incorporated into devtools itself. Extra arguments in `...` are passed to [find.package](#).

<code>packageReference</code>	<i>Package References</i>
-------------------------------	---------------------------

Description

Create a citation string from package specific BibTeX entries, suitable to be used in Rd files. The entries are looked in a file named REFERENCES.bib in the package's root directory (i.e. `inst/` in development mode).

Usage

```
packageReference(key, short = FALSE, PACKAGE = NULL)
```

Arguments

<code>key</code>	character vector of BibTeX keys
<code>short</code>	logical that indicates if the reference should be shorten as First Author et al. if it has more than one author.
<code>PACKAGE</code>	package in which the BiBTeX entry is defined.

Value

a character string containing the text formatted BibTeX entries

<code>packageRegistry</code>	<i>Package Registry</i>
------------------------------	-------------------------

Description

`packageRegistry` provides ways to create query package specific registries.

Usage

```
packageRegistry(
  regname = NULL,
  quiet = FALSE,
  entry = FALSE,
  update = !entry,
  package = toplevel(parent.frame())
)
```

```
packageRegistries(regname = NULL, package = NULL, primary = FALSE)
```

```
hasPackageRegistry(regname = NULL, package)
```

```
setPackageRegistry(
  regname,
  regobj,
  description = "",
  entrydesc = NA,
  ...,
  package = toplevel(parent.frame()),
  overwrite = FALSE
)
```

```
setPackageRegistryEntry(
  regname,
  key,
  ...,
  overwrite = FALSE,
  verbose = FALSE,
  where = toplevel(parent.frame()),
  msg = NULL
)
```

Arguments

regname	Name of a sub-registry, used as its identifier.
quiet	a logical that indicates that one should return the (meta-)registry if it exists, or NULL otherwise, without throwing any error.
entry	logical that indicates if the corresponding meta registry entry should be directly returned, without any other processing.
update	logical that indicates if the package registry should be updated, by adding/removing entries from other loaded/unloaded packages.
package	package where to store or look for the registry.
primary	logical that indicates if only primary registries should be listed.
regobj	a registry object or a single character string that indicates the class of the objects that are stored in the sub-registry. See details for the list of the sub-registry's fields in this latter case.

description	short description line about the registry. It is recommended to provide such description as it makes clearer the purpose of the registry. This description is shown when the registry object is printed/formated/listed.
entrydesc	human readable description that is used in log messages when registering/removing entries.
...	named values used to set extra information about the new registry, that are stored in the corresponding fields of the meta-registry. Currently not used, as no extra field other than 'description' is defined.
overwrite	a logical that indicate if an existing registry with the same should be overwritten if it exists.
key	entry identifier.
verbose	a logical that indicates if verbosity should be toggle on.
where	package name or namespace that owns the registry.
msg	addon message to print at the end of the output log line, when verbose=TRUE.

Details

Package registries are organised in a meta-registry (a registry of registries) within a package's namespace. Each registry can be used to store sets of built-in or user-defined objects in an organised way, e.g. algorithms or datasets.

A package meta-registry is a `registry` object, whose entries are `registry` objects themselves. A sub-registry entry is defined by the following fields:

key The sub-registry's accession key/identifier (a character string).

regobj The sub-registry itself (a `registry` object)

description Human readable description of the purpose of the registry (a character string)

description Short human readable description of the type of entries (a character string)

package owner package, which is forced to be the package in which the meta registry is defined.

parent The name of the package that holds the parent registry, which we call the primary package. This field is non empty for cross-package registries, i.e. registries that derive from primary package's own registry. Their entries are defined when (lazy-)loading the dependent package's namespace.

Note that this function cannot be called from the global environment, but from a package namespace, e.g., when a package is lazy-loaded on installation or loaded via the function `load_all` from the `devtools` package.

Value

a `registry` object or NULL (see argument `quiet`).

Functions

- `packageRegistries`: lists registries from loaded packages.
- `hasPackageRegistry`: tells if a given package has a meta-registry or a given registry.

pkgmaker-deprecated *Deprecated Functions in pkgmaker*

Description

These functions have been deprecated and will be defunct in the next release.

Usage

```
requirePackage(pkg, ...)
```

Arguments

pkg	package name to load.
...	extra arguments

postponeAction *Postponing Actions*

Description

This function implement a mechanism to postpone actions, which can be executed at a later stage. This is useful when developing packages, where actions that need to be run in the `link{.onLoad}` function but can be defined close to their context.

Usage

```
postponeAction(
  expr,
  key = digest(tempfile()),
  group = NULL,
  envir = topns(strict = FALSE),
  verbose = getOption("verbose")
)
```

```
runPostponedAction(group = NULL, verbose = getOption("verbose"))
```

Arguments

expr	expression that define the action to postpone. Currently only functions are supported.
key	identifier for this specific action. It should be unique across the postponed actions from the same group.
group	optional parent action group. This enables to define meaningful sets of actions that can be run all at once.
envir	environment in which the action should be executed. Currently not used.
verbose	logical that toggles verbose messages.

Examples

```

opt <- options(verbose=2)

# define actions
postponeAction(function(){print(10)}, "print")
postponeAction(function(){print(1:10)}, "more")
postponeAction()
# execute actions
runPostponedAction()
runPostponedAction()

# restore options
options(opt)

```

quickinstall

Quick Installation of a Source Package

Description

Builds and install a minimal version of a package from its source directory.

Usage

```

quickinstall(
  path,
  destdir = NULL,
  vignettes = FALSE,
  force = TRUE,
  ...,
  lib.loc = if (!is.null(destdir)) TRUE
)

```

Arguments

path	path to the package source directory
destdir	installation directory. If NULL, the package is installed in the default installation library. If NA, the package is installed in a temporary directory, whose path is returned as a value.
vignettes	logical that indicates if the vignettes should be rebuilt and installed.
force	logical that indicates if the package should be installed even if a previous installation exists in the installation library.
...	extra arguments passed to R.CMD
lib.loc	library specification. If TRUE then the installation directory destdir is added to the default library paths. This can be usefull if dependencies are installed in this directory. If NULL, then the default library path is left unchanged.

Value

The path of the library where the package was installed.

R.exec

Executing R Commands

Description

Functions to execute R commands.

Usage

```
R.exec(..., lib.loc = NULL)
```

```
R.CMD(cmd, ...)
```

```
R.SHLIB(libname, ...)
```

Arguments

...	extra arguments that are concatenated and appended to the command.
lib.loc	logical that indicates if the current library locations should be used. If a character vector, then it is used as the library path specification.
cmd	command to run, e.g. ‘check’ or ‘INSTALL’.
libname	name of the output compiled library

Functions

- R.exec: executes a single R command via [system2](#).
- R.CMD: executes R CMD commands.
- R.SHLIB: executes R CMD SHLIB commands.

RdSection2latex

Format Rd Sections into LaTeX

Description

This function extract sections from Rd files and convert them into LaTeX code. This can be useful to include Rd text into vignettes, hence keeping them up to date.

Usage

```
RdSection2latex(topic, package, i = 1L, notitle = TRUE)
```

Arguments

topic	Rd topic
package	package in which to search the topic
i	index of the section to format
notitle	logical that indicates if the section's title should be removed

Example section

This is a nice section, with a bullet list:

- tata
- toto

Examples

```
RdSection2latex('RdSection2latex', package = 'pkgmaker')
```

read.yaml_section *Reads YAML Options Embedded into a File*

Description

Reads YAML Options Embedded into a File

Usage

```
read.yaml_section(section, file = "~/Rprofile", text = NULL)
```

Arguments

section	section name to lookup in the file. In the file this defined by paired tags " <code>#<section_name></code> ", " <code>#</section_name></code> " or a single tag " <code>#<section_name@file_path></code> " that redirect to a YAML file.
file	path to the file to parse. Default is to parse the user's <i>Rprofile</i> .
text	text to parse. If provided, then argument file is not used.

regfetch	<i>Finds an entry in a registry.</i>
----------	--------------------------------------

Description

This function provides extra control on how entries are queried from a [registry](#) object.

Usage

```
regfetch(
  regobj,
  ...,
  all = FALSE,
  error = TRUE,
  exact = FALSE,
  KEYS = NULL,
  verbose = FALSE,
  entry = FALSE,
  msg = NULL
)
```

```
pkgreg_fetch(regname, ..., msg = NULL, where = topenv(parent.frame()))
```

```
pkgreg_remove(
  regname,
  ...,
  msg = NULL,
  where = topenv(parent.frame()),
  quiet = FALSE
)
```

Arguments

regobj	a registry object
...	key value(s) to look up. If multiple indexes are used, then the primary key should come first.
all	logical to indicate if hidden keys (starting with a '.') should be returned and output in message.
error	a logical that indicates if an error should be thrown if the key has no match or multiple matches
exact	a logical that indicates if matching should be exact or partial. Note that if exact matches exist then they are returned, independently of the value of exact.
KEYS	alternative way of passing the key value(s). If not missing, then arguments in ... are discarded.
verbose	a logical that indicates if verbosity should be toggle on

entry	a logical that indicates if the
msg	a header to use in case of error.
regname	Name of a sub-registry, used as its identifier.
where	package name or namespace that owns the registry.
quiet	a logical that indicates if the operation should be performed quietly, without throwing errors or warnings.

Functions

- `pkgreg_fetch`: fetches entries in a package registry, as set up by `setPackageRegistry`. It loads the requested package registry and uses `regfetch` to retrieve data from it.
- `pkgreg_remove`: removes an entry from a package registry.

render_notes	<i>Renders rmarkdown Documents Using User Default Options</i>
--------------	---

Description

Renders rmarkdown Documents Using User Default Options

Usage

```
render_notes(
  input,
  output_format = NULL,
  output_options = NULL,
  ...,
  .config = NULL
)
```

Arguments

input	The input file to be rendered. This can be an R script (.R), an R Markdown document (.Rmd), or a plain markdown document.
output_format	The R Markdown output format to convert to. The option "all" will render all formats defined within the file. The option can be the name of a format (e.g. "html_document") and that will render the document to that single format. One can also use a vector of format names to render to multiple formats. Alternatively, you can pass an output format object (e.g. <code>html_document()</code>). If using NULL then the output format is the first one defined in the YAML frontmatter in the input file (this defaults to HTML if no format is specified there).
output_options	List of output options that can override the options specified in metadata (e.g. could be used to force <code>self_contained</code> or <code>mathjax = "local"</code>). Note that this is only valid when the output format is read from metadata (i.e. not a custom format object passed to <code>output_format</code>).

... other arguments passed to [render](#)

.config location of the default options (a YAML file). Default behaviour is to look for file '.rmarkdown.yaml' in the user's home directory, or, if missing, for a yaml section rmarkdown::render in the user's R profile.

See Also

[read.yaml_section](#)

reorder_columns *Reordering Columns*

Description

Reorders columns according to a preferred target order

Usage

```
reorder_columns(x, target, decreasing = FALSE)
```

Arguments

x an object with columns, such as a `matrix` or a `data.frame`, or from a class that support subsetting via `x[, i, drop = FALSE]` and has a method `colnames`.

target a character or named numeric vector that specifies the column preferred order. If a numeric vector, then its names are assumed to correspond to columns, and its values determine the target order – according to argument `decreasing`.

decreasing logical that indicates in which direction a numeric target vector should be ordered.

Details

Column names will be reordered so that their order match the one in `target`. Any column that does not appear in `target` will be put after those that are listed in `target`.

Value

an object of the same type and dimension

require.quiet	<i>Loading Packages</i>
---------------	-------------------------

Description

require.quiet silently requires a package, and qrequire is an alias to require.quiet.

Usage

```
require.quiet(...)
```

```
qrequire(...)
```

```
qlibrary(...)
```

```
mrequire(msg, package, lib.loc = NULL, quietly = FALSE)
```

Arguments

...	extra arguments passed to library or require .
msg	error message to use, to which is appended the string ' requires package <pkg>' to build the error message.
package	name of the package to load.
lib.loc	a character vector describing the location of R library trees to search through, or NULL. The default value of NULL corresponds to all libraries currently known to .libPaths() . Non-existent library trees are silently ignored.
quietly	a logical. If TRUE, no message confirming package attaching is printed, and most often, no errors/warnings are printed if package attaching fails.

Functions

- [qlibrary](#): silently loads a package.
- [mrequire](#): tries loading a package with base [require](#) and stops with a – custom – error message if it fails to do so.

See Also

Other require: [irequire\(\)](#)

Examples

```
mrequire('Running this example', 'stringr')
try( mrequire('Doing impossible things', 'notapackage') )
```

requireRUnit	<i>Load RUnit Compatible Package</i>
--------------	--------------------------------------

Description

Loads the package responsible for the implementation of the RUnit framework, choosing amongst 'RUnitX', 'svUnit' and 'RUnit'.

Usage

```
requireRUnit(...)
```

Arguments

... arguments not used.

Value

nothing

rnw	<i>Utilities for Vignettes</i>
-----	--------------------------------

Description

rnw provides a unified interface to run vignettes that detects the type of vignette (Sweave or knitr), and which Sweave driver to use (either automatically or from an embedded command `\VignetteDriver` command).

Usage

```
rnw(x, file = NULL, ..., raw = FALSE)
```

```
isManualVignette()
```

```
as.rnw(x, ..., load = TRUE)
```

```
rnwCompiler(x, verbose = TRUE)
```

```
rnwWrapper(x, verbose = TRUE)
```

```
rnwDriver(x)
```

```
rnwIncludes(x)
```

```
rnwChildren(x)
```

```

vignetteMakefile(
  package = NULL,
  skip = NULL,
  print = TRUE,
  template = NULL,
  temp = FALSE,
  checkMode = isCHECK() || vignetteCheckMode(),
  user = NULL,
  tests = TRUE
)

compactVignettes(paths, ...)

```

Arguments

x	vignette source file specification as a path or a rnw object.
file	output file
...	extra arguments passed to <code>as.rnw</code> that can be used to force certain building parameters.
raw	a logical that indicates if the raw result for the compilation should be returned, instead of the result file path.
load	logical to indicate if all the object's properties should be loaded, which is done by parsing the file and looking up for specific tags.
verbose	logical that toggles verbosity
package	package name. If <code>NULL</code> , a <code>DESCRIPTION</code> file is looked for one directory up: this is meant to work when building a vignette directly from a package's 'vignettes' sub-directory.
skip	Vignette files to skip (basename).
print	logical that specifies if the path should be printed or only returned.
template	template Makefile to use. The default is to use the file "vignette.mk" shipped with the package pkgmaker and can be found in its install root directory.
temp	logical that indicates if the generated makefile should use a temporary filename (<code>TRUE</code>), or simply named "vignette.mk"
checkMode	logical that indicates if the vignettes should be generated as in a CRAN check (<code>TRUE</code>) or in development mode, in which case <code>pdflatex</code> , <code>bibtex</code> , and, optionally, <code>qpdf</code> are required.
user	character vector containing usernames that enforce <code>checkMode=TRUE</code> , if the function is called from within their session.
tests	logical that enables the compilation of a vignette that gathers all unit test results. Note that this means that all unit tests are run before generating the vignette. However, unit tests are not (re)-run at this stage when the vignettes are built when checking the package with R CMD check.
paths	A character vector of paths to PDF files, or a length-one character vector naming a directory, when all '.pdf' files in that directory will be used.

Functions

- `isManualVignette`: tells if a vignette is being run through the function `runVignette` of **pkgmaker**, allowing disabling behaviours not allowed in package vignettes that are checked via R CMD check.
- `as.rnw`: creates a S3 `rnw` object that contains information about a vignette, e.g., source filename, driver, fixed included files, etc..
- `rnwCompiler`: tries to detect the vignette compiler to use on a vignette source file, e.g., [Sweave](#) or [knitr](#).
- `rnwWrapper`: tries to detect the type of vignette and if it is meant to be wrapped into another main file.
- `rnwDriver`: tries to detect Sweave driver to use on a vignette source file, e.g., `SweaveCache`, `highlight`, etc..
- `rnwIncludes`: detects fixed includes, e.g., image or pdf files, that are required to build the final document.
- `rnwChildren`: detects included vignette documents and return them as a list of vignette objects.
- `vignetteMakefile`: returns the path to a generic makefile used to make vignettes.
- `compactVignettes`: compacts vignette PDFs using either `gs_quality='none'` or `'ebook'`, depending on which compacts best (as per CRAN check criteria).

Rversion

Complete R version

Description

Returns the complete R version, e.g. 2.15.0

Usage

```
Rversion()
```

Examples

```
Rversion()
```

setBiocMirror	<i>Setting Mirrors and Repositories</i>
---------------	---

Description

setBiocMirror sets all Bioconductor repositories (software, data, annotation, etc.) so that they are directly available to [install.packages](#). It differs from [chooseBioCmirror](#) in that it effectively enables the repositories.

Usage

```
setBiocMirror(  
  url = "http://www.bioconductor.org",  
  version = NULL,  
  unique = TRUE  
)  
  
getBiocMirror()  
  
getBiocRepos(url = "http://www.bioconductor.org", version = NULL)  
  
setCRANMirror(url = CRAN, unique = TRUE)
```

Arguments

url	or Bioconductor mirror url
version	version number
unique	logical that indicate if duplicated urls or names should be removed.

Functions

- getBiocMirror: is a shortcut for `getOption('BioC_mirror')`, which returns the current Bioconductor mirror as used by `biocLite`.
- getBiocRepos: returns urls to all Bioconductor repositories on a given mirror.
- setCRANMirror: sets the preferred CRAN mirror.

setClassRegistry	<i>Automatic S4 Class for Registry Entries</i>
------------------	--

Description

Automatic S4 Class for Registry Entries

Usage

```
setClassRegistry(registry, Class, ...)
```

Arguments

registry	a registry object
Class	name of the class to generate
...	extra arguments passed to <code>setClass</code> .

```
setPackageExtraHandler
```

Install/Run Extra Things After Standard Package Installation

Description

These functions define a framework to register actions for which default sets of arguments can be defined when (lazy-)loading a package, and run later on, e.g., after the package is installed using dedicated commands.

`setPackageExtraHandler` defines main action handler functions, for which actions are defined as a set of arguments and registered using `setPackageExtra`.

Usage

```
setPackageExtraHandler(handler, fun, ...)
```

```
packageExtraHandler(handler = NULL, ...)
```

```
setPackageExtra(handler, extra, ...)
```

```
packageExtra(handler = NULL, extra = NULL, package = NULL, .wrap = FALSE)
```

```
packageExtraRunner(handler)
```

```
install.extras(  
  package,  
  extra = NULL,  
  handler = NULL,  
  ...,  
  .verbose = getOption("verbose")  
)
```

```
install.extrapackages(  
  package,  
  extra = NULL,  
  handler = NULL,  
  ...,
```

```

    .verbose = getOption("verbose")
  )

```

Arguments

handler	name of a handler, e.g, 'install'. It must be unique across all handlers registered by any other packages.
fun	handler function that will be called with the arguments registered with <code>packageExtra(name, ...)</code>
...	extra arguments passed to internal function calls. In <code>packageExtraHandler</code> , these are passed to pkgreg_fetch . In <code>setPackageExtra</code> , these define default arguments for the handler function. These are overwritten by arguments in the call to runner function if any.
extra	name of the extra action.
package	package name where to store/look for the internal registries. End users should not need to use this argument.
.wrap	logical that indicates if a function that runs the extra action should be returned or only the default arguments
.verbose	logical that indicates if verbose messages about the extra actions being run should be displayed.

Value

the runner function associated with the newly registered handler, as built by `packageExtraRunner`.

Functions

- `packageExtraHandler`: retrieves a given handler from the registry.
- `setPackageExtra`: registers extra actions for a given handler.
For example, calling `setPackageExtra('install', pkgs='non_CRAN_pkg', repos='http://non-standard-repo')` in a source file of package 'myPkg' registers the call `install.packages('non_CRAN_pkg', repos='http://non-standard-repo')` in a registry internal to the package. All calls to `setPackageExtra('install', ...)` can then be run by the user, as a post installation step via `install.extrapackages('myPkg', ...)`.
- `packageExtra`: retrieve a given extra action, either as its registry entry, or as a function that would perform the given action.
- `packageExtraRunner`: defines a function to run all or some of the actions registered for a given handler in a given package. For example, the function `install.extrapackages` is the runner defined for the extra handler 'install' via `packageExtraRunner('install')`.
- `install.extras`: runs all extra actions registered for a given package.
- `install.extrapackages`: install sets of packages that can enhance a package, but may not be available from CRAN.
It is defined as the extra handler for the extra action handler 'install.packages'. All arguments in ... are passed to [install.packages](#). By default, packages that are already installed are not re-installed. An extra argument `force` allows to force their installation. The packages are loaded if their installation is successful.

setupPackageOptions *Package Specific Options*

Description

The following functions to access/set the options from the set are assigned in `envir`:

Usage

```
setupPackageOptions(
  ...,
  NAME = NULL,
  ENVIR = topenv(parent.frame()),
  RESET = isLoadingNamespace()
)
```

Arguments

...	a single named list or named arguments that provide the default options and their values.
NAME	name of the set of options. This is used as a prefix for the name of the associated global option: <code>package:<name></code> .
ENVIR	environment where the option wrapper functions will be defined. No function is defined if <code>ENVIR=NULL</code> .
RESET	a logical that indicates whether the option set should overwrite one that already exists if necessary. The default is <code>FALSE</code> (i.e. no reset), except when loading a namespace, either from an installed package or a development package – with devtools. If <code>FALSE</code> , an error is thrown if trying to setup options with the same name.

Details

- `<subset>Options`
- `<subset>GetOption`

simpleRegistry *Simple Package Registry*

Description

Simple Package Registry

Usage

```
simpleRegistry(name, envir = topenv(parent.frame()), verbose = FALSE)
```

Arguments

name	name of the registry object, with which it will be assigned in <code>envir</code> .
envir	environment where to store the registry object. Defaults to the caller's top environment.
verbose	logical that toggle a verbose message when the object is first created.

source_files *Source Multiple Files*

Description

Vectorised version of `source`.

Usage

```
source_files(x, pattern = NULL, ...)
```

Arguments

x	character vector containing filenames
pattern	an optional regular expression . Only file names which match the regular expression will be returned.
...	extra arguments passed to source .

str_diff *Finding Differences Between Strings*

Description

Computes which characters differ between two strings.

Usage

```
str_diff(x, y)
```

Arguments

x	a single string
y	a single string

Value

an integer vector containing the index of all mis-matched characters in the first string.

Examples

```
# strings to compare
x <- "once upon a time"
y <- "once upon a time there was"
z <- "once upon two times"

# diff: x - y
d <- str_diff(x, y)
d
str(d)

# other comparisons
str_diff(y, x)
str_diff(x, x)
str_diff(x, z)
str_diff(y, z)
```

str_out

Formatting Utilities

Description

str_out formats character vectors for use in show methods or error/warning messages.

Usage

```
str_out(
  x,
  max = 3L,
  quote = is.character(x),
  use.names = FALSE,
  sep = ", ",
  total = FALSE
)

str_desc(object, exdent = 0L)

str_fun(object)

str_class(x, max = Inf, ...)

str_pkg(pkg, lib.loc = NULL)

str_md5sum(x)

str_hash(x, algo = "md5")
```

```
str_dim(x, dims = dim(x))
```

```
str_bs(x)
```

Arguments

x	character vector
max	maximum number of values to appear in the list. If x has more elements than max, a "... " suffix is appended.
quote	a logical indicating whether the values should be quoted with single quotes (defaults) or not.
use.names	a logical indicating whether names should be added to the list as NAME=VAL, ... or not (default).
sep	separator character
total	logical that indicates if the total number of elements should be appended to the formatted string as "'a', ..., 'z' (<N> total)".
object	an R object
exdent	extra indentation passed to str_wrap, and used if the output should spread over more than one lines.
...	other arguments passed to str_out.
pkg	package name
lib.loc	path to a library of R packages
algo	The algorithms to be used; currently available choices are md5, which is also the default, sha1, crc32, sha256, sha512, xxhash32, xxhash64, murmur32 and spookyhash.
dims	a numeric vector of dimensions. Default is to use the input object dimensions (via function dims())

Value

a single character string

Functions

- str_desc: builds formatted string from a list of complex values.
- str_fun: extracts and formats a function signature. It typically formats the output capture.output(args(object)).
- str_class: outputs the class(es) of an object using str_out.
- str_pkg: formats a package name and version
- str_md5sum: computes md5sum on character vector using md5sum.
- str_hash: computes hash of a character vector using digest.
- str_dim: builds a string that describes the dimension of an object, in the form n x m for 2D-objects, n x m x p for 3D-objects, and so on.
- str_bs: substitutes backspace characters (\b) to produce a character string as it would be displayed in the console.

Author(s)

Renaud Gaujoux

str_bs was adapted from a proposal from Yihui Xie.

Examples

```
x <- letters[1:10]
str_out(x)
str_out(x, 8)
str_out(x, Inf)
str_out(x, quote=FALSE)
str_out(x, total = TRUE)

str_fun(install.packages)
str_class(matrix())

# Backspace substitution
str_bs("abc")
str_bs("abc\b")
str_bs("abc\b\b")
str_bs("abc\bd")
str_bs("abc\b\bde\b")

# more complex example
x <- "\bab\nc\bd\n\babc\b\bd"
cat(x, "\n")
y <- str_bs(x)
y
cat(y, "\n")
```

sVariable

Global Static Variable

Description

sVariable defines a function that acts as a global static variable.

Usage

```
sVariable(default = NULL)
```

Arguments

default default value for the static variable.

Examples

```
# define variable
x <- sVariable(1)
# get value (default)
x()
# set new value: return old value
old <- x(3)
old
# get new value
x()
```

Sys.getenv_value	<i>System Environment Variables</i>
------------------	-------------------------------------

Description

System Environment Variables

Usage

```
Sys.getenv_value(name, raw = FALSE)
```

Arguments

name	variable name as a character string.
raw	logical that indicates if one should return the raw value or the conversion of any false value to FALSE.

Value

the value of the environment variable as a character string or NA is the variable is not defined **at all**.

Examples

```
# undefined returns FALSE
Sys.getenv_value('TOT0')
# raw undefined returns NA
Sys.getenv_value('TOT0', raw = TRUE)

Sys.setenv(TOT0='bla')
Sys.getenv_value('TOT0')

# anything false-like returns FALSE
Sys.setenv(TOT0='false'); Sys.getenv_value('TOT0')
Sys.setenv(TOT0='0'); Sys.getenv_value('TOT0')
```

```
# cleanup
Sys.unsetenv('TOTO')
```

sys_call_stack	<i>System Call Stack Utilities</i>
----------------	------------------------------------

Description

System Call Stack Utilities

Usage

```
sys.function_digest(n = NULL)

sys.function_nframe(fun)

sys.function_frame(fun)

sys.source_file()
```

Arguments

n	a single frame
fun	the function object to find in the call stack.

Functions

- `sys.function_digest`: computes digest hash for each function in the call stack.
- `sys.function_nframe`: returns the index of the frame that calls a given function.
- `sys.function_frame`: returns the frame that calls a given function.
- `sys.source_file`: returns path to the script that is being sourced either by `base::source` or `base::sys.source`.

testRversion	<i>Testing R Version</i>
--------------	--------------------------

Description

Compares current R version with a given target version, which may be useful for implementing version dependent code.

Usage

```
testRversion(x, test = 1L)
```

Arguments

x	target version to compare with.
test	numeric value that indicates the comparison to be carried out. The comparison is based on the result from <code>utils::compareVersion(R.version,x)</code> : <ul style="list-style-type: none"> • 1: is R.version > x? • 0: is R.version = x? • -1: is R.version < x?

Value

a logical

Examples

```
testRversion("2.14")
testRversion("2.15")
testRversion("10")
testRversion("10", test = -1)
testRversion("< 10")
testRversion(Rversion())
testRversion(paste0('=', Rversion()))
```

unit.test

Embedded Unit Tests

Description

The function `unit.test` provides a way to write unit tests embedded within package source files. These tests are stored and organised in the package namespace, and can be run using the unified interface provided by the function `link{utest}`. Both `Runit` and `testthat` tests are supported – and automatically detected.

Usage

```
unit.test(x, expr, framework = NULL, envir = parent.frame())
```

Arguments

x	single character string used as test identifier/label
expr	expression containing the actual test commands. It is not evaluated, but only stored in the package namespace.
framework	Unit test framework
envir	the definition environment of object x.

Value

a test function with no arguments that wrapping around expr

unlist_	<i>Flatten a List Conserving Names</i>
---------	--

Description

unlist2 is a replacement for `base::unlist` that does not mangle the names.

Usage

```
unlist_(x, recursive = TRUE, use.names = TRUE, what.names = "inherited")
```

Arguments

x	See ?unlist.
recursive	See ?unlist.
use.names	See ?unlist.
what.names	"inherited" or "full".

Details

Use this function if you don't like the mangled names returned by the standard `unlist` function from the base package. Using `unlist` with annotation data is dangerous and it is highly recommended to use `unlist_` instead.

Author(s)

Herve Pages

Source

Bioconductor AnnotationDbi::unlist2

Examples

```
x <- list(A=c(b=-4, 2, b=7), B=3:-1, c(a=1, a=-2), C=list(c(2:-1, d=55), e=99))
unlist(x)
unlist_(x)

# annotation maps (as in AnnotationDbi objects)
egids2pbids <- list('10' = 'a', '100' = c('b', 'c'), '1000' = c('d', 'e'))
egids2pbids

unlist(egids2pbids) # 1001, 1002, 10001 and 10002 are not real
# Entrez ids but are the result of unlist()
```

```

                                # mangling the names!
unlist_(egids2pbids) # much cleaner! yes the names are not unique
                                # but at least they are correct...

```

```

unlist_with_sep      Flattens All List Levels Using Separated Names

```

Description

Flattens All List Levels Using Separated Names

Usage

```
unlist_with_sep(x, sep = "/", use.names = TRUE, depth = Inf)
```

Arguments

x	a list object, usually containing other lists – of lists.
sep	character string used to separate each component of the final element names.
use.names	logical that indicates if the original names of each the successive nested list elements should be used to build the final names of the result list.
depth	maximum number of levels to unlist. Root level is 1L.

Examples

```

x <- list(X = list(a = 1
                  , b = list(b.1 = 2
                            , b.2 = list(b.2.1 = 4, b.2.2 = data.frame())
                            , b.3 = 3)
                  , c = matrix()))
unlist_with_sep(x)
unlist_with_sep(x, '###')

```

```

userData      User Data Directory userData returns the path to a local direc-
              tory/file where package-related user data can be stored. Note that a
              base directory is always created if necessary (see details).

```

Description

The package-specific user data base directory is the sub-directory *R-data/*, located in the user's home or within a directory defined by global option 'userData.path'.

If in interactive mode, and the base directory does not exist yet, the user is asked if it should be created in his home directory. Otherwise, or if the user does not allow the creation in his home, this directory is created in the current R session's temporary directory.

Usage

```
userData(..., create = NULL, package = toplevel(parent.frame()))
```

Arguments

`...` path parts passed to `file.path` to be appended to the main path.

`create` logical that indicates if the **base** directory should be created if it does not exist. Note that directories – and files – under the base directory are not automatically created. The user should therefore care of it in the caller function if necessary. If `create=TRUE`, then the base directory is forced to be created in the user's home directory. If `create=FALSE`, then the base directory is never created. See also section *Details*.

`package` name of the package associated with the user data path. It is used to prefix the path, within the user R data directory.

See Also

[tempdir](#)

userIs

Checking R User

Description

Tests if the current R user is amongst a given set of users.

Usage

```
userIs(user)
```

Arguments

`user` the usernames to check for, as a character vector.

using_something	<i>Execute code in temporarily altered environment.</i>
-----------------	---

Description

These functions were extracted from the **devtools** package to make them available without a dependency to **devtools**.

Usage

```
using_envvar(new, code, action = "replace")  
  
using_env(new, code)  
  
using_locale(new, code)  
  
using_collate(new, code)  
  
using_dir(new, code)  
  
using_libpaths(new, code)  
  
using_lib(new, code)  
  
using_options(new, code)  
  
using_par(new, code)  
  
using_path(new, code, add = TRUE, prepend = FALSE)
```

Arguments

new	values for setting
code	code to execute in that environment
action	(for <code>using_envvar</code> only): should new values "replace", "suffix", "prefix" existing environmental variables with the same name.
add	Combine with existing values? Currently for <code>using_path</code> only. If FALSE all existing paths are overwritten, which you don't usually want.
prepend	logical that indicates if the new paths should be added in front of the current ones.

Details

- `using_dir`: working directory
- `using_collate`: collation order

- `using_envvar`: environmental variables
- `using_libpaths`: library paths, replacing current libpaths
- `using_lib`: library paths, prepending to current libpaths
- `using_locale`: any locale setting
- `using_options`: options
- `using_path`: PATH environment variable
- `using_par`: graphics parameters

Deprecation

`using_env` will be deprecated in devtools 1.2 and removed in devtools 1.3

Author(s)

Hadley Wickham

Examples

```
getwd()
using_dir(tempdir(), getwd())
getwd()

Sys.getenv("HADLEY")
using_envvar(c("HADLEY" = 2), Sys.getenv("HADLEY"))
Sys.getenv("HADLEY")

using_envvar(c("A" = 1),
  using_envvar(c("A" = 2), action = "suffix", Sys.getenv("A"))
)
```

utest

Running Unit Tests

Description

Run unit tests in a variety of settings. This is still **very** experimental.

Usage

```
utest(x, ...)
```

S4 method for signature ``function``

```
utest(x, run = TRUE)
```

S4 method for signature 'character'

```
utest(
  x,
```

```

    filter = "^runit.+\\.\\. [rR]$",
    fun = "^test\\.\\. ",
    ...,
    testdir = "tests",
    framework = c("RUnit", "testthat"),
    quiet = Sys.getenv("RCMDCHECK") != "FALSE",
    lib.loc = NULL
)

## S4 method for signature 'RUnitTestSuite'
utest(x, ..., quiet = FALSE, outdir = NULL)

```

Arguments

x	object to which a unit test is attached
...	extra arguments to allow extensions and are passed to the unit framework running functions.
run	a logical that indicates if the unit test should be run
filter	pattern to match files that contain the definition of the unit tests functions to run.
fun	patter to match the test functions to run.
testdir	directory where to look for the test files
framework	unit test framework
quiet	a logical that indicates if the tests should be run silently
lib.loc	path to a library where installed packages are searched for. Used is of the form x='package:*'.
outdir	output directory

Methods (by class)

- function: Run the unit test assoicated to a function.
- character: Run a package test suite
- RUnitTestSuite: Runs a RUnit test suite

utestFramework	<i>Inferring Unit Test Framework</i>
----------------	--------------------------------------

Description

Inferring Unit Test Framework

Usage

```
utestFramework(x, eval = FALSE)
```

Arguments

x an filename, a function or the body of a function
 eval a logical that indicates if the value of x should be used.

Value

the name of the framework as a character string or NULL if it could not be detected.

utestPath	<i>Unit Tests Result Directory</i>
-----------	------------------------------------

Description

Returns the path to the directory where the results of unit tests are stored. This path is used by `utest` to save unit test results, which are read by `makeUnitVignette` to update the unit test vignette when running R CMD check.

Usage

```
utestPath(...)
```

Arguments

... extra arguments passed to `packagePath`, e.g., package.

winbuild	<i>Build a Windows Binary Package</i>
----------	---------------------------------------

Description

Build a Windows Binary Package

Usage

```
winbuild(path, outdir = ".", verbose = TRUE)
```

Arguments

path path to a source or already installed package
 outdir output directory
 verbose logical or numeric that indicates the verbosity level

Value

Invisibly returns the full path to the generated zip file.

Examples

```
## Not run:

# from source directory
winbuild('path/to/package/source/dir/')
# from tar ball
winbuild('PKG_1.0.tar.gz')

## End(Not run)
```

`write.bib`*Defunct Functions in pkgmaker*

Description

These functions have been defunct or superseded by other functions.

Usage

```
write.bib(...)
```

Arguments

```
...          extra arguments
```

`write.pkgbib`*Generate a Bibtex File from Package Citations*

Description

Generates a Bibtex file from a list of packages or all the installed packages. It is useful for adding relevant citations in Sweave documents.

Usage

```
write.pkgbib(
  entry = NULL,
  file = "Rpackages.bib",
  prefix = "",
  append = FALSE,
  verbose = TRUE
)
```

Arguments

entry	a <code>bibentry</code> object or a character vector of package names. If NULL, then the list of all installed packages is used.
file	output Bibtex file. It can be specified as a filename (as a single character string), NULL for stdout, or a <code>link{connection}</code> object. If file is a character string, an extension '.bib' is appended if not already present.
prefix	character string to prepend to the generated packages' Bibtex key.
append	a logical that indicates that the Bibtex entries should be added to the file. If FALSE (default), the file is overwritten.
verbose	a logical to toggle verbosity. If file=NULL, verbosity is forced off.

Details

Multiple citations are handled by adding a numeric suffix to the Bibtex key (other than the first/main citation) as "`<pkgname>%i`" (e.g. pkg, pkg2, pkg3).

Value

the list of Bibtex objects – invisibly.

Note

The Old version of this function `write.bib` has now been integrated by Romain Francois in the `bibtex` package.

Author(s)

Renaud Gaujoux, based on the function `Rpackages.bib` from Achim Zeileis (see *References*).

References

Creating bibtex file of all installed packages? Achim Zeileis. R-help mailing list. <https://stat.ethz.ch/pipermail/r-help/2009-December/415181.html>

See Also

`link{connection}`, `link{bibentry}`

Examples

```
write.pkgbib(c('rbibutils', 'utils', 'tools'), file='references')
bibs <- rbibutils::readBib('references.bib', "UTF-8")
write.pkgbib(bibs, 'references2.bib')
bibs2 <- rbibutils::readBib('references.bib', "UTF-8")
identical(bibs, bibs2)

# write to stdout()
```

```
write.pkgbib(c('rbibutils', 'utils', 'tools'), file=NULL)

# clean up
unlink(c('references.bib', 'references2.bib'))
```

writeUnitVignette	<i>Writes Unit Tests Vignette</i>
-------------------	-----------------------------------

Description

Writes a vignette that contains the results from running unit test suites.

Usage

```
writeUnitVignette(pkg, file, results = NULL, check = FALSE)
```

Arguments

pkg	Package name
file	Output Sweave (.Rnw) file
results	result file or output character vector
check	logical that indicates the call was made from R CMD check, in which case the vignette is updated only if results of unit tests can be found in the unit test output directory, where they would have been generated by utest .

Index

- * **datasets**
 - CRAN, 12
- * **require**
 - irequire, 23
 - require.quiet, 59
- .libPaths, 6, 59
- .options (mkoptions), 39
- .silenceF, 4
- [[.package_options (option_symlink), 43
- \$, 16

- add_lib, 6
- addnames, 5
- addNamespaceExport
 - (getLoadingNamespace), 19
- addToLogger, 6
- allFormals (extractLocalFun), 17
- alphacol, 7
- as.package, 48
- as.package_options (option_symlink), 43
- as.rnw (rnw), 60
- as_package (packageEnv), 46
- askUser, 8
- attr_mode (ExposeAttribute), 16
- attr_mode<- (ExposeAttribute), 16

- base::source, 72
- base::sys.source, 72
- base::unlist, 74
- bibentry, 82
- bibtex, 9

- cgetAnywhere, 10
- charmap, 10
- checkWarning, 11
- chooseBioCmirror, 63
- citecmd, 11
- colors, 8
- compactVignettes (rnw), 60
- compile_src, 12

- CRAN, 12

- data, 45
- devtools::load_all, 34
- digest, 69
- digest::digest, 13
- digest_function, 13

- environment, 45
- exitCheck, 13
- expand_dots (expand_list), 14
- expand_list, 14
- ExposeAttribute, 16
- extractLocalFun, 17

- factor2character, 17
- file.path, 47, 76
- file_extension, 18
- find.package, 47, 48
- find_devpackage, 18
- formals, 17

- get0, 19
- getAnywhere, 10
- getBiocMirror (setBiocMirror), 63
- getBiocRepos (setBiocMirror), 63
- getLoadingNamespace, 19
- getOption, 39
- gettext, 39
- gfile, 20
- graphics-utils, 20

- hasArg, 21
- hasArg2, 21
- hasEnvar, 22
- hasNames (is_something), 26
- hasPackageRegistry (packageRegistry), 48
- hook_backspace (knit_ex), 28
- hook_toggle (knit_ex), 28
- hook_try (knit_ex), 28

- install.extrapackages
 - (setPackageExtraHandler), 64
- install.extras
 - (setPackageExtraHandler), 64
- install.packages, 12, 23, 63, 65
- inSweave, 22
- irequire, 23, 59
- is.dir (is_something), 26
- is.file (is_something), 26
- is.verbose (lverbose), 35
- is_NA (is_something), 26
- is_option_symlink (option_symlink), 43
- is_package_path, 25
- is_something, 26
- isCHECK (isCRANcheck), 24
- isCRAN_timing (isCRANcheck), 24
- isCRANcheck, 24
- isDevNamespace (getLoadingNamespace), 19
- isFALSE (is_something), 26
- isInteger (is_something), 26
- isLoadingNamespace
 - (getLoadingNamespace), 19
- isManualVignette (rnw), 60
- isNamespace, 20
- isNamespaceLoaded, 20
- isNamespaceLoaded2
 - (getLoadingNamespace), 19
- isNumber (is_something), 26
- isPackageInstalled (packageEnv), 46
- isReal (is_something), 26
- isString (is_something), 26
- isTRUE, 27
- iterCount, 27

- knit, 28
- knit2html, 28
- knit_ex, 28
- knitr, 62
- knitr::current_input, 38
- knitr::knit_hooks, 28

- latex_bibliography (latex_preamble), 30
- latex_preamble, 30, 38
- ldata, 32
- ldata (packageData), 45
- libname (list.libs), 33
- library, 59
- library_project (load_project), 34
- list.data, 32
- list.files, 33
- list.libs, 33
- listPackageOptions (option_symlink), 43
- lmessage (lverbose), 35
- load_all, 35, 46, 50
- load_all_file, 34
- load_project, 34
- loadingNamespaceInfo, 19
- log_append (lverbose), 35
- lsilent (lverbose), 35
- lverbose, 35

- make_vignette_auxfiles, 38
- makeFakeVignette, 37
- makeUnitVignette, 37, 80
- md5sum, 69
- message, 39
- messagef, 38
- mfrow (graphics-utils), 20
- mkoptions, 39
- mrequire (require.quiet), 59

- new, 40
- new2, 40
- ns_get (getLoadingNamespace), 19

- on.exit, 13
- oneoffVariable, 41
- onLoad, 42
- onUnload (onLoad), 42
- option_symlink, 43
- option_symlink_target (option_symlink), 43
- options, 39, 40, 43
- order, 44
- orderVersion, 44

- package_bibliography (bibtex), 9
- packageData, 45
- packageEnv, 46
- packageExtra (setPackageExtraHandler), 64
- packageExtraHandler
 - (setPackageExtraHandler), 64
- packageExtraRunner
 - (setPackageExtraHandler), 64
- packageName, 47
- packageName (packageEnv), 46
- packageOptions (option_symlink), 43

- packagePath, [80](#)
- packagePath (packageEnv), [46](#)
- packageReference, [48](#)
- packageReferenceFile (bibtex), [9](#)
- packageRegistries (packageRegistry), [48](#)
- packageRegistry, [48](#)
- packageTestEnv, [51](#)
- palette, [8](#)
- par, [20](#)
- parsePackageCitation, [51](#)
- pdf, [20](#)
- pkgmaker-defunct (write.bib), [81](#)
- pkgmaker-deprecated, [52](#)
- pkgreg_fetch, [65](#)
- pkgreg_fetch (regfetch), [56](#)
- pkgreg_remove (regfetch), [56](#)
- png, [20](#)
- postponeAction, [52](#)

- qlibrary (require.quiet), [59](#)
- require (require.quiet), [59](#)
- quickinstall, [53](#)

- R.CMD, [53](#)
- R.CMD (R.exec), [54](#)
- R.exec, [54](#)
- R.SHLIB (R.exec), [54](#)
- RdSection2latex, [54](#)
- read.yaml_section, [55, 58](#)
- regfetch, [56](#)
- registry, [49, 50, 56](#)
- regular expression, [67](#)
- render, [58](#)
- render_notes, [57](#)
- reorder_columns, [58](#)
- require, [23, 59](#)
- require.quiet, [23, 24, 59](#)
- requirePackage (pkgmaker-deprecated), [52](#)
- requireRUnit, [60](#)
- rgb, [8](#)
- rnw, [60](#)
- rnwChildren (rnw), [60](#)
- rnwCompiler (rnw), [60](#)
- rnwDriver (rnw), [60](#)
- rnwIncludes (rnw), [60](#)
- rnwWrapper (rnw), [60](#)
- runPostponedAction (postponeAction), [52](#)
- Rversion, [62](#)

- setBiocMirror, [63](#)
- setClass, [64](#)
- setClassRegistry, [63](#)
- setCRANMirror (setBiocMirror), [63](#)
- setPackageExtra
 (setPackageExtraHandler), [64](#)
- setPackageExtraHandler, [64](#)
- setPackageRegistry, [57](#)
- setPackageRegistry (packageRegistry), [48](#)
- setPackageRegistryEntry
 (packageRegistry), [48](#)
- setupPackageOptions, [40, 66](#)
- simpleRegistry, [66](#)
- sortVersion (orderVersion), [44](#)
- source, [67](#)
- source_files, [67](#)
- sprintf, [39](#)
- str_bs (str_out), [68](#)
- str_class (str_out), [68](#)
- str_desc (str_out), [68](#)
- str_diff, [67](#)
- str_dim (str_out), [68](#)
- str_fun (str_out), [68](#)
- str_hash (str_out), [68](#)
- str_md5sum (str_out), [68](#)
- str_ns (packageEnv), [46](#)
- str_out, [68, 69](#)
- str_pkg (str_out), [68](#)
- sVariable, [70](#)
- Sweave, [62](#)
- sys.function_digest (sys_call_stack), [72](#)
- sys.function_frame (sys_call_stack), [72](#)
- sys.function_nframe (sys_call_stack), [72](#)
- Sys.getenv_value, [71](#)
- sys.source_file (sys_call_stack), [72](#)
- sys_call_stack, [72](#)
- system2, [54](#)

- tempdir, [76](#)
- testRversion, [72](#)
- topenv, [46](#)
- topns (packageEnv), [46](#)
- topns_name (packageEnv), [46](#)
- try, [28](#)

- unit.test, [73](#)
- unlist_, [74](#)
- unlist_with_sep, [75](#)
- userData, [75](#)

userIs, [76](#)
using_collate (using_something), [77](#)
using_dir (using_something), [77](#)
using_env (using_something), [77](#)
using_envvar (using_something), [77](#)
using_lib (using_something), [77](#)
using_libpaths (using_something), [77](#)
using_locale (using_something), [77](#)
using_options (using_something), [77](#)
using_par (using_something), [77](#)
using_path, [77](#)
using_path (using_something), [77](#)
using_something, [77](#)
utest, [24](#), [25](#), [37](#), [78](#), [80](#), [83](#)
utest, character-method (utest), [78](#)
utest, function-method (utest), [78](#)
utest, RUnitTestSuite-method (utest), [78](#)
utestFramework, [79](#)
utestPath, [80](#)
utils::bibentry, [9](#)
utils::data, [32](#)

vignetteMakefile (rnw), [60](#)
vmessage (lverbose), [35](#)

winbuild, [80](#)
wnote (messagef), [38](#)
write.bib, [81](#)
write.pkgbib, [81](#)
writeUnitVignette, [83](#)