

Package ‘seasonal’

April 18, 2022

Type Package

Title R Interface to X-13-ARIMA-SEATS

Version 1.9.0

Description Easy-to-use interface to X-13-ARIMA-SEATS, the seasonal adjustment software by the US Census Bureau. It offers full access to almost all options and outputs of X-13, including X-11 and SEATS, automatic ARIMA model search, outlier detection and support for user defined holiday variables, such as Chinese New Year or Indian Diwali. A graphical user interface can be used through the 'seasonalview' package. Uses the X-13-binaries from the 'x13binary' package.

Depends R (>= 2.15)

Imports x13binary

Suggests seasonalview (>= 0.1.3), testthat (>= 3.0.0), covr, knitr, rmarkdown, spelling

License GPL-3

URL <http://www.seasonal.website>

BugReports <https://github.com/christophsax/seasonal>

LazyData true

RoxygenNote 7.1.2

Encoding UTF-8

Config/testthat/edition 3

VignetteBuilder knitr

Language en-US

NeedsCompilation no

Author Christoph Sax [aut, cre] (<<https://orcid.org/0000-0002-7192-7044>>),
Dirk Eddelbuettel [ctb] (<<https://orcid.org/0000-0001-6419-907X>>)

Maintainer Christoph Sax <christoph.sax@gmail.com>

Repository CRAN

Date/Publication 2022-04-18 07:00:02 UTC

R topics documented:

seasonal-package	2
as.data.frame.seas	4
checkX13	5
cpi	5
easter	6
exp	6
final	7
fivebestmdl	8
genhol	9
identify.seas	12
iip	13
import.spc	14
import.ts	16
na.x13	17
out	18
outlier	19
plot.seas	20
predict.seas	22
seas	23
series	27
spc	34
SPECS	35
static	36
summary.seas	37
transformfunction	39
udg	40
unemp	42
update.seas	42
view	43
Index	45

 seasonal-package

seasonal: R interface to X-13ARIMA-SEATS

Description

seasonal is an asy-to-use interface to X-13-ARIMA-SEATS, the seasonal adjustment software by the US Census Bureau. It offers full access to almost all options and outputs of X-13, including X-11 and SEATS, automatic ARIMA model search, outlier detection and support for user defined holiday variables, such as Chinese New Year or Indian Diwali. A graphical user interface can be used through the **seasonalview** package. Uses the X-13-binaries from the **x13binary** package.

The best way to start is to have a look at the vignette:

```
vignette("seas")
```

Installation

Seasonal depends on the **x13binary** package, which downloads and installs the X-13 binaries. To install both packages, simply type to the R console:

```
install.packages("seasonal")
```

A startup message is given if the path to X-13 is specified manually. To suppress the message, use [suppressPackageStartupMessages\(\)](#).

Setting the X-13 path manually

Sometimes, you either cannot or don't want to rely on the binaries provided by **x13binary**:

- because you are on an unsupported system, like Solaris. If you manage to build X-13 on such a system, please let the developers of **x13binary** know.
- because you cannot run executable files in your R library folders, due to corporate IT policy.
- because you are using your own Fortran compilation of X-13ARIMA-SEATS.

Setting the path manually can be done as in previous versions of seasonal. In order to tell seasonal where to find the binary executables of X-13ARIMA- SEATS, the specific environmental variable X13_PATH needs to be set. This may be done during your active session in R:

```
Sys.setenv(X13_PATH = "YOUR_X13_DIRECTORY")
```

Exchange YOUR_X13_DIRECTORY with the path to your installation of X-13ARIMA- SEATS. You can always check your installation with:

```
checkX13()
```

If it works, you may want to set the environmental variable permanently, by adding the Sys.setenv line to one of your `.Rprofile` files. The easiest is to use the one located in your home directory, which can be written directly from R:

```
write('Sys.setenv(X13_PATH = "YOUR_X13_DIRECTORY")', file = "~/.Rprofile", append = TRUE)
```

If the file does not exist (by default), it will be created. Make sure that you get the quotes right: double quotes around your directory, single quotes around the whole Sys.setenv line, such that R understands your string. Check first that the Sys.setenv line works correctly; once it is written you may have to edit `.Rprofile` manually. (Or add a second, overwriting line to it.) For other ways to set an environmental variable permanently in R, see [Startup\(\)](#).

Author(s)

Christoph Sax <christoph.sax@gmail.com>

References

Sax C, Eddelbuettel D (2018). "Seasonal Adjustment by X-13ARIMA-SEATS in R." *Journal of Statistical Software*, 87(11), 1-17. doi: [10.18637/jss.v087.i11](https://doi.org/10.18637/jss.v087.i11).

See Also

[seas\(\)](#) for the core function and more information on package usage.

as.data.frame.seas *Coerce Output to data.frame*

Description

These methods coerce the output to a `data.frame`. This is useful for further processing. (This is a second attempt to do that; the first experimental attempt in version 1.4 used an argument `data.frame` in the call to the functions, and is now obsolete. The present approach seems cleaner and is likely to stay, but still consider it as **experimental**.)

Usage

```
## S3 method for class 'seas'  
as.data.frame(x, ...)  
  
## S3 method for class 'summary.seas'  
as.data.frame(x, ...)
```

Arguments

<code>x</code>	an object of class "seas" or "summary.seas", usually, the result of a call to the functions with the same name.
<code>...</code>	unused.

Details

The `data.frames` produced by these functions follow the naming conventions from the 'broom' package, but do not depend on it otherwise.

Value

a `data.frame` without row names.

Examples

```
m <- seas(AirPassengers, x11 = "")  
  
# a data.frame containing data  
as.data.frame(m)  
  
# a data.frame containing the summary information on the coefficients  
as.data.frame(summary(m))
```

 checkX13

Check Installation of X-13ARIMA-SEATS

Description

Check the installation of the binary executables of X-13ARIMA-SEATS. See [seasonal\(\)](#) for details on how to set X13_PATH manually if you intend to use your own binaries.

Usage

```
checkX13(fail = FALSE, fullcheck = TRUE, htmlcheck = TRUE)
```

Arguments

fail	logical, whether an error should interrupt the process. If FALSE, a message is returned.
fullcheck	logical, whether a full test should be performed. Runs Testairline.spc (which is shipped with X-13ARIMA-SEATS) to test the working of the binaries. Returns a message.
htmlcheck	logical, whether the presence of the the HTML version of X-13 should be checked.

Examples

```
old.path <- Sys.getenv("X13_PATH")
Sys.setenv(X13_PATH = "") # its broken now
try(checkX13())

# fix it (provided it worked in the first place)
if (old.path == "") {
  Sys.unsetenv("X13_PATH")
} else {
  Sys.setenv(X13_PATH = old.path)
}
try(checkX13())
```

 cpi

Consumer Price Index of Switzerland

Description

Monthly consumer price index of Switzerland. Base year is 1993.

Format

Time series of class "ts".

Source

Federal Statistical Office, Switzerland

Examples

```
data(seasonal)
cpi
```

easter

Dates of Chinese New Year, Indian Diwali and Easter

Description

Dates of Chinese New Year, Indian Diwali and Easter, suitable for the use in `genhol()`.

Format

Objects of class "Date".

Source

https://www.census.gov/srd/www/genhol/genhol_downloads.html

<http://www.chinesenewyears.info/chinese-new-year-calendar.php>

Ministry of Statistics and Programme Implementation, with help from Pinaki Mukherjee

Examples

```
data(holiday)
cny
diwali
easter
```

exp

Exports and Imports of China

Description

Monthly exports and imports of China (July 1983 to December 2013).

Format

Each time series is an object of class "ts".

Details

In 100 mio U.S. Dollar.

Source

China Customs

Examples

```
data(seasonal)
imp
exp
```

final

Time Series of a Seasonal Adjustment Model

Description

Functions to extract the main time series from a "seas" object. For universal import of X-13ARIMA-SEATS tables, use the [series\(\)](#) function.

Usage

```
final(object)

original(object)

trend(object)

irregular(object)

## S3 method for class 'seas'
residuals(object, ...)
```

Arguments

object	an object of class "seas".
...	not used. For compatibility with the generic.

Details

These functions support R default NA handling. If `na.action = na.exclude` is specified in the call to `seas`, the time series will also contain NAs.

Value

returns a "ts" object, depending on the function.

References

Vignette with a more detailed description: <http://www.seasonal.website/seasonal.html>

Comprehensive list of R examples from the X-13ARIMA-SEATS manual: <http://www.seasonal.website/examples.html>

Official X-13ARIMA-SEATS manual: <https://www2.census.gov/software/x-13arima-seats/x13as/windows/documentation/docx13as.pdf>

See Also

[seas\(\)](#) for the main function of seasonal.

[series\(\)](#), for universal X-13 output extraction.

Examples

```
m <- seas(AirPassengers)

final(m)
original(m)
irregular(m)
trend(m)

# NA handling
AirPassengersNA <- window(AirPassengers, end = 1962, extend = TRUE)
final(seas(AirPassengersNA, na.action = na.omit)) # no NA in final series
final(seas(AirPassengersNA, na.action = na.exclude)) # NA in final series
final(seas(AirPassengersNA, na.action = na.x13)) # NA filled by x13
# final(seas(AirPassengersNA, na.action = na.fail)) # fails
```

fivebestmdl

Five Best ARIMA Models

Description

Returns the five best models as chosen by the BIC criterion. It needs the `automdl` spec to be activated (default). If it is not activated, the function tries to re-evaluate the model with the `automdl` spec activated.

Usage

```
fivebestmdl(x)
```

Arguments

`x` object of class "seas"

References

Vignette with a more detailed description: <http://www.seasonal.website/seasonal.html>

Comprehensive list of R examples from the X-13ARIMA-SEATS manual: <http://www.seasonal.website/examples.html>

Official X-13ARIMA-SEATS manual: <https://www2.census.gov/software/x-13arima-seats/x13as/windows/documentation/docx13as.pdf>

See Also

`seas()` for the main function.

`series()`, for universal X-13 output extraction.

`plot.seas()`, for diagnostical plots.

`out()`, for accessing the full output of X-13ARIMA-SEATS.

Examples

```
m <- seas(AirPassengers)
fivebestmdl(m)
```

genhol

Generate Holiday Regression Variables

Description

A replacement for the genhol software by the U.S. Census Bureau, a utility that uses the same procedure as X-12-ARIMA to create regressors for the U. S. holidays of Easter, Labor Day, and Thanksgiving. **This is a replacement written in R, the U.S. Census Bureau software is not needed.**

Usage

```
genhol(x, start = 0, end = 0, frequency = 12, center = "none")
```

Arguments

x	a vector of class "Date", containing the occurrences of the holiday. It can be generated with <code>as.Date()</code> .
start	integer, shifts the start point of the holiday. Use negative values if start is before the specified date.
end	integer, shifts end point of the holiday. Use negative values if end is before the specified date.
frequency	integer, frequency of the resulting series

center character string. Either "calendar", "mean" or "none" (default). Centering avoids a bias in the resulting series. Use "calendar" for Easter or Chinese New Year, "mean" for Ramadan. See references: Notes on centering holiday.

Details

The resulting time series can be used as a user defined variable in `seas()`. Usually, you want the holiday effect to be removed from the final series, so you need to specify `regression.usertype = "holiday"`. (The default is to include user defined variables in the final series.)

Value

an object of class "ts" that can be used as a user defined variable in `seas()`.

See Also

`seas()` for the main function of seasonal.

Examples

```
data(holiday) # dates of Chinese New Year, Indian Diwali and Easter

### use of genhol

# 10 day before Easter day to one day after, quarterly data:
genhol(easter, start = -10, end = 1, frequency = 4)
genhol(easter, frequency = 2) # easter is allways in the first half-year

# centering for overall mean or monthly calendar means
genhol(easter, center = "mean")
genhol(easter, center = "calendar")

### replicating X-13's built-in Easter adjustment

# built-in
m1 <- seas(x = AirPassengers,
  regression.variables = c("td1coef", "easter[1]", "ao1951.May"),
  arima.model = "(0 1 1)(0 1 1)", regression.aicctest = NULL,
  outlier = NULL, transform.function = "log", x11 = "")
summary(m1)

# user defined variable
ea1 <- genhol(easter, start = -1, end = -1, center = "calendar")

# regression.usertype = "holiday" ensures that the effect is removed from
# the final series.
m2 <- seas(x = AirPassengers,
  regression.variables = c("td1coef", "ao1951.May"),
  xreg = ea1, regression.usertype = "holiday",
```

```

        arima.model = "(0 1 1)(0 1 1)", regression.aictest = NULL,
        outlier = NULL, transform.function = "log", x11 = "")
summary(m2)

all.equal(final(m2), final(m1), tolerance = 1e-06)

# with genhol, its possible to do slightly better, by adjusting the length
# of easter from Friday to Monday:

ea2 <- genhol(easter, start = -2, end = +1, center = "calendar")
m3 <- seas(x = AirPassengers,
          regression.variables = c("td1coef", "ao1951.May"),
          xreg = ea2, regression.usertype = "holiday",
          arima.model = "(0 1 1)(0 1 1)", regression.aictest = NULL,
          outlier = NULL, transform.function = "log", x11 = "")
summary(m3)

### Chinese New Year

data(seasonal)
data(holiday) # dates of Chinese New Year, Indian Diwali and Easter

# de facto holiday length: http://en.wikipedia.org/wiki/Chinese\_New\_Year
cny.ts <- genhol(cny, start = 0, end = 6, center = "calendar")

m1 <- seas(x = imp, xreg = cny.ts, regression.usertype = "holiday", x11 = "",
          regression.variables = c("td1coef", "ls1985.Jan", "ls2008.Nov"),
          arima.model = "(0 1 2)(0 1 1)", regression.aictest = NULL,
          outlier = NULL, transform.function = "log")
summary(m1)

# compare to identical no-CNY model
m2 <- seas(x = imp, x11 = "",
          regression.variables = c("td1coef", "ls1985.Jan", "ls2008.Nov"),
          arima.model = "(0 1 2)(0 1 1)", regression.aictest = NULL,
          outlier = NULL, transform.function = "log")
summary(m2)

ts.plot(final(m1), final(m2), col = c("red", "black"))

# modeling complex holiday effects in Chinese imports
# - positive pre-CNY effect
# - negative post-CNY effect
pre_cny <- genhol(cny, start = -6, end = -1, frequency = 12, center = "calendar")
post_cny <- genhol(cny, start = 0, end = 6, frequency = 12, center = "calendar")
m3 <- seas(x = imp, x11 = "",
          xreg = cbind(pre_cny, post_cny), regression.usertype = "holiday",
          x11 = list())
summary(m3)

```

```

### Indian Diwali (thanks to Pinaki Mukherjee)

# adjusting Indian industrial production
m4 <- seas(iip,
x11 = "",
xreg = genhol(diwali, start = 0, end = 0, center = "calendar"),
regression.usertype = "holiday"
)
summary(m4)

# without specification of 'regression.usertype', Diwali effects are added
# back to the final series
m5 <- seas(iip,
x11 = "",
xreg = genhol(diwali, start = 0, end = 0, center = "calendar")
)

ts.plot(final(m4), final(m5), col = c("red", "black"))

# plot the Diwali factor in Indian industrial production
plot(series(m4, "regression.holiday"))

### Using genhol to replicate the regARIMA estimation in R

# easter regressor
ea <- genhol(easter, start = -1, end = -1, center = "calendar")
ea <- window(ea, start = start(AirPassengers), end = end(AirPassengers))

# estimating ARIMA model in R base
arima(log(AirPassengers), order = c(0,1,1), seasonal = c(0,1,1), xreg = ea)

summary(seas(AirPassengers, regression.variables = c("easter[1]"),
regression.aictest = NULL))

# Note that R defines the ARIMA model with negative signs before the MA term,
# X-13 with a positive sign.

```

identify.seas

Manually Identify Outliers

Description

Select or deselect outliers by point and click. To quit and return the call, press ESC. Click several times to loop through different outlier types.

Usage

```

## S3 method for class 'seas'
identify(x, type = c("ao", "tc", "ls"), ...)

```

Arguments

x an object of class "seas".
type character vector, types of outlier to loop through.
... unused, for compatibility with the generic function.

Value

an object of class "seas", containing the static call of the selected model.

Examples

```
m <- seas(AirPassengers)
identify(m)
```

iip *Industrial Production of India*

Description

Industrial Production of India (IIP).

Format

Time series of class "ts".

Details

Index value. IIP is used for measuring the performance overall industrial sector of the Indian economy. IIP is compiled by using data from 16 source agencies.

Source

Central Statistics Office of the Ministry of Statistics and Programme Implementation, with help from Pinaki Mukherjee

Examples

```
data(seasonal)
iip
```

import.spc

*Import X-13 .spc Files***Description**

Utility function to import .spc files from X-13. It generates a list of calls to seas (and import.ts) that can be run in R. Evaluating these calls should perform the same X-13 procedure as the original .spc file. The print method displays the calls in a way that they can be copy-pasted into an R script.

Usage

```
import.spc(file, text = NULL)

## S3 method for class 'import.spc'
print(x, ...)
```

Arguments

file	character, path to the X-13 .spc file
text	character, alternatively, the content of a .spc file as a character string.
x	object of class import.spc
...	further arguments, not used

Value

returns an object of class import.spc, which is a list with the following (optional) objects of class call:

x	the call to retrieve the data for the input series
xtrans	the call to retrieve the data for the xtrans series (if required by the call)
xreg	the call to retrieve the data for the xreg series (if required by the call)
seas	the call to seas()

See Also

[import.ts\(\)](#), for importing X-13 data files.
[seas\(\)](#) for the main function of seasonal.

Examples

```
# importing the original X-13 example file
import.spc(text =
',
  series{
```

```

    title="International Airline Passengers Data from Box and Jenkins"
    start=1949.01
    data=(
    112 118 132 129 121 135 148 148 136 119 104 118
    115 126 141 135 125 149 170 170 158 133 114 140
    145 150 178 163 172 178 199 199 184 162 146 166
    171 180 193 181 183 218 230 242 209 191 172 194
    196 196 236 235 229 243 264 272 237 211 180 201
    204 188 235 227 234 264 302 293 259 229 203 229
    242 233 267 269 270 315 364 347 312 274 237 278
    284 277 317 313 318 374 413 405 355 306 271 306
    315 301 356 348 355 422 465 467 404 347 305 336
    340 318 362 348 363 435 491 505 404 359 310 337
    360 342 406 396 420 472 548 559 463 407 362 405
    417 391 419 461 472 535 622 606 508 461 390 432)
    span=(1952.01, )
  }
  spectrum{
    save_log=peaks
  }
  transform{
    function=auto
    save_log=autotransform
  }
  regression{
    aic_test=(td easter)
    save_log=aic_test
  }
  automdl{
    save_log=automodel
  }
  outlier{ }
  x11{ }
,
)

### reading .spc with multiple user regression and transformation series

# running a complex seas call and save output in a temporary directory
tdir <- tempdir()
seas(x = AirPassengers, xreg = cbind(a = genhol(cny, start = 1, end = 4,
  center = "calendar"), b = genhol(cny, start = -3, end = 0,
  center = "calendar")), xtrans = cbind(sqrt(AirPassengers), AirPassengers^3),
  transform.function = "log", transform.type = "temporary",
  regression.aic_test = "td", regression.usertype = "holiday", dir = tdir,
  out = TRUE)

# importing the .spc file from the temporary location
ll <- import.spc(file.path(tdir, "iofile.spc"))

# ll is list containing four calls:

```

```

# - 'll$x', 'll$xreg' and 'll$xtrans': calls to import.ts(), which read the
#   series from the X-13 data files
# - 'll$seas': a call to seas() which performs the seasonal adjustment in R
str(ll)

# to replicate the original X-13 operation, run all four calls in a series.
# You can either copy/paste and run the print() output:
ll

# or use eval() to evaluate the call(s). To evaluate the first call and
# import the x variable:
eval(ll$x)

# to run all four calls in 'll', use lapply() and eval():
ee <- lapply(ll, eval, envir = globalenv())
ee$seas # the 'seas' object, produced by the final call to seas()

```

import.ts

Import Time Series from X-13 Data Files

Description

Utility function to read time series from X-13 data files. A call to `import.ts` is constructed and included in the output of `import.spc()`.

Usage

```

import.ts(
  file,
  format = "datevalue",
  start = NULL,
  frequency = NULL,
  name = NULL
)

```

Arguments

file	character, name of the X-13 file which the data are to be read from
format	a valid X-13 file format as described in 7.15 of the X-13 manual: "datevalue", "datevaluecomma", "free", "freecomma", "x13save", "tramo" or an X-11 or Fortran format.
start	vector of length 2, time of the first observation (only for formats "free" and "freecomma" and the Fortran formats.)
frequency	the number of observations per unit of time (only for formats "free", "freecomma" and the X-11 or Fortran formats.)
name	(X-11 formats only) name of the series, to select from a file with multiple time series. Omit if you want to read all time series from an X-11 format file.

Value

an object of class `ts` or `mts`

See Also

[import.spc\(\)](#), for importing X-13 .spc files.

[seas\(\)](#) for the main function of seasonal.

Examples

```
tdir <- tempdir()
seas(x = AirPassengers, dir = tdir)
import.ts(file.path(tdir, "iofile.dta"))
import.ts(file.path(tdir, "iofile.rsd"), format = "x13save")
```

na.x13

Handle Missing Values by X-13

Description

Utility function to substitute NA values by -99999. Useful as a value for the `na.action` argument in [seas\(\)](#).

Usage

```
na.x13(x)
```

Arguments

`x` an object of class `"ts"`

Value

a time series, with NA values substituted by -99999.

Examples

```
AirPassengersNA <- AirPassengers
AirPassengersNA[20] <- NA
na.x13(AirPassengersNA)

seas(AirPassengersNA, na.action = na.x13)
```

out *Display X-13ARIMA-SEATS Output*

Description

The out function shows the full content of the X-13ARIMA-SEATS output in the browser. If you want to use a specific statistic in R, the `udg()` function is preferable.

Usage

```
out(x, browser = getOption("browser"), ...)
```

Arguments

x	an object of class "seas".
browser	browser to be used, passed on to <code>browseURL()</code> .
...	additional spec-arguments options sent to X-13ARIMA-SEATS during re-evaluation, passed to <code>update()</code> .

Details

To keep the size of "seas" objects small, seas does not save the output by default. Instead, out re-evaluates the model.

Value

displays the output as a side effect.

References

Vignette with a more detailed description: <http://www.seasonal.website/seasonal.html>

Comprehensive list of R examples from the X-13ARIMA-SEATS manual: <http://www.seasonal.website/examples.html>

Official X-13ARIMA-SEATS manual: <https://www2.census.gov/software/x-13arima-seats/x13as/windows/documentation/docx13as.pdf>

See Also

`seas()` for the main function of seasonal.

Examples

```
## Not run:
m <- seas(AirPassengers)
out(m)
# customizing the output with additional elements
out(m, automdl.print = "autochoicemdl")

## End(Not run)
```

outlier

Outlier Time series

Description

Returns an object of class "ts" that contains the names of the outliers.

Usage

```
outlier(x, full = FALSE)
```

Arguments

x an object of class "seas".

full logical, should the full label of the outlier be shown? If FALSE, only the type of the outlier is shown.

Value

character string time series with outliers.

Examples

```
x <- seas(AirPassengers)
outlier(x)
```

plot.seas

Seasonal Adjustment Plots

Description

Functions to graphically analyze a "seas" object.

Usage

```
## S3 method for class 'seas'
plot(
  x,
  outliers = TRUE,
  trend = FALSE,
  main = "Original and Adjusted Series",
  xlab = "Time",
  ylab = "",
  transform = c("none", "PC", "PCY"),
  ...
)

residplot(
  x,
  outliers = TRUE,
  main = "residuals of regARIMA",
  xlab = "Time",
  ylab = "",
  ...
)

## S3 method for class 'seas'
monthplot(x, choice = c("seasonal", "irregular"), main, ...)
```

Arguments

x	an object of class "seas", usually, a result of a call to seas() .
outliers	logical, should the outliers be drawn.
trend	logical, should the trend be drawn.
main	character string, title of the graph.
xlab	character string, title for the x axis.
ylab	character string, title for the y axis.
transform	character string, optionally transform the data to period to period "PC" or year to year "PCY" percentage change rates.
...	further arguments passed to the plotting functions.
choice	character string, "seasonal" (default) or "irregular".

Details

plot calls the plot method for class "seas". It plots the adjusted and unadjusted series, as well as the outliers. Optionally draws the trend series.

residplot plots the residuals and the outliers.

monthplot calls the monthplot method for class "seas". It plot the seasonal and SI component periodwise. Despite its name, monthplot can be used for series of all frequencies.

Value

All plot functions return a plot as their side effect.

References

Vignette with a more detailed description: <http://www.seasonal.website/seasonal.html>

Comprehensive list of R examples from the X-13ARIMA-SEATS manual: <http://www.seasonal.website/examples.html>

Official X-13ARIMA-SEATS manual: <https://www2.census.gov/software/x-13arima-seats/x13as/windows/documentation/docx13as.pdf>

See Also

[seas\(\)](#), for the main function.

[udg\(\)](#), for diagnostical statistics.

Examples

```
m <- seas(AirPassengers)

plot(m)
plot(m, outliers = FALSE)
plot(m, trend = TRUE)

residplot(m)
residplot(m, outliers = FALSE)

monthplot(m)

# use standard R functions to analyze "seas" models
pacf(resid(m))
spectrum(diff(resid(m)))
plot(density(resid(m)))
qqnorm(resid(m))
```

`predict.seas`*Seasonal Adjusted Series*

Description

Returns the seasonally adjusted series of an (optionally re-evaluated) model of class "seas". Without further arguments, this is equivalent to a call to the `final()` function.

Usage

```
## S3 method for class 'seas'  
predict(object, newdata, ...)
```

Arguments

<code>object</code>	an object of class "seas".
<code>newdata</code>	an object of class "ts". new data values for the x argument in the <code>seas()</code> function.
<code>...</code>	further arguments, passed to <code>update.seas()</code> , to re-evaluate the model.

Details

With the `newdata` argument supplied, the "seas" object is re-evaluated, using the original model call. This is equivalent of calling `final(update(m, x = newdata))`.

Value

Object of class "ts".

Examples

```
# Using data from Dec. 59 to estimate a model  
ap.short <- window(AirPassengers, end = c(1959, 12))  
m <- seas(ap.short)  
predict(m)  
final(m)    # equivalent  
  
# Use Dec. 59 model specification to estimate data up to Dec. 60  
predict(m, AirPassengers)
```

Description

Main function of the seasonal package. With the default options, seas calls the automatic procedures of X-13ARIMA-SEATS to perform a seasonal adjustment that works well in most circumstances. Via the `...` argument, it is possible to invoke almost all options that are available in X-13ARIMA-SEATS (see details). The default options of seas are listed as explicit arguments and are discussed in the arguments section. A full-featured graphical user interface can be accessed by the `view()` function.

Usage

```
seas(
  x = NULL,
  xreg = NULL,
  xtrans = NULL,
  seats.noadmiss = "yes",
  transform.function = "auto",
  regression.aictest = c("td", "easter"),
  outlier = "",
  automdl = "",
  composite = NULL,
  na.action = na.omit,
  out = FALSE,
  dir = NULL,
  multimode = c("x13", "R"),
  ...,
  list = NULL
)
```

Arguments

<code>x</code>	object of class "ts" or "mts", or a list of "ts" objects: time series to seasonally adjust.
<code>xreg</code>	(optional) object of class "ts": one or several user defined exogenous variables for regARIMA modeling, can be used both with regression or x11regression.
<code>xtrans</code>	(optional) object of class "ts": one or two user defined exogenous variables for the transform spec. Can be specified together with xreg.
<code>seats.noadmiss</code>	spec 'seats' with argument noadmiss = "yes" (default). Seasonal adjustment by SEATS, if SEATS decomposition is invalid, an alternative model is used (a message is returned). If noadmiss = "no", no approximation is done. If the seats spec is removed (seats = NULL), no seasonal adjustment is performed.

<code>transform.function</code>	spec <code>transform</code> with argument <code>function = "auto"</code> (default). Automatic log transformation detection. Set equal to <code>"none"</code> , <code>"log"</code> or any value that is allowed by X-13 to turn it off.
<code>regression.aictest</code>	spec <code>regression</code> with argument <code>aictest = c("td", "easter")</code> (default). AIC test for trading days and Easter effects. Set equal to <code>NULL</code> to turn it off.
<code>outlier</code>	spec <code>outlier</code> without arguments (default). Automatic outlier detection. Set equal to <code>NULL</code> to turn it off.
<code>automdl</code>	spec <code>automdl</code> without arguments (default). Automatic model search with the <code>automdl</code> spec. Set equal to <code>NULL</code> to turn it off.
<code>composite</code>	spec <code>composite</code> . A named list with spec-arguments for the aggregation of multiple series. Also requires <code>series.comtype = "add"</code> or similar. Set equal to <code>NULL</code> to turn it off (default). See <code>vignette("multiple")</code> .
<code>na.action</code>	a function which indicates what should happen when the data contain NAs. <code>na.omit</code> (default), <code>na.exclude</code> or <code>na.fail</code> . If <code>na.action = na.x13</code> , NA handling is done by X-13, i.e. NA values are substituted by <code>-99999</code> .
<code>out</code>	logical. Should the X-13ARIMA-SEATS standard output be saved in the <code>"seas"</code> object? (this increases object size substantially, it is recommended to re-evaluate the model using the <code>out()</code> function instead.)
<code>dir</code>	character string with a user defined file path. If specified, the X-13ARIMA-SEATS output files are copied to this folder. Useful for debugging.
<code>multimode</code>	one of <code>"x13"</code> or <code>"R"</code> . When multiple series are supplied, should they be processed in a single call (<code>"x13"</code>) or processed individually (<code>"R"</code>). See <code>vignette("multiple")</code> .
<code>...</code>	additional spec-arguments options sent to X-13ARIMA-SEATS (see details).
<code>list</code>	a named list with additional spec-arguments options. This is an alternative to the <code>...</code> argument. It is useful for programming.

Details

It is possible to use the almost complete syntax of X-13ARIMA-SEAT via the `...` argument. The syntax of X-13ARIMA-SEATS uses *specs* and *arguments*, and each spec optionally contains some arguments. In `seas`, an additional spec-argument can be added by separating spec and argument by a dot (`.`) (see examples). Alternatively, spec-argument combinations can be supplied as a named list, which is useful for programming.

Similarly, the `series()` function can be used to read almost all series from X-13ARIMA-SEATS. The `udg()` function provides access to a large number of diagnostical statistics.

For a more extensive description, consider `vignette("seas")` or the wiki page, which contains replications of almost all examples from the official X-13ARIMA-SEATS manual.

Value

returns an object of class `"seas"`, essentially a list with the following components:

<code>series</code>	a list containing the output tables of X-13. To be accessed by the <code>series</code> function.
---------------------	--

data	seasonally adjusted data, the raw data, the trend component, the irregular component and the seasonal component (deprecated).
err	warning messages from X-13ARIMA-SEATS
udg	content of the .udg output file
est	content of the .est output file
model	list with the model specification, similar to "spc". It typically contains "regression", which contains the regressors and parameter estimates, and "arima", which contains the ARIMA specification and the parameter estimates.
fivebestmdl	Best Five ARIMA Models (unparsed)
x	input series
spc	object of class "spclist", a list containing the content of the .spc file that is used by X-13ARIMA-SEATS. Each spec is on the first level, each argument is on the second level.
call	function call
wdir	temporary directory in which X-13ARIMA-SEATS has been run

The final function returns the final adjusted series, the plot method shows a plot with the unadjusted and the adjusted series. summary gives an overview of the regARIMA model. The `udg()` function returns diagnostical statistics.

References

- Sax C, Eddelbuettel D (2018). "Seasonal Adjustment by X-13ARIMA-SEATS in R." *Journal of Statistical Software*, 87(11), 1-17. doi: [10.18637/jss.v087.i11](https://doi.org/10.18637/jss.v087.i11).
- On-Line Interface to seasonal <http://www.seasonal.website>
- Comprehensive list of R examples from the X-13ARIMA-SEATS manual: <http://www.seasonal.website/examples.html>
- Official X-13ARIMA-SEATS manual: <https://www2.census.gov/software/x-13arima-seats/x13as/windows/documentation/docx13as.pdf>

See Also

- `view()`, for accessing the graphical user interface.
- `update.seas()`, to update an existing "seas" model.
- `static()`, to return the 'static' call, with automated procedures substituted by their choices.
- `series()`, for universal X-13 table series import.
- `out()`, to view the full X-13 diagnostical output.

Examples

```
# Basic call

m <- seas(AirPassengers)
summary(m)
```

```

# Graphical user interface
## Not run:
view(m)

## End(Not run)

# invoke X-13ARIMA-SEATS options as 'spec.argument' through the ... argument
# (consult the X-13ARIMA-SEATS manual for many more options and the list of
# R examples for more examples)
seas(AirPassengers, regression.aictest = c("td")) # no easter testing
seas(AirPassengers, force.type = "denton") # force equality of annual values
seas(AirPassengers, x11 = "") # use x11, overrides the 'seats' spec

# 'spec.argument' combinations can also be supplied as a named list, which is
# useful for programming
seas(AirPassengers, list = list(regression.aictest = c("td"), outlier = NULL))
# constructing the list step by step
ll <- list()
ll[["x"]] <- AirPassengers
ll[["regression.aictest"]] <- "td"
ll[["outlier"]] <- list(NULL) # assigning NULL to a list using single brackets
seas(list = ll)

# options can be entered as vectors
seas(AirPassengers, regression.variables = c("td1coef", "easter[1]"))
seas(AirPassengers, arima.model = c(0, 1, 1, 0, 1, 1))
seas(AirPassengers, arima.model = "(0 1 1)(0 1 1)" # equivalent

# turn off the automatic procedures
seas(AirPassengers, regression.variables = c("td1coef", "easter[1]",
"ao1951.May"), arima.model = "(0 1 1)(0 1 1)", regression.aictest = NULL,
outlier = NULL, transform.function = "log")

# static replication of 'm <- seas(AirPassengers)'
static(m) # this also tests the equivalence of the static call
static(m, test = FALSE) # no testing (much faster)
static(m, coef = TRUE) # also fixes the coefficients

# updating an existing model
update(m, x11 = "")

# specific extractor functions
final(m)
predict(m) # equivalent
original(m)
resid(m)
coef(m)
fivebestmdl(m)
spc(m) # the .spc input file to X-13 (for debugging)

```

```

# universal extractor function for any X-13ARIMA-SEATS output (see ?series)
series(m, "forecast.forecasts")

# user defined regressors (see ?genhol for more examples)
# a temporary level shift in R base
tls <- ts(0, start = 1949, end = 1965, freq = 12)
window(tls, start = c(1955, 1), end = c(1957, 12)) <- 1
seas(AirPassengers, xreg = tls, outlier = NULL)
# identical to a X-13ARIMA-SEATS specification of the the level shift
seas(AirPassengers, regression.variables = c("t1955.01-1957.12"),
      outlier = NULL)

# forecasting an annual series without seasonal adjustment
m <- seas(airmiles, seats = NULL, regression.aictest = NULL)
series(m, "forecast.forecasts")

# NA handling
AirPassengersNA <- window(AirPassengers, end = 1962, extend = TRUE)
final(seas(AirPassengersNA, na.action = na.omit)) # no NA in final series
final(seas(AirPassengersNA, na.action = na.exclude)) # NA in final series
# final(seas(AirPassengersNA, na.action = na.fail)) # fails

# NA handling by X-13 (works with internal NAs)
AirPassengersNA[20] <- NA
final(seas(AirPassengersNA, na.action = na.x13))

## performing 'composite' adjustment
seas(
  cbind(mdeaths, fdeaths),
  composite = list(),
  series.comptype = "add"
)

```

series

Import X-13ARIMA-SEATS Output Tables

Description

With the exception of the composite spec, the series function imports all tables that can be saved in X-13ARIMA-SEATS.

Usage

```
series(x, series, reeval = TRUE, verbose = TRUE)
```

Arguments

x an object of class "seas".

series	character vector, short or long names of an X-13ARIMA-SEATS table. If a long name is specified, it needs to be combined with the spec name and separated by a dot (it is not unique, otherwise. See list below.). More than one series can be specified (see examples).
reeval	logical, if TRUE, the model is re-evaluated with the corresponding specs enabled.
verbose	logical, if TRUE, a message is returned if a spec is added during reevaluation.

Details

If the save argument is not specified in the model call, `series` re-evaluates the call with the corresponding specs enabled (also returning a message). Note that re-evaluation doubles the overall computational time. If you want to accelerate the procedure, you have to be explicit about the output in the model call (see examples).

List of all importable tables from X-13ARIMA-SEATS:

spec	long name	short name
check	check.acf	acf
check	check.acfsquared	ac2
check	check.pacf	pcf
composite	composite.adjcompositesrs	b1
composite	composite.calendaradjcomposite	cac
composite	composite.compositesrs	cms
composite	composite.indadjsatot	iaa
composite	composite.indadjustfac	iaf
composite	composite.indaoutlier	iao
composite	composite.indcalendar	ica
composite	composite.indirregular	iir
composite	composite.indlevelshift	ils
composite	composite.indmcdmovavg	if1
composite	composite.indmodirr	ie3
composite	composite.indmodoriginal	ie1
composite	composite.indmodsadj	ie2
composite	composite.indrevsachanges	i6a
composite	composite.indrndsachanges	i6r
composite	composite.indrobustsa	iee
composite	composite.indsachanges	ie6
composite	composite.indsadjround	irn
composite	composite.indseasadj	isa
composite	composite.indseasonal	isf
composite	composite.indseasonaldiff	isd
composite	composite.indtotaladjustment	ita
composite	composite.indtrend	itn
composite	composite.indtrendchanges	ie7
composite	composite.indunmodsi	id8
composite	composite.origchanges	ie5
composite	composite.outlieradjcomposite	oac
composite	composite.prioradjcomposite	ia3
estimate	estimate.armacmatrix	acm

estimate	estimate.iterations	itr
estimate	estimate.regcmatrix	rcm
estimate	estimate.regressioneffects	ref
estimate	estimate.residuals	rsd
estimate	estimate.roots	rts
force	force.forcefactor	ffc
force	force.revsachanges	e6a
force	force.rndsachanges	e6r
force	force.saround	rnd
force	force.seasadjtot	saa
forecast	forecast.backcasts	bct
forecast	forecast.forecasts	fct
forecast	forecast.transformed	frt
forecast	forecast.transformedbcst	btr
forecast	forecast.variances	fvr
history	history.chngestimates	che
history	history.chngrevisions	chr
history	history.fcsterrors	fce
history	history.fcsthhistory	fch
history	history.indsaestimates	iae
history	history.indsarevisions	iar
history	history.lkhdhistory	lkh
history	history.outlierhistory	rot
history	history.saestimates	sae
history	history.sarevisions	sar
history	history.seatsmdlhistory	smh
history	history.sfestimates	sfe
history	history.sfilterhistory	sfh
history	history.sfrevisions	sfr
history	history.trendchngestimates	tce
history	history.trendchngrevisions	ter
history	history.trendestimates	tre
history	history.trendrevisions	trr
identify	identify.acf	iac
identify	identify.pacf	ipc
outlier	outlier.finaltests	fts
outlier	outlier.iterations	oit
regression	regression.aoutlier	ao
regression	regression.holiday	hol
regression	regression.levelshift	ls
regression	regression.outlier	otl
regression	regression.regressionmatrix	rmx
regression	regression.regseasonal	a10
regression	regression.seasonaloutlier	so
regression	regression.temporarychange	tc
regression	regression.tradingday	td
regression	regression.transitory	a13
regression	regression.userdef	usr

seats	seats.adjustfac	s16
seats	seats.adjustmentratio	s18
seats	seats.cycle	cyc
seats	seats.diffseasonaladj	dsa
seats	seats.difftrend	dtr
seats	seats.irregular	s13
seats	seats.longtermtrend	ltt
seats	seats.seasadjconst	sec
seats	seats.seasonal	s10
seats	seats.seasonaladj	s11
seats	seats.seasonaladjfcstdecomp	afd
seats	seats.seasonalfcstdecomp	sfd
seats	seats.seasonalsum	ssm
seats	seats.seriesfcstdecomp	ofd
seats	seats.totaladjustment	sta
seats	seats.transitory	s14
seats	seats.transitoryfcstdecomp	yfd
seats	seats.trend	s12
seats	seats.trendconst	stc
seats	seats.trendfcstdecomp	tfd
series	series.adjoriginal	b1
series	series.calendaradjorig	a18
series	series.outlieradjorig	a19
series	series.seriesmvdj	mv
series	series.span	a1
seats	seats.componentmodels	mdc
seats	seats.filtersaconc	fac
seats	seats.filtersasym	faf
seats	seats.filtertrendconc	ftc
seats	seats.filtertrendsym	ftf
seats	seats.squaredgainsaconc	gac
seats	seats.squaredgainsasym	gaf
seats	seats.squaredgaintrendconc	gtc
seats	seats.squaredgaintrendsym	gtf
seats	seats.timeshiftsaconc	tac
seats	seats.timeshifttrendconc	ttc
seats	seats.wkendfilter	wkf
slidingspans	slidingspans.chngspans	chs
slidingspans	slidingspans.indchngspans	cis
slidingspans	slidingspans.indsaspan	ais
slidingspans	slidingspans.indsfspan	sis
slidingspans	slidingspans.indychngspans	yis
slidingspans	slidingspans.sfspan	sfs
slidingspans	slidingspans.tdspans	tds
slidingspans	slidingspans.ychngspans	yes
spectrum	spectrum.speccomposite	is0
spectrum	spectrum.specindir	is2
spectrum	spectrum.specindsa	is1

spectrum	spectrum.specirr	sp2
spectrum	spectrum.specorig	sp0
spectrum	spectrum.specresidual	spr
spectrum	spectrum.specsa	sp1
spectrum	spectrum.specseatsextresiduals	ser
spectrum	spectrum.specseatsirr	s2s
spectrum	spectrum.specseatsssa	s1s
transform	transform.permprior	a2p
transform	transform.permprioradjusted	a3p
transform	transform.permprioradjustedptd	a4p
transform	transform.prior	a2
transform	transform.prioradjusted	a3
transform	transform.prioradjustedptd	a4d
transform	transform.seriesconstant	a1c
transform	transform.tempprior	a2t
transform	transform.transformed	trn
x11	x11.adjoriginalc	c1
x11	x11.adjoriginald	d1
x11	x11.adjustdiff	fad
x11	x11.adjustfac	d16
x11	x11.adjustmentratio	e18
x11	x11.biasfactor	bcf
x11	x11.calendar	d18
x11	x11.calendaradjchanges	e8
x11	x11.combholiday	chl
x11	x11.extreme	c20
x11	x11.extremeb	b20
x11	x11.irregular	d13
x11	x11.irregularadjao	ira
x11	x11.irregularb	b13
x11	x11.irregularc	c13
x11	x11.irrwt	c17
x11	x11.irrwtb	b17
x11	x11.mcdmovavg	f1
x11	x11.modirregular	e3
x11	x11.modoriginal	e1
x11	x11.modseasadj	e2
x11	x11.modsic4	c4
x11	x11.modsid4	d4
x11	x11.origchanges	e5
x11	x11.replacsi	d9
x11	x11.replacsic9	c9
x11	x11.robustsa	e11
x11	x11.sachanges	e6
x11	x11.seasadj	d11
x11	x11.seasadjb11	b11
x11	x11.seasadjb6	b6
x11	x11.seasadjc11	c11

x11	x11.seasadjc6	c6
x11	x11.seasadjconst	sac
x11	x11.seasadjd6	d6
x11	x11.seasonal	d10
x11	x11.seasonaladjregsea	ars
x11	x11.seasonalb10	b10
x11	x11.seasonalb5	b5
x11	x11.seasonalc10	c10
x11	x11.seasonalc5	c5
x11	x11.seasonald5	d5
x11	x11.seasonaldi_	fsd
x11	x11.sib3	b3
x11	x11.sib8	b8
x11	x11.tdadjorig	c19
x11	x11.tdadjorigb	b19
x11	x11.totaladjustment	tad
x11	x11.trend	d12
x11	x11.trendadjls	tal
x11	x11.trendb2	b2
x11	x11.trendb7	b7
x11	x11.trendc2	c2
x11	x11.trendc7	c7
x11	x11.trendchanges	e7
x11	x11.trendconst	tac
x11	x11.trendd2	d2
x11	x11.trendd7	d7
x11	x11.unmodsi	d8
x11	x11.unmodsiox	d8b
x11	x11.yrtotals	e4
x11regression	x11regression.calendar	xca
x11regression	x11regression.calendarb	bxc
x11regression	x11regression.combcalendar	xcc
x11regression	x11regression.combcalendarb	bcc
x11regression	x11regression.combtradingday	c18
x11regression	x11regression.combtradingdayb	b18
x11regression	x11regression.extremeval	c14
x11regression	x11regression.extremevalb	b14
x11regression	x11regression.holiday	xh1
x11regression	x11regression.holidayb	bxh
x11regression	x11regression.outlieriter	xoi
x11regression	x11regression.priortd	a4
x11regression	x11regression.tradingday	c16
x11regression	x11regression.tradingdayb	b16
x11regression	x11regression.x11reg	c15
x11regression	x11regression.x11regb	b15
x11regression	x11regression.xregressioncmatrix	xrc
x11regression	x11regression.xregressionmatrix	xrm

Value

depending on the table, either an object of class "ts" or "data.frame".

References

Vignette with a more detailed description: <http://www.seasonal.website/seasonal.html>

Comprehensive list of R examples from the X-13ARIMA-SEATS manual: <http://www.seasonal.website/examples.html>

Official X-13ARIMA-SEATS manual: <https://www2.census.gov/software/x-13arima-seats/x13as/windows/documentation/docx13as.pdf>

See Also

[seas\(\)](#) for the main function.

Examples

```
m <- seas(AirPassengers)
series(m, "fct") # re-evaluate with the forecast spec activated

# more than one series
series(m, c("rsd", "fct"))

m <- seas(AirPassengers, forecast.save = "fct")
series(m, "fct") # no re-evaluation (much faster!)

# using long names
series(m, "forecast.forecasts")

# history spec
series(m, "history.trendestimates")
series(m, "history.sfestimates")
series(m, "history.saestimates")
series(m, c("history.sfestimates", "history.trendestimates"))

# slidingspans spec
series(m, "slidingspans.sfspans")
series(m, "slidingspans.ychnspans")

# fundamental identities of seasonal adjustment
# Y = T * I * (S * TD)
all.equal(AirPassengers, series(m, "seats.trend") *
          series(m, "seats.irregular") * series(m, "seats.adjustfac"))
# Y_sa = Y / (S * TD)
all.equal(final(m), AirPassengers / series(m, "seats.adjustfac"))

### Some X-13ARIMA-SEATS functions can be replicated in R:
```

```
# X-13ARIMA-SEATS spectrum
plot(series(m, "spectrum.specorig")[,-1], t = "l")
# R equivalent: spectrum from stats
spectrum(diff(log(AirPassengers)), method = "ar")

# X-13ARIMA-SEATS pacf
x13.pacf <- series(m, "identify.pacf")
plot(x13.pacf[,1], t = "h")
lines(x13.pacf[,2])
lines(-x13.pacf[,2])
# R equivalent: pacf from stats
pacf(AirPassengers, lag.max = 35)

# use with composite (see vignette("multiple", "seasonal"))
m_composite <- seas(
  cbind(mdeaths, fdeaths),
  composite = list(),
  series.comptype = "add"
)
series(m_composite, "composite.indseasadj")
```

spc

.spc *File Content*

Description

Access the content of the .spc file that governs the behavior of X-13ARIMA-SEATS.

Usage

```
spc(x)
```

Arguments

x object of class "seas"

Value

returns an object of class "spclist", essentially a list that contains the information that is sent to X-13ARIMA-SEATS. The corresponding print method displays the content of the list as written to the .spc file.

References

Vignette with a more detailed description: <http://www.seasonal.website/seasonal.html>

Comprehensive list of R examples from the X-13ARIMA-SEATS manual: <http://www.seasonal.website/examples.html>

Official X-13ARIMA-SEATS manual: <https://www2.census.gov/software/x-13arima-seats/x13as/windows/documentation/docx13as.pdf>

See Also

`seas()` for the main function.

`series()`, for universal X-13 output extraction.

`plot.seas()`, for diagnostical plots.

`out()`, for accessing the full output of X-13ARIMA-SEATS.

Examples

```
m <- seas(AirPassengers)
spc(m)
```

SPECS

List of Available X-13ARIMA-SEATS Outputs

Description

The data is used by several functions as a look-up table. Users should consider the table in `series()` or in the official manual.

Format

An object of class "data.frame"

Source

United States Census Bureau

References

Official X-13ARIMA-SEATS manual: <https://www2.census.gov/software/x-13arima-seats/x13as/windows/documentation/docx13as.pdf>

 static

Static Call of a seas Object

Description

In a 'static' call, the default automatic procedures in the model call are substituted by the choices they made.

Usage

```
static(
  x,
  coef = FALSE,
  x11.filter = FALSE,
  test = TRUE,
  fail = FALSE,
  evaluate = FALSE
)
```

Arguments

x	an object of class seas.
coef	logical. If TRUE, the coefficients are treated as fixed, instead of being estimated.
x11.filter	logical. X-11 only. if TRUE, the X-11 moving averages will be fixed as well. This leads to different filters at different stages, and the resulting series can be are slightly different. If test = TRUE, this may cause a warning message.
test	logical. By default the static call is executed and compared to the input call. If the final series is not identical, a message is returned. If FALSE, no test is performed (faster).
fail	logical. If TRUE, differences will cause an error. Ignored if test = FALSE.
evaluate	logical. If TRUE, the call is evaluated.

Details

If evaluate = TRUE, the call is evaluated. The call can be copy/pasted to a script and used for further manipulations or future evaluation of the same model.

By default, the static call is tested. It is executed and compared to the input call. If the final series is not identical, a message is returned.

If coef = TRUE, the coefficients are fixed as well. If x11.filter = TRUE, the X-11 moving averages are fixed as well.

Value

Object of class "call". Or an object of class "seas" if evaluate = TRUE.

References

Vignette with a more detailed description: <http://www.seasonal.website/seasonal.html>

Comprehensive list of R examples from the X-13ARIMA-SEATS manual: <http://www.seasonal.website/examples.html>

Official X-13ARIMA-SEATS manual: <https://www2.census.gov/software/x-13arima-seats/x13as/windows/documentation/docx13as.pdf>

See Also

`stats::getCall()` to extract the actual call.

`seas()` for the main function of seasonal.

Examples

```
m <- seas(AirPassengers)
getCall(m)           # default call
static(m)            # static call
static(m, test = FALSE) # much faster
static(m, evaluate = TRUE) # returns an object of class "seas"

m <- seas(AirPassengers, x11 = "")

static(m, x11.filter = TRUE) # also fixes the X-11 filter (with a warning)
static(m, coef = TRUE)      # also fixes the coefficients
```

summary.seas

Summary of a X13-ARIMA-SEATS seasonal adjustment

Description

Like the corresponding method for "lm" objects, the method for "seas" objects returns the estimated coefficients, its standard errors, z-statistics and corresponding (two-sided) p-values. Coefficients are returned both for the exogenous regressors and the coefficients of the ARIMA model.

Usage

```
## S3 method for class 'seas'
summary(object, stats = getOption("seas.stats"), ...)

## S3 method for class 'summary.seas'
print(
  x,
  digits = max(3, getOption("digits") - 3),
  signif.stars = getOption("show.signif.stars"),
  ...
)
```

Arguments

object	an object of class "seas", usually, a result of a call to <code>seas()</code> .
stats	(experimental) character vector, additional stat to be shown in the summary output. function. For a list of all possible values, see the <code>udg()</code> function. If a value is not present, it will be ignored. Values can be specified via options. See examples.
...	further arguments passed to or from other methods.
x	an object of class "summary.seas", usually, a result of a call to <code>summary.seas</code> .
digits	the number of significant digits to use when printing.
signif.stars	logical. If TRUE, 'significance stars' are printed for each coefficient.

Details

The lower part of the output shows additional information on the estimation:

Adjustment use of SEATS or X11

ARIMA structure of the seasonal ARIMA model

Obs. number of observations

Transform prior transformation

AICc, BIC value of the information criterion (lower is better)

QS test for seasonality in the final series; null hypothesis: no seasonality in final; signif. codes are shown if the null hypothesis is rejected. QS statistics for more series (e.g., the original series) can be extracted with `qs()`.

Box-Ljung test for residual autocorrelation; null hypothesis: no autocorrelation in residuals; signif. codes are shown if the null hypothesis is rejected. The test statistic is the result of `Box.test(resid(m), lag = 24, type = "Ljung")`

Shapiro test for normality of the residuals; null hypothesis: normal distribution of the residuals; signif. codes are shown if the null hypothesis is rejected. The test statistic is the result of `shapiro.test(resid(m))`

Value

`summary.seas` returns a list containing the summary statistics included in object, and computes the following additional statistics:

coefficients	a named matrix containing coefficients, standard deviations, t-values and p-values
transform	character string with the type of initial transformation

The print method prints the summary output in a similar way as the method for "lm".

Examples

```
m <- seas(AirPassengers)
summary(m)

### user defined stats from the udg function
# (experimental, see ?udg)

# also show some M quality statistics for X11 in summary
options(seas.stats = c("f3.m01", "f3.m02", "f3.m03", "f3.m04"))
summary(seas(AirPassengers, x11 = ""))

# this does not affect the SEATS output
summary(seas(AirPassengers))

# reset to default
options(seas.stats = NULL)
```

transformfunction	<i>Applied Transformation</i>
-------------------	-------------------------------

Description

Returns the transform function that has been applied.

Usage

```
transformfunction(x)
```

Arguments

x object of class "seas"

References

Vignette with a more detailed description: <http://www.seasonal.website/seasonal.html>

Comprehensive list of R examples from the X-13ARIMA-SEATS manual: <http://www.seasonal.website/examples.html>

Official X-13ARIMA-SEATS manual: <https://www2.census.gov/software/x-13arima-seats/x13as/windows/documentation/docx13as.pdf>

See Also

[seas\(\)](#) for the main function.

[series\(\)](#), for universal X-13 output extraction.

[plot.seas\(\)](#), for diagnostical plots.

[out\(\)](#), for accessing the full output of X-13ARIMA-SEATS.

Examples

```
m <- seas(AirPassengers)
transformfunction(m)
```

 udg

Diagnostical Statistics

Description

The `udg` function provides access to a large number of diagnostical statistics. The `qs` function and the `AIC`, `BIC` and `logLik` methods are wrappers that use `udg` to access some specific diagnostical statistics.

Usage

```
udg(x, stats = NULL, simplify = TRUE, fail = TRUE)
```

```
qs(x)
```

```
## S3 method for class 'seas'
AIC(object, ...)
```

```
## S3 method for class 'seas'
BIC(object, ...)
```

```
## S3 method for class 'seas'
nobs(object, ...)
```

```
## S3 method for class 'seas'
logLik(object, ...)
```

Arguments

<code>x</code> , <code>object</code>	an object of class "seas".
<code>stats</code>	character vector; if specified, only a subset of the available stats are returned. This speeds up the call, as only a subset needs to be type converted. Should be used for programming.
<code>simplify</code>	logical; should the result be simplified to a vector or matrix, if possible?
<code>fail</code>	logical; if TRUE, an error is dropped if an element of <code>stats</code> is missing in <code>names(udg(x))</code> .
<code>...</code>	further arguments (not used)

Value

qs returns the QS statistics for seasonality of input and output series and the corresponding p-values.
AIC, BIC, nobs and logLik return the corresponding statistics.

References

Vignette with a more detailed description: <http://www.seasonal.website/seasonal.html>

Comprehensive list of R examples from the X-13ARIMA-SEATS manual: <http://www.seasonal.website/examples.html>

Official X-13ARIMA-SEATS manual: <https://www2.census.gov/software/x-13arima-seats/x13as/windows/documentation/docx13as.pdf>

See Also

[seas\(\)](#) for the main function.

[series\(\)](#), for universal X-13 output extraction.

[plot.seas\(\)](#), for diagnostical plots.

[out\(\)](#), for accessing the full output of X-13ARIMA-SEATS.

Examples

```
m <- seas(AirPassengers, x11 = "")

qs(m)
AIC(m)
BIC(m)
nobs(m)
logLik(m)

# a list with all entries from udg
udg(m)

# extracting a few selected stats from udg
udg(m, c("f3.m02", "f3.m05", "qsori")) # returns a list
udg(m, c("f3.m02", "f3.m05"))         # returns a vector

# faster than:
udg(m)[c("f3.m01", "f3.m02", "qsori")]
```

unemp	<i>United States Unemployment Level</i>
-------	---

Description

Thousands of Persons

Format

Each time series is an object of class "ts".

Source

U.S. Bureau of Labor Statistics, retrieved from FRED, Federal Reserve Bank of St. Louis; <https://fred.stlouisfed.org/series/LNU03000000>, December 14, 2016.

Examples

```
data(seasonal)
unemp
```

update.seas	<i>Update and Re-evaluate a Seasonal Adjustment Model</i>
-------------	---

Description

Method to update and re-evaluate an object of class "seas".

Usage

```
## S3 method for class 'seas'
update(object, ..., evaluate = TRUE)
```

Arguments

object	an object of class "seas", usually, a result of a call to seas() .
...	spec-argument options sent to X-13 (with the same syntax as in seas())
evaluate	logical. If TRUE, the call is evaluated.

Details

Contrary to the default method of [update\(\)](#), the "seas" method uses the evaluated call, rather than the actual call for re- evaluation. This means you can safely use it in other functions, which is useful with [lapply\(\)](#) and friends (see examples.)

Value

Object of class "seas". Or an object of class "call" if evaluate = FALSE.

See Also

[seas\(\)](#) for the main function.

[static\(\)](#), to return the (optionally evaluated) static call of a "seas" object.

Examples

```
# updating the call
m <- seas(AirPassengers)
update(m, x11 = "")
update(m, x = sqrt(AirPassengers), x11 = "")

# 'update' can be also used with lapply (or mapply)

# a list of time series
dta <- list(fdeaths = fdeaths, mdeaths = mdeaths)

# use 'seas' via lapply
ll <- lapply(dta, seas, x11 = "")

# use 'update' via lapply
lapply(ll, update, arima.model = c(0, 1, 1, 0, 1, 1))
```

view

Interactively Modify a Seasonal Adjustment Model

Description

Interactively modify a "seas" object. The goal of `view` is to summarize all relevant options, plots and statistics of a seasonal adjustment model. The `view` function in the **seasonal** package imports the identical `seasonalview::view()` function from the **seasonalview** package, so there is no need to explicitly load the **seasonalview** package.

Usage

```
view(x = NULL, story = NULL, quiet = TRUE, ...)
```

Arguments

<code>x</code>	an object of class "seas".
<code>story</code>	character, local file path or URL to an ".Rmd" file.
<code>quiet</code>	logical, if TRUE (default), error messages from calls in <code>view</code> are not shown in the console.

... arguments passed to `runApp`. E.g., for selecting if the GUI should open in the browser or in the RStudio viewer pane.

Details

Frequently used options can be modified using the drop down selectors in the upper left box. Each change will result in a re-estimation of the seasonal adjustment model. The R-call, the X-13 call, the graphical output and the summary are updated accordingly.

Alternatively, the R call can be modified manually in the lower left box. Click 'Run Call' to re-estimate the model and to adjust the option selectors, the graphical output, and the summary. With the 'To console' button, the GUI is closed and the call is imported to R. The 'Static' button substitutes automatic procedures by the automatically chosen spec-argument options, in the same way as the `static()` function.

If you are familiar with the X-13 spec syntax, you can modify the X-13 call, with the same consequences as when modifying the R call.

The lower right panel shows the summary, as described in the help page of `summary.seas()`. The 'X-13 output' button opens the complete output of X-13 in a separate tab or window.

If you have the `x13story` package installed (not yet on CRAN, see references), you can call the function with the `story` argument. This will render an R Markdown document and produce a *story* on seasonal adjustment that can be manipulated interactively.

Value

`view` returns an object of class "seas", the modified model; or NULL, if the `story` argument is supplied.

References

Seasonal vignette with a more detailed description: <http://www.seasonal.website/seasonal.html>

Development version of the `x13story` package: <https://github.com/christophsax/x13story>

Examples

```
## Not run:

m <- seas(AirPassengers)
view(m)

# store the model after closing the GUI, for further processing in R
m.upd <- view(m)

## End(Not run)
```

Index

- * **datasets**
 - cpi, 5
 - easter, 6
 - exp, 6
 - iip, 13
 - SPECS, 35
 - unemp, 42
- * **package**
 - seasonal-package, 2
- AIC.seas (udg), 40
- as.data.frame.seas, 4
- as.data.frame.summary.seas
(as.data.frame.seas), 4
- as.Date(), 9
- BIC.seas (udg), 40
- browseURL(), 18
- checkX13, 5
- cny (easter), 6
- cpi, 5
- diwali (easter), 6
- easter, 6
- exp, 6
- final, 7
- final(), 22
- fivebestmdl, 8
- genhol, 9
- genhol(), 6
- identify.seas, 12
- iip, 13
- imp (exp), 6
- import.spc, 14
- import.spc(), 16, 17
- import.ts, 16
- import.ts(), 14
- INSPDATA (SPECS), 35
- irregular (final), 7
- lapply(), 42
- logLik.seas (udg), 40
- monthplot.seas (plot.seas), 20
- na.x13, 17
- nobs.seas (udg), 40
- original (final), 7
- out, 18
- out(), 9, 24, 25, 35, 39, 41
- outlier, 19
- plot.seas, 20
- plot.seas(), 9, 35, 39, 41
- predict.seas, 22
- print.import.spc (import.spc), 14
- print.summary.seas (summary.seas), 37
- qs (udg), 40
- qs(), 38
- residplot (plot.seas), 20
- residuals.seas (final), 7
- seas, 23
- seas(), 3, 8–10, 14, 17, 18, 20–22, 33, 35, 37–39, 41–43
- seasonal (seasonal-package), 2
- seasonal(), 5
- seasonal-package, 2
- seasonalview::view(), 43
- series, 27
- series(), 7–9, 24, 25, 35, 39, 41
- spc, 34
- SPECS, 35
- Startup(), 3

static, 36
static(), 25, 43, 44
stats::getCall(), 37
summary.seas, 37
summary.seas(), 44
suppressPackageStartupMessages(), 3

transformfunction, 39
trend(final), 7

udg, 40
udg(), 18, 21, 24, 25, 38
unemp, 42
update(), 18, 42
update.seas, 42
update.seas(), 22, 25

view, 43
view(), 23, 25