

# Package ‘sf’

September 13, 2020

**Version** 0.9-6

**Title** Simple Features for R

**Description** Support for simple features, a standardized way to encode spatial vector data. Binds to 'GDAL' for reading and writing data, to 'GEOS' for geometrical operations, and to 'PROJ' for projection conversions and datum transformations. Optionally uses the 's2' package for spherical geometry operations on geographic coordinates.

**License** GPL-2 | MIT + file LICENSE

**URL** <https://r-spatial.github.io/sf/>, <https://github.com/r-spatial/sf/>

**BugReports** <https://github.com/r-spatial/sf/issues/>

**Depends** methods, R (>= 3.3.0)

**Imports** classInt (>= 0.4-1), DBI (>= 0.8), graphics, grDevices, grid, magrittr, Rcpp (>= 0.12.18), stats, tools, units (>= 0.6-0), utils

**Suggests** blob, covr, dplyr (>= 0.8-3), ggplot2, knitr, lwgeom (>= 0.2-1), maps, mapview, microbenchmark, odbc, pillar, pool, raster, rgdal, rgeos, rlang, rmarkdown, RPostgres (>= 1.1.0), RPostgreSQL, RSQLite, s2 (>= 1.0.1), sp (>= 1.2-4), spatstat, spatstat.utils, stars (>= 0.2-0), testthat, tibble (>= 1.4.1), tidyr (>= 1.0-0), tidyselect (>= 1.0.0), tmap (>= 2.0), vctrs

**LinkingTo** Rcpp

**VignetteBuilder** knitr

**Encoding** UTF-8

**RoxygenNote** 7.1.1

**SystemRequirements** C++11, GDAL (>= 2.0.1), GEOS (>= 3.4.0), PROJ (>= 4.8.0)

**Collate** 'RcppExports.R' 'init.R' 'crs.R' 'bbox.R' 'read.R' 'db.R' 'sfc.R' 'sfg.R' 'sf.R' 'bind.R' 'wkb.R' 'wkt.R' 'plot.R' 'geom-measures.R' 'geom-predicates.R' 'geom-transformers.R' 'transform.R' 'sp.R' 'grid.R' 'arith.R' 'tidyverse.R' 'tidyverse-vctrs.R' 'cast\_sfg.R' 'cast\_sfc.R' 'graticule.R'

'datasets.R' 'aggregate.R' 'agr.R' 'maps.R' 'join.R' 'sample.R'  
 'valid.R' 'collection\_extract.R' 'jitter.R' 'sgbp.R'  
 'spatstat.R' 'stars.R' 'crop.R' 'gdal\_utils.R' 'nearest.R'  
 'normalize.R' 'defunct.R' 'z\_range.R' 'm\_range.R'  
 'shift\_longitude.R' 'make\_grid.R' 's2.R'

**NeedsCompilation** yes

**Author** Edzer Pebesma [aut, cre] (<<https://orcid.org/0000-0001-8049-7069>>),  
 Roger Bivand [ctb] (<<https://orcid.org/0000-0003-2392-6140>>),  
 Etienne Racine [ctb],  
 Michael Sumner [ctb],  
 Ian Cook [ctb],  
 Tim Keitt [ctb],  
 Robin Lovelace [ctb],  
 Hadley Wickham [ctb],  
 Jeroen Ooms [ctb] (<<https://orcid.org/0000-0002-4035-0289>>),  
 Kirill Müller [ctb],  
 Thomas Lin Pedersen [ctb],  
 Dan Baston [ctb]

**Maintainer** Edzer Pebesma <[edzer.pebesma@uni-muenster.de](mailto:edzer.pebesma@uni-muenster.de)>

**Repository** CRAN

**Date/Publication** 2020-09-13 15:00:03 UTC

**R topics documented:**

aggregate.sf . . . . .	4
as . . . . .	5
bind . . . . .	6
dbDataType,PostgreSQLConnection,sf-method . . . . .	8
db_drivers . . . . .	8
extension_map . . . . .	9
gdal . . . . .	9
gdal_utils . . . . .	12
geos_binary_ops . . . . .	13
geos_binary_pred . . . . .	16
geos_combine . . . . .	18
geos_measures . . . . .	19
geos_query . . . . .	21
geos_unary . . . . .	22
internal . . . . .	26
is_driver_available . . . . .	26
is_driver_can . . . . .	27
is_geometry_column . . . . .	27
merge.sf . . . . .	28
nc . . . . .	28
Ops . . . . .	29
plot . . . . .	30

prefix_map	36
rawToHex	36
s2	36
sf	38
sf-defunct	40
sfc	41
sf_extSoftVersion	42
sf_project	42
sf_proj_search_paths	43
sgbp	43
st	44
stars	47
st_agr	48
st_as_binary	49
st_as_grob	50
st_as_sf	51
st_as_sfc	53
st_as_text	56
st_bbox	57
st_cast	59
st_cast_sfc_default	62
st_collection_extract	62
st_coordinates	64
st_crop	65
st_crs	66
st_drivers	68
st_geometry	69
st_geometry_type	71
st_graticule	71
st_interpolate_aw	73
st_is	74
st_is_longlat	74
st_jitter	75
st_join	75
st_layers	78
st_line_sample	78
st_make_grid	79
st_m_range	80
st_nearest_feature	82
st_nearest_points	83
st_normalize	85
st_precision	85
st_read	86
st_relate	90
st_sample	91
st_shift_longitude	94
st_transform	95
st_viewport	97

st_write . . . . .	98
st_zm . . . . .	101
st_z_range . . . . .	102
summary.sfc . . . . .	104
tibble . . . . .	104
tidyverse . . . . .	105
transform.sf . . . . .	109
valid . . . . .	110
vctrs . . . . .	111

<b>Index</b>	<b>112</b>
--------------	------------

---

aggregate.sf	<i>aggregate an sf object</i>
--------------	-------------------------------

---

## Description

aggregate an sf object, possibly union-ing geometries

## Usage

```
## S3 method for class 'sf'
aggregate(
  x,
  by,
  FUN,
  ...,
  do_union = TRUE,
  simplify = TRUE,
  join = st_intersects
)
```

## Arguments

x	object of class <a href="#">sf</a>
by	either a list of grouping vectors with length equal to <code>nrow(x)</code> (see <a href="#">aggregate</a> ), or an object of class <code>sf</code> or <code>sfc</code> with geometries that are used to generate groupings, using the binary predicate specified by the argument <code>join</code>
FUN	function passed on to <a href="#">aggregate</a> , in case <code>ids</code> was specified and attributes need to be grouped
...	arguments passed on to FUN
do_union	logical; should grouped geometries be unioned using <a href="#">st_union</a> ? See details.
simplify	logical; see <a href="#">aggregate</a>
join	logical spatial predicate function to use if <code>by</code> is a simple features object or geometry; see <a href="#">st_join</a>

## Details

In case `do_union` is `FALSE`, `aggregate` will simply combine geometries using `c.sfg`. When polygons sharing a boundary are combined, this leads to geometries that are invalid; see <https://github.com/r-spatial/sf/issues/681>.

## Value

an `sf` object with aggregated attributes and geometries; additional grouping variables having the names of `names(ids)` or are named `Group.i` for `ids[[i]]`; see [aggregate](#).

## Note

Does not work using the formula notation involving `~` defined in [aggregate](#).

## Examples

```
m1 = cbind(c(0, 0, 1, 0), c(0, 1, 1, 0))
m2 = cbind(c(0, 1, 1, 0), c(0, 0, 1, 0))
pol = st_sfc(st_polygon(list(m1)), st_polygon(list(m2)))
set.seed(1985)
d = data.frame(matrix(runif(15), ncol = 3))
p = st_as_sf(x = d, coords = 1:2)
plot(pol)
plot(p, add = TRUE)
(p_ag1 = aggregate(p, pol, mean))
plot(p_ag1) # geometry same as pol
# works when x overlaps multiple objects in 'by':
p_buff = st_buffer(p, 0.2)
plot(p_buff, add = TRUE)
(p_ag2 = aggregate(p_buff, pol, mean)) # increased mean of second
# with non-matching features
m3 = cbind(c(0, 0, -0.1, 0), c(0, 0.1, 0.1, 0))
pol = st_sfc(st_polygon(list(m3)), st_polygon(list(m1)), st_polygon(list(m2)))
(p_ag3 = aggregate(p, pol, mean))
plot(p_ag3)
# In case we need to pass an argument to the join function:
(p_ag4 = aggregate(p, pol, mean,
  join = function(x, y) st_is_within_distance(x, y, dist = 0.3)))
```

---

 as

*Methods to coerce simple features to Spatial\* and Spatial\*DataFrame objects*

---

## Description

`as_Spatial()` allows to convert `sf` and `sfc` to `Spatial*DataFrame` and `Spatial*` for `sp` compatibility. You can also use `as(x, "Spatial")` To transform `sp` objects to `sf` and `sfc` with `as(x, "sf")`.

**Usage**

```
as_Spatial(from, cast = TRUE, IDs = paste0("ID", seq_along(from)))
```

**Arguments**

from	object of class sf, sfc_POINT, sfc_MULTIPPOINT, sfc_LINESTRING, sfc_MULTILINESTRING, sfc_POLYGON, or sfc_MULTIPOLYGON.
cast	logical; if TRUE, <code>st_cast()</code> from before converting, so that e.g. GEOMETRY objects with a mix of POLYGON and MULTIPOLYGON are cast to MULTIPOLYGON.
IDs	character vector with IDs for the Spatial* geometries

**Details**

Package sp supports three dimensions for POINT and MULTIPPOINT (SpatialPoint\*). Other geometries must be two-dimensional (XY). Dimensions can be dropped using `st_zm()` with `what = "M"` or `what = "ZM"`.

For converting simple features (i.e., sf objects) to their Spatial counterpart, use `as(obj, "Spatial")`

**Value**

geometry-only object deriving from Spatial, of the appropriate class

**Examples**

```
nc <- st_read(system.file("shape/nc.shp", package="sf"))
# convert to SpatialPolygonsDataFrame
spdf <- as_Spatial(nc)
# identical to
spdf <- as(nc, "Spatial")
# convert to SpatialPolygons
as(st_geometry(nc), "Spatial")
# back to sf
as(spdf, "sf")
```

---

 bind

*Bind rows (features) of sf objects*


---

**Description**

Bind rows (features) of sf objects

Bind columns (variables) of sf objects

**Usage**

```
## S3 method for class 'sf'
rbind(..., deparse.level = 1)

## S3 method for class 'sf'
cbind(..., deparse.level = 1, sf_column_name = NULL)

st_bind_cols(...)
```

**Arguments**

... objects to bind; note that for the rbind and cbind methods, all objects have to be of class sf; see [dotsMethods](#)

deparse.level integer; see [rbind](#)

sf\_column\_name character; specifies active geometry; passed on to [st\\_sf](#)

**Details**

both rbind and cbind have non-standard method dispatch (see [cbind](#)): the rbind or cbind method for sf objects is only called when all arguments to be binded are of class sf.

If you need to cbind e.g. a data.frame to an sf, use [data.frame](#) directly and use [st\\_sf](#) on its result, or use [bind\\_cols](#); see examples.

st\_bind\_cols is deprecated; use cbind instead.

**Value**

cbind called with multiple sf objects warns about multiple geometry columns present when the geometry column to use is not specified by using argument sf\_column\_name; see also [st\\_sf](#).

**Examples**

```
crs = st_crs(3857)
a = st_sf(a=1, geom = st_sfc(st_point(0:1)), crs = crs)
b = st_sf(a=1, geom = st_sfc(st_linestring(matrix(1:4,2))), crs = crs)
c = st_sf(a=4, geom = st_sfc(st_multilinestring(list(matrix(1:4,2)))), crs = crs)
rbind(a,b,c)
rbind(a,b)
rbind(a,b)
rbind(b,c)
cbind(a,b,c) # warns
if (require(dplyr))
  dplyr::bind_cols(a,b)
c = st_sf(a=4, geomc = st_sfc(st_multilinestring(list(matrix(1:4,2)))), crs = crs)
cbind(a,b,c, sf_column_name = "geomc")
df = data.frame(x=3)
st_sf(data.frame(c, df))
dplyr::bind_cols(c, df)
```

dbDataType,PostgreSQLConnection,sf-method  
*Determine database type for R vector*

---

**Description**

Determine database type for R vector

Determine database type for R vector

**Usage**

```
## S4 method for signature 'PostgreSQLConnection,sf'  
dbDataType(dbObj, obj)
```

```
## S4 method for signature 'DBIObject,sf'  
dbDataType(dbObj, obj)
```

**Arguments**

dbObj            DBIObject driver or connection.  
obj              Object to convert

---

db\_drivers            *Drivers for which update should be TRUE by default*

---

**Description**

Drivers for which update should be TRUE by default

**Usage**

```
db_drivers
```

**Format**

An object of class character of length 12.



---

extension_map	<i>Map extension to driver</i>
---------------	--------------------------------

---

**Description**

Map extension to driver

**Usage**

extension\_map

**Format**

An object of class list of length 25.

---

gdal	<i>functions to interact with gdal not meant to be called directly by users (but e.g. by stars::read_stars)</i>
------	---

---

**Description**

functions to interact with gdal not meant to be called directly by users (but e.g. by stars::read\_stars)

**Usage**

```
gdal_read(
  x,
  ...,
  options = character(),
  driver = character(),
  read_data = TRUE,
  NA_value = NA_real_,
  RasterIO_parameters = list()
)
```

```
gdal_write(
  x,
  ...,
  file,
  driver = "GTiff",
  options = character(),
  type = "Float32",
  NA_value = NA_real_,
  geotransform,
  update = FALSE
)
```

```

)

gdal_inv_geotransform(gt)

gdal_crs(file, options = character(0))

gdal_metadata(
  file,
  domain_item = character(0),
  options = character(0),
  parse = TRUE
)

gdal_subdatasets(file, options = character(0), name = TRUE)

gdal_polygonize(
  x,
  mask = NULL,
  file = tempfile(),
  driver = "GTiff",
  use_integer = TRUE,
  geotransform,
  breaks = classInt::classIntervals(na.omit(as.vector(x[[1]])))$brks,
  use_contours = FALSE,
  contour_lines = FALSE,
  connect8 = FALSE,
  ...
)

gdal_rasterize(sf, x, gt, file, driver = "GTiff", options = character())

```

### Arguments

<code>x</code>	character vector, possibly of length larger than 1 when more than one raster is read
<code>...</code>	ignored
<code>options</code>	character; raster layer read options
<code>driver</code>	character; when empty vector, driver is auto-detected.
<code>read_data</code>	logical; if FALSE, only the imagery metadata is returned
<code>NA_value</code>	(double) non-NA value to use for missing values; if NA, when writing missing values are not specially flagged in output dataset, when reading the default (dataset) missing values are used (if present / set).
<code>RasterIO_parameters</code>	list with named parameters to GDAL's RasterIO; see the <code>stars::read_stars</code> documentation.
<code>file</code>	character; file name
<code>type</code>	gdal write type

geotransform	length 6 numeric vector with GDAL geotransform parameters.
update	logical; TRUE if in an existing raster file pixel values shall be updated.
gt	double vector of length 6
domain_item	character vector of length 0, 1 (with domain), or 2 (with domain and item); use "" for the default domain, use NA_character_ to query the domain names.
parse	logical; should metadata be parsed into a named list (TRUE) or returned as character data?
name	logical; retrieve name of subdataset? If FALSE, retrieve description
mask	stars object with NA mask (0 where NA), or NULL
use_integer	boolean; if TRUE, raster values are read as (and rounded to) unsigned 32-bit integers values; if FALSE they are read as 32-bit floating points numbers. The former is supposedly faster.
breaks	numeric vector with break values for contour polygons (or lines)
use_contours	logical;
contour_lines	logical;
connect8	logical; if TRUE use 8 connection algorithm, rather than 4
sf	object of class sf

### Details

These functions are exported for the single purpose of being used by package stars, they are not meant to be used directly and may change or disappear without prior notice or deprecation warnings.

gdal\_inv\_geotransform returns the inverse geotransform

gdal\_crs reads coordinate reference system from GDAL data set

get\_metadata gets metadata of a raster layer

gdal\_subdatasets returns the subdatasets of a gdal dataset

### Value

object of class crs, see [st\\_crs](#).

named list with metadata items

gdal\_subdatasets returns a zero-length list if file does not have subdatasets, and else a named list with subdatasets.

### Examples

```
## Not run:
f = system.file("tif/L7_ETMs.tif", package="stars")
f = system.file("nc/avhrr-only-v2.19810901.nc", package = "stars")
gdal_metadata(f)
gdal_metadata(f, NA_character_)
try(gdal_metadata(f, "wrongDomain"))
gdal_metadata(f, c("", "AREA_OR_POINT"))

## End(Not run)
```

---

 gdal\_utils

*Native interface to gdal utils*


---

## Description

Native interface to gdal utils

## Usage

```
gdal_utils(
  util = "info",
  source,
  destination,
  options = character(0),
  quiet = !(util %in% c("info", "mdiminfo")),
  processing = character(0),
  colorfilename = character(0)
)
```

## Arguments

util	character; one of info, warp, rasterize, translate, vectortranslate (for ogr2ogr), buildvrt, demprocessing, nearblack, grid, mdiminfo and mdimtranslate (the last two requiring GDAL 3.1)
source	character; name of input layer(s); for warp, buildvrt or mdimtranslate this can be more than one
destination	character; name of output layer
options	character; options for the utility
quiet	logical; if TRUE, suppress printing the output for info and mdiminfo, and suppress printing progress
processing	character; processing options for demprocessing
colorfilename	character; name of color file for demprocessing (mandatory if processing="color-relief")

## Value

info returns a character vector with the raster metadata; all other utils return (invisibly) a logical indicating success (i.e., TRUE); in case of failure, an error is raised.

## Examples

```
if (sf_extSoftVersion()["GDAL"] > "2.1.0") {
  # info utils can be used to list information about about a raster
  # dataset. More info: https://gdal.org/programs/gdalinfo.html
  in_file <- system.file("tif/geomatrix.tif", package = "sf")
  gdal_utils("info", in_file, options = c("-mm", "-proj4"))
}
```

```

# vectortranslate utils can be used to convert simple features data between
# file formats. More info: https://gdal.org/programs/ogr2ogr.html
in_file <- system.file("shape/storms_xyz.shp", package="sf")
out_file <- paste0(tempfile(), ".gpkg")
gdal_utils(
  util = "vectortranslate",
  source = in_file,
  destination = out_file, # output format must be specified for GDAL < 2.3
  options = c("-f", "GPKG")
)
# The parameters can be specified as c("name") or c("name", "value"). The
# vectortranslate utils can perform also various operations during the
# conversion process. For example we can reproject the features during the
# translation.
gdal_utils(
  util = "vectortranslate",
  source = in_file,
  destination = out_file,
  options = c(
    "-f", "GPKG", # output file format for GDAL < 2.3
    "-s_srs", "EPSG:4326", # input file SRS
    "-t_srs", "EPSG:2264", # output file SRS
    "-overwrite"
  )
)
st_read(out_file)
# The parameter s_srs had to be specified because, in this case, the in_file
# has no associated SRS.
st_read(in_file)
}

```

---

geos\_binary\_ops

*Geometric operations on pairs of simple feature geometry sets*


---

## Description

Perform geometric set operations with simple feature geometry collections

## Usage

```

st_intersection(x, y, ...)

## S3 method for class 'sfc'
st_intersection(x, y, ...)

## S3 method for class 'sf'
st_intersection(x, y, ...)

```

```

st_difference(x, y, ...)

## S3 method for class 'sfc'
st_difference(x, y, ...)

st_sym_difference(x, y, ...)

st_snap(x, y, tolerance)

```

### Arguments

x	object of class sf, sfc or sfg
y	object of class sf, sfc or sfg
...	arguments passed on to <a href="#">s2_options</a>
tolerance	tolerance values used for st_snap; numeric value or object of class units; may have tolerance values for each feature in x

### Details

When using GEOS and not using s2, a spatial index is built on argument x; see <https://www.r-spatial.org/r/2017/06/22/spatial-index.html>. The reference for the STR tree algorithm is: Leutenegger, Scott T., Mario A. Lopez, and Jeffrey Edgington. "STR: A simple and efficient algorithm for R-tree packing." Data Engineering, 1997. Proceedings. 13th international conference on. IEEE, 1997. For the pdf, search Google Scholar.

When called with missing y, the sfc method for st\_intersection returns all non-empty intersections of the geometries of x; an attribute idx contains a list-column with the indexes of contributing geometries.

when called with a missing y, the sf method for st\_intersection returns an sf object with attributes taken from the contributing feature with lowest index; two fields are added: n.overlaps with the number of overlapping features in x, and a list-column origins with indexes of all overlapping features.

When st\_difference is called with a single argument, overlapping areas are erased from geometries that are indexed at greater numbers in the argument to x; geometries that are empty or contained fully inside geometries with higher priority are removed entirely. The st\_difference.sfc method with a single argument returns an object with an "idx" attribute with the original index for returned geometries.

st\_snap snaps the vertices and segments of a geometry to another geometry's vertices. If y contains more than one geometry, its geometries are merged into a collection before snapping to that collection.

(from the GEOS docs:) "A snap distance tolerance is used to control where snapping is performed. Snapping one geometry to another can improve robustness for overlay operations by eliminating nearly-coincident edges (which cause problems during nodding and intersection calculation). Too much snapping can result in invalid topology being created, so the number and location of snapped vertices is decided using heuristics to determine when it is safe to snap. This can result in some potential snaps being omitted, however."

**Value**

The intersection, difference or symmetric difference between two sets of geometries. The returned object has the same class as that of the first argument (*x*) with the non-empty geometries resulting from applying the operation to all geometry pairs in *x* and *y*. In case *x* is of class *sf*, the matching attributes of the original object(s) are added. The *sfc* geometry list-column returned carries an attribute *idx*, which is an *n*-by-2 matrix with every row the index of the corresponding entries of *x* and *y*, respectively.

**Note**

To find whether pairs of simple feature geometries intersect, use the function [st\\_intersects](#) instead of `st_intersection`.

**See Also**

[st\\_union](#) for the union of simple features collections; [intersect](#) and [setdiff](#) for the base R set operations.

**Examples**

```
set.seed(131)
library(sf)
m = rbind(c(0,0), c(1,0), c(1,1), c(0,1), c(0,0))
p = st_polygon(list(m))
n = 100
l = vector("list", n)
for (i in 1:n)
  l[[i]] = p + 10 * runif(2)
s = st_sfc(l)
plot(s, col = sf.colors(categorical = TRUE, alpha = .5))
title("overlapping squares")
d = st_difference(s) # sequential differences: s1, s2-s1, s3-s2-s1, ...
plot(d, col = sf.colors(categorical = TRUE, alpha = .5))
title("non-overlapping differences")
i = st_intersection(s) # all intersections
plot(i, col = sf.colors(categorical = TRUE, alpha = .5))
title("non-overlapping intersections")
summary(lengths(st_overlaps(s, s))) # includes self-counts!
summary(lengths(st_overlaps(d, d)))
summary(lengths(st_overlaps(i, i)))
sf = st_sf(s)
i = st_intersection(sf) # all intersections
plot(i["n.overlaps"])
summary(i$n.overlaps - lengths(i$origins))
# A helper function that erases all of y from x:
st_erase = function(x, y) st_difference(x, st_union(st_combine(y)))
poly = st_polygon(list(cbind(c(0, 0, 1, 1, 0), c(0, 1, 1, 0, 0))))
lines = st_multilinestring(list(
  cbind(c(0, 1), c(1, 1.05)),
  cbind(c(0, 1), c(0, -.05)),
  cbind(c(1, .95, 1), c(1.05, .5, -.05))
```

```

))
snapped = st_snap(poly, lines, tolerance=.1)
plot(snapped, col='red')
plot(poly, border='green', add=TRUE)
plot(lines, lwd=2, col='blue', add=TRUE)

```

---

geos\_binary\_pred

*Geometric binary predicates on pairs of simple feature geometry sets*


---

## Description

Geometric binary predicates on pairs of simple feature geometry sets

## Usage

```

st_intersects(x, y, sparse = TRUE, ...)

st_disjoint(x, y = x, sparse = TRUE, prepared = TRUE)

st_touches(x, y, sparse = TRUE, prepared = TRUE, ...)

st_crosses(x, y, sparse = TRUE, prepared = TRUE, ...)

st_within(x, y, sparse = TRUE, prepared = TRUE, ...)

st_contains(x, y, sparse = TRUE, prepared = TRUE, ..., s2_model = "open")

st_contains_properly(x, y, sparse = TRUE, prepared = TRUE, ...)

st_overlaps(x, y, sparse = TRUE, prepared = TRUE, ...)

st_equals(x, y, sparse = TRUE, prepared = FALSE, ...)

st_covers(x, y, sparse = TRUE, prepared = TRUE, ..., s2_model = "closed")

st_covered_by(
  x,
  y = x,
  sparse = TRUE,
  prepared = TRUE,
  ...,
  s2_model = "closed"
)

st_equals_exact(x, y, par, sparse = TRUE, prepared = FALSE, ...)

st_is_within_distance(x, y = x, dist, sparse = TRUE, ...)

```



**Arguments**

x	object of class sf, sfc or sfg
y	object of class sf, sfc or sfg; if missing, x is used
sparse	logical; should a sparse index list be returned (TRUE) or a dense logical matrix? See below.
...	passed on to <a href="#">s2_options</a>
prepared	logical; prepare geometry for x, before looping over y? See Details.
s2_model	character; polygon/polylin model; one of "OPEN", "SEMI_OPEN", and "CLOSED"; see Details.
par	numeric; parameter used for "equals_exact" (margin);
dist	distance threshold; geometry indexes with distances smaller or equal to this value are returned; numeric value or units value having distance units.

**Details**

If prepared is TRUE, and x contains POINT geometries and y contains polygons, then the polygon geometries are prepared, rather than the points.

For most predicates, a spatial index is built on argument x; see <https://www.r-spatial.org/r/2017/06/22/spatial-index.html>. Specifically, st\_intersects, st\_disjoint, st\_touches, st\_crosses, st\_within, st\_contains, st\_contains\_properly, st\_overlaps, st\_equals, st\_covers and st\_covered\_by all build spatial indexes for more efficient geometry calculations. st\_relate, st\_equals\_exact, and do not; st\_is\_within\_distance uses a spatial index for geographic coordinates when sf\_use\_s2() is true.

If y is missing, 'st\_predicate(x, x)' is effectively called, and a square matrix is returned with diagonal elements 'st\_predicate(x[i], x[i])'.

Sparse geometry binary predicate ([sgbp](#)) lists have the following attributes: region.id with the row.names of x (if any, else 1:n), ncol with the number of features in y, and predicate with the name of the predicate used.

for s2\_model, see <https://github.com/r-spatial/s2/issues/32>

'st\_contains\_properly(A,B)' is true if A intersects B's interior, but not its edges or exterior; A contains A, but A does not properly contain A.

See also [st\\_relate](#) and <https://en.wikipedia.org/wiki/DE-9IM> for a more detailed description of the underlying algorithms.

st\_equals\_exact returns true for two geometries of the same type and their vertices corresponding by index are equal up to a specified tolerance.

**Value**

If sparse=FALSE, st\_predicate (with predicate e.g. "intersects") returns a dense logical matrix with element i, j TRUE when predicate(x[i],y[j]) (e.g., when geometry of feature i and j intersect); if sparse=TRUE, an object of class [sgbp](#) with a sparse list representation of the same matrix, with list element i an integer vector with all indices j for which predicate(x[i],y[j]) is TRUE (and hence a zero-length integer vector if none of them is TRUE). From the dense matrix, one can find out if one or more elements intersect by `apply(mat, 1, any)`, and from the sparse list by `lengths(lst) > 0`, see examples below.

**Note**

For intersection on pairs of simple feature geometries, use the function `st_intersection` instead of `st_intersects`.

**Examples**

```
pts = st_sfc(st_point(c(.5,.5)), st_point(c(1.5, 1.5)), st_point(c(2.5, 2.5)))
pol = st_polygon(list(rbind(c(0,0), c(2,0), c(2,2), c(0,2), c(0,0))))
(lst = st_intersects(pts, pol))
(mat = st_intersects(pts, pol, sparse = FALSE))
# which points fall inside a polygon?
apply(mat, 1, any)
lengths(lst) > 0
# which points fall inside the first polygon?
st_intersects(pol, pts)[[1]]
```

---

geos\_combine

*Combine or union feature geometries*


---

**Description**

Combine several feature geometries into one, without unioning or resolving internal boundaries

**Usage**

```
st_combine(x)
```

```
st_union(x, y, ..., by_feature = FALSE, is_coverage = FALSE)
```

**Arguments**

<code>x</code>	object of class <code>sf</code> , <code>sfc</code> or <code>sfg</code>
<code>y</code>	object of class <code>sf</code> , <code>sfc</code> or <code>sfg</code> (optional)
<code>...</code>	ignored
<code>by_feature</code>	logical; if <code>TRUE</code> , union each feature, if <code>FALSE</code> return a single feature that is the geometric union of the set of features
<code>is_coverage</code>	logical; if <code>TRUE</code> , use an optimized algorithm for features that form a polygonal coverage (have no overlaps)

**Details**

`st_combine` combines geometries without resolving borders, using `c.sfg` (analogous to `c` for ordinary vectors).

If `st_union` is called with a single argument, `x`, (with `y` missing) and `by_feature` is `FALSE` all geometries are unioned together and an `sfg` or single-geometry `sfc` object is returned. If `by_feature`

is TRUE each feature geometry is unioned. This can for instance be used to resolve internal boundaries after polygons were combined using `st_combine`. If `y` is provided, all elements of `x` and `y` are unioned, pairwise (and `by_feature` is ignored). The former corresponds to [gUnaryUnion](#), the latter to [gUnion](#).

Unioning a set of overlapping polygons has the effect of merging the areas (i.e. the same effect as iteratively unioning all individual polygons together). Unioning a set of LineStrings has the effect of fully noding and dissolving the input linework. In this context "fully noded" means that there will be a node or endpoint in the output for every endpoint or line segment crossing in the input. "Dissolved" means that any duplicate (e.g. coincident) line segments or portions of line segments will be reduced to a single line segment in the output. Unioning a set of Points has the effect of merging all identical points (producing a set with no duplicates).

### Value

`st_combine` returns a single, combined geometry, with no resolved boundaries; returned geometries may well be invalid.

If `y` is missing, `st_union(x)` returns a single geometry with resolved boundaries, else the geometries for all unioned pairs of `x[i]` and `y[j]`.

### See Also

[st\\_intersection](#), [st\\_difference](#), [st\\_sym\\_difference](#)

### Examples

```
nc = st_read(system.file("shape/nc.shp", package="sf"))
st_combine(nc)
plot(st_union(nc))
```

---

geos\_measures

*Compute geometric measurements*

---

### Description

Compute Euclidian or great circle distance between pairs of geometries; compute, the area or the length of a set of geometries.

### Usage

```
st_area(x, ...)

## S3 method for class 'sfc'
st_area(x, ...)

st_length(x, ...)

st_distance(
```

```

x,
y,
...,
dist_fun,
by_element = FALSE,
which = ifelse(isTRUE(st_is_longlat(x)), "Great Circle", "Euclidean"),
par = 0,
tolerance = 0
)

```

### Arguments

x	object of class sf, sfc or sfg
...	ignored
y	object of class sf, sfc or sfg, defaults to x
dist_fun	deprecated
by_element	logical; if TRUE, return a vector with distance between the first elements of x and y, the second, etc. if FALSE, return the dense matrix with all pairwise distances.
which	character; for Cartesian coordinates only: one of Euclidean, Hausdorff or Frechet; for geodetic coordinates, great circle distances are computed; see details
par	for which equal to Hausdorff or Frechet, optionally use a value between 0 and 1 to densify the geometry
tolerance	ignored if st_is_longlat(x) is FALSE; otherwise, if set to a positive value, the first distance smaller than tolerance will be returned, and true distance may be smaller; this may speed up computation. In meters, or a units object convertible to meters.

### Details

great circle distance calculations use function `geod_inverse` from PROJ; see Karney, Charles FF, 2013, Algorithms for geodesics, Journal of Geodesy 87(1), 43–55

### Value

If the coordinate reference system of x was set, these functions return values with unit of measurement; see [set\\_units](#).

`st_area` returns the area of a geometry, in the coordinate reference system used; in case x is in degrees longitude/latitude, `st_geod_area` is used for area calculation.

`st_length` returns the length of a LINESTRING or MULTILINESTRING geometry, using the coordinate reference system. POINT, MULTIPOINT, POLYGON or MULTIPOLYGON geometries return zero.

If `by_element` is FALSE `st_distance` returns a dense numeric matrix of dimension `length(x)` by `length(y)`; otherwise it returns a numeric vector of length x or y, the shorter one being recycled. Distances involving empty geometries are NA.

**See Also**

[st\\_dimension](#), [st\\_cast](#) to convert geometry types

**Examples**

```

b0 = st_polygon(list(rbind(c(-1,-1), c(1,-1), c(1,1), c(-1,1), c(-1,-1))))
b1 = b0 + 2
b2 = b0 + c(-0.2, 2)
x = st_sfc(b0, b1, b2)
st_area(x)
line = st_sfc(st_linestring(rbind(c(30,30), c(40,40))), crs = 4326)
st_length(line)

outer = matrix(c(0,0,10,0,10,0,10,0,10,0),ncol=2, byrow=TRUE)
hole1 = matrix(c(1,1,1,2,2,2,2,1,1,1),ncol=2, byrow=TRUE)
hole2 = matrix(c(5,5,5,6,6,6,6,5,5,5),ncol=2, byrow=TRUE)

poly = st_polygon(list(outer, hole1, hole2))
mpoly = st_multipolygon(list(
list(outer, hole1, hole2),
list(outer + 12, hole1 + 12)
))

st_length(st_sfc(poly, mpoly))
p = st_sfc(st_point(c(0,0)), st_point(c(0,1)), st_point(c(0,2)))
st_distance(p, p)
st_distance(p, p, by_element = TRUE)

```

---

geos\_query

*Dimension, simplicity, validity or is\_empty queries on simple feature geometries*

---

**Description**

Dimension, simplicity, validity or is\_empty queries on simple feature geometries

**Usage**

```

st_dimension(x, NA_if_empty = TRUE)

st_is_simple(x)

st_is_empty(x)

```

**Arguments**

x object of class sf, sfc or sfg  
NA\_if\_empty logical; if TRUE, return NA for empty geometries

**Value**

`st_dimension` returns a numeric vector with 0 for points, 1 for lines, 2 for surfaces, and, if `NA_if_empty` is TRUE, NA for empty geometries.

`st_is_simple` returns a logical vector, indicating for each geometry whether it is simple (e.g., not self-intersecting)

`st_is_empty` returns for each geometry whether it is empty

**Examples**

```
x = st_sfc(
  st_point(0:1),
  st_linestring(rbind(c(0,0),c(1,1))),
  st_polygon(list(rbind(c(0,0),c(1,0),c(0,1),c(0,0)))),
  st_multipoint(),
  st_linestring(),
  st_geometrycollection())
st_dimension(x)
st_dimension(x, FALSE)
ls = st_linestring(rbind(c(0,0), c(1,1), c(1,0), c(0,1)))
st_is_simple(st_sfc(ls, st_point(c(0,0))))
ls = st_linestring(rbind(c(0,0), c(1,1), c(1,0), c(0,1)))
st_is_empty(st_sfc(ls, st_point(), st_linestring()))
```

---

geos\_unary

*Geometric unary operations on simple feature geometry sets*


---

**Description**

Geometric unary operations on simple feature geometries. These are all generics, with methods for `sfg`, `sfc` and `sf` objects, returning an object of the same class. All operations work on a per-feature basis, ignoring all other features.

**Usage**

```
st_buffer(
  x,
  dist,
  nQuadSegs = 30,
  endCapStyle = "ROUND",
  joinStyle = "ROUND",
  mitreLimit = 1,
  singleSide = FALSE,
  ...
)

st_boundary(x)
```

```

st_convex_hull(x)

st_simplify(x, preserveTopology = FALSE, dTolerance = 0)

st_triangulate(x, dTolerance = 0, bOnlyEdges = FALSE)

st_voronoi(x, envelope, dTolerance = 0, bOnlyEdges = FALSE)

st_polygonize(x)

st_line_merge(x)

st_centroid(x, ..., of_largest_polygon = FALSE)

st_point_on_surface(x)

st_reverse(x)

st_node(x)

st_segmentize(x, dfMaxLength, ...)

```

### Arguments

x	object of class <code>sfg</code> , <code>sfc</code> or <code>sf</code>
dist	numeric; buffer distance for all, or for each of the elements in x; in case dist is a units object, it should be convertible to <code>arc_degree</code> if x has geographic coordinates, and to <code>st_crs(x)\$units</code> otherwise
nQuadSegs	integer; number of segments per quadrant (fourth of a circle), for all or per-feature
endCapStyle	character; style of line ends, one of 'ROUND', 'FLAT', 'SQUARE'
joinStyle	character; style of line joins, one of 'ROUND', 'MITRE', 'BEVEL'
mitreLimit	numeric; limit of extension for a join if joinStyle 'MITRE' is used (default 1.0, minimum 0.0)
singleSide	logical; if TRUE, single-sided buffers are returned for linear geometries, in which case negative dist values give buffers on the right-hand side, positive on the left.
...	ignored
preserveTopology	logical; carry out topology preserving simplification? May be specified for each, or for all feature geometries. Note that topology is preserved only for single feature geometries, not for sets of them.
dTolerance	numeric; tolerance parameter, specified for all or for each feature geometry.
bOnlyEdges	logical; if TRUE, return lines, else return polygons
envelope	object of class <code>sfc</code> or <code>sfg</code> containing a POLYGON with the envelope for a voronoi diagram; this only takes effect when it is larger than the default envelope, chosen when envelope is an empty polygon

of_largest_polygon	logical; for <code>st_centroid</code> : if TRUE, return centroid of the largest (sub)polygon of a MULTIPOLYGON rather than of the whole MULTIPOLYGON
dfMaxLength	maximum length of a line segment. If <code>x</code> has geographical coordinates (long/lat), <code>dfMaxLength</code> is either a numeric expressed in meter, or an object of class <code>units</code> with length units <code>rad</code> or <code>degree</code> ; segmentation in the long/lat case takes place along the great circle, using <code>st_geod_segmentize</code> .

## Details

`st_buffer` computes a buffer around this geometry/each geometry. If any of `endCapStyle`, `joinStyle`, or `mitreLimit` are set to non-default values ('ROUND', 'ROUND', 1.0 respectively) then the underlying 'buffer with style' GEOS function is used. See [postgis.net/docs/ST\\_Buffer.html](http://postgis.net/docs/ST_Buffer.html) for details.

`st_boundary` returns the boundary of a geometry

`st_convex_hull` creates the convex hull of a set of points

`st_simplify` simplifies lines by removing vertices

`st_triangulate` triangulates set of points (not constrained). `st_triangulate` requires GEOS version 3.4 or above

`st_voronoi` creates voronoi tessellation. `st_voronoi` requires GEOS version 3.5 or above

`st_polygonize` creates polygon from lines that form a closed ring. In case of `st_polygonize`, `x` must be an object of class `LINESTRING` or `MULTILINESTRING`, or an `sfc` geometry list-column object containing these

`st_line_merge` merges lines. In case of `st_line_merge`, `x` must be an object of class `MULTILINESTRING`, or an `sfc` geometry list-column object containing these

`st_centroid` gives the centroid of a geometry

`st_point_on_surface` returns a point guaranteed to be on the (multi)surface.

`st_reverse` reverses the nodes in a line

`st_node` adds nodes to linear geometries at intersections without a node, and only works on individual linear geometries

`st_segmentize` adds points to straight lines

## Value

an object of the same class of `x`, with manipulated geometry.

## Examples

```
## st_buffer, style options (taken from rgeos gBuffer)
l1 = st_as_sfc("LINESTRING(0 0,1 5,4 5,5 2,8 2,9 4,4 6.5)")
op = par(mfrow=c(2,3))
plot(st_buffer(l1, dist = 1, endCapStyle="ROUND"), reset = FALSE, main = "endCapStyle: ROUND")
plot(l1,col='blue',add=TRUE)
plot(st_buffer(l1, dist = 1, endCapStyle="FLAT"), reset = FALSE, main = "endCapStyle: FLAT")
plot(l1,col='blue',add=TRUE)
plot(st_buffer(l1, dist = 1, endCapStyle="SQUARE"), reset = FALSE, main = "endCapStyle: SQUARE")
```



```

plot(l1,col='blue',add=TRUE)
plot(st_buffer(l1, dist = 1, nQuadSegs=1), reset = FALSE, main = "nQuadSegs: 1")
plot(l1,col='blue',add=TRUE)
plot(st_buffer(l1, dist = 1, nQuadSegs=2), reset = FALSE, main = "nQuadSegs: 2")
plot(l1,col='blue',add=TRUE)
plot(st_buffer(l1, dist = 1, nQuadSegs= 5), reset = FALSE, main = "nQuadSegs: 5")
plot(l1,col='blue',add=TRUE)
par(op)

l2 = st_as_sfc("LINESTRING(0 0,1 5,3 2)")
op = par(mfrow = c(2, 3))
plot(st_buffer(l2, dist = 1, joinStyle="ROUND"), reset = FALSE, main = "joinStyle: ROUND")
plot(l2, col = 'blue', add = TRUE)
plot(st_buffer(l2, dist = 1, joinStyle="MITRE"), reset = FALSE, main = "joinStyle: MITRE")
plot(l2, col= 'blue', add = TRUE)
plot(st_buffer(l2, dist = 1, joinStyle="BEVEL"), reset = FALSE, main = "joinStyle: BEVEL")
plot(l2, col= 'blue', add=TRUE)
plot(st_buffer(l2, dist = 1, joinStyle="MITRE" , mitreLimit=0.5), reset = FALSE,
      main = "mitreLimit: 0.5")
plot(l2, col = 'blue', add = TRUE)
plot(st_buffer(l2, dist = 1, joinStyle="MITRE",mitreLimit=1), reset = FALSE,
      main = "mitreLimit: 1")
plot(l2, col = 'blue', add = TRUE)
plot(st_buffer(l2, dist = 1, joinStyle="MITRE",mitreLimit=3), reset = FALSE,
      main = "mitreLimit: 3")
plot(l2, col = 'blue', add = TRUE)
par(op)
nc = st_read(system.file("shape/nc.shp", package="sf"))
plot(st_convex_hull(nc))
plot(nc, border = grey(.5))
set.seed(1)
x = st_multipoint(matrix(runif(10),,2))
box = st_polygon(list(rbind(c(0,0),c(1,0),c(1,1),c(0,1),c(0,0))))
if (sf_extSoftVersion()["GEOS"] >= "3.5.0") {
  v = st_sfc(st_voronoi(x, st_sfc(box)))
  plot(v, col = 0, border = 1, axes = TRUE)
  plot(box, add = TRUE, col = 0, border = 1) # a larger box is returned, as documented
  plot(x, add = TRUE, col = 'red', cex=2, pch=16)
  plot(st_intersection(st_cast(v), box)) # clip to smaller box
  plot(x, add = TRUE, col = 'red', cex=2, pch=16)
  # matching Voronoi polygons to data points:
  # https://github.com/r-spatial/sf/issues/1030
  # generate 50 random unif points:
  n = 100
  pts = st_as_sf(data.frame(matrix(runif(n), , 2), id = 1:(n/2)), coords = c("X1", "X2"))
  # compute Voronoi polygons:
  polys = st_collection_extract(st_voronoi(do.call(c, st_geometry(pts))))
  # match them to points:
  pts$polys = polys[unlist(st_intersects(pts, polys))]
  plot(pts["id"], pch = 16) # ID is color
  plot(st_set_geometry(pts, "polys")["id"], xlim = c(0,1), ylim = c(0,1), reset = FALSE)
  plot(st_geometry(pts), add = TRUE)
}

```

```

}
mls = st_multilinestring(list(matrix(c(0,0,0,1,1,1,0,0),,2,byrow=TRUE)))
st_polygonize(st_sfc(mls))
mls = st_multilinestring(list(rbind(c(0,0), c(1,1)), rbind(c(2,0), c(1,1))))
st_line_merge(st_sfc(mls))
plot(nc, axes = TRUE)
plot(st_centroid(nc), add = TRUE, pch = 3)
mp = st_combine(st_buffer(st_sfc(lapply(1:3, function(x) st_point(c(x,x)))), 0.2 * 1:3))
plot(mp)
plot(st_centroid(mp), add = TRUE, col = 'red') # centroid of combined geometry
plot(st_centroid(mp, of_largest_polygon = TRUE), add = TRUE, col = 'blue', pch = 3)
plot(nc, axes = TRUE)
plot(st_point_on_surface(nc), add = TRUE, pch = 3)
if (sf_extSoftVersion()["GEOS"] >= "3.7.0") {
  st_reverse(st_linestring(rbind(c(1,1), c(2,2), c(3,3))))
}
(l = st_linestring(rbind(c(0,0), c(1,1), c(0,1), c(1,0), c(0,0))))
st_polygonize(st_node(l))
st_node(st_multilinestring(list(rbind(c(0,0), c(1,1), c(0,1), c(1,0), c(0,0)))))
sf = st_sf(a=1, geom=st_sfc(st_linestring(rbind(c(0,0),c(1,1)))), crs = 4326)
seg = st_segmentize(sf, units::set_units(100, km))
seg = st_segmentize(sf, units::set_units(0.01, rad))
nrow(seg$geom[[1]])

```

---

internal

*Internal functions*

---

## Description

Internal functions

## Usage

```
.stop_geos(msg)
```

## Arguments

msg                    error message

---

is\_driver\_available

*Check if driver is available*

---

## Description

Search through the driver table if driver is listed

**Usage**

```
is_driver_available(drv, drivers = st_drivers())
```

**Arguments**

drv                    character. Name of driver  
 drivers                data.frame. Table containing driver names and support. Default is from [st\\_drivers](#)

---

is\_driver\_can            *Check if a driver can perform an action*

---

**Description**

Search through the driver table to match a driver name with an action (e.g. "write") and check if the action is supported.

**Usage**

```
is_driver_can(drv, drivers = st_drivers(), operation = "write")
```

**Arguments**

drv                    character. Name of driver  
 drivers                data.frame. Table containing driver names and support. Default is from [st\\_drivers](#)  
 operation              character. What action to check

---

is\_geometry\_column      *Check if the columns could be of a coercable type for sf*

---

**Description**

Check if the columns could be of a coercable type for sf

**Usage**

```
is_geometry_column(con, x, classes = "")
```

**Arguments**

con                    database connection  
 x                      inherits data.frame  
 classes                classes inherited

---

<code>merge.sf</code>	<i>merge method for sf and data.frame object</i>
-----------------------	--

---

### Description

merge method for sf and data.frame object

### Usage

```
## S3 method for class 'sf'  
merge(x, y, ...)
```

### Arguments

<code>x</code>	object of class <code>sf</code>
<code>y</code>	object of class <code>data.frame</code>
<code>...</code>	arguments passed on to <code>merge.data.frame</code>

### Examples

```
a = data.frame(a = 1:3, b = 5:7)  
st_geometry(a) = st_sfc(st_point(c(0,0)), st_point(c(1,1)), st_point(c(2,2)))  
b = data.frame(x = c("a", "b", "c"), b = c(2,5,6))  
merge(a, b)  
merge(a, b, all = TRUE)
```

---

<code>nc</code>	<i>North Carolina SIDS data</i>
-----------------	---------------------------------

---

### Description

Sudden Infant Death Syndrome (SIDS) sample data for North Carolina counties, two time periods (1974-78 and 1979-84). The details of the columns can be found on the [seealso URL](#), `spdep` package's vignette. Please note that, though this is basically the same as `nc.sids` dataset in `spData` package, `nc` only contains a subset of variables. The differences are also discussed on the vignette.

### See Also

<https://r-spatial.github.io/spdep/articles/sids.html>

**Description**

S3 Ops Group Generic Functions for simple feature geometries

**Usage**

```
## S3 method for class 'sfg'
Ops(e1, e2)

## S3 method for class 'sfc'
Ops(e1, e2)
```

**Arguments**

e1	object of class sfg or sfc
e2	numeric, or object of class sfg; in case e1 is of class sfc also an object of class sfc is allowed

**Details**

in case e2 is numeric, +, -, \*, /,

If e1 is of class sfc, and e2 is a length 2 numeric, then it is considered a two-dimensional point (and if needed repeated as such) only for operations + and -, in other cases the individual numbers are repeated; see commented examples.

**Value**

object of class sfg

**Examples**

```
st_point(c(1,2,3)) + 4
st_point(c(1,2,3)) * 3 + 4
m = matrix(0, 2, 2)
diag(m) = c(1, 3)
# affine:
st_point(c(1,2)) * m + c(2,5)
# world in 0-360 range:
library(maps)
w = st_as_sf(map('world', plot = FALSE, fill = TRUE))
w2 = (st_geometry(w) + c(360,90)) %% c(360) - c(0,90)
w3 = st_wrap_dateline(st_set_crs(w2 - c(180,0), 4326)) + c(180,0)
plot(st_set_crs(w3, 4326), axes = TRUE)
(mp <- st_point(c(1,2)) + st_point(c(3,4))) # MULTIPOINT (1 2, 3 4)
mp - st_point(c(3,4)) # POINT (1 2)
```

```

opar = par(mfrow = c(2,2), mar = c(0, 0, 1, 0))
a = st_buffer(st_point(c(0,0)), 2)
b = a + c(2, 0)
p = function(m) { plot(c(a,b)); plot(eval(parse(text=m)), col=grey(.9), add = TRUE); title(m) }
lapply(c('a | b', 'a / b', 'a & b', 'a %% b'), p)
par(opar)
sfc = st_sfc(st_point(0:1), st_point(2:3))
sfc + c(2,3) # added to EACH geometry
sfc * c(2,3) # first geometry multiplied by 2, second by 3
nc = st_transform(st_read(system.file("gpkg/nc.gpkg", package="sf")), 32119) # nc state plane, m
b = st_buffer(st_centroid(st_union(nc)), units::set_units(50, km)) # shoot a hole in nc:
plot(st_geometry(nc) / b, col = grey(.9))

```

---

plot

*plot sf object*


---

### Description

plot one or more attributes of an sf object on a map Plot sf object

### Usage

```

## S3 method for class 'sf'
plot(
  x,
  y,
  ...,
  main,
  pal = NULL,
  nbreaks = 10,
  breaks = "pretty",
  max.plot = if (is.null(n <- options("sf_max.plot")[[1]])) 9 else n,
  key.pos = get_key_pos(x, ...),
  key.length = 0.618,
  key.width = lcm(1.8),
  reset = TRUE,
  logz = FALSE,
  extent = x,
  xlim = st_bbox(extent)[c(1, 3)],
  ylim = st_bbox(extent)[c(2, 4)]
)

```

```
get_key_pos(x, ...)
```

```

## S3 method for class 'sfc_POINT'
plot(
  x,
  y,

```

```
    ...,
    pch = 1,
    cex = 1,
    col = 1,
    bg = 0,
    lwd = 1,
    lty = 1,
    type = "p",
    add = FALSE
)

## S3 method for class 'sfc_MULTIPPOINT'
plot(
  x,
  y,
  ...,
  pch = 1,
  cex = 1,
  col = 1,
  bg = 0,
  lwd = 1,
  lty = 1,
  type = "p",
  add = FALSE
)

## S3 method for class 'sfc_LINESTRING'
plot(x, y, ..., lty = 1, lwd = 1, col = 1, pch = 1, type = "l", add = FALSE)

## S3 method for class 'sfc_CIRCULARSTRING'
plot(x, y, ...)

## S3 method for class 'sfc_MULTILINESTRING'
plot(x, y, ..., lty = 1, lwd = 1, col = 1, pch = 1, type = "l", add = FALSE)

## S3 method for class 'sfc_POLYGON'
plot(
  x,
  y,
  ...,
  lty = 1,
  lwd = 1,
  col = NA,
  cex = 1,
  pch = NA,
  border = 1,
  add = FALSE,
  rule = "evenodd"
```

```
)  
  
## S3 method for class 'sfc_MULTIPOLYGON'  
plot(  
  x,  
  y,  
  ...,  
  lty = 1,  
  lwd = 1,  
  col = NA,  
  border = 1,  
  add = FALSE,  
  rule = "evenodd"  
)  
  
## S3 method for class 'sfc_GEOMETRYCOLLECTION'  
plot(  
  x,  
  y,  
  ...,  
  pch = 1,  
  cex = 1,  
  bg = 0,  
  lty = 1,  
  lwd = 1,  
  col = 1,  
  border = 1,  
  add = FALSE  
)  
  
## S3 method for class 'sfc_GEOMETRY'  
plot(  
  x,  
  y,  
  ...,  
  pch = 1,  
  cex = 1,  
  bg = 0,  
  lty = 1,  
  lwd = 1,  
  col = ifelse(st_dimension(x) == 2, NA, 1),  
  border = 1,  
  add = FALSE  
)  
  
## S3 method for class 'sfg'  
plot(x, ...)
```



```

plot_sf(
  x,
  xlim = NULL,
  ylim = NULL,
  asp = NA,
  axes = FALSE,
  bgc = par("bg"),
  ...,
  xaxs,
  yaxs,
  lab,
  setParUsrBB = FALSE,
  bgMap = NULL,
  expandBB = c(0, 0, 0, 0),
  graticule = NA_crs_,
  col_graticule = "grey",
  border
)

sf.colors(n = 10, cutoff.tails = c(0.35, 0.2), alpha = 1, categorical = FALSE)

```

### Arguments

<code>x</code>	object of class <code>sf</code>
<code>y</code>	ignored
<code>...</code>	further specifications, see <a href="#">plot_sf</a> and <a href="#">plot</a> and details.
<code>main</code>	title for plot (NULL to remove)
<code>pal</code>	palette function, similar to <a href="#">rainbow</a> , or palette values; if omitted, <code>sf.colors</code> is used
<code>nbreaks</code>	number of colors breaks (ignored for factor or character variables)
<code>breaks</code>	either a numeric vector with the actual breaks, or a name of a method accepted by the <code>style</code> argument of <a href="#">classIntervals</a>
<code>max.plot</code>	integer; lower boundary to maximum number of attributes to plot; the default value (9) can be overridden by setting the global option <code>sf_max.plot</code> , e.g. <code>options(sf_max.plot=2)</code>
<code>key.pos</code>	integer; side to plot a color key: 1 bottom, 2 left, 3 top, 4 right; set to NULL to omit key, or -1 to select automatically. If multiple columns are plotted in a single function call by default no key is plotted and every submap is stretched individually; if a key is requested (and <code>col</code> is missing) all maps are colored according to a single key. Auto select depends on plot size, map aspect, and, if set, parameter <code>asp</code> .
<code>key.length</code>	amount of space reserved for the key along its axis, length of the scale bar
<code>key.width</code>	amount of space reserved for the key (incl. labels), thickness/width of the scale bar
<code>reset</code>	logical; if FALSE, keep the plot in a mode that allows adding further map elements; if TRUE restore original mode after plotting <code>sf</code> objects with attributes; see details.

logz	logical; if TRUE, use log10-scale for the attribute variable. In that case, breaks and at need to be given as log10-values; see examples.
extent	object with an <code>st_bbox</code> method to define plot extent; defaults to <code>x</code>
xlim	see <a href="#">plot.window</a>
ylim	see <a href="#">plot.window</a>
pch	plotting symbol
cex	symbol size
col	color for plotting features; if <code>length(col)</code> does not equal 1 or <code>nrow(x)</code> , a warning is emitted that colors will be recycled. Specifying <code>col</code> suppresses plotting the legend key.
bg	symbol background color
lwd	line width
lty	line type
type	plot type: 'p' for points, 'l' for lines, 'b' for both
add	logical; add to current plot? Note that when using <code>add=TRUE</code> , you may have to set <code>reset=FALSE</code> in the first plot command.
border	color of polygon border(s)
rule	see <a href="#">polypath</a> ; for winding, exterior ring direction should be opposite that of the holes; with <code>evenodd</code> , plotting is robust against misspecified ring directions
asp	see below, and see <a href="#">par</a>
axes	logical; should axes be plotted? (default FALSE)
bgc	background color
xaxs	see <a href="#">par</a>
yaxs	see <a href="#">par</a>
lab	see <a href="#">par</a>
setParUsrBB	default FALSE; set the <code>par</code> "usr" bounding box; see below
bgMap	object of class <code>ggmap</code> , or returned by function <code>RgoogleMaps::GetMap</code>
expandBB	numeric; fractional values to expand the bounding box with, in each direction (bottom, left, top, right)
graticule	logical, or object of class <code>crs</code> (e.g., <code>st_crs(4326)</code> for a WGS84 graticule), or object created by <a href="#">st_graticule</a> ; TRUE will give the WGS84 graticule or object returned by <a href="#">st_graticule</a>
col_graticule	color to used for the graticule (if present)
n	integer; number of colors
cutoff.tails	numeric, in <code>[0,0.5]</code> start and end values
alpha	numeric, in <code>[0,1]</code> , transparency
categorical	logical; do we want colors for a categorical variable? (see details)

## Details

`plot.sf` maximally plots `max.plot` maps with colors following from attribute columns, one map per attribute. It uses `sf.colors` for default colors. For more control over placement of individual maps, set parameter `mfrac` with `par` prior to plotting, and plot single maps one by one; note that this only works in combination with setting parameters `key.pos=NULL` (no legend) and `reset=FALSE`.

`plot.sfc` plots the geometry, additional parameters can be passed on to control color, lines or symbols.

When setting `reset` to `FALSE`, the original device parameters are lost, and the device must be reset using `dev.off()` in order to reset it.

parameter `at` can be set to specify where labels are placed along the key; see examples.

`plot_sf` sets up the plotting area, axes, graticule, or webmap background; it is called by all `plot` methods before anything is drawn.

The argument `setParUsrBB` may be used to pass the logical value `TRUE` to functions within `plot.Spatial`. When set to `TRUE`, `par("usr")` will be overwritten with `c(xlim,ylim)`, which defaults to the bounding box of the spatial object. This is only needed in the particular context of graphic output to a specified device with given width and height, to be matched to the spatial object, when using `par("xaxs")` and `par("yaxs")` in addition to `par(mar=c(0,0,0,0))`.

The default aspect for map plots is 1; if however data are not projected (coordinates are long/lat), the aspect is by default set to  $1/\cos(My * \pi/180)$  with `My` the y coordinate of the middle of the map (the mean of `ylim`, which defaults to the y range of bounding box). This implies an **Equirectangular projection**.

non-categorical colors from `sf.colors` were taken from `bpy.colors`, with modified `cutoff.tails` defaults. If `categorical` is `TRUE`, default colors are from <https://colorbrewer2.org/> (if `n < 9`, `Set2`, else `Set3`).

## Examples

```
nc = st_read(system.file("gpkg/nc.gpkg", package="sf"), quiet = TRUE)
# plot single attribute, auto-legend:
plot(nc["SID74"])
# plot multiple:
plot(nc[c("SID74", "SID79")]) # better use ggplot2::geom_sf to facet and get a single legend!
# adding to a plot of an sf object only works when using reset=FALSE in the first plot:
plot(nc["SID74"], reset = FALSE)
plot(st_centroid(st_geometry(nc)), add = TRUE)
# log10 z-scale:
plot(nc["SID74"], logz = TRUE, breaks = c(0,.5,1,1.5,2), at = c(0,.5,1,1.5,2))
# and we need to reset the plotting device after that, e.g. by
layout(1)
# when plotting only geometries, the reset=FALSE is not needed:
plot(st_geometry(nc))
plot(st_geometry(nc)[1], col = 'red', add = TRUE)
# add a custom legend to an arbitrary plot:
layout(matrix(1:2, ncol = 2), widths = c(1, 1cm(2)))
plot(1)
.image_scale(1:10, col = sf.colors(9), key.length = 1cm(8), key.pos = 4, at = 1:10)
sf.colors(10)
```

---

prefix_map	<i>Map prefix to driver</i>
------------	-----------------------------

---

**Description**

Map prefix to driver

**Usage**

prefix\_map

**Format**

An object of class list of length 10.

---

rawToHex	<i>Convert raw vector(s) into hexadecimal character string(s)</i>
----------	---

---

**Description**

Convert raw vector(s) into hexadecimal character string(s)

**Usage**

rawToHex(x)

**Arguments**

x	raw vector, or list with raw vectors
---	--------------------------------------

---

s2	<i>functions for spherical geometry, using s2 package</i>
----	---

---

**Description**

functions for spherical geometry, using the s2 package based on the google s2geometry.io library

**Usage**

```

sf_use_s2(use_s2)

## S3 method for class 'wk_wkb'
st_as_sfc(x, ..., crs = st_crs(4326))

## S3 method for class 's2_geography'
st_as_sfc(
  x,
  ...,
  crs = st_crs(4326),
  endian = match(.Platform$endian, c("big", "little")) - 1L
)

## S3 method for class 's2_geography'
st_as_sf(x, ..., crs = st_crs(4326))

st_as_s2(x, ...)

## S3 method for class 'sf'
st_as_s2(x, ...)

## S3 method for class 'sfc'
st_as_s2(x, ..., oriented = FALSE)

```

**Arguments**

<code>use_s2</code>	logical; if TRUE, use the s2 spherical geometry package for geographical coordinate operations
<code>x</code>	object of class <code>sf</code> , <code>sfc</code> or <code>sfg</code>
<code>...</code>	passed on
<code>crs</code>	coordinate reference system; object of class <code>crs</code>
<code>endian</code>	integer; 0 or 1: defaults to the endian of the native machine
<code>oriented</code>	logical; if FALSE, polygons that cover more than half of the globe are inverted; if TRUE, no reversal takes place and it is assumed that the inside of the polygon is to the left of the polygon's path.

**Details**

`st_as_s2` converts an `sf` POLYGON object into a form readable by s2.

**Value**

`sf_use_s2` returns the value of this variable before (re)setting it, invisibly if `use_s2` is not missing.

## Examples

```
m = rbind(c(-1,-1), c(1,-1), c(1,1), c(-1,1), c(-1,-1))
m1 = rbind(c(-1,-1), c(1,-1), c(1,1), c(-1,1), c(-1,0), c(-1,-1))
m0 = m[5:1,]
mp = st_multipolygon(list(
  list(m, 0.8 * m0, 0.01 * m1 + 0.9),
  list(0.7* m, 0.6*m0),
  list(0.5 * m0),
  list(m+2),
  list(m+4,(.9*m0)+4)
))
sf = st_sfc(mp, mp, crs = 'EPSG:4326')
s2 = st_as_s2(sf)
```

---

sf	<i>Create sf object</i>
----	-------------------------

---

## Description

Create sf, which extends data.frame-like objects with a simple feature list column

## Usage

```
st_sf(
  ...,
  agr = NA_agr_,
  row.names,
  stringsAsFactors = sf_stringsAsFactors(),
  crs,
  precision,
  sf_column_name = NULL,
  check_ring_dir = FALSE,
  sfc_last = TRUE
)

## S3 method for class 'sf'
x[i, j, ..., drop = FALSE, op = st_intersects]

## S3 method for class 'sf'
print(x, ..., n = getOption("sf_max_print", default = 10))
```

## Arguments

...	column elements to be binded into an sf object or a single list or data.frame with such columns; at least one of these columns shall be a geometry list-column of class sfc or be a list-column that can be converted into an sfc by <a href="#">st_as_sfc</a> .
agr	character vector; see details below.

row.names	row.names for the created sf object
stringsAsFactors	logical; see <a href="#">st_read</a>
crs	coordinate reference system, something suitable as input to <a href="#">st_crs</a>
precision	numeric; see <a href="#">st_as_binary</a>
sf_column_name	character; name of the active list-column with simple feature geometries; in case there is more than one and sf_column_name is NULL, the first one is taken.
check_ring_dir	see <a href="#">st_read</a>
sfc_last	logical; if TRUE, sfc columns are always put last, otherwise column order is left unmodified.
x	object of class sf
i	record selection, see <a href="#">[.data.frame</a>
j	variable selection, see <a href="#">[.data.frame</a>
drop	logical, default FALSE; if TRUE drop the geometry column and return a data.frame, else make the geometry sticky and return a sf object.
op	function; geometrical binary predicate function to apply when i is a simple feature object
n	maximum number of features to print; can be set globally by <code>options(sf_max_print=...)</code>

## Details

`agr`, attribute-geometry-relationship, specifies for each non-geometry attribute column how it relates to the geometry, and can have one of following values: "constant", "aggregate", "identity". "constant" is used for attributes that are constant throughout the geometry (e.g. land use), "aggregate" where the attribute is an aggregate value over the geometry (e.g. population density or population count), "identity" when the attributes uniquely identifies the geometry of particular "thing", such as a building ID or a city name. The default value, `NA_agr_`, implies we don't know.

When a single value is provided to `agr`, it is cascaded across all input columns; otherwise, a named vector like `c(feature1='constant', ...)` will set `agr` value to 'constant' for the input column named `feature1`. See `demo(nc)` for a worked example of this.

When confronted with a `data.frame`-like object, `st_sf` will try to find a geometry column of class `sfc`, and otherwise try to convert list-columns when available into a geometry column, using [st\\_as\\_sfc](#).

`[.sf` will return a `data.frame` or vector if the geometry column (of class `sfc`) is dropped (`drop=TRUE`), an `sfc` object if only the geometry column is selected, and otherwise return an `sf` object; see also [\[.data.frame](#); for `[.sf ...` arguments are passed to `op`.

## Examples

```
g = st_sfc(st_point(1:2))
st_sf(a=3,g)
st_sf(g, a=3)
st_sf(a=3, st_sfc(st_point(1:2))) # better to name it!
# create empty structure with preallocated empty geometries:
nrows <- 10
```

```

geometry = st_sfc(lapply(1:nrows, function(x) st_geometrycollection()))
df <- st_sf(id = 1:nrows, geometry = geometry)
g = st_sfc(st_point(1:2), st_point(3:4))
s = st_sf(a=3:4, g)
s[1,]
class(s[1,])
s[,1]
class(s[,1])
s[,2]
class(s[,2])
g = st_sf(a=2:3, g)
pol = st_sfc(st_polygon(list(cbind(c(0,3,3,0,0),c(0,0,3,3,0))))))
h = st_sf(r = 5, pol)
g[h,]
h[g,]

```

---

sf-defunct

*Deprecated functions in sf*


---

### Description

These functions are provided for compatibility with older version of sf. They may eventually be completely removed.

### Usage

```

st_read_db(
  conn = NULL,
  table = NULL,
  query = NULL,
  geom_column = NULL,
  EWKB = TRUE,
  ...
)

```

### Arguments

conn	open database connection
table	table name
query	SQL query to select records; see details
geom_column	deprecated. Geometry column name
EWKB	logical; is the WKB of type EWKB? if missing, defaults to TRUE
...	parameter(s) passed on to <a href="#">st_as_sf</a>

### Details

The `geom_column` argument is deprecated. The function will automatically find the geometry type columns. For the RPostgreSQL drivers it will try to cast all the character columns, which can be long for very wide tables.



**Details**

st\_read\_db now a synonym for [st\\_read](#)  
 st\_write\_db now a synonym for [st\\_write](#)

sfc

*Create simple feature geometry list column***Description**

Create simple feature geometry list column, set class, and add coordinate reference system and precision

**Usage**

```
st_sfc(..., crs = NA_crs_, precision = 0, check_ring_dir = FALSE, dim)
```

**Arguments**

... zero or more simple feature geometries (objects of class `sfg`), or a single list of such objects; NULL values will get replaced by empty geometries.

crs coordinate reference system: integer with the EPSG code, or character with proj4string

precision numeric; see [st\\_as\\_binary](#)

check\_ring\_dir see [st\\_read](#)

dim character; if this function is called without valid geometries, this argument may carry the right dimension to set empty geometries

**Details**

A simple feature geometry list-column is a list of class `c("stc_TYPE", "sfc")` which most often contains objects of identical type; in case of a mix of types or an empty set, TYPE is set to the superclass GEOMETRY.

**Value**

an object of class `sfc`, which is a classed list-column with simple feature geometries.

**Examples**

```
pt1 = st_point(c(0,1))
pt2 = st_point(c(1,1))
(sfc = st_sfc(pt1, pt2))
d = st_sf(data.frame(a=1:2, geom=sfc))
```

---

sf_extSoftVersion	<i>Provide the external dependencies versions of the libraries linked to sf</i>
-------------------	---

---

**Description**

Provide the external dependencies versions of the libraries linked to sf

**Usage**

```
sf_extSoftVersion()
```

---

sf_project	<i>directly transform a set of coordinates</i>
------------	--

---

**Description**

directly transform a set of coordinates

**Usage**

```
sf_add_proj_units()

sf_project(
  from,
  to,
  pts,
  keep = FALSE,
  warn = TRUE,
  authority_compliant = st_axis_order()
)
```

**Arguments**

from	character description of source CRS, or object of class <code>crs</code>
to	character description of target CRS, or object of class <code>crs</code>
pts	two-column numeric matrix, or object that can be coerced into a matrix
keep	logical value controlling the handling of unprojectable points. If 'keep' is 'TRUE', then such points will yield 'Inf' or '-Inf' in the return value; otherwise an error is reported and nothing is returned.
warn	logical; if TRUE, warn when non-finite values are generated
authority_compliant	logical; TRUE means handle axis order authority compliant (e.g. EPSG:4326 implying x=lat, y=lon), FALSE means use visualisation order (i.e. always x=lon, y=lat)

**Details**

sf\_add\_proj\_units loads the PROJ units 'link', 'us\_in', 'ind\_yd', 'ind\_ft', and 'ind\_ch' into the uunits database, and returns TRUE invisibly on success.

**Value**

two-column numeric matrix with transformed/converted coordinates, returning invalid values as Inf

---

sf\_proj\_search\_paths *Get or set the PROJ search paths*

---

**Description**

Get or set the PROJ search paths

**Usage**

```
sf_proj_search_paths(paths = NULL)
```

**Arguments**

paths                    the search path to be set; omit if no paths need to be set

**Value**

the search path (possibly after setting to paths)

---

sgbp                    *Methods for dealing with sparse geometry binary predicate lists*

---

**Description**

Methods for dealing with sparse geometry binary predicate lists

**Usage**

```
## S3 method for class 'sgbp'
print(x, ..., n = 10, max_nb = 10)
```

```
## S3 method for class 'sgbp'
t(x)
```

```
## S3 method for class 'sgbp'
as.matrix(x, ...)
```

```
## S3 method for class 'sgbp'
dim(x)
```

**Arguments**

x	object of class sgbp
...	ignored
n	integer; maximum number of items to print
max_nb	integer; maximum number of neighbours to print for each item

**Details**

sgbp are sparse matrices, stored as a list with integer vectors holding the ordered TRUE indices of each row. This means that for a dense,  $m \times n$  matrix  $Q$  and a list  $L$ , if  $Q[i, j]$  is TRUE then  $j$  is an element of  $L[[i]]$ . Reversed: when  $k$  is the value of  $L[[i]][j]$ , then  $Q[i, k]$  is TRUE.

---

st	<i>Create simple feature from a numeric vector, matrix or list</i>
----	--

---

**Description**

Create simple feature from a numeric vector, matrix or list

**Usage**

```

st_point(x = c(NA_real_, NA_real_), dim = "XYZ")
st_multipoint(x = matrix(numeric(0), 0, 2), dim = "XYZ")
st_linestring(x = matrix(numeric(0), 0, 2), dim = "XYZ")
st_polygon(x = list(), dim = if (length(x)) "XYZ" else "XY")
st_multilinestring(x = list(), dim = if (length(x)) "XYZ" else "XY")
st_multipolygon(x = list(), dim = if (length(x)) "XYZ" else "XY")
st_geometrycollection(x = list(), dims = "XY")

## S3 method for class 'sfg'
print(x, ..., width = 0)

## S3 method for class 'sfg'
head(x, n = 10L, ...)

## S3 method for class 'sfg'
format(x, ..., width = 30)

## S3 method for class 'sfg'
c(..., recursive = FALSE, flatten = TRUE)

```

```
## S3 method for class 'sfg'
as.matrix(x, ...)
```

### Arguments

x	for <code>st_point</code> , numeric vector (or one-row-matrix) of length 2, 3 or 4; for <code>st_linestring</code> and <code>st_multipoint</code> , numeric matrix with points in rows; for <code>st_polygon</code> and <code>st_multilinestring</code> , list with numeric matrices with points in rows; for <code>st_multipolygon</code> , list of lists with numeric matrices; for <code>st_geometrycollection</code> list with (non- <code>geometrycollection</code> ) simple feature objects
dim	character, indicating dimensions: "XY", "XYZ", "XYM", or "XYZM"; only really needed for three-dimensional points (which can be either XYZ or XYM) or empty geometries; see details
dims	character; specify dimensionality in case of an empty (NULL) <code>geometrycollection</code> , in which case x is the empty <code>list()</code> .
...	objects to be pasted together into a single simple feature
width	integer; number of characters to be printed (max 30; 0 means print everything)
n	integer; number of elements to be selected
recursive	logical; ignored
flatten	logical; if TRUE, try to simplify results; if FALSE, return <code>geometrycollection</code> containing all objects

### Details

"XYZ" refers to coordinates where the third dimension represents altitude, "XYM" refers to three-dimensional coordinates where the third dimension refers to something else ("M" for measure); checking of the sanity of x may be only partial.

When `flatten=TRUE`, this method may merge points into a multipoint structure, and may not preserve order, and hence cannot be reverted. When given fish, it returns fish soup.

### Value

object of the same nature as x, but with appropriate class attribute set

`as.matrix` returns the set of points that form a geometry as a single matrix, where each point is a row; use `unlist(x, recursive = FALSE)` to get sets of matrices.

### Examples

```
(p1 = st_point(c(1,2)))
class(p1)
st_bbox(p1)
(p2 = st_point(c(1,2,3)))
class(p2)
(p3 = st_point(c(1,2,3), "XYM"))
pts = matrix(1:10, , 2)
(mp1 = st_multipoint(pts))
```

```

pts = matrix(1:15, , 3)
(mp2 = st_multipoint(pts))
(mp3 = st_multipoint(pts, "XYM"))
pts = matrix(1:20, , 4)
(mp4 = st_multipoint(pts))
pts = matrix(1:10, , 2)
(ls1 = st_linestring(pts))
pts = matrix(1:15, , 3)
(ls2 = st_linestring(pts))
(ls3 = st_linestring(pts, "XYM"))
pts = matrix(1:20, , 4)
(ls4 = st_linestring(pts))
outer = matrix(c(0,0,10,0,10,10,0,10,0,0),ncol=2, byrow=TRUE)
hole1 = matrix(c(1,1,1,2,2,2,2,1,1,1),ncol=2, byrow=TRUE)
hole2 = matrix(c(5,5,5,6,6,6,6,5,5,5),ncol=2, byrow=TRUE)
pts = list(outer, hole1, hole2)
(ml1 = st_multilinestring(pts))
pts3 = lapply(pts, function(x) cbind(x, 0))
(ml2 = st_multilinestring(pts3))
(ml3 = st_multilinestring(pts3, "XYM"))
pts4 = lapply(pts3, function(x) cbind(x, 0))
(ml4 = st_multilinestring(pts4))
outer = matrix(c(0,0,10,0,10,10,0,10,0,0),ncol=2, byrow=TRUE)
hole1 = matrix(c(1,1,1,2,2,2,2,1,1,1),ncol=2, byrow=TRUE)
hole2 = matrix(c(5,5,5,6,6,6,6,5,5,5),ncol=2, byrow=TRUE)
pts = list(outer, hole1, hole2)
(pl1 = st_polygon(pts))
pts3 = lapply(pts, function(x) cbind(x, 0))
(pl2 = st_polygon(pts3))
(pl3 = st_polygon(pts3, "XYM"))
pts4 = lapply(pts3, function(x) cbind(x, 0))
(pl4 = st_polygon(pts4))
pol1 = list(outer, hole1, hole2)
pol2 = list(outer + 12, hole1 + 12)
pol3 = list(outer + 24)
mp = list(pol1,pol2,pol3)
(mp1 = st_multipolygon(mp))
pts3 = lapply(mp, function(x) lapply(x, function(y) cbind(y, 0)))
(mp2 = st_multipolygon(pts3))
(mp3 = st_multipolygon(pts3, "XYM"))
pts4 = lapply(mp2, function(x) lapply(x, function(y) cbind(y, 0)))
(mp4 = st_multipolygon(pts4))
(gc = st_geometrycollection(list(p1, ls1, pl1, mp1)))
st_geometrycollection() # empty geometry
c(st_point(1:2), st_point(5:6))
c(st_point(1:2), st_multipoint(matrix(5:8,2)))
c(st_multipoint(matrix(1:4,2)), st_multipoint(matrix(5:8,2)))
c(st_linestring(matrix(1:6,3)), st_linestring(matrix(11:16,3)))
c(st_multilinestring(list(matrix(1:6,3))), st_multilinestring(list(matrix(11:16,3))))
pl = list(rbind(c(0,0), c(1,0), c(1,1), c(0,1), c(0,0)))
c(st_polygon(pl), st_polygon(pl))
c(st_polygon(pl), st_multipolygon(list(pl)))
c(st_linestring(matrix(1:6,3)), st_point(1:2))

```

```

c(st_geometrycollection(list(st_point(1:2), st_linestring(matrix(1:6,3)))),
  st_geometrycollection(list(st_multilinestring(list(matrix(11:16,3)))))
c(st_geometrycollection(list(st_point(1:2), st_linestring(matrix(1:6,3))),
  st_multilinestring(list(matrix(11:16,3))), st_point(5:6),
  st_geometrycollection(list(st_point(10:11))))

```

---

stars

*functions only exported to be used internally by stars*


---

## Description

functions only exported to be used internally by stars

## Usage

```

.get_layout(bb, n, total_size, key.pos, key.length)

.degAxis(side, at, labels, ..., lon, lat, ndiscr, reset)

.image_scale(
  z,
  col,
  breaks = NULL,
  key.pos,
  add.axis = TRUE,
  at = NULL,
  ...,
  axes = FALSE,
  key.length,
  logz = FALSE
)

.image_scale_factor(
  z,
  col,
  key.pos,
  add.axis = TRUE,
  ...,
  axes = FALSE,
  key.width,
  key.length
)

```

## Arguments

bb	ignore
n	ignore

total_size	ignore
key.pos	ignore
key.length	ignore
side	ignore
at	ignore
labels	ignore
...	ignore
lon	ignore
lat	ignore
ndiscr	ignore
reset	ignore
z	ignore
col	ignore
breaks	ignore
add.axis	ignore
axes	ignore
logz	ignore
key.width	ignore

---

st_agr	<i>get or set relation_to_geometry attribute of an sf object</i>
--------	--

---

### Description

get or set relation\_to\_geometry attribute of an sf object

### Usage

```
NA_agr_

st_agr(x, ...)

st_agr(x) <- value

st_set_agr(x, value)
```

### Arguments

x	object of class sf
...	ignored
value	character, or factor with appropriate levels; if named, names should correspond to the non-geometry list-column columns of x



**Format**

An object of class factor of length 1.

**Details**

NA\_agr\_ is the agr object with a missing value.

---

st_as_binary	<i>Convert sfc object to an WKB object</i>
--------------	--

---

**Description**

Convert sfc object to an WKB object

**Usage**

```
st_as_binary(x, ...)
```

```
## S3 method for class 'sfc'
st_as_binary(
  x,
  ...,
  EWKB = FALSE,
  endian = .Platform$endian,
  pureR = FALSE,
  precision = attr(x, "precision"),
  hex = FALSE
)
```

```
## S3 method for class 'sfg'
st_as_binary(
  x,
  ...,
  endian = .Platform$endian,
  EWKB = FALSE,
  pureR = FALSE,
  hex = FALSE,
  srid = 0
)
```

**Arguments**

x	object to convert
...	ignored
EWKB	logical; use EWKB (PostGIS), or (default) ISO-WKB?
endian	character; either "big" or "little"; default: use that of platform

pureR	logical; use pure R solution, or C++?
precision	numeric; if zero, do not modify; to reduce precision: negative values convert to float (4-byte real); positive values convert to round(x*precision)/precision. See details.
hex	logical; return as (unclassed) hexadecimal encoded character vector?
srid	integer; override srid (can be used when the srid is unavailable locally).

## Details

st\_as\_binary is called on sfc objects on their way to the GDAL or GEOS libraries, and hence does rounding (if requested) on the fly before e.g. computing spatial predicates like `st_intersects`. The examples show a round-trip of an sfc to and from binary.

For the precision model used, see also <https://locationtech.github.io/jts/javadoc/org/locationtech/jts/geom/PrecisionModel.html>. There, it is written that: "... to specify 3 decimal places of precision, use a scale factor of 1000. To specify -3 decimal places of precision (i.e. rounding to the nearest 1000), use a scale factor of 0.001.". Note that ALL coordinates, so also Z or M values (if present) are affected.

## Examples

```
# examples of setting precision:
st_point(c(1/3, 1/6)) %>% st_sfc(precision = 1000) %>% st_as_binary %>% st_as_sfc
st_point(c(1/3, 1/6)) %>% st_sfc(precision = 100) %>% st_as_binary %>% st_as_sfc
st_point(1e6 * c(1/3, 1/6)) %>% st_sfc(precision = 0.01) %>% st_as_binary %>% st_as_sfc
st_point(1e6 * c(1/3, 1/6)) %>% st_sfc(precision = 0.001) %>% st_as_binary %>% st_as_sfc
```

---

st_as_grob	<i>Convert sf* object to a grob</i>
------------	-------------------------------------

---

## Description

Convert sf\* object to an grid graphics object (grob)

## Usage

```
st_as_grob(x, ...)
```

## Arguments

x	object to be converted into an object class grob
...	passed on to the xxxGrob function, e.g. gp = gpar(col = 'red')

---

st_as_sf	<i>Convert foreign object to an sf object</i>
----------	---

---

**Description**

Convert foreign object to an sf object

**Usage**

```
st_as_sf(x, ...)  
  
## S3 method for class 'data.frame'  
st_as_sf(  
  x,  
  ...,  
  agr = NA_agr_,  
  coords,  
  wkt,  
  dim = "XYZ",  
  remove = TRUE,  
  na.fail = TRUE,  
  sf_column_name = NULL  
)  
  
## S3 method for class 'sf'  
st_as_sf(x, ...)  
  
## S3 method for class 'sfc'  
st_as_sf(x, ...)  
  
## S3 method for class 'Spatial'  
st_as_sf(x, ...)  
  
## S3 method for class 'map'  
st_as_sf(x, ..., fill = TRUE, group = TRUE)  
  
## S3 method for class 'ppp'  
st_as_sf(x, ...)  
  
## S3 method for class 'psp'  
st_as_sf(x, ...)  
  
## S3 method for class 'lpp'  
st_as_sf(x, ...)
```

**Arguments**

x                    object to be converted into an object class sf

...	passed on to <a href="#">st_sf</a> , might included named arguments crs or precision
agr	character vector; see details section of <a href="#">st_sf</a>
coords	in case of point data: names or numbers of the numeric columns holding coordinates
wkt	name or number of the character column that holds WKT encoded geometries
dim	passed on to <a href="#">st_point</a> (only when argument coords is given)
remove	logical; when coords or wkt is given, remove these columns from data.frame?
na.fail	logical; if TRUE, raise an error if coordinates contain missing values
sf_column_name	character; name of the active list-column with simple feature geometries; in case there is more than one and sf_column_name is NULL, the first one is taken.
fill	logical; the value for fill that was used in the call to <a href="#">map</a> .
group	logical; if TRUE, group id labels from <a href="#">map</a> by their prefix before :

### Details

setting argument wkt annihilates the use of argument coords. If x contains a column called "geometry", coords will result in overwriting of this column by the [sfc](#) geometry list-column. Setting wkt will replace this column with the geometry list-column, unless remove\_coordinates is FALSE.

### Examples

```
pt1 = st_point(c(0,1))
pt2 = st_point(c(1,1))
st_sfc(pt1, pt2)
d = data.frame(a = 1:2)
d$geom = st_sfc(pt1, pt2)
df = st_as_sf(d)
d$geom = c("POINT(0 0)", "POINT(0 1)")
df = st_as_sf(d, wkt = "geom")
d$geom2 = st_sfc(pt1, pt2)
st_as_sf(d) # should warn
data(meuse, package = "sp")
meuse_sf = st_as_sf(meuse, coords = c("x", "y"), crs = 28992, agr = "constant")
meuse_sf[1:3,]
summary(meuse_sf)
library(sp)
x = rbind(c(-1,-1), c(1,-1), c(1,1), c(-1,1), c(-1,-1))
x1 = 0.1 * x + 0.1
x2 = 0.1 * x + 0.4
x3 = 0.1 * x + 0.7
y = x + 3
y1 = x1 + 3
y3 = x3 + 3
m = matrix(c(3, 0), 5, 2, byrow = TRUE)
z = x + m
z1 = x1 + m
z2 = x2 + m
z3 = x3 + m
p1 = Polygons(list( Polygon(x[5:1,]), Polygon(x2), Polygon(x3),
```

```

    Polygon(y[5:1,]), Polygon(y1), Polygon(x1), Polygon(y3)), "ID1")
p2 = Polygons(list( Polygon(z[5:1,]), Polygon(z2), Polygon(z3), Polygon(z1)),
  "ID2")
if (require("rgeos")) {
  r = createSPComment(SpatialPolygons(list(p1,p2)))
  comment(r)
  comment(r@polygons[[1]])
  scan(text = comment(r@polygons[[1]]), quiet = TRUE)
  library(sf)
  a = st_as_sf(r)
  summary(a)
}
demo(meuse, ask = FALSE, echo = FALSE)
summary(st_as_sf(meuse))
summary(st_as_sf(meuse.grid))
summary(st_as_sf(meuse.area))
summary(st_as_sf(meuse.riv))
summary(st_as_sf(as(meuse.riv, "SpatialLines")))
pol.grd = as(meuse.grid, "SpatialPolygonsDataFrame")
# summary(st_as_sf(pol.grd))
# summary(st_as_sf(as(pol.grd, "SpatialLinesDataFrame")))
if (require(spatstat)) {
  g = st_as_sf(gorillas)
  # select only the points:
  g[st_is(g, "POINT"),]
}
if (require(spatstat)) {
  data(chicago)
  plot(st_as_sf(chicago)["label"])
  plot(st_as_sf(chicago)[-1,"label"])
}

```

---

st\_as\_sfc

---

*Convert foreign geometry object to an sfc object*


---

## Description

Convert foreign geometry object to an sfc object

## Usage

```

## S3 method for class 'pq_geometry'
st_as_sfc(
  x,
  ...,
  EWKB = TRUE,
  spatialite = FALSE,
  pureR = FALSE,
  crs = NA_crs_

```

```
)

## S3 method for class 'list'
st_as_sfc(x, ..., crs = NA_crs_)

## S3 method for class 'blob'
st_as_sfc(x, ...)

## S3 method for class 'bbox'
st_as_sfc(x, ...)

## S3 method for class 'WKB'
st_as_sfc(
  x,
  ...,
  EWKB = FALSE,
  spatialite = FALSE,
  pureR = FALSE,
  crs = NA_crs_
)

## S3 method for class 'raw'
st_as_sfc(x, ...)

## S3 method for class 'character'
st_as_sfc(x, crs = NA_integer_, ..., GeoJSON = FALSE)

## S3 method for class 'factor'
st_as_sfc(x, ...)

st_as_sfc(x, ...)

## S3 method for class 'SpatialPoints'
st_as_sfc(x, ..., precision = 0)

## S3 method for class 'SpatialPixels'
st_as_sfc(x, ..., precision = 0)

## S3 method for class 'SpatialMultiPoints'
st_as_sfc(x, ..., precision = 0)

## S3 method for class 'SpatialLines'
st_as_sfc(x, ..., precision = 0, forceMulti = FALSE)

## S3 method for class 'SpatialPolygons'
st_as_sfc(x, ..., precision = 0, forceMulti = FALSE)

## S3 method for class 'map'
```

```
st_as_sfc(x, ...)
```

### Arguments

x	object to convert
...	further arguments
EWKB	logical; if TRUE, parse as EWKB (extended WKB; PostGIS: ST_AsEWKB), otherwise as ISO WKB (PostGIS: ST_AsBinary)
spatialite	logical; if TRUE, WKB is assumed to be in the spatialite dialect, see <a href="https://www.gaia-gis.it/gaia-sins/BLOB-Geometry.html">https://www.gaia-gis.it/gaia-sins/BLOB-Geometry.html</a> ; this is only supported in native endian-ness (i.e., files written on system with the same endian-ness as that on which it is being read).
pureR	logical; if TRUE, use only R code, if FALSE, use compiled (C++) code; use TRUE when the endian-ness of the binary differs from the host machine (.Platform\$endian).
crs	integer or character; coordinate reference system for the
GeoJSON	logical; if TRUE, try to read geometries from GeoJSON text strings geometry, see <a href="#">st_crs()</a>
precision	precision value; see <a href="#">st_as_binary</a>
forceMulti	logical; if TRUE, force coercion into MULTIPOLYGON or MULTILINE objects, else autodetect

### Details

When converting from WKB, the object x is either a character vector such as typically obtained from PostGIS (either with leading "0x" or without), or a list with raw vectors representing the features in binary (raw) form.

If x is a character vector, it should be a vector containing [well-known-text](#), or [Postgis EWKT](#) or [GeoJSON](#) representations of a single geometry for each vector element.

If x is a factor, it is converted to character.

### Examples

```
wkb = structure(list("0101000020407100000000000000801A064100000000AC5C1441"), class = "WKB")
st_as_sfc(wkb, EWKB = TRUE)
wkb = structure(list("0x0101000020407100000000000000801A064100000000AC5C1441"), class = "WKB")
st_as_sfc(wkb, EWKB = TRUE)
st_as_sfc(st_as_binary(st_sfc(st_point(0:1)))[[1]], crs = 4326)
st_as_sfc("SRID=3978;LINESTRING(1663106 -105415,1664320 -104617)")
```

---

st_as_text	<i>Return Well-known Text representation of simple feature geometry or coordinate reference system</i>
------------	--

---

## Description

Return Well-known Text representation of simple feature geometry or coordinate reference system

## Usage

```
## S3 method for class 'crs'
st_as_text(x, ..., pretty = FALSE)

st_as_text(x, ...)

## S3 method for class 'sfg'
st_as_text(x, ...)

## S3 method for class 'sfc'
st_as_text(x, ..., EWKT = FALSE)
```

## Arguments

x	object of class sfg, sfc or crs
...	modifiers; in particular digits can be passed to control the number of digits used
pretty	logical; if TRUE, print human-readable well-known-text representation of a coordinate reference system
EWKT	logical; if TRUE, print SRID=xxx; before the WKT string if epsg is available

## Details

The returned WKT representation of simple feature geometry conforms to the [simple features access](#) specification and extensions, [known as EWKT](#), supported by PostGIS and other simple features implementations for addition of SRID to a WKT string.

## Examples

```
st_as_text(st_point(1:2))
st_as_text(st_sfc(st_point(c(-90,40)), crs = 4326), EWKT = TRUE)
```



---

st_bbox	<i>Return bounding of a simple feature or simple feature set</i>
---------	--

---

**Description**

Return bounding of a simple feature or simple feature set

**Usage**

```
## S3 method for class 'bbox'  
is.na(x)  
  
st_bbox(obj, ...)  
  
## S3 method for class 'POINT'  
st_bbox(obj, ...)  
  
## S3 method for class 'MULTIPOINT'  
st_bbox(obj, ...)  
  
## S3 method for class 'LINESTRING'  
st_bbox(obj, ...)  
  
## S3 method for class 'POLYGON'  
st_bbox(obj, ...)  
  
## S3 method for class 'MULTILINESTRING'  
st_bbox(obj, ...)  
  
## S3 method for class 'MULTIPOLYGON'  
st_bbox(obj, ...)  
  
## S3 method for class 'GEOMETRYCOLLECTION'  
st_bbox(obj, ...)  
  
## S3 method for class 'MULTISURFACE'  
st_bbox(obj, ...)  
  
## S3 method for class 'MULTICURVE'  
st_bbox(obj, ...)  
  
## S3 method for class 'CURVEPOLYGON'  
st_bbox(obj, ...)  
  
## S3 method for class 'COMPOUNDCURVE'  
st_bbox(obj, ...)
```

```
## S3 method for class 'POLYHEDRALSURFACE'
st_bbox(obj, ...)

## S3 method for class 'TIN'
st_bbox(obj, ...)

## S3 method for class 'TRIANGLE'
st_bbox(obj, ...)

## S3 method for class 'CIRCULARSTRING'
st_bbox(obj, ...)

## S3 method for class 'sfc'
st_bbox(obj, ...)

## S3 method for class 'sf'
st_bbox(obj, ...)

## S3 method for class 'Spatial'
st_bbox(obj, ...)

## S3 method for class 'Raster'
st_bbox(obj, ...)

## S3 method for class 'Extent'
st_bbox(obj, ..., crs = NA_crs_)

## S3 method for class 'numeric'
st_bbox(obj, ..., crs = NA_crs_)

NA_bbox_

## S3 method for class 'bbox'
format(x, ...)
```

## Arguments

x	object of class bbox
obj	object to compute the bounding box from
...	for format.bbox, passed on to <a href="#">format</a> to format individual numbers
crs	object of class crs, or argument to <a href="#">st_crs</a> , specifying the CRS of this bounding box.

## Format

An object of class bbox of length 4.

**Details**

NA\_bbox\_ represents the missing value for a bbox object

**Value**

a numeric vector of length four, with xmin, ymin, xmax and ymax values; if obj is of class sf, sfc, Spatial or Raster, the object returned has a class bbox, an attribute crs and a method to print the bbox and an st\_crs method to retrieve the coordinate reference system corresponding to obj (and hence the bounding box). [st\\_as\\_sfc](#) has a methods for bbox objects to generate a polygon around the four bounding box points.

**Examples**

```
a = st_sf(a = 1:2, geom = st_sfc(st_point(0:1), st_point(1:2)), crs = 4326)
st_bbox(a)
st_as_sfc(st_bbox(a))
st_bbox(c(xmin = 16.1, xmax = 16.6, ymax = 48.6, ymin = 47.9), crs = st_crs(4326))
```

---

st\_cast

---

*Cast geometry to another type: either simplify, or cast explicitly*


---

**Description**

Cast geometry to another type: either simplify, or cast explicitly

**Usage**

```
## S3 method for class 'MULTIPOLYGON'
st_cast(x, to, ...)

## S3 method for class 'MULTILINESTRING'
st_cast(x, to, ...)

## S3 method for class 'MULTIPOINT'
st_cast(x, to, ...)

## S3 method for class 'POLYGON'
st_cast(x, to, ...)

## S3 method for class 'LINESTRING'
st_cast(x, to, ...)

## S3 method for class 'POINT'
st_cast(x, to, ...)

## S3 method for class 'GEOMETRYCOLLECTION'
st_cast(x, to, ...)
```

```

## S3 method for class 'CIRCULARSTRING'
st_cast(x, to, ...)

## S3 method for class 'MULTISURFACE'
st_cast(x, to, ...)

## S3 method for class 'COMPOUNDCURVE'
st_cast(x, to, ...)

## S3 method for class 'MULTICURVE'
st_cast(x, to, ...)

## S3 method for class 'CURVE'
st_cast(x, to, ...)

st_cast(x, to, ...)

## S3 method for class 'sfc'
st_cast(x, to, ..., ids = seq_along(x), group_or_split = TRUE)

## S3 method for class 'sf'
st_cast(x, to, ..., warn = TRUE, do_split = TRUE)

## S3 method for class 'sfc_CIRCULARSTRING'
st_cast(x, to, ...)

```

### Arguments

x	object of class sfg, sfc or sf
to	character; target type, if missing, simplification is tried; when x is of type sfg (i.e., a single geometry) then to needs to be specified.
...	ignored
ids	integer vector, denoting how geometries should be grouped (default: no grouping)
group_or_split	logical; if TRUE, group or split geometries; if FALSE, carry out a 1-1 per-geometry conversion.
warn	logical; if TRUE, warn if attributes are assigned to sub-geometries
do_split	logical; if TRUE, allow splitting of geometries in sub-geometries

### Details

the `st_cast` method for `sf` objects can only split geometries, e.g. cast `MULTIPOINT` into multiple `POINT` features. In case of splitting, attributes are repeated and a warning is issued when non-constant attributes are assigned to sub-geometries. To merge feature geometries and attribute values, use [aggregate](#) or [summarise](#).

**Value**

object of class `to` if successful, or unmodified object if unsuccessful. If information gets lost while type casting, a warning is raised.

In case `to` is missing, `st_cast.sfc` will coerce combinations of "POINT" and "MULTIPOINT", "LINESTRING" and "MULTILINESTRING", "POLYGON" and "MULTIPOLYGON" into their "MULTI..." form, or in case all geometries are "GEOMETRYCOLLECTION" will return a list of all the contents of the "GEOMETRYCOLLECTION" objects, or else do nothing. In case `to` is specified, if `to` is "GEOMETRY", geometries are not converted, else, `st_cast` will try to coerce all elements into `to`; `ids` may be specified to group e.g. "POINT" objects into a "MULTIPOINT", if not specified no grouping takes place. If e.g. a "sfc\_MULTIPOINT" is cast to a "sfc\_POINT", the objects are split, so no information gets lost, unless `group_or_split` is FALSE.

**Examples**

```
# example(st_read)
nc = st_read(system.file("shape/nc.shp", package="sf"))
mpl <- nc$geometry[[4]]
#st_cast(x) ## error 'argument "to" is missing, with no default'
cast_all <- function(xg) {
  lapply(c("MULTIPOLYGON", "MULTILINESTRING", "MULTIPOINT", "POLYGON", "LINESTRING", "POINT"),
        function(x) st_cast(xg, x))
}
st_sfc(cast_all(mpl))
## no closing coordinates should remain for multipoint
any(duplicated(unclass(st_cast(mpl, "MULTIPOINT")))) ## should be FALSE
## number of duplicated coordinates in the linestrings should equal the number of polygon rings
## (... in this case, won't always be true)
sum(duplicated(do.call(rbind, unclass(st_cast(mpl, "MULTILINESTRING"))))
    ) == sum(unlist(lapply(mpl, length))) ## should be TRUE

p1 <- structure(c(0, 1, 3, 2, 1, 0, 0, 0, 2, 4, 4, 0), .Dim = c(6L, 2L))
p2 <- structure(c(1, 1, 2, 1, 1, 2, 2, 1), .Dim = c(4L, 2L))
st_polygon(list(p1, p2))
m1s <- st_cast(nc$geometry[[4]], "MULTILINESTRING")
st_sfc(cast_all(m1s))
mpt <- st_cast(nc$geometry[[4]], "MULTIPOINT")
st_sfc(cast_all(mpt))
p1 <- st_cast(nc$geometry[[4]], "POLYGON")
st_sfc(cast_all(p1))
l1s <- st_cast(nc$geometry[[4]], "LINESTRING")
st_sfc(cast_all(l1s))
pt <- st_cast(nc$geometry[[4]], "POINT")
## st_sfc(cast_all(pt)) ## Error: cannot create MULTIPOLYGON from POINT
st_sfc(lapply(c("POINT", "MULTIPOINT"), function(x) st_cast(pt, x)))
s = st_multipoint(rbind(c(1,0)))
st_cast(s, "POINT")
```

---

st\_cast\_sfc\_default    *Coerce geometry to MULTI\* geometry*

---

### Description

Mixes of POINTS and MULTIPOINTS, LINESTRING and MULTILINESTRING, POLYGON and MULTIPOLYGON are returned as MULTIPOINTS, MULTILINESTRING and MULTIPOLYGONS respectively

### Usage

```
st_cast_sfc_default(x)
```

### Arguments

x                    list of geometries or simple features

### Details

Geometries that are already MULTI\* are left unchanged. Features that can't be cast to a single MULTI\* geometry are return as a GEOMETRYCOLLECTION

---

st\_collection\_extract    *Given an object with geometries of type GEOMETRY or GEOMETRYCOLLECTION, return an object consisting only of elements of the specified type.*

---

### Description

Similar to ST\_CollectionExtract in PostGIS. If there are no sub-geometries of the specified type, an empty geometry is returned.

### Usage

```
st_collection_extract(
  x,
  type = c("POLYGON", "POINT", "LINESTRING"),
  warn = FALSE
)

## S3 method for class 'sfg'
st_collection_extract(
  x,
  type = c("POLYGON", "POINT", "LINESTRING"),
  warn = FALSE
)
```

```
## S3 method for class 'sfc'
st_collection_extract(
  x,
  type = c("POLYGON", "POINT", "LINESTRING"),
  warn = FALSE
)

## S3 method for class 'sf'
st_collection_extract(
  x,
  type = c("POLYGON", "POINT", "LINESTRING"),
  warn = FALSE
)
```

### Arguments

x	an object of class sf, sfc or sfg that has mixed geometry (GEOMETRY or GEOMETRYCOLLECTION).
type	character; one of "POLYGON", "POINT", "LINESTRING"
warn	logical; if TRUE, warn if attributes are assigned to sub-geometries when casting (see <a href="#">st_cast</a> )

### Value

An object having the same class as x, with geometries consisting only of elements of the specified type. For sfg objects, an sfg object is returned if there is only one geometry of the specified type, otherwise the geometries are combined into an sfc object of the relevant type. If any subgeometries in the input are MULTI, then all of the subgeometries in the output will be MULTI.

### Examples

```
pt <- st_point(c(1, 0))
ls <- st_linestring(matrix(c(4, 3, 0, 0), ncol = 2))
poly1 <- st_polygon(list(matrix(c(5.5, 7, 7, 6, 5.5, 0, 0, -0.5, -0.5, 0), ncol = 2)))
poly2 <- st_polygon(list(matrix(c(6.6, 8, 8, 7, 6.6, 1, 1, 1.5, 1.5, 1), ncol = 2)))
multipoly <- st_multipolygon(list(poly1, poly2))

i <- st_geometrycollection(list(pt, ls, poly1, poly2))
j <- st_geometrycollection(list(pt, ls, poly1, poly2, multipoly))

st_collection_extract(i, "POLYGON")
st_collection_extract(i, "POINT")
st_collection_extract(i, "LINESTRING")

## A GEOMETRYCOLLECTION
aa <- rbind(st_sf(a=1, geom = st_sfc(i)),
  st_sf(a=2, geom = st_sfc(j)))

## With sf objects
st_collection_extract(aa, "POLYGON")
```

```

st_collection_extract(aa, "LINESTRING")
st_collection_extract(aa, "POINT")

## With sfc objects
st_collection_extract(st_geometry(aa), "POLYGON")
st_collection_extract(st_geometry(aa), "LINESTRING")
st_collection_extract(st_geometry(aa), "POINT")

## A GEOMETRY of single types
bb <- rbind(
  st_sf(a = 1, geom = st_sfc(pt)),
  st_sf(a = 2, geom = st_sfc(ls)),
  st_sf(a = 3, geom = st_sfc(poly1)),
  st_sf(a = 4, geom = st_sfc(multipoly))
)

st_collection_extract(bb, "POLYGON")

## A GEOMETRY of mixed single types and GEOMETRYCOLLECTIONS
cc <- rbind(aa, bb)

st_collection_extract(cc, "POLYGON")

```

---

st_coordinates	<i>retrieve coordinates in matrix form</i>
----------------	--

---

## Description

retrieve coordinates in matrix form

## Usage

```
st_coordinates(x, ...)
```

## Arguments

x	object of class sf, sfc or sfg
...	ignored

## Value

matrix with coordinates (X, Y, possibly Z and/or M) in rows, possibly followed by integer indicators L1,...,L3 that point out to which structure the coordinate belongs; for POINT this is absent (each coordinate is a feature), for LINESTRING L1 refers to the feature, for MULTIPOLYGON L1 refers to the main ring or holes, L2 to the ring id in the MULTIPOLYGON, and L3 to the simple feature.



---

st_crop	<i>crop an sf object to a specific rectangle</i>
---------	--

---

### Description

crop an sf object to a specific rectangle

### Usage

```
st_crop(x, y, ...)  
  
## S3 method for class 'sfc'  
st_crop(x, y, ..., xmin, ymin, xmax, ymax)  
  
## S3 method for class 'sf'  
st_crop(x, y, ...)
```

### Arguments

x	object of class sf or sfc
y	numeric vector with named elements xmin, ymin, xmax and ymax, or object of class bbox, or object for which there is an <a href="#">st_bbox</a> method to convert it to a bbox object
...	ignored
xmin	minimum x extent of cropping area
ymin	minimum y extent of cropping area
xmax	maximum x extent of cropping area
ymax	maximum y extent of cropping area

### Details

setting arguments xmin, ymin, xmax and ymax implies that argument y gets ignored.

### Examples

```
box = c(xmin = 0, ymin = 0, xmax = 1, ymax = 1)  
pol = st_sfc(st_buffer(st_point(c(.5, .5)), .6))  
pol_sf = st_sf(a=1, geom=pol)  
plot(st_crop(pol, box))  
plot(st_crop(pol_sf, st_bbox(box)))  
# alternative:  
plot(st_crop(pol, xmin = 0, ymin = 0, xmax = 1, ymax = 1))
```

---

`st_crs`*Retrieve coordinate reference system from object*

---

**Description**

Retrieve coordinate reference system from sf or sfc object

Set or replace retrieve coordinate reference system from object

**Usage**

```
st_crs(x, ...)  
  
## S3 method for class 'sf'  
st_crs(x, ...)  
  
## S3 method for class 'numeric'  
st_crs(x, ...)  
  
## S3 method for class 'character'  
st_crs(x, ...)  
  
## S3 method for class 'sfc'  
st_crs(x, ..., parameters = FALSE)  
  
## S3 method for class 'bbox'  
st_crs(x, ...)  
  
## S3 method for class 'CRS'  
st_crs(x, ...)  
  
## S3 method for class 'crs'  
st_crs(x, ...)  
  
st_crs(x) <- value  
  
## S3 replacement method for class 'sf'  
st_crs(x) <- value  
  
## S3 replacement method for class 'sfc'  
st_crs(x) <- value  
  
st_set_crs(x, value)  
  
NA_crs_  
  
## S3 method for class 'crs'
```

```

is.na(x)

## S3 method for class 'crs'
x$name

## S3 method for class 'crs'
format(x, ...)

st_axis_order(authority_compliant = logical(0))

```

### Arguments

x	numeric, character, or object of class <code>sf</code> or <code>sfc</code>
...	ignored
parameters	logical; FALSE by default; if TRUE return a list of coordinate reference system parameters, with named elements <code>SemiMajor</code> , <code>InvFlattening</code> , <code>units_gdal</code> , <code>IsVertical</code> , <code>WktPretty</code> , and <code>Wkt</code>
value	one of (i) character: a string accepted by GDAL, (ii) integer, a valid EPSG value (numeric), or (iii) an object of class <code>crs</code> .
name	element name
authority_compliant	logical; specify whether axis order should be handled compliant to the authority; if omitted, the current value is printed.

### Format

An object of class `crs` of length 2.

### Details

The `*crs` functions create, get, set or replace the `crs` attribute of a simple feature geometry list-column. This attribute is of class `crs`, and is a list consisting of input (user input, e.g. "EPSG:4326" or "WGS84" or a proj4string), and `wkt`, an automatically generated wkt representation of the crs.

Comparison of two objects of class `crs` uses the GDAL function `OGRSpatialReference::IsSame`.

In case a coordinate reference system is replaced, no transformation takes place and a warning is raised to stress this.

`NA_crs_` is the `crs` object with missing values for input and `wkt`.

the `$` method for `crs` objects retrieves named elements using the GDAL interface; named elements include "SemiMajor", "SemiMinor", "InvFlattening", "IsGeographic", "units\_gdal", "IsVertical", "WktPretty", "Wkt", "Name", "proj4string", "epsg", "yx" and "ud\_unit" (this may be subject to changes in future GDAL versions).

`format.crs` returns NA if the `crs` is missing valued, or else the name of a `crs` if it is different from "unknown", or else the user input if it was set, or else its "proj4string" representation;

`st_axis_order` can be used to get and set the axis order: TRUE indicates axes order according to the authority (e.g. EPSG:4326 defining coordinates to be latitude,longitude pairs), FALSE indicates the usual GIS (display) order (longitude,latitude). This can be useful when data are read, or have

to be written, with coordinates in authority compliant order. The return value is the current state of this (FALSE, by default).

### Value

If `x` is numeric, return crs object for EPSG:`x`; if `x` is character, return crs object for `x`; if `x` is of class `sf` or `sfc`, return its crs object.

Object of class `crs`, which is a list with elements `input` (length-1 character) and `wkt` (length-1 character). Elements may be NA valued; if all elements are NA the CRS is missing valued, and coordinates are assumed to relate to an arbitrary Cartesian coordinate system.

`st_axis_order` returns the (logical) current value if called without argument, or (invisibly) the previous value if it is being set.

### Examples

```
sfc = st_sfc(st_point(c(0,0)), st_point(c(1,1)))
sf = st_sf(a = 1:2, geom = sfc)
st_crs(sf) = 4326
st_geometry(sf)
sfc = st_sfc(st_point(c(0,0)), st_point(c(1,1)))
st_crs(sfc) = 4326
sfc
sfc = st_sfc(st_point(c(0,0)), st_point(c(1,1)))
library(dplyr)
x = sfc %>% st_set_crs(4326) %>% st_transform(3857)
x
st_crs("EPSG:3857")$input
st_crs(3857)$proj4string
st_crs(3857)$b      # numeric
st_crs(3857)$units # character
pt = st_sfc(st_point(c(0, 60)), crs = 4326)
# st_axis_order() only has effect in GDAL >= 2.5.0:
st_axis_order() # query default: FALSE means interpret pt as (longitude latitude)
st_transform(pt, 3857)[[1]]
old_value = FALSE
if (sf_extSoftVersion()["GDAL"] >= "2.5.0")
  (old_value = st_axis_order(TRUE))
# now interpret pt as (latitude longitude), as EPSG:4326 prescribes:
st_axis_order() # query current value
st_transform(pt, 3857)[[1]]
st_axis_order(old_value) # set back to old value
```

---

st\_drivers

*Get GDAL drivers*

---

### Description

Get a list of the available GDAL drivers

**Usage**

```
st_drivers(what = "vector")
```

**Arguments**

what                    character: "vector" or "raster", anything else will return all drivers.

**Details**

The drivers available will depend on the installation of GDAL/OGR, and can vary; the `st_drivers()` function shows all the drivers that are readable, and which may be written. The field `vsi` refers to the driver's capability to read/create datasets through the VSI\*`L` API. [See GDAL website for additional details on driver support.](#)

**Value**

A `data.frame` with driver metadata.

**Examples**

```
st_drivers()
```

---

<code>st_geometry</code>	<i>Get, set, or replace geometry from an sf object</i>
--------------------------	--

---

**Description**

Get, set, or replace geometry from an sf object

**Usage**

```
## S3 method for class 'sfc'
st_geometry(obj, ...)

st_geometry(obj, ...)

## S3 method for class 'sf'
st_geometry(obj, ...)

## S3 method for class 'sfc'
st_geometry(obj, ...)

## S3 method for class 'sfg'
st_geometry(obj, ...)

st_geometry(x) <- value
```

```
st_set_geometry(x, value)
```

```
st_drop_geometry(x)
```

### Arguments

obj	object of class sf or sfc
...	ignored
x	object of class data.frame
value	object of class sfc, or character

### Details

when applied to a data.frame and when value is an object of class sfc, st\_set\_geometry and st\_geometry<- will first check for the existence of an attribute sf\_column and overwrite that, or else look for list-columns of class sfc and overwrite the first of that, or else write the geometry list-column to a column named geometry. In case value is character and x is of class sf, the "active" geometry column is set to x[[value]].

the replacement function applied to sf objects will overwrite the geometry list-column, if value is NULL, it will remove it and coerce x to a data.frame.

st\_drop\_geometry drops the geometry of its argument, and reclasses it accordingly

### Value

st\_geometry returns an object of class sfc, a list-column with geometries

st\_geometry returns an object of class sfc. Assigning geometry to a data.frame creates an sf object, assigning it to an sf object replaces the geometry list-column.

### Examples

```
df = data.frame(a = 1:2)
sfc = st_sfc(st_point(c(3,4)), st_point(c(10,11)))
st_geometry(sfc)
st_geometry(df) <- sfc
class(df)
st_geometry(df)
st_geometry(df) <- sfc # replaces
st_geometry(df) <- NULL # remove geometry, coerce to data.frame
sf <- st_set_geometry(df, sfc) # set geometry, return sf
st_set_geometry(sf, NULL) # remove geometry, coerce to data.frame
```

---

st_geometry_type	<i>Return geometry type of an object</i>
------------------	--

---

**Description**

Return geometry type of an object, as a factor

**Usage**

```
st_geometry_type(x, by_geometry = TRUE)
```

**Arguments**

x	object of class <a href="#">sf</a> or <a href="#">sfc</a>
by_geometry	logical; if TRUE, return geometry type of each geometry, else return geometry type of the set

**Value**

a factor with the geometry type of each simple feature geometry in x, or that of the whole set

---

st_graticule	<i>Compute graticules and their parameters</i>
--------------	--

---

**Description**

Compute graticules and their parameters

**Usage**

```
st_graticule(  
  x = c(-180, -90, 180, 90),  
  crs = st_crs(x),  
  datum = st_crs(4326),  
  ...,  
  lon = NULL,  
  lat = NULL,  
  ndiscr = 100,  
  margin = 0.001  
)
```

**Arguments**

x	object of class <code>sf</code> , <code>sfc</code> or <code>sfg</code> or numeric vector with bounding box given as (minx, miny, maxx, maxy).
crs	object of class <code>crs</code> , with the display coordinate reference system
datum	either an object of class <code>crs</code> with the coordinate reference system for the graticules, or <code>NULL</code> in which case a grid in the coordinate system of <code>x</code> is drawn, or <code>NA</code> , in which case an empty <code>sf</code> object is returned.
...	ignored
lon	numeric; degrees east for the meridians
lat	numeric; degrees north for the parallels
ndiscr	integer; number of points to discretize a parallel or meridian
margin	numeric; small number to trim a longlat bounding box that touches or crosses +/-180 long or +/-90 latitude.

**Value**

an object of class `sf` with additional attributes describing the type (E: meridian, N: parallel) degree value, label, start and end coordinates and angle; see example.

**Use of graticules**

In cartographic visualization, the use of graticules is not advised, unless the graphical output will be used for measurement or navigation, or the direction of North is important for the interpretation of the content, or the content is intended to display distortions and artifacts created by projection. Unnecessary use of graticules only adds visual clutter but little relevant information. Use of coastlines, administrative boundaries or place names permits most viewers of the output to orient themselves better than a graticule.

**Examples**

```
library(sf)
library(maps)

usa = st_as_sf(map('usa', plot = FALSE, fill = TRUE))
laea = st_crs("+proj=laea +lat_0=30 +lon_0=-95") # Lambert equal area
usa <- st_transform(usa, laea)

bb = st_bbox(usa)
bbox = st_linestring(rbind(c( bb[1],bb[2]),c( bb[3],bb[2]),
  c( bb[3],bb[4]),c( bb[1],bb[4]),c( bb[1],bb[2])))

g = st_graticule(usa)
plot(usa, xlim = 1.2 * c(-2450853.4, 2186391.9))
plot(g[1], add = TRUE, col = 'grey')
plot(bbox, add = TRUE)
points(g$x_start, g$y_start, col = 'red')
points(g$x_end, g$y_end, col = 'blue')
```



```
invisible(lapply(seq_len(nrow(g)), function(i) {
  if (g$type[i] == "N" && g$x_start[i] - min(g$x_start) < 1000)
    text(g[i,"x_start"], g[i,"y_start"], labels = parse(text = g[i,"degree_label"]),
         srt = g$angle_start[i], pos = 2, cex = .7)
  if (g$type[i] == "E" && g$y_start[i] - min(g$y_start) < 1000)
    text(g[i,"x_start"], g[i,"y_start"], labels = parse(text = g[i,"degree_label"]),
         srt = g$angle_start[i] - 90, pos = 1, cex = .7)
  if (g$type[i] == "N" && g$x_end[i] - max(g$x_end) > -1000)
    text(g[i,"x_end"], g[i,"y_end"], labels = parse(text = g[i,"degree_label"]),
         srt = g$angle_end[i], pos = 4, cex = .7)
  if (g$type[i] == "E" && g$y_end[i] - max(g$y_end) > -1000)
    text(g[i,"x_end"], g[i,"y_end"], labels = parse(text = g[i,"degree_label"]),
         srt = g$angle_end[i] - 90, pos = 3, cex = .7)
}))
plot(usa, graticule = st_crs(4326), axes = TRUE, lon = seq(-60,-130,by=-10))
```

---

st\_interpolate\_aw      *Areal-weighted interpolation of polygon data*

---

### Description

Areal-weighted interpolation of polygon data

### Usage

```
st_interpolate_aw(x, to, extensive, ...)
```

### Arguments

x	object of class sf, for which we want to aggregate attributes
to	object of class sf or sfc, with the target geometries
extensive	logical; if TRUE, the attribute variables are assumed to be spatially extensive (like population) and the sum is preserved, otherwise, spatially intensive (like population density) and the mean is preserved.
...	ignored

### Examples

```
nc = st_read(system.file("shape/nc.shp", package="sf"))
g = st_make_grid(nc, n = c(20,10))
a1 = st_interpolate_aw(nc["BIR74"], g, extensive = FALSE)
sum(a1$BIR74) / sum(nc$BIR74) # not close to one: property is assumed spatially intensive
a2 = st_interpolate_aw(nc["BIR74"], g, extensive = TRUE)
# verify mass preservation (pyncophylactic) property:
sum(a2$BIR74) / sum(nc$BIR74)
a1$intensive = a1$BIR74
a1$extensive = a2$BIR74
plot(a1[c("intensive", "extensive")], key.pos = 4)
```

---

st\_is *test equality between the geometry type and a class or set of classes*

---

### Description

test equality between the geometry type and a class or set of classes

### Usage

```
st_is(x, type)
```

### Arguments

x                    object of class sf, sfc or sfg  
 type                character; class, or set of classes, to test against

### Examples

```
st_is(st_point(0:1), "POINT")
sfc = st_sfc(st_point(0:1), st_linestring(matrix(1:6,,2)))
st_is(sfc, "POINT")
st_is(sfc, "POLYGON")
st_is(sfc, "LINESTRING")
st_is(st_sf(a = 1:2, sfc), "LINESTRING")
st_is(sfc, c("POINT", "LINESTRING"))
```

---

st\_is\_longlat *Assert whether simple feature coordinates are longlat degrees*

---

### Description

Assert whether simple feature coordinates are longlat degrees

### Usage

```
st_is_longlat(x)
```

### Arguments

x                    object of class sf or sfc, or otherwise an object of a class that has an st\_crs method returning a crs object

### Value

TRUE if x has geographic coordinates, FALSE if it has projected coordinates, or NA if is.na(st\_crs(x)).

---

st_jitter	<i>jitter geometries</i>
-----------	--------------------------

---

**Description**

jitter geometries

**Usage**

```
st_jitter(x, amount, factor = 0.002)
```

**Arguments**

x	object of class sf or sfc
amount	numeric; amount of jittering applied; if missing, the amount is set to factor * the bounding box diagonal; units of coordinates.
factor	numeric; fractional amount of jittering to be applied

**Details**

jitters coordinates with an amount such that `runif(1, -amount, amount)` is added to the coordinates. x- and y-coordinates are jittered independently but all coordinates of a single geometry are jittered with the same amount, meaning that the geometry shape does not change. For longlat data, a latitude correction is made such that jittering in East and North directions are identical in distance in the center of the bounding box of x.

**Examples**

```
nc = read_sf(system.file("gpkg/nc.gpkg", package="sf"))
pts = st_centroid(st_geometry(nc))
plot(pts)
plot(st_jitter(pts, .05), add = TRUE, col = 'red')
plot(st_geometry(nc))
plot(st_jitter(st_geometry(nc), factor = .01), add = TRUE, col = '#ff8888')
```

---

st_join	<i>spatial join, spatial filter</i>
---------	-------------------------------------

---

**Description**

spatial join, spatial filter

**Usage**

```

st_join(x, y, join, ...)

## S3 method for class 'sf'
st_join(
  x,
  y,
  join = st_intersects,
  ...,
  suffix = c(".x", ".y"),
  left = TRUE,
  largest = FALSE
)

st_filter(x, y, ...)

## S3 method for class 'sf'
st_filter(x, y, ..., .predicate = st_intersects)

```

**Arguments**

x	object of class sf
y	object of class sf
join	geometry predicate function with the same profile as <a href="#">st_intersects</a> ; see details
...	arguments passed on to the join or .predicate function, e.g. prepared, or a pattern for <a href="#">st_relate</a>
suffix	length 2 character vector; see <a href="#">merge</a>
left	logical; if TRUE return the left join, otherwise an inner join; see details. see also <a href="#">left_join</a>
largest	logical; if TRUE, return x features augmented with the fields of y that have the largest overlap with each of the features of x; see <a href="https://github.com/r-spatial/sf/issues/578">https://github.com/r-spatial/sf/issues/578</a>
.predicate	geometry predicate function with the same profile as <a href="#">st_intersects</a> ; see details

**Details**

alternative values for argument join are:

- [st\\_contains\\_properly](#)
- [st\\_contains](#)
- [st\\_covered\\_by](#)
- [st\\_covers](#)
- [st\\_crosses](#)
- [st\\_disjoint](#)
- [st\\_equals\\_exact](#)
- [st\\_equals](#)

- [st\\_is\\_within\\_distance](#)
- [st\\_nearest\\_feature](#)
- [st\\_overlaps](#)
- [st\\_touches](#)
- [st\\_within](#)
- any user-defined function of the same profile as the above

A left join returns all records of the x object with y fields for non-matched records filled with NA values; an inner join returns only records that spatially match.

### Value

an object of class sf, joined based on geometry

### Examples

```
a = st_sf(a = 1:3,
  geom = st_sfc(st_point(c(1,1)), st_point(c(2,2)), st_point(c(3,3))))
b = st_sf(a = 11:14,
  geom = st_sfc(st_point(c(10,10)), st_point(c(2,2)), st_point(c(2,2)), st_point(c(3,3))))
st_join(a, b)
st_join(a, b, left = FALSE)
# two ways to aggregate y's attribute values outcome over x's geometries:
st_join(a, b) %>% aggregate(list(. $a.x), mean)
library(dplyr)
st_join(a, b) %>% group_by(a.x) %>% summarise(mean(a.y))
# example of largest = TRUE:
nc <- st_transform(st_read(system.file("shape/nc.shp", package="sf")), 2264)
gr = st_sf(
  label = apply(expand.grid(1:10, LETTERS[10:1])[,2:1], 1, paste0, collapse = " "),
  geom = st_make_grid(st_as_sfc(st_bbox(nc))))
gr$col = sf.colors(10, categorical = TRUE, alpha = .3)
# cut, to check, NA's work out:
gr = gr[-(1:30),]
nc_j <- st_join(nc, gr, largest = TRUE)
# the two datasets:
opar = par(mfrow = c(2,1), mar = rep(0,4))
plot(st_geometry(nc_j))
plot(st_geometry(gr), add = TRUE, col = gr$col)
text(st_coordinates(st_centroid(gr)), labels = gr$label)
# the joined dataset:
plot(st_geometry(nc_j), border = 'black', col = nc_j$col)
text(st_coordinates(st_centroid(nc_j)), labels = nc_j$label, cex = .8)
plot(st_geometry(gr), border = 'green', add = TRUE)
par(opar)
```

---

st_layers	<i>List layers in a datasource</i>
-----------	------------------------------------

---

**Description**

List layers in a datasource

**Usage**

```
st_layers(dsn, options = character(0), do_count = FALSE)
```

**Arguments**

dsn	data source name (interpretation varies by driver - for some drivers, dsn is a file name, but may also be a folder, or contain the name and access credentials of a database)
options	character; driver dependent dataset open options, multiple options supported.
do_count	logical; if TRUE, count the features by reading them, even if their count is not reported by the driver

---

st_line_sample	<i>Sample points on a linear geometry</i>
----------------	---

---

**Description**

Sample points on a linear geometry

**Usage**

```
st_line_sample(x, n, density, type = "regular", sample = NULL)
```

**Arguments**

x	object of class sf, sfc or sfg
n	integer; number of points to choose per geometry; if missing, n will be computed as <code>round(density * st_length(geom))</code> .
density	numeric; density (points per distance unit) of the sampling, possibly a vector of length equal to the number of features (otherwise recycled); density may be of class units.
type	character; indicate the sampling type, either "regular" or "random"
sample	numeric; a vector of numbers between 0 and 1 indicating the points to sample - if defined sample overrules n, density and type.

**Examples**

```

ls = st_sfc(st_linestring(rbind(c(0,0),c(0,1))),
st_linestring(rbind(c(0,0),c(10,0))))
st_line_sample(ls, density = 1)
ls = st_sfc(st_linestring(rbind(c(0,0),c(0,1))),
st_linestring(rbind(c(0,0),c(.1,0))), crs = 4326)
try(st_line_sample(ls, density = 1/1000)) # error
st_line_sample(st_transform(ls, 3857), n = 5) # five points for each line
st_line_sample(st_transform(ls, 3857), n = c(1, 3)) # one and three points
st_line_sample(st_transform(ls, 3857), density = 1/1000) # one per km
st_line_sample(st_transform(ls, 3857), density = c(1/1000, 1/10000)) # one per km, one per 10 km
st_line_sample(st_transform(ls, 3857), density = units::set_units(1, 1/km)) # one per km
# five equidistant points including start and end:
st_line_sample(st_transform(ls, 3857), sample = c(0, 0.25, 0.5, 0.75, 1))

```

---

st_make_grid	<i>Create a regular tessellation over the bounding box of an sf or sfc object</i>
--------------	---

---

**Description**

Create a square or hexagonal grid covering the bounding box of the geometry of an sf or sfc object

**Usage**

```

st_make_grid(
  x,
  cellsize = c(diff(st_bbox(x)[c(1, 3)]), diff(st_bbox(x)[c(2, 4)]))/n,
  offset = st_bbox(x)[c("xmin", "ymin")],
  n = c(10, 10),
  crs = if (missing(x)) NA_crs_ else st_crs(x),
  what = "polygons",
  square = TRUE,
  flat_topped = FALSE
)

```

**Arguments**

x	object of class <a href="#">sf</a> or <a href="#">sfc</a>
cellsize	target cellsize
offset	numeric of length 2; lower left corner coordinates (x, y) of the grid
n	integer of length 1 or 2, number of grid cells in x and y direction (columns, rows)
crs	object of class <a href="#">crs</a> ; coordinate reference system of the target of the target grid in case argument x is missing, if x is not missing, its crs is inherited.
what	character; one of: "polygons", "corners", or "centers"
square	logical; if FALSE, create hexagonal grid
flat_topped	logical; if TRUE generate flat topped hexagons, else generate pointy topped

**Value**

Object of class `sfc` (simple feature geometry list column) with, depending on `what` and `square`, square, square or hexagonal polygons, corner points of these polygons, or center points of these polygons.

**Examples**

```
plot(st_make_grid(what = "centers"), axes = TRUE)
plot(st_make_grid(what = "corners", add = TRUE, col = 'green', pch=3)
sfc = st_sfc(st_polygon(list(rbind(c(0,0), c(1,0), c(1,1), c(0,0)))))
plot(st_make_grid(sfc, cellsize = .1, square = FALSE))
plot(sfc, add = TRUE)
# non-default offset:
plot(st_make_grid(sfc, cellsize = .1, square = FALSE, offset = c(0, .05 / (sqrt(3)/2))))
plot(sfc, add = TRUE)
nc = read_sf(system.file("shape/nc.shp", package="sf"))
g = st_make_grid(nc)
plot(g)
plot(st_geometry(nc), add = TRUE)
# g[nc] selects cells that intersect with nc:
plot(g[nc], col = '#ff000088', add = TRUE)
```

---

`st_m_range`
*Return 'm' range of a simple feature or simple feature set*


---

**Description**

Return 'm' range of a simple feature or simple feature set

**Usage**

```
## S3 method for class 'm_range'
is.na(x)

st_m_range(obj, ...)

## S3 method for class 'POINT'
st_m_range(obj, ...)

## S3 method for class 'MULTIPOINT'
st_m_range(obj, ...)

## S3 method for class 'LINESTRING'
st_m_range(obj, ...)

## S3 method for class 'POLYGON'
st_m_range(obj, ...)

## S3 method for class 'MULTILINESTRING'
```



```
st_m_range(obj, ...)  
  
## S3 method for class 'MULTIPOLYGON'  
st_m_range(obj, ...)  
  
## S3 method for class 'GEOMETRYCOLLECTION'  
st_m_range(obj, ...)  
  
## S3 method for class 'MULTISURFACE'  
st_m_range(obj, ...)  
  
## S3 method for class 'MULTICURVE'  
st_m_range(obj, ...)  
  
## S3 method for class 'CURVEPOLYGON'  
st_m_range(obj, ...)  
  
## S3 method for class 'COMPOUNDCURVE'  
st_m_range(obj, ...)  
  
## S3 method for class 'POLYHEDRALSURFACE'  
st_m_range(obj, ...)  
  
## S3 method for class 'TIN'  
st_m_range(obj, ...)  
  
## S3 method for class 'TRIANGLE'  
st_m_range(obj, ...)  
  
## S3 method for class 'CIRCULARSTRING'  
st_m_range(obj, ...)  
  
## S3 method for class 'sfc'  
st_m_range(obj, ...)  
  
## S3 method for class 'sf'  
st_m_range(obj, ...)  
  
## S3 method for class 'numeric'  
st_m_range(obj, ..., crs = NA_crs_)  
  
NA_m_range_
```

### Arguments

x	object of class m_range
obj	object to compute the m range from
...	ignored

crs                    object of class crs, or argument to [st\\_crs](#), specifying the CRS of this bounding box.

### Format

An object of class `m_range` of length 2.

### Details

`NA_m_range_` represents the missing value for a `m_range` object

### Value

a numeric vector of length two, with `mmin` and `mmax` values; if `obj` is of class `sf` or `sfc` the object if `obj` is of class `sf` or `sfc` the object returned has a class `m_range`

### Examples

```
a = st_sf(a = 1:2, geom = st_sfc(st_point(0:3), st_point(1:4)), crs = 4326)
st_m_range(a)
st_m_range(c(mmin = 16.1, mmax = 16.6), crs = st_crs(4326))
```

---

`st_nearest_feature`      *get index of nearest feature*

---

### Description

get index of nearest feature

### Usage

```
st_nearest_feature(x, y)
```

### Arguments

`x`                    object of class `sfg`, `sfc` or `sf`  
`y`                    object of class `sfg`, `sfc` or `sf`

### Value

for each feature (geometry) in `x` the index of the nearest feature (geometry) in set `y`; empty geometries result in NA indexes

### See Also

[st\\_nearest\\_points](#) for finding the nearest points for pairs of feature geometries

**Examples**

```

ls1 = st_linestring(rbind(c(0,0), c(1,0)))
ls2 = st_linestring(rbind(c(0,0.1), c(1,0.1)))
ls3 = st_linestring(rbind(c(0,1), c(1,1)))
(l = st_sfc(ls1, ls2, ls3))

p1 = st_point(c(0.1, -0.1))
p2 = st_point(c(0.1, 0.11))
p3 = st_point(c(0.1, 0.09))
p4 = st_point(c(0.1, 0.9))

(p = st_sfc(p1, p2, p3, p4))
try(st_nearest_feature(p, l))
try(st_nearest_points(p, l[st_nearest_feature(p,l)], pairwise = TRUE))

r = sqrt(2)/10
b1 = st_buffer(st_point(c(.1,.1)), r)
b2 = st_buffer(st_point(c(.9,.9)), r)
b3 = st_buffer(st_point(c(.9,.1)), r)
circles = st_sfc(b1, b2, b3)
plot(circles, col = NA, border = 2:4)
pts = st_sfc(st_point(c(.3,.1)), st_point(c(.6,.2)), st_point(c(.6,.6)), st_point(c(.4,.8)))
plot(pts, add = TRUE, col = 1)
# draw points to nearest circle:
nearest = try(st_nearest_feature(pts, circles))
if (inherits(nearest, "try-error")) # GEOS 3.6.1 not available
  nearest = c(1, 3, 2, 2)
ls = st_nearest_points(pts, circles[nearest], pairwise = TRUE)
plot(ls, col = 5:8, add = TRUE)

```

---

st\_nearest\_points      *get nearest points between pairs of geometries*

---

**Description**

get nearest points between pairs of geometries

**Usage**

```

st_nearest_points(x, y, ...)

## S3 method for class 'sfc'
st_nearest_points(x, y, ..., pairwise = FALSE)

## S3 method for class 'sfg'
st_nearest_points(x, y, ...)

## S3 method for class 'sf'
st_nearest_points(x, y, ...)

```

**Arguments**

x	object of class sfg, sfc or sf
y	object of class sfg, sfc or sf
...	ignored
pairwise	logical; if FALSE (default) return nearest points between all pairs, if TRUE, return nearest points between subsequent pairs.

**Details**

in case x lies inside y, when using S2, the end points are on polygon boundaries, when using GEOS the end point are identical to x.

**Value**

an *sfc* object with all two-point LINESTRING geometries of point pairs from the first to the second geometry, of length  $x * y$ , with y cycling fastest. See examples for ideas how to convert these to POINT geometries.

**See Also**

[st\\_nearest\\_feature](#) for finding the nearest feature

**Examples**

```
r = sqrt(2)/10
pt1 = st_point(c(.1,.1))
pt2 = st_point(c(.9,.9))
pt3 = st_point(c(.9,.1))
b1 = st_buffer(pt1, r)
b2 = st_buffer(pt2, r)
b3 = st_buffer(pt3, r)
(ls0 = st_nearest_points(b1, b2)) # sfg
(ls = st_nearest_points(st_sfc(b1), st_sfc(b2, b3))) # sfc
plot(b1, xlim = c(-.2,1.2), ylim = c(-.2,1.2), col = NA, border = 'green')
plot(st_sfc(b2, b3), add = TRUE, col = NA, border = 'blue')
plot(ls, add = TRUE, col = 'red')

nc = read_sf(system.file("gpkg/nc.gpkg", package="sf"))
plot(st_geometry(nc))
ls = st_nearest_points(nc[1,], nc)
plot(ls, col = 'red', add = TRUE)
pts = st_cast(ls, "POINT") # gives all start & end points
# starting, "from" points, corresponding to x:
plot(pts[seq(1, 200, 2)], add = TRUE, col = 'blue')
# ending, "to" points, corresponding to y:
plot(pts[seq(2, 200, 2)], add = TRUE, col = 'green')
```

---

st_normalize	<i>Normalize simple features</i>
--------------	----------------------------------

---

**Description**

st\_normalize transforms the coordinates in the input feature to fall between 0 and 1. By default the current domain is set to the bounding box of the input, but other domains can be used as well

**Usage**

```
st_normalize(x, domain = st_bbox(x), ...)
```

**Arguments**

x	object of class sf, sfc or sfg
domain	The domain x should be normalized from as a length 4 vector of the form c(xmin,ymin,xmax,ymax). Defaults to the bounding box of x
...	ignored

**Examples**

```
p1 = st_point(c(7,52))
st_normalize(p1, domain = c(0, 0, 10, 100))

p2 = st_point(c(-30,20))
sfc = st_sfc(p1, p2, crs = 4326)
sfc
sfc_norm <- st_normalize(sfc)
st_bbox(sfc_norm)
```

---

st_precision	<i>Get precision</i>
--------------	----------------------

---

**Description**

Get precision  
Set precision

**Usage**

```
st_precision(x)

st_set_precision(x, precision)

st_precision(x) <- value
```

**Arguments**

x	object of class sfc or sf
precision	numeric, or object of class units with distance units (but see details); see <a href="#">st_as_binary</a> for how to do this.
value	precision value

**Details**

If precision is a units object, the object on which we set precision must have a coordinate reference system with compatible distance units.

Setting a precision has no direct effect on coordinates of geometries, but merely set an attribute tag to an sfc object. The effect takes place in [st\\_as\\_binary](#) or, more precise, in the C++ function CPL\_write\_wkb, where simple feature geometries are being serialized to well-known-binary (WKB). This happens always when routines are called in GEOS library (geometrical operations or predicates), for writing geometries using [st\\_write](#) or [write\\_sf](#), [st\\_make\\_valid](#) in package lwgeom; also [aggregate](#) and [summarise](#) by default union geometries, which calls a GEOS library function. Routines in these libraries receive rounded coordinates, and possibly return results based on them. [st\\_as\\_binary](#) contains an example of a roundtrip of sfc geometries through WKB, in order to see the rounding happening to R data.

The reason to support precision is that geometrical operations in GEOS or liblwgeom may work better at reduced precision. For writing data from R to external resources it is harder to think of a good reason to limiting precision.

**See Also**

[st\\_as\\_binary](#) for an explanation of what setting precision does, and the examples therein.

**Examples**

```
x <- st_sfc(st_point(c(pi, pi)))
st_precision(x)
st_precision(x) <- 0.01
st_precision(x)
```

---

st\_read

*Read simple features or layers from file or database*


---

**Description**

Read simple features from file or database, or retrieve layer names and their geometry type(s)

Read PostGIS table directly through DBI and RPostgreSQL interface, converting Well-Know Binary geometries to sfc

**Usage**

```

st_read(dsn, layer, ...)

## S3 method for class 'character'
st_read(
  dsn,
  layer,
  ...,
  query = NA,
  options = NULL,
  quiet = FALSE,
  geometry_column = 1L,
  type = 0,
  promote_to_multi = TRUE,
  stringsAsFactors = sf_stringsAsFactors(),
  int64_as_string = FALSE,
  check_ring_dir = FALSE,
  fid_column_name = character(0),
  drivers = character(0),
  wkt_filter = character(0)
)

read_sf(..., quiet = TRUE, stringsAsFactors = FALSE, as_tibble = TRUE)

## S3 method for class 'DBIObject'
st_read(
  dsn = NULL,
  layer = NULL,
  query = NULL,
  EWKB = TRUE,
  quiet = TRUE,
  as_tibble = FALSE,
  geometry_column = NULL,
  ...
)

```

**Arguments**

dsn	data source name (interpretation varies by driver - for some drivers, dsn is a file name, but may also be a folder, or contain the name and access credentials of a database); in case of GeoJSON, dsn may be the character string holding the geojson data. It can also be an open database connection.
layer	layer name (varies by driver, may be a file name without extension); in case layer is missing, st_read will read the first layer of dsn, give a warning and (unless quiet = TRUE) print a message when there are multiple layers, or give an error if there are no layers in dsn. If dsn is a database connection, then layer can be a table name or a database identifier (see <a href="#">Id</a> ). It is also possible to omit layer and rather use the query argument.

...	parameter(s) passed on to <code>st_as_sf</code>
query	SQL query to select records; see details
options	character; driver dependent dataset open options, multiple options supported. For possible values, see the "Open options" section of the GDAL documentation of the corresponding driver, and <a href="https://github.com/r-spatial/sf/issues/1157">https://github.com/r-spatial/sf/issues/1157</a> for an example.
quiet	logical; suppress info on name, driver, size and spatial reference, or signaling no or multiple layers
geometry_column	integer or character; in case of multiple geometry fields, which one to take?
type	integer; ISO number of desired simple feature type; see details. If left zero, and <code>promote_to_multi</code> is TRUE, in case of mixed feature geometry types, conversion to the highest numeric type value found will be attempted. A vector with different values for each geometry column can be given.
promote_to_multi	logical; in case of a mix of Point and MultiPoint, or of LineString and MultiLineString, or of Polygon and MultiPolygon, convert all to the Multi variety; defaults to TRUE
stringsAsFactors	logical; logical: should character vectors be converted to factors? Default for <code>read_sf</code> or R version $\geq 4.1.0$ is FALSE, for <code>st_read</code> and R version $< 4.1.0$ equal to <code>default.stringsAsFactors()</code>
int64_as_string	logical; if TRUE, Int64 attributes are returned as string; if FALSE, they are returned as double and a warning is given when precision is lost (i.e., values are larger than $2^{53}$ ).
check_ring_dir	logical; if TRUE, polygon ring directions are checked and if necessary corrected (when seen from above: exterior ring counter clockwise, holes clockwise)
fid_column_name	character; name of column to write feature IDs to; defaults to not doing this
drivers	character; limited set of driver short names to be tried (default: try all)
wkt_filter	character; WKT representation of a spatial filter (may be used as bounding box, selecting overlapping geometries); see examples
as_tibble	logical; should the returned table be of class tibble or data.frame?
EWKB	logical; is the WKB of type EWKB? if missing, defaults to TRUE

### Details

for `geometry_column`, see also [https://trac.osgeo.org/gdal/wiki/rfc41\\_multiple\\_geometry\\_fields](https://trac.osgeo.org/gdal/wiki/rfc41_multiple_geometry_fields)

for values for `type` see [https://en.wikipedia.org/wiki/Well-known\\_text#Well-known\\_binary](https://en.wikipedia.org/wiki/Well-known_text#Well-known_binary), but note that not every target value may lead to successful conversion. The typical conversion from POLYGON (3) to MULTIPOLYGON (6) should work; the other way around (`type=3`), secondary rings from MULTIPOLYGONS may be dropped without warnings. `promote_to_multi` is handled on a per-geometry column basis; `type` may be specified for each geometry column.



Note that stray files in data source directories (such as \*.dbf) may lead to spurious errors that accompanying \*.shp are missing.

In case of problems reading shapefiles from USB drives on OSX, please see <https://github.com/r-spatial/sf/issues/252>.

For query with a character dsn the query text is handed to 'ExecuteSQL' on the GDAL/OGR data set and will result in the creation of a new layer (and layer is ignored). See 'OGRSQL' [https://gdal.org/user/ogr\\_sql\\_dialect.html](https://gdal.org/user/ogr_sql_dialect.html) for details. Please note that the 'FID' special field is driver-dependent, and may be either 0-based (e.g. ESRI Shapefile), 1-based (e.g. MapInfo) or arbitrary (e.g. OSM). Other features of OGRSQL are also likely to be driver dependent. The available layer names may be obtained with [st\\_layers](#). Care will be required to properly escape the use of some layer names.

read\_sf and write\_sf are aliases for st\_read and st\_write, respectively, with some modified default arguments. read\_sf and write\_sf are quiet by default: they do not print information about the data source. read\_sf returns an sf-tibble rather than an sf-data.frame. write\_sf delete layers by default: it overwrites existing files without asking or warning.

if table is not given but query is, the spatial reference system (crs) of the table queried is only available in case it has been stored into each geometry record (e.g., by PostGIS, when using EWKB)

The function will automatically find the 'geometry' type columns for drivers that support it. For the other drivers, it will try to cast all the character columns, which can be slow for very wide tables.

## Value

object of class [sf](#) when a layer was successfully read; in case argument layer is missing and data source dsn does not contain a single layer, an object of class [sf\\_layers](#) is returned with the layer names, each with their geometry type(s). Note that the number of layers may also be zero.

## Note

The use of `system.file` in examples make sure that examples run regardless where R is installed: typical users will not use `system.file` but give the file name directly, either with full path or relative to the current working directory (see [getwd](#)). "Shapefiles" consist of several files with the same basename that reside in the same directory, only one of them having extension `.shp`.

## See Also

[st\\_layers](#), [st\\_drivers](#)

## Examples

```
nc = st_read(system.file("shape/nc.shp", package="sf"))
summary(nc) # note that AREA was computed using Euclidian area on lon/lat degrees

## only three fields by select clause
## only two features by where clause
nc_sql = st_read(system.file("shape/nc.shp", package="sf"),
                  query = "SELECT NAME, SID74, FIPS FROM \"nc\" WHERE BIR74 > 20000")
## Not run:
library(sp)
example(meuse, ask = FALSE, echo = FALSE)
```

```

try(st_write(st_as_sf(meuse), "PG:dbname=postgis", "meuse",
  layer_options = "OVERWRITE=true"))
try(st_meuse <- st_read("PG:dbname=postgis", "meuse"))
if (exists("st_meuse"))
  summary(st_meuse)

## End(Not run)

## Not run:
## note that we need special escaping of layer within single quotes (nc.gpkg)
## and that geom needs to be included in the select, otherwise we don't detect it
layer <- st_layers(system.file("gpkg/nc.gpkg", package = "sf"))$name[1]
nc_gpkg_sql = st_read(system.file("gpkg/nc.gpkg", package = "sf"),
  query = sprintf("SELECT NAME, SID74, FIPS, geom FROM \"%s\" WHERE BIR74 > 20000", layer))

## End(Not run)
# spatial filter, as wkt:
wkt = st_as_text(st_geometry(nc[1,]))
# filter by (bbox overlaps of) first feature geometry:
read_sf(system.file("gpkg/nc.gpkg", package="sf"), wkt_filter = wkt)
# read geojson from string:
geojson_txt <- paste("{\"type\":\"MultiPoint\",\"coordinates\":",
  "[[[3.2,4],[3,4.6],[3.8,4.4],[3.5,3.8],[3.4,3.6],[3.9,4.5]]]}")
x = read_sf(geojson_txt)
x
## Not run:
library(RPostgreSQL)
try(conn <- dbConnect(PostgreSQL(), dbname = "postgis"))
if (exists("conn") && !inherits(conn, "try-error")) {
  x = st_read(conn, "meuse", query = "select * from meuse limit 3;")
  x = st_read(conn, table = "public.meuse")
  print(st_crs(x)) # SRID resolved by the database, not by GDAL!
  dbDisconnect(conn)
}

## End(Not run)

```

---

st\_relate

---

*Compute DE9-IM relation between pairs of geometries, or match it to a given pattern*


---

## Description

Compute DE9-IM relation between pairs of geometries, or match it to a given pattern

## Usage

```
st_relate(x, y, pattern = NA_character_, sparse = !is.na(pattern))
```

**Arguments**

x	object of class sf, sfc or sfg
y	object of class sf, sfc or sfg
pattern	character; define the pattern to match to, see details.
sparse	logical; should a sparse matrix be returned (TRUE) or a dense matrix?

**Value**

In case pattern is not given, st\_relate returns a dense character matrix; element [i,j] has nine characters, referring to the DE9-IM relationship between x[i] and y[j], encoded as IxIy,IxBx,IxEy,BxIy,BxBx,BxEy,ExIy,ExBx where I refers to interior, B to boundary, and E to exterior, and e.g. BxIy the dimensionality of the intersection of the the boundary of x[i] and the interior of y[j], which is one of 0,1,2,F, digits denoting dimensionality, F denoting not intersecting. When pattern is given, a dense logical matrix or sparse index list returned with matches to the given pattern; see [st\\_intersection](#) for a description of the returned matrix or list. See also <https://en.wikipedia.org/wiki/DE-9IM> for further explanation.

**Examples**

```
p1 = st_point(c(0,0))
p2 = st_point(c(2,2))
pol1 = st_polygon(list(rbind(c(0,0),c(1,0),c(1,1),c(0,1),c(0,0)))) - 0.5
pol2 = pol1 + 1
pol3 = pol1 + 2
st_relate(st_sfc(p1, p2), st_sfc(pol1, pol2, pol3))
sfc = st_sfc(st_point(c(0,0)), st_point(c(3,3)))
grd = st_make_grid(sfc, n = c(3,3))
st_intersects(grd)
st_relate(grd, pattern = "****1****") # sides, not corners, internals
st_relate(grd, pattern = "****0****") # only corners touch
st_rook = function(a, b = a) st_relate(a, b, pattern = "F***1****")
st_rook(grd)
# queen neighbours, see \url{https://github.com/r-spatial/sf/issues/234#issuecomment-300511129}
st_queen <- function(a, b = a) st_relate(a, b, pattern = "F***T****")
```

---

st\_sample

*sample points on or in (sets of) spatial features*


---

**Description**

Sample points on or in (sets of) spatial features. By default, returns a pre-specified number of points that is equal to size (if type = "random" and exact = TRUE) or an approximation of size otherwise. spatstat methods are interfaced and do not use the size argument, see examples.

**Usage**

```

st_sample(x, size, ...)

## S3 method for class 'sf'
st_sample(x, size, ...)

## S3 method for class 'sfc'
st_sample(
  x,
  size,
  ...,
  type = "random",
  exact = TRUE,
  warn_if_not_integer = TRUE,
  by_polygon = FALSE
)

## S3 method for class 'sfg'
st_sample(x, size, ...)

```

**Arguments**

x	object of class sf or sfc
size	sample size(s) requested; either total size, or a numeric vector with sample sizes for each feature geometry. When sampling polygons, the returned sampling size may differ from the requested size, as the bounding box is sampled, and sampled points intersecting the polygon are returned.
...	passed on to <a href="#">sample</a> for multipoint sampling, or to spatstat functions for spatstat sampling types (see details)
type	character; indicates the spatial sampling type; one of random, hexagonal (triangular really), regular, or one of the spatstat methods such as Thomas for calling spatstat::rThomas (see Details).
exact	logical; should the length of output be exactly
warn_if_not_integer	logical; if FALSE then no warning is emitted if size is not an integer
by_polygon	logical; for MULTIPOLYGON geometries, should the effort be split by POLYGON? See <a href="https://github.com/r-spatial/sf/issues/1480">https://github.com/r-spatial/sf/issues/1480</a> <a href="https://github.com/r-spatial/sf/issues/1480">https://github.com/r-spatial/sf/issues/1480</a> the same as specified by size? TRUE by default. Only applies to polygons, and when type = "random".

**Details**

The function is vectorised: it samples size points across all geometries in the object if size is a single number, or the specified number of points in each feature if size is a vector of integers equal in length to the geometry of x.

if x has dimension 2 (polygons) and geographical coordinates (long/lat), uniform random sampling on the sphere is applied, see e.g. <http://mathworld.wolfram.com/SpherePointPicking.html>

For regular or hexagonal sampling of polygons, the resulting size is only an approximation.

As parameter called `offset` can be passed to control ("fix") regular or hexagonal sampling: for polygons a length 2 numeric vector (by default: a random point from `st_bbox(x)`); for lines use a number like `runif(1)`.

Sampling methods from package `spatstat` are interfaced (see examples), and need their own parameters to be set. For instance, to use `spatstat::rThomas()`, set `type = "Thomas"`.

## Value

an `sfc` object containing the sampled POINT geometries

## Examples

```
nc = st_read(system.file("shape/nc.shp", package="sf"))
p1 = st_sample(nc[1:3, ], 6)
p2 = st_sample(nc[1:3, ], 1:3)
plot(st_geometry(nc)[1:3])
plot(p1, add = TRUE)
plot(p2, add = TRUE, pch = 2)
x = st_sfc(st_polygon(list(rbind(c(0,0),c(90,0),c(90,90),c(0,90),c(0,0))))), crs = st_crs(4326))
plot(x, axes = TRUE, graticule = TRUE)
if (sf_extSoftVersion()["proj.4"] >= "4.9.0")
  plot(p <- st_sample(x, 1000), add = TRUE)
x2 = st_transform(st_segmentize(x, 1e4), st_crs("+proj=ortho +lat_0=30 +lon_0=45"))
g = st_transform(st_graticule(), st_crs("+proj=ortho +lat_0=30 +lon_0=45"))
plot(x2, graticule = g)
if (sf_extSoftVersion()["proj.4"] >= "4.9.0") {
  p2 = st_transform(p, st_crs("+proj=ortho +lat_0=30 +lon_0=45"))
  plot(p2, add = TRUE)
}
x = st_sfc(st_polygon(list(rbind(c(0,0),c(90,0),c(90,10),c(0,90),c(0,0)))))) # NOT long/lat:
plot(x)
p_exact = st_sample(x, 1000, exact = TRUE)
p_not_exact = st_sample(x, 1000, exact = FALSE)
length(p_exact); length(p_not_exact)
plot(st_sample(x, 1000), add = TRUE)
x = st_sfc(st_polygon(list(rbind(c(-180,-90),c(180,-90),c(180,90),c(-180,90),c(-180,-90))))),
  crs=st_crs(4326))
# FIXME:
#if (sf_extSoftVersion()["proj.4"] >= "4.9.0") {
# p = st_sample(x, 1000)
# st_sample(p, 3)
#}
# hexagonal:
sfc = st_sfc(st_polygon(list(rbind(c(0,0), c(1,0), c(1,1), c(0,0))))))
plot(sfc)
h = st_sample(sfc, 100, type = "hexagonal")
h1 = st_sample(sfc, 100, type = "hexagonal")
plot(h, add = TRUE)
plot(h1, col = 'red', add = TRUE)
c(length(h), length(h1)) # approximate!
pt = st_multipoint(matrix(1:20,2))
```

```

ls = st_sfc(st_linestring(rbind(c(0,0),c(0,1))),
  st_linestring(rbind(c(0,0),c(.1,0))),
  st_linestring(rbind(c(0,1),c(.1,1))),
  st_linestring(rbind(c(2,2),c(2,2.00001))))
st_sample(ls, 80)
plot(st_sample(ls, 80))
# spatstat example:
if (require(spatstat)) {
  x <- sf::st_sfc(sf::st_polygon(list(rbind(c(0, 0), c(10, 0), c(10, 10), c(0, 0)))))
  # for spatstat::rThomas(), set type = "Thomas":
  pts <- st_sample(x, kappa = 1, mu = 10, scale = 0.1, type = "Thomas")
}

```

---

st\_shift\_longitude      *Shift or re-center geographical coordinates for a Pacific view*

---

### Description

All longitudes  $< 0$  are added to 360, to avoid for instance parts of Alaska being represented on the far left and right of a plot because they have values straddling 180 degrees. In general, using a projected coordinate reference system is to be preferred, but this method permits a geographical coordinate reference system to be used. This is the sf equivalent of [recenter](#) in the sp package and ST\_ShiftLongitude in PostGIS.

### Usage

```

st_shift_longitude(x)

## S3 method for class 'sfc'
st_shift_longitude(x, ...)

## S3 method for class 'sf'
st_shift_longitude(x, ...)

```

### Arguments

x	object of class sf or sfc
...	ignored

### Examples

```

## sfc
pt1 = st_point(c(-170, 50))
pt2 = st_point(c(170, 50))
(sfc = st_sfc(pt1, pt2))
sfc = st_set_crs(sfc, 4326)
st_shift_longitude(sfc)

## sf

```

```
d = st_as_sf(data.frame(id = 1:2, geometry = sfc))
st_shift_longitude(d)
```

---

st_transform	<i>Transform or convert coordinates of simple feature</i>
--------------	---

---

## Description

Transform or convert coordinates of simple feature

## Usage

```
st_transform(x, crs, ...)

## S3 method for class 'sfc'
st_transform(
  x,
  crs = st_crs(x),
  ...,
  aoi = numeric(0),
  pipeline = character(0),
  reverse = FALSE,
  partial = TRUE,
  check = FALSE
)

## S3 method for class 'sf'
st_transform(x, crs = st_crs(x), ...)

## S3 method for class 'sfg'
st_transform(x, crs = st_crs(x), ...)

sf_proj_info(type = "proj", path)

st_wrap_dateline(x, options, quiet)

## S3 method for class 'sfc'
st_wrap_dateline(x, options = "WRAPDATELINE=YES", quiet = TRUE)

## S3 method for class 'sf'
st_wrap_dateline(x, options = "WRAPDATELINE=YES", quiet = TRUE)

## S3 method for class 'sfg'
st_wrap_dateline(x, options = "WRAPDATELINE=YES", quiet = TRUE)
```

**Arguments**

x	object of class sf, sfc or sfg
crs	coordinate reference system: integer with the EPSG code, or character with proj4string
...	ignored
aoi	area of interest, in degrees: WestLongitude, SouthLatitude, EastLongitude, NorthLatitude
pipeline	character; proj4 or WKT coordinate operation, to override the default operation
reverse	boolean; if TRUE, the inverse operation of the pipeline is applied
partial	logical; allow for partial projection, if not all points of a geometry can be projected (corresponds to setting environment variable OGR_ENABLE_PARTIAL_REPROJECTION to TRUE)
check	logical; perform a sanity check on resulting polygons?
type	character; one of have_datum_files, proj, ellps, datum, units or prime_meridians; see Details.
path	character; PROJ search path to be set
options	character; should have "WRAPDATELINE=YES" to function; another parameter that is used is "DATELINEOFFSET=10" (where 10 is the default value)
quiet	logical; print options after they have been parsed?

**Details**

Transforms coordinates of object to new projection. Features that cannot be transformed are returned as empty geometries.

Projecting to projections not supported by GDAL may be done by [st\\_transform\\_proj](#), part of package lwgeom.

The st\_transform method for sfg objects assumes that the CRS of the object is available as an attribute of that name.

sf\_proj\_info lists the available projections, ellipses, datums, units, or data search path of the PROJ library when type is equal to proj, ellps, datum, units or path; when type equals have\_datum\_files a boolean is returned indicating whether datum files are installed and accessible (checking for conus).

for PROJ >= 6, sf\_proj\_info does not provide option type = "datums". PROJ < 6 does not provide the option type = "prime\_meridians".

for PROJ >= 7.1.0, the "units" query of sf\_proj\_info returns the to\_meter variable as numeric, previous versions return a character vector containing a numeric expression.

For a discussion of using options, see <https://github.com/r-spatial/sf/issues/280> and <https://github.com/r-spatial/sf/issues/541>



**Examples**

```

p1 = st_point(c(7,52))
p2 = st_point(c(-30,20))
sfc = st_sfc(p1, p2, crs = 4326)
sfc
st_transform(sfc, 3857)
st_transform(st_sf(a=2:1, geom=sfc), "+init=epsg:3857")
try(st_transform(sfc, 3857, aoi = c(-280,-90,180,90)))
if (sf_extSoftVersion()["GDAL"] >= "3.0.0") {
  st_transform(sfc, pipeline =
    "+proj=pipeline +step +proj=axisswap +order=2,1") # reverse axes
  st_transform(sfc, pipeline =
    "+proj=pipeline +step +proj=axisswap +order=2,1", reverse = TRUE) # also reverse axes
}
nc = st_read(system.file("shape/nc.shp", package="sf"))
st_area(nc[1,]) # area from long/lat
st_area(st_transform(nc[1,], 32119)) # NC state plane, m
st_area(st_transform(nc[1,], 2264)) # NC state plane, US foot
library(units)
set_units(st_area(st_transform(nc[1,], 2264)), m^2)
st_transform(structure(p1, proj4string = "+init=epsg:4326"), "+init=epsg:3857")
sf_proj_info("datum")
st_wrap_dateline(st_sfc(st_linestring(rbind(c(-179,0),c(179,0)))), crs = 4326))
library(maps)
wrld <- st_as_sf(maps::map("world", fill = TRUE, plot = FALSE))
wrld_wrap <- st_wrap_dateline(wrld, options = c("WRAPDATELINE=YES", "DATELINEOFFSET=180"),
  quiet = TRUE)
wrld_moll <- st_transform(wrld_wrap, "+proj=moll")
plot(st_geometry(wrld_moll), col = "transparent")

```

---

**st\_viewport***Create viewport from sf, sfc or sfg object*

---

**Description**

Create viewport from sf, sfc or sfg object

**Usage**

```
st_viewport(x, ..., bbox = st_bbox(x), asp)
```

**Arguments**

x	object of class sf, sfc or sfg object
...	parameters passed on to <a href="#">viewport</a>
bbox	the bounding box used for aspect ratio
asp	numeric; target aspect ratio (y/x), see Details

**Details**

parameters width, height, xscale and yscale are set such that aspect ratio is honoured and plot size is maximized in the current viewport; others can be passed as . . .

If asp is missing, it is taken as 1, except when isTRUE(st\_is\_longlat(x)), in which case it is set to  $1.0 / \cos(y)$ , with y the middle of the latitude bounding box.

**Value**

The output of the call to [viewport](#)

**Examples**

```
library(grid)
nc = st_read(system.file("shape/nc.shp", package="sf"))
grid.newpage()
pushViewport(viewport(width = 0.8, height = 0.8))
pushViewport(st_viewport(nc))
invisible(lapply(st_geometry(nc), function(x) grid.draw(st_as_grob(x, gp = gpar(fill = 'red')))))
```

---

st\_write

---

*Write simple features object to file or database*


---

**Description**

Write simple features object to file or database

**Usage**

```
st_write(obj, dsn, layer, ...)

## S3 method for class 'sfc'
st_write(obj, dsn, layer, ...)

## S3 method for class 'sf'
st_write(
  obj,
  dsn,
  layer = NULL,
  ...,
  driver = guess_driver_can_write(dsn),
  dataset_options = NULL,
  layer_options = NULL,
  quiet = FALSE,
  factorsAsCharacter = TRUE,
  append = NA,
  delete_dsn = FALSE,
  delete_layer = !is.na(append) && !append,
```

```

    fid_column_name = NULL
  )

## S3 method for class 'data.frame'
st_write(obj, dsn, layer = NULL, ...)

write_sf(..., quiet = TRUE, append = FALSE, delete_layer = TRUE)

## S4 method for signature 'PostgreSQLConnection,character,sf'
dbWriteTable(
  conn,
  name,
  value,
  ...,
  row.names = FALSE,
  overwrite = FALSE,
  append = FALSE,
  field.types = NULL,
  factorsAsCharacter = TRUE,
  binary = TRUE
)

## S4 method for signature 'DBIObject,character,sf'
dbWriteTable(
  conn,
  name,
  value,
  ...,
  row.names = FALSE,
  overwrite = FALSE,
  append = FALSE,
  field.types = NULL,
  factorsAsCharacter = TRUE,
  binary = TRUE
)

```

### Arguments

obj	object of class sf or sfc
dsn	data source name (interpretation varies by driver - for some drivers, dsn is a file name, but may also be a folder or contain a database name) or a Database Connection (currently official support is for RPostgreSQL connections)
layer	layer name (varies by driver, may be a file name without extension); if layer is missing, the <a href="#">basename</a> of dsn is taken.
...	other arguments passed to <a href="#">dbWriteTable</a> when dsn is a Database Connection
driver	character; name of driver to be used; if missing and dsn is not a Database Connection, a driver name is guessed from dsn; <a href="#">st_drivers()</a> returns the drivers

that are available with their properties; links to full driver documentation are found at [https://gdal.org/ogr\\_formats.html](https://gdal.org/ogr_formats.html).

dataset_options	character; driver dependent dataset creation options; multiple options supported.
layer_options	character; driver dependent layer creation options; multiple options supported.
quiet	logical; suppress info on name, driver, size and spatial reference
factorsAsCharacter	logical; convert factor objects into character strings (default), else into numbers by <code>as.numeric</code> .
append	Append rows to existing table; default FALSE.
delete_dsn	logical; delete data source dsn before attempting to write?
delete_layer	logical; delete layer layer before attempting to write?
fid_column_name	character, name of column with feature IDs; if specified, this column is no longer written as feature attribute.
conn	DBIObject
name	character vector of names (table names, fields, keywords).
value	a data.frame.
row.names	Add a row.name column, or a vector of length <code>nrow(obj)</code> containing row.names; default FALSE.
overwrite	Will try to drop table before writing; default FALSE.
field.types	default NULL. Allows to override type conversion from R to PostgreSQL. See <code>dbDataType()</code> for details.
binary	Send geometries serialized as Well-Known Binary (WKB); if FALSE, uses Well-Known Text (WKT). Defaults to TRUE (WKB).

### Details

Columns (variables) of a class not supported are dropped with a warning.

When updating an existing layer, records are appended to it if the updating object has the right variable names and types. If names don't match an error is raised. If types don't match, behaviour is undefined: GDAL may raise warnings or errors or fail silently.

When deleting layers or data sources is not successful, no error is emitted. `delete_dsn` and `delete_layer` should be handled with care; the former may erase complete directories or databases.

### Value

`obj`, invisibly; in case `obj` is of class `sfc`, it is returned as an `sf` object.

### See Also

[st\\_drivers](#)

## Examples

```
nc = st_read(system.file("shape/nc.shp", package="sf"))
st_write(nc, paste0(tempdir(), "/", "nc.shp"))
st_write(nc, paste0(tempdir(), "/", "nc.shp"), delete_layer = TRUE) # overwrites
data(meuse, package = "sp") # loads data.frame from sp
meuse_sf = st_as_sf(meuse, coords = c("x", "y"), crs = 28992)
# writes X and Y as columns:
st_write(meuse_sf, paste0(tempdir(), "/", "meuse.csv"), layer_options = "GEOMETRY=AS_XY")
st_write(meuse_sf, paste0(tempdir(), "/", "meuse.csv"), layer_options = "GEOMETRY=AS_WKT",
  delete_dsn=TRUE) # overwrites
## Not run:
library(sp)
example(meuse, ask = FALSE, echo = FALSE)
try(st_write(st_as_sf(meuse), "PG:dbname=postgis", "meuse_sf",
  layer_options = c("OVERWRITE=yes", "LAUNDER=true")))
demo(nc, ask = FALSE)
try(st_write(nc, "PG:dbname=postgis", "sids", layer_options = "OVERWRITE=true"))

## End(Not run)
```

---

st\_zm

*Drop or add Z and/or M dimensions from feature geometries*


---

## Description

Drop Z and/or M dimensions from feature geometries, resetting classes appropriately

## Usage

```
st_zm(x, ..., drop = TRUE, what = "ZM")
```

## Arguments

x	object of class sfg, sfc or sf
...	ignored
drop	logical; drop, or (FALSE) add?
what	character which dimensions to drop or add

## Details

Only combinations drop=TRUE, what = "ZM", and drop=FALSE, what="Z" are supported so far. In case add=TRUE, x should have XY geometry, and zero values are added for Z.

**Examples**

```

st_zm(st_linestring(matrix(1:32,8)))
x = st_sfc(st_linestring(matrix(1:32,8)), st_linestring(matrix(1:8,2)))
st_zm(x)
a = st_sf(a = 1:2, geom=x)
st_zm(a)

```

---

st\_z\_range

*Return 'z' range of a simple feature or simple feature set*


---

**Description**

Return 'z' range of a simple feature or simple feature set

**Usage**

```

## S3 method for class 'z_range'
is.na(x)

st_z_range(obj, ...)

## S3 method for class 'POINT'
st_z_range(obj, ...)

## S3 method for class 'MULTIPOINT'
st_z_range(obj, ...)

## S3 method for class 'LINESTRING'
st_z_range(obj, ...)

## S3 method for class 'POLYGON'
st_z_range(obj, ...)

## S3 method for class 'MULTILINESTRING'
st_z_range(obj, ...)

## S3 method for class 'MULTIPOLYGON'
st_z_range(obj, ...)

## S3 method for class 'GEOMETRYCOLLECTION'
st_z_range(obj, ...)

## S3 method for class 'MULTISURFACE'
st_z_range(obj, ...)

## S3 method for class 'MULTICURVE'
st_z_range(obj, ...)

```

```
## S3 method for class 'CURVEPOLYGON'  
st_z_range(obj, ...)  
  
## S3 method for class 'COMPOUNDCURVE'  
st_z_range(obj, ...)  
  
## S3 method for class 'POLYHEDRALSURFACE'  
st_z_range(obj, ...)  
  
## S3 method for class 'TIN'  
st_z_range(obj, ...)  
  
## S3 method for class 'TRIANGLE'  
st_z_range(obj, ...)  
  
## S3 method for class 'CIRCULARSTRING'  
st_z_range(obj, ...)  
  
## S3 method for class 'sfc'  
st_z_range(obj, ...)  
  
## S3 method for class 'sf'  
st_z_range(obj, ...)  
  
## S3 method for class 'numeric'  
st_z_range(obj, ..., crs = NA_crs_)  
  
NA_z_range_
```

## Arguments

x	object of class z_range
obj	object to compute the z range from
...	ignored
crs	object of class crs, or argument to <a href="#">st_crs</a> , specifying the CRS of this bounding box.

## Format

An object of class z\_range of length 2.

## Details

NA\_z\_range\_ represents the missing value for a z\_range object

**Value**

a numeric vector of length two, with zmin and zmax values; if obj is of class sf or sfc the object returned has a class z\_range

**Examples**

```
a = st_sf(a = 1:2, geom = st_sfc(st_point(0:2), st_point(1:3)), crs = 4326)
st_z_range(a)
st_z_range(c(zmin = 16.1, zmax = 16.6), crs = st_crs(4326))
```

---

summary.sfc	<i>Summarize simple feature column</i>
-------------	--

---

**Description**

Summarize simple feature column

**Usage**

```
## S3 method for class 'sfc'
summary(object, ..., maxsum = 7L, maxp4s = 10L)
```

**Arguments**

object	object of class sfc
...	ignored
maxsum	maximum number of classes to summarize the simple feature column to
maxp4s	maximum number of characters to print from the PROJ string

---

tibble	<i>Summarize simple feature type for tibble</i>
--------	---

---

**Description**

Summarize simple feature type for tibble

Summarize simple feature item for tibble

**Usage**

```
type_sum.sfc(x, ...)
```

```
obj_sum.sfc(x)
```

```
pillar_shaft.sfc(x, ...)
```



**Arguments**

x                    object of class sfc  
...                   ignored

**Details**

see [type\\_sum](#)

---

tidyverse

*Tidyverse methods for sf objects (remove .sf suffix!)*

---

**Description**

Tidyverse methods for sf objects. Geometries are sticky, use [as.data.frame](#) to let dplyr's own methods drop them. Use these methods without the .sf suffix and after loading the tidyverse package with the generic (or after loading package tidyverse).

**Usage**

```
filter.sf(.data, ..., .dots)

arrange.sf(.data, ..., .dots)

group_by.sf(.data, ..., add = FALSE)

ungroup.sf(x, ...)

mutate.sf(.data, ..., .dots)

transmute.sf(.data, ..., .dots)

select.sf(.data, ...)

rename.sf(.data, ...)

slice.sf(.data, ..., .dots)

summarise.sf(.data, ..., .dots, do_union = TRUE)

distinct.sf(.data, ..., .keep_all = FALSE)

gather.sf(
  data,
  key,
  value,
  ...,
```

```
na.rm = FALSE,
convert = FALSE,
factor_key = FALSE
)

spread.sf(
  data,
  key,
  value,
  fill = NA,
  convert = FALSE,
  drop = TRUE,
  sep = NULL
)

sample_n.sf(tbl, size, replace = FALSE, weight = NULL, .env = parent.frame())

sample_frac.sf(
  tbl,
  size = 1,
  replace = FALSE,
  weight = NULL,
  .env = parent.frame()
)

nest.sf(.data, ...)

separate.sf(
  data,
  col,
  into,
  sep = "[^[:alnum:]]+",
  remove = TRUE,
  convert = FALSE,
  extra = "warn",
  fill = "warn",
  ...
)

separate_rows.sf(data, ..., sep = "[^[:alnum:]]+", convert = FALSE)

unite.sf(data, col, ..., sep = "_", remove = TRUE)

unnest.sf(data, ..., .preserve = NULL)

inner_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)

left_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)
```

```
right_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)
```

```
full_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)
```

```
semi_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)
```

```
anti_join.sf(x, y, by = NULL, copy = FALSE, suffix = c(".x", ".y"), ...)
```

## Arguments

<code>.data</code>	data object of class <a href="#">sf</a>
<code>...</code>	other arguments
<code>.dots</code>	see corresponding function in package <a href="#">dplyr</a>
<code>add</code>	see corresponding function in <a href="#">dplyr</a>
<code>x</code>	A pair of data frames, data frame extensions (e.g. a tibble), or lazy data frames (e.g. from <a href="#">dbplyr</a> or <a href="#">dtplyr</a> ). See <i>Methods</i> , below, for more details.
<code>do_union</code>	logical; in case summary does not create a geometry column, should geometries be created by unioning using <a href="#">st_union</a> , or simply by combining using <a href="#">st_combine</a> ? Using <a href="#">st_union</a> resolves internal boundaries, but in case of unioning points, this will likely change the order of the points; see <i>Details</i> .
<code>.keep_all</code>	see corresponding function in <a href="#">dplyr</a>
<code>data</code>	see original function docs
<code>key</code>	see original function docs
<code>value</code>	see original function docs
<code>na.rm</code>	see original function docs
<code>convert</code>	see <a href="#">separate_rows</a>
<code>factor_key</code>	see original function docs
<code>fill</code>	see original function docs
<code>drop</code>	see original function docs
<code>sep</code>	see <a href="#">separate_rows</a>
<code>tbl</code>	see original function docs
<code>size</code>	see original function docs
<code>replace</code>	see original function docs
<code>weight</code>	see original function docs
<code>.env</code>	see original function docs
<code>col</code>	see <a href="#">separate</a>
<code>into</code>	see <a href="#">separate</a>
<code>remove</code>	see <a href="#">separate</a>
<code>extra</code>	see <a href="#">separate</a>
<code>.preserve</code>	see <a href="#">unnest</a>

<code>y</code>	A pair of data frames, data frame extensions (e.g. a tibble), or lazy data frames (e.g. from <code>dbplyr</code> or <code>dtplyr</code> ). See <i>Methods</i> , below, for more details.
<code>by</code>	A character vector of variables to join by. If NULL, the default, <code>*_join()</code> will perform a natural join, using all variables in common across <code>x</code> and <code>y</code> . A message lists the variables so that you can check they're correct; suppress the message by supplying <code>by</code> explicitly. To join by different variables on <code>x</code> and <code>y</code> , use a named vector. For example, <code>by = c("a" = "b")</code> will match <code>x\$a</code> to <code>y\$b</code> . To join by multiple variables, use a vector with length > 1. For example, <code>by = c("a", "b")</code> will match <code>x\$a</code> to <code>y\$a</code> and <code>x\$b</code> to <code>y\$b</code> . Use a named vector to match different variables in <code>x</code> and <code>y</code> . For example, <code>by = c("a" = "b", "c" = "d")</code> will match <code>x\$a</code> to <code>y\$b</code> and <code>x\$c</code> to <code>y\$d</code> . To perform a cross-join, generating all combinations of <code>x</code> and <code>y</code> , use <code>by = character()</code> .
<code>copy</code>	If <code>x</code> and <code>y</code> are not from the same data source, and <code>copy</code> is TRUE, then <code>y</code> will be copied into the same <code>src</code> as <code>x</code> . This allows you to join tables across <code>srcs</code> , but it is a potentially expensive operation so you must opt into it.
<code>suffix</code>	If there are non-joined duplicate variables in <code>x</code> and <code>y</code> , these suffixes will be added to the output to disambiguate them. Should be a character vector of length 2.

## Details

`select` keeps the geometry regardless whether it is selected or not; to deselect it, first pipe through `as.data.frame` to let `dplyr`'s own `select` drop it.

In case one or more of the arguments (expressions) in the `summarise` call creates a geometry list-column, the first of these will be the (active) geometry of the returned object. If this is not the case, a geometry column is created, depending on the value of `do_union`.

In case `do_union` is FALSE, `summarise` will simply combine geometries using `c.sfg`. When polygons sharing a boundary are combined, this leads to geometries that are invalid; see for instance <https://github.com/r-spatial/sf/issues/681>.

`distinct` gives distinct records for which all attributes and geometries are distinct; `st_equals` is used to find out which geometries are distinct.

`nest` assumes that a simple feature geometry list-column was among the columns that were nested.

## Value

an object of class `sf`

## Examples

```
library(dplyr)
nc = st_read(system.file("shape/nc.shp", package="sf"))
nc %>% filter(AREA > .1) %>% plot()
# plot 10 smallest counties in grey:
st_geometry(nc) %>% plot()
nc %>% select(AREA) %>% arrange(AREA) %>% slice(1:10) %>% plot(add = TRUE, col = 'grey')
title("the ten counties with smallest area")
nc$area_c1 = cut(nc$AREA, c(0, .1, .12, .15, .25))
```

```

nc %>% group_by(area_c1) %>% class()
nc2 <- nc %>% mutate(area10 = AREA/10)
nc %>% transmute(AREA = AREA/10, geometry = geometry) %>% class()
nc %>% transmute(AREA = AREA/10) %>% class()
nc %>% select(SID74, SID79) %>% names()
nc %>% select(SID74, SID79, geometry) %>% names()
nc %>% select(SID74, SID79) %>% class()
nc %>% select(SID74, SID79, geometry) %>% class()
nc2 <- nc %>% rename(area = AREA)
nc %>% slice(1:2)
nc$area_c1 = cut(nc$AREA, c(0, .1, .12, .15, .25))
nc.g <- nc %>% group_by(area_c1)
nc.g %>% summarise(mean(AREA))
nc.g %>% summarise(mean(AREA)) %>% plot(col = grey(3:6 / 7))
nc %>% as.data.frame %>% summarise(mean(AREA))
nc[c(1:100, 1:10), ] %>% distinct() %>% nrow()
library(tidyr)
nc %>% select(SID74, SID79) %>% gather("VAR", "SID", -geometry) %>% summary()
library(tidyr)
nc$row = 1:100 # needed for spread to work
nc %>% select(SID74, SID79, geometry, row) %>%
gather("VAR", "SID", -geometry, -row) %>%
spread(VAR, SID) %>% head()
storms.sf = st_as_sf(storms, coords = c("long", "lat"), crs = 4326)
x <- storms.sf %>% group_by(name, year) %>% nest
trs = lapply(x$data, function(tr) st_cast(st_combine(tr), "LINESTRING")[[1]]) %>%
  st_sfc(crs = 4326)
trs.sf = st_sf(x[,1:2], trs)
plot(trs.sf["year"], axes = TRUE)

```

---

transform.sf

*transform method for sf objects*


---

## Description

Can be used to create or modify attribute variables; for transforming geometries see [st\\_transform](#), and all other functions starting with `st_`.

## Usage

```

## S3 method for class 'sf'
transform(`_data`, ...)

```

## Arguments

<code>_data</code>	object of class <code>sf</code>
<code>...</code>	Further arguments of the form <code>new_variable=expression</code>

**Examples**

```
a = data.frame(x1 = 1:3, x2 = 5:7)
st_geometry(a) = st_sfc(st_point(c(0,0)), st_point(c(1,1)), st_point(c(2,2)))
transform(a, x1_sq = x1^2)
transform(a, x1_x2 = x1*x2)
```

---

 valid

---

*Check validity or make an invalid geometry valid*


---

**Description**

Checks whether a geometry is valid, or makes an invalid geometry valid

**Usage**

```
st_is_valid(x, ...)

## S3 method for class 'sfc'
st_is_valid(x, ..., NA_on_exception = TRUE, reason = FALSE)

## S3 method for class 'sf'
st_is_valid(x, ...)

## S3 method for class 'sfg'
st_is_valid(x, ...)

st_make_valid(x)

## S3 method for class 'sfg'
st_make_valid(x)
```

**Arguments**

x	object of class sfg, sfg or sf
...	passed on to sfc method
NA_on_exception	logical; if TRUE, for polygons that would otherwise raise a GEOS error (exception, e.g. for a POLYGON having more than zero but less than 4 points, or a LINESTRING having one point) return an NA rather than raising an error, and suppress warning messages (e.g. about self-intersection); if FALSE, regular GEOS errors and warnings will be emitted.
reason	logical; if TRUE, return a character with, for each geometry, the reason for invalidity, NA on exception, or "Valid Geometry" otherwise.

**Details**

st\_make\_valid uses the lwgeom\_makevalid method also used by the PostGIS command ST\_makevalid if the GEOS version linked to is smaller than 3.8.0, and otherwise the version shipped in GEOS.

**Value**

`st_is_valid` returns a logical vector indicating for each geometries of `x` whether it is valid.  
Object of the same class as `x`

**Examples**

```
p1 = st_as_sfc("POLYGON((0 0, 0 10, 10 0, 10 10, 0 0))")
st_is_valid(p1)
st_is_valid(st_sfc(st_point(0:1), p1[[1]]), reason = TRUE)
library(sf)
x = st_sfc(st_polygon(list(rbind(c(0,0),c(0.5,0),c(0.5,0.5),c(0.5,0),c(1,0),c(1,1),c(0,1),c(0,0))))))
suppressWarnings(st_is_valid(x))
y = st_make_valid(x)
st_is_valid(y)
y %>% st_cast()
```

vctrs

*vctrs methods for sf objects***Description**

vctrs methods for sf objects

**Usage**

```
vec_ptype2.sfc(x, y, ...)
```

## Default S3 method:  
vec\_ptype2.sfc(x, y, ..., x\_arg = "x", y\_arg = "y")

## S3 method for class 'sfc'  
vec\_ptype2.sfc(x, y, ...)

```
vec_cast.sfc(x, to, ...)
```

## S3 method for class 'sfc'  
vec\_cast.sfc(x, to, ...)

## Default S3 method:  
vec\_cast.sfc(x, to, ...)

**Arguments**

<code>x</code>	Vector types.
<code>y</code>	Vector types.
<code>...</code>	These dots are for future extensions and must be empty.
<code>x_arg, y_arg</code>	Argument names for <code>x</code> and <code>y</code> .
<code>to</code>	Type to cast to. If NULL, <code>x</code> will be returned as is.

# Index

- \* **datasets**
  - db\_drivers, 8
  - extension\_map, 9
  - prefix\_map, 36
  - st\_agr, 48
  - st\_bbox, 57
  - st\_crs, 66
  - st\_m\_range, 80
  - st\_z\_range, 102
- \* **data**
  - nc, 28
  - .degAxis (stars), 47
  - .get\_layout (stars), 47
  - .image\_scale (stars), 47
  - .image\_scale\_factor (stars), 47
  - .stop\_geos (internal), 26
  - [.data.frame, 39
  - [.sf (sf), 38
  - \$.crs (st\_crs), 66
  
  - aggregate, 4, 5, 60, 86
  - aggregate (aggregate.sf), 4
  - aggregate.sf, 4
  - anti\_join.sf (tidyverse), 105
  - arrange.sf (tidyverse), 105
  - as, 5
  - as.data.frame, 105
  - as.matrix.sfg (st), 44
  - as.matrix.sgbp (sgbp), 43
  - as\_Spatial (as), 5
  - as\_Spatial(), 5
  
  - basename, 99
  - bind, 6
  - bind\_cols, 7
  - bpy.colors, 35
  
  - c, 18
  - c.sfg, 5, 18, 108
  - c.sfg (st), 44
  
  - cbind, 7
  - cbind.sf (bind), 6
  - classIntervals, 33
  - coerce, crs, CRS-method (as), 5
  - coerce, sf, Spatial-method (as), 5
  - coerce, sfc, Spatial-method (as), 5
  - coerce, Spatial, sf-method (as), 5
  - coerce, Spatial, sfc-method (as), 5
  
  - data.frame, 7
  - db\_drivers, 8
  - dbDataType, DBIObject, sf-method  
(dbDataType, PostgreSQLConnection, sf-method),  
8
  - dbDataType, PostgreSQLConnection, sf-method,  
8
  - dbWriteTable, 99
  - dbWriteTable, DBIObject, character, sf-method  
(st\_write), 98
  - dbWriteTable, PostgreSQLConnection, character, sf-method  
(st\_write), 98
  - dim.sgbp (sgbp), 43
  - distinct.sf (tidyverse), 105
  - dotsMethods, 7
  
  - extension\_map, 9
  
  - filter.sf (tidyverse), 105
  - format, 58
  - format.bbox (st\_bbox), 57
  - format.crs (st\_crs), 66
  - format.sfg (st), 44
  - full\_join.sf (tidyverse), 105
  
  - gather.sf (tidyverse), 105
  - gdal, 9
  - gdal\_crs (gdal), 9
  - gdal\_inv\_geotransform (gdal), 9
  - gdal\_metadata (gdal), 9
  - gdal\_polygonize (gdal), 9



- gdal\_rasterize (gdal), 9
- gdal\_read (gdal), 9
- gdal\_subdatasets (gdal), 9
- gdal\_utils, 12
- gdal\_write (gdal), 9
- geos\_binary\_ops, 13
- geos\_binary\_pred, 16
- geos\_combine, 18
- geos\_measures, 19
- geos\_query, 21
- geos\_unary, 22
- get\_key\_pos (plot), 30
- getwd, 89
- group\_by.sf (tidyverse), 105
- gUnaryUnion, 19
- gUnion, 19
  
- head.sfg (st), 44
  
- Id, 87
- inner\_join.sf (tidyverse), 105
- internal, 26
- intersect, 15
- is.na.bbox (st\_bbox), 57
- is.na.crs (st\_crs), 66
- is.na.m\_range (st\_m\_range), 80
- is.na.z\_range (st\_z\_range), 102
- is\_driver\_available, 26
- is\_driver\_can, 27
- is\_geometry\_column, 27
  
- left\_join, 76
- left\_join.sf (tidyverse), 105
  
- map, 52
- merge, 76
- merge.sf, 28
- mutate.sf (tidyverse), 105
  
- NA\_agr\_ (st\_agr), 48
- NA\_bbox\_ (st\_bbox), 57
- NA\_crs\_ (st\_crs), 66
- NA\_m\_range\_ (st\_m\_range), 80
- NA\_z\_range\_ (st\_z\_range), 102
- nc, 28
- nest.sf (tidyverse), 105
  
- obj\_sum.sfc (tibble), 104
- Ops, 29
  
- par, 34, 35
- pillar\_shaft.sfc (tibble), 104
- plot, 30, 33
- plot.window, 34
- plot\_sf, 33
- plot\_sf (plot), 30
- polypath, 34
- prefix\_map, 36
- print.sf (sf), 38
- print.sfg (st), 44
- print.sgbp (sgbp), 43
  
- rainbow, 33
- rawToHex, 36
- rbind, 7
- rbind.sf (bind), 6
- read\_sf (st\_read), 86
- recenter, 94
- rename.sf (tidyverse), 105
- right\_join.sf (tidyverse), 105
  
- s2, 36
- s2\_options, 14, 17
- sample, 92
- sample\_frac.sf (tidyverse), 105
- sample\_n.sf (tidyverse), 105
- select.sf (tidyverse), 105
- semi\_join.sf (tidyverse), 105
- separate, 107
- separate.sf (tidyverse), 105
- separate\_rows, 107
- separate\_rows.sf (tidyverse), 105
- set\_units, 20
- setdiff, 15
- sf, 4, 38, 67, 70, 71, 74, 79, 89, 107, 108
- sf-defunct, 40
- sf.colors (plot), 30
- sf\_add\_proj\_units (sf\_project), 42
- sf\_extSoftVersion, 42
- sf\_proj\_info (st\_transform), 95
- sf\_proj\_search\_paths, 43
- sf\_project, 42
- sf\_use\_s2 (s2), 36
- sfc, 41, 52, 67, 70, 71, 74, 79, 84
- sfc\_GEOMETRYCOLLECTION (sfc), 41
- sfc\_LINestring (sfc), 41
- sfc\_MULTILINESTRING (sfc), 41
- sfc\_MULTIPPOINT (sfc), 41
- sfc\_MULTIPOLYGON (sfc), 41

- sfc\_POINT (sfc), 41
- sfc\_POLYGON (sfc), 41
- sgbp, 17, 43
- slice.sf (tidyverse), 105
- spread.sf (tidyverse), 105
- st, 44
- st\_agr, 48
- st\_agr<- (st\_agr), 48
- st\_area (geos\_measures), 19
- st\_as\_binary, 39, 41, 49, 55, 86
- st\_as\_grob, 50
- st\_as\_s2 (s2), 36
- st\_as\_sf, 40, 51, 88
- st\_as\_sf.s2\_geography (s2), 36
- st\_as\_sfc, 38, 39, 53, 59
- st\_as\_sfc.s2\_geography (s2), 36
- st\_as\_sfc.wk\_wkb (s2), 36
- st\_as\_text, 56
- st\_axis\_order (st\_crs), 66
- st\_bbox, 57, 65
- st\_bind\_cols (bind), 6
- st\_boundary (geos\_unary), 22
- st\_buffer (geos\_unary), 22
- st\_cast, 21, 59, 63
- st\_cast(), 6
- st\_cast\_sfc\_default, 62
- st\_centroid (geos\_unary), 22
- st\_collection\_extract, 62
- st\_combine, 107
- st\_combine (geos\_combine), 18
- st\_contains, 76
- st\_contains (geos\_binary\_pred), 16
- st\_contains\_properly, 76
- st\_contains\_properly (geos\_binary\_pred), 16
- st\_convex\_hull (geos\_unary), 22
- st\_coordinates, 64
- st\_covered\_by, 76
- st\_covered\_by (geos\_binary\_pred), 16
- st\_covers, 76
- st\_covers (geos\_binary\_pred), 16
- st\_crop, 65
- st\_crosses, 76
- st\_crosses (geos\_binary\_pred), 16
- st\_crs, 11, 39, 58, 66, 74, 82, 103
- st\_crs(), 55
- st\_crs<- (st\_crs), 66
- st\_difference, 19
- st\_difference (geos\_binary\_ops), 13
- st\_dimension, 21
- st\_dimension (geos\_query), 21
- st\_disjoint, 76
- st\_disjoint (geos\_binary\_pred), 16
- st\_distance (geos\_measures), 19
- st\_drivers, 27, 68, 89, 100
- st\_drop\_geometry (st\_geometry), 69
- st\_equals, 76, 108
- st\_equals (geos\_binary\_pred), 16
- st\_equals\_exact, 76
- st\_equals\_exact (geos\_binary\_pred), 16
- st\_filter (st\_join), 75
- st\_geod\_area, 20
- st\_geod\_segmentize, 24
- st\_geometry, 69
- st\_geometry<- (st\_geometry), 69
- st\_geometry\_type, 71
- st\_geometrycollection (st), 44
- st\_graticule, 34, 71
- st\_interpolate\_aw, 73
- st\_intersection, 18, 19, 91
- st\_intersection (geos\_binary\_ops), 13
- st\_intersects, 15, 50, 76
- st\_intersects (geos\_binary\_pred), 16
- st\_is, 74
- st\_is\_empty (geos\_query), 21
- st\_is\_longlat, 74
- st\_is\_simple (geos\_query), 21
- st\_is\_valid (valid), 110
- st\_is\_within\_distance, 77
- st\_is\_within\_distance (geos\_binary\_pred), 16
- st\_jitter, 75
- st\_join, 4, 75
- st\_layers, 78, 89
- st\_length (geos\_measures), 19
- st\_line\_merge (geos\_unary), 22
- st\_line\_sample, 78
- st\_linestring (st), 44
- st\_m\_range, 80
- st\_make\_grid, 79
- st\_make\_valid (valid), 110
- st\_multilinestring (st), 44
- st\_multipoint (st), 44
- st\_multipolygon (st), 44
- st\_nearest\_feature, 77, 82, 84
- st\_nearest\_points, 82, 83

st\_node (geos\_unary), 22  
st\_normalize, 85  
st\_overlaps, 77  
st\_overlaps (geos\_binary\_pred), 16  
st\_point, 52  
st\_point (st), 44  
st\_point\_on\_surface (geos\_unary), 22  
st\_polygon (st), 44  
st\_polygonize (geos\_unary), 22  
st\_precision, 85  
st\_precision<- (st\_precision), 85  
st\_read, 39, 41, 86  
st\_read\_db (sf-defunct), 40  
st\_read\_db, (sf-defunct), 40  
st\_relate, 17, 76, 90  
st\_reverse (geos\_unary), 22  
st\_sample, 91  
st\_segmentize (geos\_unary), 22  
st\_set\_agr (st\_agr), 48  
st\_set\_crs (st\_crs), 66  
st\_set\_geometry (st\_geometry), 69  
st\_set\_precision (st\_precision), 85  
st\_sf, 7, 52  
st\_sf (sf), 38  
st\_sfc (sfc), 41  
st\_shift\_longitude, 94  
st\_simplify (geos\_unary), 22  
st\_snap (geos\_binary\_ops), 13  
st\_sym\_difference, 19  
st\_sym\_difference (geos\_binary\_ops), 13  
st\_touches, 77  
st\_touches (geos\_binary\_pred), 16  
st\_transform, 95, 109  
st\_transform\_proj, 96  
st\_triangulate (geos\_unary), 22  
st\_union, 4, 15, 107  
st\_union (geos\_combine), 18  
st\_viewport, 97  
st\_voronoi (geos\_unary), 22  
st\_within, 77  
st\_within (geos\_binary\_pred), 16  
st\_wrap\_dateline (st\_transform), 95  
st\_write, 41, 86, 98  
st\_write\_db (sf-defunct), 40  
st\_z\_range, 102  
st\_zm, 101  
st\_zm(), 6  
stars, 47  
summarise, 60, 86  
summarise (tidyverse), 105  
summary.sfc, 104  
t.sgbp (sgbp), 43  
tibble, 104  
tidyverse, 105  
transform.sf, 109  
transmute.sf (tidyverse), 105  
type\_sum, 105  
type\_sum.sfc (tibble), 104  
ungroup.sf (tidyverse), 105  
unite.sf (tidyverse), 105  
unnest, 107  
unnest.sf (tidyverse), 105  
valid, 110  
vctrs, 111  
vec\_cast.sfc (vctrs), 111  
vec\_ptype2.sfc (vctrs), 111  
viewport, 97, 98  
write\_sf, 86  
write\_sf (st\_write), 98