

# Package ‘LUCIDus’

November 8, 2022

**Type** Package

**Title** Latent Unknown Clustering Integrating Multi-View Data

**Version** 2.2.1

**Description**

An implementation of the LUCID model (Peng (2019) <[doi:10.1093/bioinformatics/btz667](https://doi.org/10.1093/bioinformatics/btz667)>). LUCID conducts integrated clustering using exposures, omics data (and outcome as an option). An EM algorithm is implemented to estimate MLE of the LUCID model. LUCIDus features integrated variable selection, incorporation of missing omics data, bootstrap inference, prediction and visualization of the model.

**Depends** R (>= 3.6.0)

**License** GPL-3

**Encoding** UTF-8

**RoxygenNote** 7.2.1

**LazyData** true

**URL** <https://github.com/USCbiostats/LUCIDus>

**BugReports** <https://github.com/USCbiostats/LUCIDus/issues>

**Suggests** knitr, testthat (>= 3.0.0), rmarkdown

**VignetteBuilder** knitr

**Config/testthat/edition** 3

**Imports** boot, glasso, glmnet, jsonlite, mclust, mix, networkD3, nnet, progress

**NeedsCompilation** no

**Author** Yinqi Zhao [aut, cre] (<<https://orcid.org/0000-0003-2413-732X>>),  
David Conti [ths] (<<https://orcid.org/0000-0002-2941-7833>>),  
Jesse Goodrich [ctb] (<<https://orcid.org/0000-0001-6615-0472>>),  
Cheng Peng [ctb]

**Maintainer** Yinqi Zhao <yinqiz@usc.edu>

**Repository** CRAN

**Date/Publication** 2022-11-08 10:10:02 UTC

## R topics documented:

boot.lucid . . . . .	2
boot_lucid . . . . .	3
check_na . . . . .	4
est.lucid . . . . .	5
est_lucid . . . . .	7
fill_data . . . . .	10
gen_ci . . . . .	10
helix_data . . . . .	11
Istep_Z . . . . .	12
lucid . . . . .	12
plot_lucid . . . . .	14
predict_lucid . . . . .	15
print.lucid . . . . .	17
print.sumlucid . . . . .	17
sim_data . . . . .	18
summary_lucid . . . . .	18
tune_lucid . . . . .	19
<b>Index</b>	<b>22</b>

---

boot.lucid	<i>Deprecated function boot.lucid</i>
------------	---------------------------------------

---

### Description

This function deprecates. Please use boot\_lucid instead.

### Usage

```
boot.lucid(G, Z, Y, CoG = NULL, CoY = NULL, model, conf = 0.95, R = 100)
```

### Arguments

G	Exposures, a numeric vector, matrix, or data frame. Categorical variable should be transformed into dummy variables. If a matrix or data frame, rows represent observations and columns correspond to variables.
Z	Omics data, a numeric matrix or data frame. Rows correspond to observations and columns correspond to variables.
Y	Outcome, a numeric vector. Categorical variable is not allowed. Binary outcome should be coded as 0 and 1.
CoG	Optional, covariates to be adjusted for estimating the latent cluster. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.

CoY	Optional, covariates to be adjusted for estimating the association between latent cluster and the outcome. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
model	A LUCID model fitted by <code>est.lucid</code> .
conf	A numeric scalar between 0 and 1 to specify confidence level(s) of the required interval(s).
R	An integer to specify number of bootstrap replicates for LUCID model. If feasible, it is recommended to set $R \geq 1000$ .

boot\_lucid

*Inference of LUCID model based on bootstrap resampling***Description**

Generate R bootstrap replicates of LUCID parameters and derive confidence interval (CI) base on bootstrap. Bootstrap replicates are generated based on nonparameteric resampling, implemented by ordinary method of `codeboot::boot` function.

**Usage**

```
boot_lucid(G, Z, Y, CoG = NULL, CoY = NULL, model, conf = 0.95, R = 100)
```

**Arguments**

G	Exposures, a numeric vector, matrix, or data frame. Categorical variable should be transformed into dummy variables. If a matrix or data frame, rows represent observations and columns correspond to variables.
Z	Omics data, a numeric matrix or data frame. Rows correspond to observations and columns correspond to variables.
Y	Outcome, a numeric vector. Categorical variable is not allowed. Binary outcome should be coded as 0 and 1.
CoG	Optional, covariates to be adjusted for estimating the latent cluster. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
CoY	Optional, covariates to be adjusted for estimating the association between latent cluster and the outcome. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
model	A LUCID model fitted by <code>est.lucid</code> .
conf	A numeric scalar between 0 and 1 to specify confidence level(s) of the required interval(s).
R	An integer to specify number of bootstrap replicates for LUCID model. If feasible, it is recommended to set $R \geq 1000$ .



**Value**

1. index: indices for missing values in omics data 2. indicator\_na: missing pattern for each observation 3. impute\_flag: - flag to initialize imputation. Only happens when sporadic missing pattern is observed

---

est.lucid	<i>Deprecated function est.lucid</i>
-----------	--------------------------------------

---

**Description**

This function deprecates. Please use `est_lucid` instead.

**Usage**

```
est.lucid(
  G,
  Z,
  Y,
  CoG = NULL,
  CoY = NULL,
  K = 2,
  family = c("normal", "binary"),
  useY = TRUE,
  tol = 0.001,
  max_itr = 1000,
  max_tot_itr = 10000,
  Rho_G = 0,
  Rho_Z_Mu = 0,
  Rho_Z_Cov = 0,
  modelName = "VVV",
  seed = 123,
  init_impute = c("mclust", "lod"),
  init_par = c("mclust", "random"),
  verbose = FALSE
)
```

**Arguments**

G	Exposures, a numeric vector, matrix, or data frame. Categorical variable should be transformed into dummy variables. If a matrix or data frame, rows represent observations and columns correspond to variables.
Z	Omics data, a numeric matrix or data frame. Rows correspond to observations and columns correspond to variables.
Y	Outcome, a numeric vector. Categorical variable is not allowed. Binary outcome should be coded as 0 and 1.

CoG	Optional, covariates to be adjusted for estimating the latent cluster. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
CoY	Optional, covariates to be adjusted for estimating the association between latent cluster and the outcome. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
K	Number of latent clusters. An integer greater or equal to 2. User can use <code>lucid</code> to determine the optimal number of latent clusters.
family	Distribution of outcome. For continuous outcome, use "normal"; for binary outcome, use "binary". Default is "normal".
useY	Flag to include information of outcome when estimating the latent cluster. Default is TRUE.
tol	Tolerance for convergence of EM algorithm. Default is 1e-3.
max_itr	Max number of iterations for EM algorithm.
max_tot_itr	Max number of total iterations for <code>est_lucid</code> function. <code>est_lucid</code> may conduct EM algorithm for multiple times if the algorithm fails to converge.
Rho_G	A scalar. This parameter is the LASSO penalty to regularize exposures. If user wants to tune the penalty, use the wrapper function <code>lucid</code>
Rho_Z_Mu	A scalar. This parameter is the LASSO penalty to regularize cluster-specific means for omics data (Z). If user wants to tune the penalty, use the wrapper function <code>lucid</code>
Rho_Z_Cov	A scalar. This parameter is the graphical LASSO penalty to estimate sparse cluster-specific variance-covariance matrices for omics data (Z). If user wants to tune the penalty, use the wrapper function <code>lucid</code>
modelName	The variance-covariance structure for omics data. See <code>mclust::mclustModelNames</code> for details.
seed	An integer to initialize the EM algorithm or imputing missing values. Default is 123.
init_impute	Method to initialize the imputation of missing values in LUCID. "mclust" will use <code>mclust::imputeData</code> to implement EM Algorithm for Unrestricted General Location Model to impute the missing values in omics data; <code>lod</code> will initialize the imputation via replacing missing values by $LOD / \sqrt{2}$ . LOD is determined by the minimum of each variable in omics data.
init_par	Method to initialize the EM algorithm. "mclust" will use <code>mclust</code> model to initialize parameters; "random" initialize parameters from uniform distribution.
verbose	A flag indicates whether detailed information for each iteration of EM algorithm is printed in console. Default is FALSE.

---

`est_lucid`*Fit LUCID model to conduct integrated clustering*

---

## Description

The Latent Unknown Clustering with Integrated Data (LUCID) performs integrative clustering using multi-view data. LUCID model is estimated via EM algorithm for model-based clustering. It also features variable selection, integrated imputation, bootstrap inference and visualization via Sankey diagram.

## Usage

```
est_lucid(  
  G,  
  Z,  
  Y,  
  CoG = NULL,  
  CoY = NULL,  
  K = 2,  
  family = c("normal", "binary"),  
  useY = TRUE,  
  tol = 0.001,  
  max_itr = 1000,  
  max_tot_itr = 10000,  
  Rho_G = 0,  
  Rho_Z_Mu = 0,  
  Rho_Z_Cov = 0,  
  modelName = NULL,  
  seed = 123,  
  init_impute = c("mclust", "lod"),  
  init_par = c("mclust", "random"),  
  verbose = FALSE  
)
```

## Arguments

- |     |  |
|-----|--|
| G   | Exposures, a numeric vector, matrix, or data frame. Categorical variable should be transformed into dummy variables. If a matrix or data frame, rows represent observations and columns correspond to variables. |
| Z   | Omics data, a numeric matrix or data frame. Rows correspond to observations and columns correspond to variables.   |
| Y   | Outcome, a numeric vector. Categorical variable is not allowed. Binary outcome should be coded as 0 and 1.   |
| CoG | Optional, covariates to be adjusted for estimating the latent cluster. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.                                  |

CoY	Optional, covariates to be adjusted for estimating the association between latent cluster and the outcome. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
K	Number of latent clusters. An integer greater or equal to 2. User can use <code>lucid</code> to determine the optimal number of latent clusters.
family	Distribution of outcome. For continuous outcome, use "normal"; for binary outcome, use "binary". Default is "normal".
useY	Flag to include information of outcome when estimating the latent cluster. Default is TRUE.
tol	Tolerance for convergence of EM algorithm. Default is 1e-3.
max_itr	Max number of iterations for EM algorithm.
max_tot_itr	Max number of total iterations for <code>est_lucid</code> function. <code>est_lucid</code> may conduct EM algorithm for multiple times if the algorithm fails to converge.
Rho_G	A scalar. This parameter is the LASSO penalty to regularize exposures. If user wants to tune the penalty, use the wrapper function <code>lucid</code>
Rho_Z_Mu	A scalar. This parameter is the LASSO penalty to regularize cluster-specific means for omics data (Z). If user wants to tune the penalty, use the wrapper function <code>lucid</code>
Rho_Z_Cov	A scalar. This parameter is the graphical LASSO penalty to estimate sparse cluster-specific variance-covariance matrices for omics data (Z). If user wants to tune the penalty, use the wrapper function <code>lucid</code>
modelName	The variance-covariance structure for omics data. See <code>mclust::mclustModelNames</code> for details.
seed	An integer to initialize the EM algorithm or imputing missing values. Default is 123.
init_impute	Method to initialize the imputation of missing values in LUCID. "mclust" will use <code>mclust::imputeData</code> to implement EM Algorithm for Unrestricted General Location Model to impute the missing values in omics data; <code>lod</code> will initialize the imputation via relacing missing values by $LOD / \sqrt{2}$ . <code>LOD</code> is determined by the minimum of each variable in omics data.
init_par	Method to initialize the EM algorithm. "mclust" will use <code>mclust</code> model to initialize parameters; "random" initialize parameters from uniform distribution.
verbose	A flag indicates whether detailed information for each iteration of EM algorithm is printed in console. Default is FALSE.

### Value

A list which contains the several features of LUCID, including:

pars	Estimates of parameters of LUCID, including beta (effect of exposure), mu (cluster-specific mean for omics data), sigma (cluster-specific variance-covariance matrix for omics data) and gamma (effect estimate of association between latent cluster and outcome)
K	Number of latent cluster



modelName	Geometric model to estimate variance-covariance matrix for omics data
likelihood	The log likelihood of the LUCID model
post.p	Posterior inclusion probability (PIP) for assigning observation <i>i</i> to latent cluster <i>j</i>
Z	If missing values are observed, this is the complete dataset for omics data with missing values imputed by LUCID

## References

Cheng Peng, Jun Wang, Isaac Asante, Stan Louie, Ran Jin, Lida Chatzi, Graham Casey, Duncan C Thomas, David V Conti, A Latent Unknown Clustering Integrating Multi-Omics Data (LUCID) with Phenotypic Traits, *Bioinformatics*, btz667, <https://doi.org/10.1093/bioinformatics/btz667>.

## Examples

```
## Not run:
# use simulated data
G <- sim_data$G
Z <- sim_data$Z
Y_normal <- sim_data$Y_normal
Y_binary <- sim_data$Y_binary
cov <- sim_data$Covariate

# fit LUCID model with continuous outcome
fit1 <- est_lucid(G = G, Z = Z, Y = Y_normal, family = "normal", K = 2,
seed = 1008)

# fit LUCID model with block-wise missing pattern in omics data
Z_miss_1 <- Z
Z_miss_1[sample(1:nrow(Z), 0.3 * nrow(Z)), ] <- NA
fit2 <- est_lucid(G = G, Z = Z_miss_1, Y = Y_normal, family = "normal", K = 2)

# fit LUCID model with sporadic missing pattern in omics data
Z_miss_2 <- Z
index <- arrayInd(sample(length(Z_miss_2), 0.3 * length(Z_miss_2)), dim(Z_miss_2))
Z_miss_2[index] <- NA
# initialize imputation by imputing
fit3 <- est_lucid(G = G, Z = Z_miss_2, Y = Y_normal, family = "normal",
K = 2, seed = 1008, init_impute = "lod")
LOD
# initialize imputation by mclust
fit4 <- est_lucid(G = G, Z = Z_miss_2, Y = Y, family = "normal", K = 2,
seed = 123, init_impute = "mclust")

# fit LUCID model with binary outcome
fit5 <- est_lucid(G = G, Z = Z, Y = Y_binary, family = "binary", K = 2,
seed = 1008)

# fit LUCID model with covariates
fit6 <- est_lucid(G = G, Z = Z, Y = Y_binary, CoY = cov, family = "binary",
K = 2, seed = 1008)
```

```

# use LUCID model to conduct integrated variable selection
# select exposure
fit6 <- est_lucid(G = G, Z = Z, Y = Y_normal, CoY = NULL, family = "normal",
K = 2, seed = 1008, Rho_G = 0.1)
# select omics data
fit7 <- est_lucid(G = G, Z = Z, Y = Y_normal, CoY = NULL, family = "normal",
K = 2, seed = 1008, Rho_Z_Mu = 90, Rho_Z_Cov = 0.1, init_par = "random")

## End(Not run)

```

---

fill\_data

*Impute missing data by optimizing the likelihood function*


---

### Description

Impute missing data by optimizing the likelihood function

### Usage

```
fill_data(obs, mu, sigma, p, index)
```

### Arguments

obs	a vector of length M
mu	a matrix of size M x K
sigma	a matrix of size M x M x K
p	a vector of length K
index	a vector of length M, indicating whether a value is missing or not in the raw data

### Value

an observation with updated imputed value

---

gen\_ci

*generate bootstrap ci (normal, basic and percentile)*


---

### Description

generate bootstrp ci (normal, basic and percentile)

### Usage

```
gen_ci(x, conf = 0.95)
```

**Arguments**

x	an object return by boot function
conf	A numeric scalar between 0 and 1 to specify confidence level(s) of the required interval(s).

**Value**

a matrix, the first column is t0 statistic from original model

---

helix_data	<i>HELIX data</i>
------------	-------------------

---

**Description**

The Human Early-Life Exposome (HELIX) project is multi-center research project that aims to characterize early-life environmental exposures and associate these with omics biomarkers and child health outcomes (Vrijheid, 2014. doi: 10.1289/ehp.1307204). We used a subset of HELIX data from Exposome Data Challenge 2021 (hold by ISGlobal) as an example to illustrate LUCID model.

**Usage**

```
helix_data
```

**Format**

A list with 4 matrices corresponding to exposures (G), omics data (Z), outcome (Y) and covariates (CoY)

**exposure** 8 exposures to environmental pollutants. Variables end with m represent maternal exposures; end with c represent children exposures

**omics** 10 proteins

**outcome** A continuous outcome for BMI-z score based on WHO standard, A binary outcome for body mass index categories at 6-11 years old based on WHO reference (0: Thinness or Normal; 1: Overweight or Obese)

**covariate** 3 covariates including mother's bmi, child sex, maternal age

---

Istep_Z	<i>I-step of LUCID</i>
---------	------------------------

---

**Description**

Impute missing data in  $Z$  by maximizing the likelihood given fixed parameters of LUCID

**Usage**

```
Istep_Z(Z, p, mu, sigma, index)
```

**Arguments**

$Z$	an $N$ by $P$ matrix representing the omics data
$p$	an $N$ by $K$ matrix representing posterior inclusion probability for each latent cluster
$\mu$	an $M$ by $K$ matrix representing cluster-specific means
$\sigma$	an $M$ by $M$ by $K$ array representing cluster-specific covariance
$index$	an $N$ by $M$ matrix representing missing values in $Z$

**Value**

a complete dataset of  $Z$

---

lucid	<i>Fit a lucid model for integrated analysis on exposure, outcome and multi-omics data</i>
-------	--

---

**Description**

Fit a lucid model for integrated analysis on exposure, outcome and multi-omics data

**Usage**

```
lucid(
  G,
  Z,
  Y,
  CoG = NULL,
  CoY = NULL,
  family = "normal",
  K = 2,
  Rho_G = 0,
  Rho_Z_Mu = 0,
```

```

  Rho_Z_Cov = 0,
  verbose_tune = FALSE,
  ...
)

```

### Arguments

G	Exposures, a numeric vector, matrix, or data frame. Categorical variable should be transformed into dummy variables. If a matrix or data frame, rows represent observations and columns correspond to variables.
Z	Omics data, a numeric matrix or data frame. Rows correspond to observations and columns correspond to variables.
Y	Outcome, a numeric vector. Categorical variable is not allowed. Binary outcome should be coded as 0 and 1.
CoG	Optional, covariates to be adjusted for estimating the latent cluster. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
CoY	Optional, covariates to be adjusted for estimating the association between latent cluster and the outcome. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
family	Distribution of outcome. For continuous outcome, use "normal"; for binary outcome, use "binary". Default is "normal".
K	Number of latent clusters (should be greater or equal than 2). Either an integer or a vector of integer. If K is a vector, model selection on K is performed.
Rho_G	A scalar or a vector. This parameter is the LASSO penalty to regularize exposures. If it is a vector, <code>lucid</code> will call <code>tune_lucid</code> to conduct model selection and variable selection. User can try penalties from 0 to 1.
Rho_Z_Mu	A scalar or a vector. This parameter is the LASSO penalty to regularize cluster-specific means for omics data (Z). If it is a vector, <code>lucid</code> will call <code>tune_lucid</code> to conduct model selection and variable selection. User can try penalties from 1 to 100.
Rho_Z_Cov	A scalar or a vector. This parameter is the graphical LASSO penalty to estimate sparse cluster-specific variance-covariance matrices for omics data (Z). If it is a vector, <code>lucid</code> will call <code>tune_lucid</code> to conduct model selection and variable selection. User can try penalties from 0 to 1.
verbose_tune	A flag to print details of tuning process.
...	Other parameters passed to <code>est_lucid</code>

### Value

An optimal lucid model

### Examples

```

## Not run:
G <- sim_data$G

```

```

Z <- sim_data$Z
Y_normal <- sim_data$Y_normal
Y_binary <- sim_data$Y_binary
cov <- sim_data$Covariate

# fit lucid model
fit1 <- lucid(G = G, Z = Z, Y = Y_normal, family = "normal")
fit2 <- lucid(G = G, Z = Z, Y = Y_binary, family = "binary", useY = FALSE)

# including covariates
fit3 <- lucid(G = G, Z = Z, Y = Y_binary, family = "binary", CoG = cov)
fit4 <- lucid(G = G, Z = Z, Y = Y_binary, family = "binary", CoY = cov)

# tune K
fit5 <- lucid(G = G, Z = Z, Y = Y_binary, family = "binary", K = 2:5)

# variable selection
fit6 <- lucid(G = G, Z = Z, Y = Y_binary, family = "binary", Rho_G = seq(0.01, 0.1, by = 0.01))
fit7 <- lucid(G = G, Z = Z, Y = Y_binary, family = "binary",
Rho_Z_Mu = seq(10, 100, by = 10), Rho_Z_Cov = 0.5,
init_par = "random", verbose_tune = TRUE)

## End(Not run)

```

---

plot\_lucid

*Visualize LUCID model through a Sankey diagram*


---

## Description

In the Sankey diagram, each node either represents a variable (exposure, omics or outcome) or a latent cluster. Each line represents an association. The color of the node represents variable type, either exposure, omics or outcome. The width of the line represents the effect size of a certain association; the color of the line represents the direction of a certain association.

## Usage

```

plot_lucid(
  x,
  G_color = "dimgray",
  X_color = "#eb8c30",
  Z_color = "#2fa4da",
  Y_color = "#afa58e",
  pos_link_color = "#67928b",
  neg_link_color = "#d1e5eb",
  fontsize = 7
)

```

**Arguments**

x	A LUCID model fitted by <a href="#">est_lucid</a>
G_color	Color of node for exposure
X_color	Color of node for latent cluster
Z_color	Color of node for omics data
Y_color	Color of node for outcome
pos_link_color	Color of link corresponds to positive association
neg_link_color	Color of link corresponds to negative association
fontsize	Font size for annotation

**Value**

A DAG graph created by [sankeyNetwork](#)

**Examples**

```
## Not run:
# prepare data
G <- sim_data$G
Z <- sim_data$Z
Y_normal <- sim_data$Y_normal
Y_binary <- sim_data$Y_binary
cov <- sim_data$Covariate

# plot lucid model
fit1 <- est_lucid(G = G, Z = Z, Y = Y_normal, CoY = NULL, family = "normal",
K = 2, seed = 1008)
plot_lucid(fit1)

# change node color
plot_lucid(fit1, G_color = "yellow")
plot_lucid(fit1, Z_color = "red")

# change link color
plot_lucid(fit1, pos_link_color = "red", neg_link_color = "green")

## End(Not run)
```

---

predict\_lucid

*Predict cluster assignment and outcome based on LUCID model*

---

**Description**

Predict cluster assignment and outcome based on LUCID model

**Usage**

```
predict_lucid(model, G, Z, Y = NULL, CoG = NULL, CoY = NULL, response = TRUE)
```

**Arguments**

model	A model fitted and returned by <code>est_lucid</code>
G	Exposures, a numeric vector, matrix, or data frame. Categorical variable should be transformed into dummy variables. If a matrix or data frame, rows represent observations and columns correspond to variables.
Z	Omics data, a numeric matrix or data frame. Rows correspond to observations and columns correspond to variables.
Y	Outcome, a numeric vector. Categorical variable is not allowed. Binary outcome should be coded as 0 and 1.
CoG	Optional, covariates to be adjusted for estimating the latent cluster. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
CoY	Optional, covariates to be adjusted for estimating the association between latent cluster and the outcome. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
response	If TRUE, when predicting binary outcome, the response will be returned. If FALSE, the linear predictor is returned.

**Value**

A list contains predicted latent cluster and outcome for each observation

**Examples**

```
## Not run:  
# prepare data  
G <- sim_data$G  
Z <- sim_data$Z  
Y_normal <- sim_data$Y_normal  
  
# fit lucid model  
fit1 <- est_lucid(G = G, Z = Z, Y = Y_normal, K = 2, family = "normal")  
  
# prediction on training set  
pred1 <- predict_lucid(model = fit1, G = G, Z = Z, Y = Y_normal)  
pred2 <- predict_lucid(model = fit1, G = G, Z = Z)  
  
## End(Not run)
```



---

print.lucid	<i>Print the output of est_lucid</i>
-------------	--------------------------------------

---

**Description**

Print the output of est\_lucid

**Usage**

```
## S3 method for class 'lucid'  
print(x, ...)
```

**Arguments**

x	An object of LUCID model, returned by est_lucid
...	Other arguments to be passed to print

---

print.sumlucid	<i>Print the output of LUCID in a nicer table</i>
----------------	---

---

**Description**

Print the output of LUCID in a nicer table

**Usage**

```
## S3 method for class 'sumlucid'  
print(x, ...)
```

**Arguments**

x	An object returned by summary_lucid
...	Other parameters to be passed to print

---

sim_data	<i>A simulated dataset for LUCID</i>
----------	--------------------------------------

---

### Description

This is an example dataset to illustrate LUCID model. It is simulated by assuming there are 2 latent clusters in the data. We assume the exposures are associated with latent cluster which ultimately affects the PFAS concentration and liver injury in children. The latent clusters are also characterized by differential levels of metabolites.

### Usage

```
sim_data
```

### Format

A list with 5 matrices corresponding to exposures (**G**), omics data (**Z**), a continuous outcome, a binary outcome and 2 covariates (can be used either as CoX or CoY). Each matrix contains 2000 observations.

**G** 10 exposures

**Z** 10 metabolites

**Y\_normal** Outcome, PFAS concentration in children

**Y\_binary** Binary outcome, liver injury status

**Covariates** 2 continuous covariates, can be treated as either CoX or CoY

**X** Latent clusters

---

summary_lucid	<i>Summarize results of LUCID model</i>
---------------	---

---

### Description

Summarize results of LUCID model

### Usage

```
summary_lucid(object, boot.se = NULL)
```

### Arguments

**object** A LUCID model fitted by [est\\_lucid](#)

**boot.se** An object returned by [boot\\_lucid](#), which contains the bootstrap confidence intervals

**Examples**

```

## Not run:
# use simulated data
G <- sim_data$G
Z <- sim_data$Z
Y_normal <- sim_data$Y_normal

# fit lucid model
fit1 <- est_lucid(G = G, Z = Z, Y = Y_normal, family = "normal", K = 2,
seed = 1008)

# conduct bootstrap resampling
boot1 <- boot_lucid(G = G, Z = Z, Y = Y_normal, model = fit1, R = 100)

# summarize lucid model
summary_lucid(fit1)

# summarize lucid model with bootstrap CIs
summary_lucid(fit1, boot.se = boot1)

## End(Not run)

```

---

tune\_lucid

*A wrapper function to perform model selection for LUCID*


---

**Description**

Given a grid of K and L1 penalties (including  $\text{Rho}_G$ ,  $\text{Rho}_Z$ ,  $\mu$  and  $\text{Rho}_Z$ ,  $\text{Cov}$ ), fit LUCID model over all combinations of K and L1 penalties to determine the optimal penalty.

**Usage**

```

tune_lucid(
  G,
  Z,
  Y,
  CoG = NULL,
  CoY = NULL,
  family = "normal",
  K = 2:5,
  Rho_G = 0,
  Rho_Z_Mu = 0,
  Rho_Z_Cov = 0,
  ...
)

```

**Arguments**

G	Exposures, a numeric vector, matrix, or data frame. Categorical variable should be transformed into dummy variables. If a matrix or data frame, rows represent observations and columns correspond to variables.
Z	Omics data, a numeric matrix or data frame. Rows correspond to observations and columns correspond to variables.
Y	Outcome, a numeric vector. Categorical variable is not allowed. Binary outcome should be coded as 0 and 1.
CoG	Optional, covariates to be adjusted for estimating the latent cluster. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
CoY	Optional, covariates to be adjusted for estimating the association between latent cluster and the outcome. A numeric vector, matrix or data frame. Categorical variable should be transformed into dummy variables.
family	Distribution of outcome. For continuous outcome, use "normal"; for binary outcome, use "binary". Default is "normal".
K	Number of latent clusters. An integer greater or equal to 2. If K is a vector, model selection on K is performed
Rho_G	A scalar or a vector. This parameter is the LASSO penalty to regularize exposures. If it is a vector, tune_lucid will conduct model selection and variable selection. User can try penalties from 0 to 1.
Rho_Z_Mu	A scalar or a vector. This parameter is the LASSO penalty to regularize cluster-specific means for omics data (Z). If it is a vector, tune_lucid will conduct model selection and variable selection. User can try penalties from 1 to 100.
Rho_Z_Cov	A scalar or a vector. This parameter is the graphical LASSO penalty to estimate sparse cluster-specific variance-covariance matrices for omics data (Z). If it is a vector, tune_lucid will conduct model selection and variable selection. User can try penalties from 0 to 1.
...	Other parameters passed to est_lucid

**Value**

A list:

best_model	the best model over different combination of tuning parameters
tune_list	a data frame contains combination of tuning parameters and c corresponding BIC
res_model	a list of LUCID models corresponding to each combination of tuning parameters

**Examples**

```
## Not run:
# use simulated data
G <- sim_data$G
Z <- sim_data$Z
Y_normal <- sim_data$Y_normal
```

```
# find the optimal model over the grid of K
tune_K <- tune_lucid(G = G, Z = Z, Y = Y_normal, useY = FALSE, tol = 1e-3,
seed = 1, K = 2:5)

# tune penalties
tune_Rho_G <- tune_lucid(G = G, Z = Z, Y = Y_normal, useY = FALSE, tol = 1e-3,
seed = 1, K = 2, Rho_G = c(0.1, 0.2, 0.3, 0.4))
tune_Rho_Z_Mu <- tune_lucid(G = G, Z = Z, Y = Y_normal, useY = FALSE, tol = 1e-3,
seed = 1, K = 2, Rho_Z_Mu = c(10, 20, 30, 40))
tune_Rho_Z_Cov <- tune_lucid(G = G, Z = Z, Y = Y_normal, useY = FALSE, tol = 1e-3,
seed = 1, K = 2, Rho_Z_Cov = c(0.1, 0.2, 0.3))

## End(Not run)
```

# Index

## \* datasets

helix\_data, 11

sim\_data, 18

boot.lucid, 2

boot\_lucid, 3, 18

check\_na, 4

est.lucid, 5

est\_lucid, 7, 15, 16, 18

fill\_data, 10

gen\_ci, 10

helix\_data, 11

Istep\_Z, 12

lucid, 6, 8, 12

plot\_lucid, 14

predict\_lucid, 15

print.lucid, 17

print.sumlucid, 17

sankeyNetwork, 15

sim\_data, 18

summary\_lucid, 18

tune\_lucid, 19