

Package ‘OmicNavigator’

December 1, 2021

Type Package

Title Open-Source Software for 'Omic' Data Analysis and Visualization

Description A tool for interactive exploration of the results from 'omics' experiments to facilitate novel discoveries from high-throughput biology. The software includes R functions for the 'bioinformatician' to deposit study metadata and the outputs from statistical analyses (e.g. differential expression, enrichment). These results are then exported to an interactive JavaScript dashboard that can be interrogated on the user's local machine or deployed online to be explored by collaborators. The dashboard includes 'sortable' tables, interactive plots including network visualization, and fine-grained filtering based on statistical significance.

Version 1.8.0

URL <https://github.com/abbvie-external/OmicNavigator>

BugReports <https://github.com/abbvie-external/OmicNavigator/issues>

License MIT + file LICENSE

License_restricts_use no

License_is_FOSS yes

Encoding UTF-8

LazyData true

Depends R (>= 3.2.0)

Imports data.table (>= 1.12.4), graphics, jsonlite, stats, tools,
utils

Suggests faviconPlease, ggplot2, opencpu, tinytest (>= 1.2.3), ttdo
(>= 0.0.6), UpSetR

RoxygenNote 7.1.1

NeedsCompilation no

Author Terrence Ernst [aut] (Web application),
John Blischak [aut, cre] (<<https://orcid.org/0000-0003-2634-9879>>),
Paul Nordlund [aut] (Web application),
Justin Moore [aut] (UpSet-related functions and web application),

Joe Dalen [aut] (Barcode functionality and web application),
 Akshay Bhamidipati [aut] (Web application),
 Brett Engelmann [aut],
 Marco Curado [aut] (Improved plotting capabilities),
 AbbVie Inc. [cph, fnd]

Maintainer John Blischak <jdblischak@gmail.com>

Repository CRAN

Date/Publication 2021-12-01 05:40:02 UTC

R topics documented:

addAnnotations	3
addAssays	4
addBarcodes	5
addEnrichments	6
addEnrichmentsLinkouts	6
addFeatures	8
addMapping	8
addMetaFeatures	9
addMetaFeaturesLinkouts	10
addModels	11
addOverlaps	12
addPlots	13
addReports	14
addResults	15
addResultsLinkouts	15
addSamples	17
addTests	17
basal.vs.lp	19
basal.vs.ml	20
cam.BasalvsLP	21
cam.BasalvsML	22
createStudy	23
exportStudy	27
getAnnotations	27
getAssays	28
getBarcodeData	29
getBarcodes	30
getEnrichments	30
getEnrichmentsIntersection	31
getEnrichmentsLinkouts	32
getEnrichmentsNetwork	33
getEnrichmentsTable	34
getEnrichmentsUpset	35
getFavicons	35
getFeatures	36
getInstalledStudies	37

getLinkFeatures	37
getMapping	38
getMetaFeatures	38
getMetaFeaturesLinkouts	39
getMetaFeaturesTable	40
getModels	40
getNodeFeatures	41
getOverlaps	42
getPackageVersion	42
getPlots	43
getPlottingData	43
getReportLink	44
getReports	45
getResults	46
getResultsIntersection	47
getResultsLinkouts	48
getResultsTable	48
getResultsUpset	49
getSamples	50
getTests	50
getUpsetCols	51
group	52
importStudy	53
installApp	53
installStudy	54
lane	54
lcpm	55
listStudies	56
Mm.c2	56
OmicNavigator	57
plotStudy	58
removeStudy	59
samplenames	59
startApp	60
summary.onStudy	61
validateStudy	61
Index	62

addAnnotations	<i>Add annotations</i>
----------------	------------------------

Description

Add annotations

Usage

```
addAnnotations(study, annotations, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
annotations	The annotations used for the enrichment analyses. The input is a nested list. The top-level list contains one entry per annotation database, e.g. reactome. The names correspond to the name of each annotation database. Each of these elements should be list of that contains more information about each annotation database. Specifically the sublist should contain 1) description, a character vector that describes the resource, 2) featureID, the name of the column in the features table that was used for the enrichment analysis, and 3) terms, a list of annotation terms. The names of terms sublist correspond to the name of the annotation terms. Each of the annotation terms should be a character vector of featureIDs.
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

addAssays	<i>Add assays</i>
-----------	-------------------

Description

Add assays

Usage

```
addAssays(study, assays, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
assays	The assays from the study. The input object is a list of data frames (one per model). The row names should correspond to the featureIDs (addFeatures). The column names should correspond to the sampleIDs (addSamples). The data frame should only contain numeric values. To share a data frame across multiple models, use the modelID "default".
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

addBarcodes	<i>Add barcode plot metadata</i>
-------------	----------------------------------

Description

The app can display a barcode plot of the enrichment results for a given annotation term. The metadata in 'barcodes' instructs the app how to create and label the barcode plot.

Usage

```
addBarcodes(study, barcodes, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
barcodes	The metadata variables that describe the barcode plot. The input object is a list of lists (one per model). Each sublist must contain the element <code>statistic</code> , which is the column name in the results table to use to construct the barcode plot. Each sublist may additionally contain any of the following optional elements: 1) <code>absolute</code> - Should the statistic be converted to its absolute value (default is TRUE). 2) <code>logFoldChange</code> - The column name in the results table that contains the log fold change values. 3) <code>labelStat</code> - The x-axis label to describe the statistic. 4) <code>labelLow</code> - The left-side label to describe low values of the statistic. 5) <code>labelHigh</code> - The right-side label to describe high values of the statistic. 6) <code>featureDisplay</code> - The feature variable to use to label the barcode plot on hover. To share metadata across multiple models, use the modelID "default".
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting <code>reset = TRUE</code> enables you to remove existing data you no longer want to include in the study.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

addEnrichments *Add enrichment results*

Description

Add enrichment results

Usage

```
addEnrichments(study, enrichments, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
enrichments	The enrichment results from each model. The input is a nested named list. The names of the list correspond to the model names. Each list element should be a list of the annotation databases tested (addAnnotations). The names of the list correspond to the annotation databases. Each list element should be another list of tests (addTests). The names correspond to the tests performed. Each of these elements should be a data frame with enrichment results. Each table must contain the following columns: "termID", "description", "nominal" (the nominal statistics), and "adjusted" (the statistics after adjusting for multiple testing). Any additional columns are ignored.
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

addEnrichmentsLinkouts *Add linkouts to external resources in the enrichments table*

Description

You can provide additional information on the annotation terms in your study by providing linkouts to external resources. These will be embedded directly in the enrichments table.

Usage

```
addEnrichmentsLinkouts(study, enrichmentsLinkouts, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
enrichmentsLinkouts	The URL patterns that describe linkouts to external resources (see Details below). The input object is a named list. The names of the list correspond to the annotation names. Each element of the list is a character vector of linkouts for that annotationID.
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Details

For each linkout, the URL pattern you provide will be concatenated with the value of the termID column. As an example, if you used the annotation database [AmiGO 2](#) for your enrichments analysis, you can provide a linkout for each termID using the following pattern:

```
go = "http://amigo.geneontology.org/amigo/term/"
```

As another example, if you used the annotation database [Reactome](#) for your enrichments analysis, you can provide a linkout for each termID using the following pattern:

```
reactome = "https://reactome.org/content/detail/"
```

Note that you can provide more than one linkout per termID.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

See Also

[addAnnotations](#), [addEnrichments](#)

Examples

```
study <- createStudy("example")
enrichmentsLinkouts <- list(
  gobp = c("http://amigo.geneontology.org/amigo/term/",
           "https://www.ebi.ac.uk/QuickGO/term/"),
  reactome = "https://reactome.org/content/detail/"
)
study <- addEnrichmentsLinkouts(study, enrichmentsLinkouts)
```

addFeatures	<i>Add feature metadata</i>
-------------	-----------------------------

Description

Add feature metadata

Usage

```
addFeatures(study, features, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
features	The metadata variables that describe the features in the study. The input object is a list of data frames (one per model). The first column of each data frame is used as the featureID, so it must contain unique values. To share a data frame across multiple models, use the modelID "default". All columns will be coerced to character strings.
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

addMapping	<i>Add mapping object</i>
------------	---------------------------

Description

Includes a mapping list connecting features across models.

Usage

```
addMapping(study, mapping, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
mapping	Feature IDs from models. The input object is a list object with element names matching model names, and each element containing a vector with feature IDs per model. Features with same index position across models are considered found across models. For each model, the feature IDs must match the feature IDs from results object of the respective model.
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Details

Mapping object consists of a list with element names matching the model names, and each element consisting in a vector with feature IDs found in the result object. For making meaningful connections between models, feature IDs for distinct models must be aligned per index position in the vector. E.g., if in a study there are models "transcriptomics" and "proteomics" and the user wants to create a plot based on data from both, a mapping list with element names "transcriptomics" and "proteomics" should be created, where feature IDs of both models are found in the same index position in each list element.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

See Also

[getPlottingData](#), [plotStudy](#)

addMetaFeatures	<i>Add meta-feature metadata</i>
-----------------	----------------------------------

Description

The meta-features table is useful anytime there are metadata variables that cannot be mapped 1:1 to your features. For example, a peptide may be associated with multiple proteins.

Usage

```
addMetaFeatures(study, metaFeatures, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
metaFeatures	The metadata variables that describe the meta-features in the study. The input object is a list of data frames (one per model). The first column of each data frame is used as the featureID, so it must contain the same IDs as the corresponding features data frame (addFeatures). To share a data frame across multiple models, use the modelID "default". All columns will be coerced to character strings.
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

addMetaFeaturesLinkouts

Add linkouts to external resources in the metaFeatures table

Description

You can provide additional information on the metaFeatures in your study by providing linkouts to external resources. These will be embedded directly in the metaFeatures table.

Usage

```
addMetaFeaturesLinkouts(study, metaFeaturesLinkouts, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
metaFeaturesLinkouts	The URL patterns that describe linkouts to external resources (see Details below). The input object is a nested named list. The names of the list correspond to the model names. Each element of the list is a named list of character vectors. The names of this nested list must correspond to the column names of the matching metaFeatures table (addMetaFeatures). To share linkouts across multiple models, use the modelID "default".
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Details

For each linkout, the URL pattern you provide will be concatenated with the value of that column for each row. As an example, if your metaFeatures table included a column named "ensembl" that contained the Ensembl Gene ID for each feature, you could create a linkout to Ensembl using the following pattern:

```
ensembl = "https://ensembl.org/Homo_sapiens/Gene/Summary?g="
```

As another example, if you had a column named "entrez" that contained the Entrez Gene ID for each feature, you could create a linkout to Entrez using the following pattern:

```
entrez = "https://www.ncbi.nlm.nih.gov/gene/"
```

Note that you can provide more than one linkout per column.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

See Also

[addMetaFeatures](#)

Examples

```
study <- createStudy("example")
metaFeaturesLinkouts <- list(
  default = list(
    ensembl = c("https://ensembl.org/Homo_sapiens/Gene/Summary?g=",
               "https://www.genome.ucsc.edu/cgi-bin/hgGene?hgg_gene="),
    entrez = "https://www.ncbi.nlm.nih.gov/gene/"
  )
)
study <- addMetaFeaturesLinkouts(study, metaFeaturesLinkouts)
```

addModels

Add models

Description

Add models

Usage

```
addModels(study, models, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
models	The models analyzed in the study. The input is a named list. The names correspond to the names of the models. The elements correspond to the descriptions of the models. Alternatively, instead of a single character string, you can provide a list of metadata fields about each model. The field "description" will be used to derive the tooltip displayed in the app.
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

Examples

```
study <- createStudy("example")
models <- list(
  model_01 = "Name of first model",
  model_02 = "Name of second model"
)
study <- addModels(study, models)

# Alternative: provide additional metadata about each model
models <- list(
  model_01 = list(
    description = "Name of first model",
    data_type = "transcriptomics"
  ),
  model_02 = list(
    description = "Name of second model",
    data_type = "proteomics"
  )
)
```

addOverlaps

Add overlaps between annotation gene sets

Description

The app's network view of the enrichments results requires pairwise overlap metrics between all the terms of each annotation in order to draw the edges between the nodes/terms. These overlaps are calculated automatically when installing or exporting an OmicNavigator study. If you'd like, you can manually calculate these pairwise overlaps by calling `addOverlaps` prior to installing or exporting your study.

Usage

```
addOverlaps(study, reset = FALSE)
```

Arguments

study An OmicNavigator study created with [createStudy](#)

reset Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting `reset = TRUE` enables you to remove existing data you no longer want to include in the study.

Value

Returns the original `onStudy` object passed to the argument `study`, but modified to include the newly added data

addPlots	<i>Add custom plotting functions</i>
----------	--------------------------------------

Description

Include custom plots that the app will display when a feature is selected by the user.

Usage

```
addPlots(study, plots, reset = FALSE)
```

Arguments

study An OmicNavigator study created with [createStudy](#)

plots Custom plotting functions for the study. The input object is a nested list. The first list corresponds to the `modelID(s)`. The second list corresponds to the name(s) of the function(s) defined in the current R session. The third list provides metadata to describe each plot. The only required metadata element is `displayName`, which controls how the plot will be named in the app. You are encouraged to also specify the `plotType`, e.g. "singleFeature", "multiFeature", "multiTest", "multiModel". `plotType` accepts vector of entries, whenever applicable, e.g., `plotType = c("multiFeature", "multiTest")`. If you do not specify the `plotType`, the plot will be assumed to be "singleFeature" and "singleTest". Optionally, if the plotting function requires external packages, these can be defined in the element `packages`. To share plots across multiple models, use the `modelID` "default".

reset Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting `reset = TRUE` enables you to remove existing data you no longer want to include in the study.

Details

Custom plotting functions are passed a list of data frames: `assays` with the measurements, `features` with the feature data, `samples` with the sample data, and `results` with test results data. Note that `assays`, `features` and `results` only include data for the specified `featureID(s)` (and re-ordered so their rows match). Thus your custom plotting function must have at least one argument. It can have additional arguments if you wish, but these must be provided with default values, because `plotStudy` only passes the plotting data to the first argument.

Note that any `ggplot2` plots will require extra care. This is because the plotting code will be inserted into a study package, and thus must follow the [best practices for using ggplot2 within packages](#). Specifically, when you refer to columns of the data frame, e.g. `aes(x = group)`, you need to prefix it with `.data$`, so that it becomes `aes(x = .data$group)`. Fortunately this latter code will also run fine as you interactively develop the function.

Value

Returns the original `onStudy` object passed to the argument `study`, but modified to include the newly added data

See Also

[getPlottingData](#), [plotStudy](#)

addReports	<i>Add reports</i>
------------	--------------------

Description

You can include reports of the analyses you performed to generate the results.

Usage

```
addReports(study, reports, reset = FALSE)
```

Arguments

<code>study</code>	An OmicNavigator study created with createStudy
<code>reports</code>	The analysis report(s) that explain how the study results were generated. The input object is a list of character vectors (one per model). Each element should be either a URL or a path to a file on your computer. If it is a path to a file, this file will be included in the exported study package. To share a report across multiple models, use the <code>modelID</code> "default".
<code>reset</code>	Reset the data prior to adding the new data (default: <code>FALSE</code>). The default is to add to or modify any previously added data (if it exists). Setting <code>reset = TRUE</code> enables you to remove existing data you no longer want to include in the study.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

addResults	<i>Add inference results</i>
------------	------------------------------

Description

Add inference results

Usage

```
addResults(study, results, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
results	The inference results from each model. The input is a nested named list. The names of the list correspond to the model names. Each element in the list should be a list of data frames with inference results, one for each test. In each data frame, the featureID must be in the first column, and all other columns must be numeric.
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

addResultsLinkouts	<i>Add linkouts to external resources in the results table</i>
--------------------	--

Description

You can provide additional information on the features in your study by providing linkouts to external resources. These will be embedded directly in the results table.

Usage

```
addResultsLinkouts(study, resultsLinkouts, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
resultsLinkouts	The URL patterns that describe linkouts to external resources (see Details below). The input object is a nested named list. The names of the list correspond to the model names. Each element of the list is a named list of character vectors. The names of this nested list must correspond to the column names of the matching features table. To share linkouts across multiple models, use the modelID "default".
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Details

For each linkout, the URL pattern you provide will be concatenated with the value of that column for each row. As an example, if your features table included a column named "ensembl" that contained the Ensembl Gene ID for each feature, you could create a linkout to Ensembl using the following pattern:

```
ensembl = "https://ensembl.org/Homo_sapiens/Gene/Summary?g="
```

As another example, if you had a column named "entrez" that contained the Entrez Gene ID for each feature, you could create a linkout to Entrez using the following pattern:

```
entrez = "https://www.ncbi.nlm.nih.gov/gene/"
```

Note that you can provide more than one linkout per column.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

See Also

[addFeatures](#)

Examples

```
study <- createStudy("example")
resultsLinkouts <- list(
  default = list(
    ensembl = c("https://ensembl.org/Homo_sapiens/Gene/Summary?g=",
               "https://www.genome.ucsc.edu/cgi-bin/hgGene?hgg_gene="),
    entrez = "https://www.ncbi.nlm.nih.gov/gene/"
  )
)
study <- addResultsLinkouts(study, resultsLinkouts)
```

addSamples	<i>Add sample metadata</i>
------------	----------------------------

Description

Add sample metadata

Usage

```
addSamples(study, samples, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
samples	The metadata variables that describe the samples in the study. The input object is a named list of data frames (one per model). The first column of each data frame is used as the sampleID, so it must contain unique values. To share a data frame across multiple models, use the modelID "default".
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

addTests	<i>Add tests</i>
----------	------------------

Description

Add tests

Usage

```
addTests(study, tests, reset = FALSE)
```

Arguments

study	An OmicNavigator study created with createStudy
tests	The tests from the study. The input object is a list of lists. Each element of the top-level list is a model. The names should be the modelIDs. For each modelID, each element of the nested list is a test. The names should be the testIDs. The value should be a single character string describing the testID. To share tests across multiple models, use the modelID "default". Instead of a single character string, you can provide a list of metadata fields about each test. The field "description" will be used to derive the tooltip displayed in the app.
reset	Reset the data prior to adding the new data (default: FALSE). The default is to add to or modify any previously added data (if it exists). Setting reset = TRUE enables you to remove existing data you no longer want to include in the study.

Value

Returns the original onStudy object passed to the argument study, but modified to include the newly added data

Examples

```
study <- createStudy("example")
tests <- list(
  default = list(
    test_01 = "Name of first test",
    test_02 = "Name of second test"
  )
)
study <- addTests(study, tests)

# Alternative: provide additional metadata about each test
tests <- list(
  default = list(
    test_01 = list(
      description = "Name of first test",
      comparison_type = "treatment vs control",
      effect_size = "beta"
    ),
    test_02 = list(
      description = "Name of second test",
      comparison_type = "treatment vs control",
      effect_size = "logFC"
    )
  )
)
```

`basal.vs.lp`*basal.vs.lp* from Bioconductor workflow RNAseq123

Description

A subset of the object `basal.vs.lp` from Bioconductor workflow RNAseq123.

Usage

```
basal.vs.lp
```

Format

A data frame with 24 rows and 8 columns:

ENTREZID Entrez ID of mouse gene

SYMBOL Symbol of mouse gene

TXCHROM Chromosome location of mouse gene

logFC Log fold change

AveExpr Average expression level of the gene across all samples

t Moderated t-statistic

P.Value p-value

adj.P.Val Adjusted p-value

Source

<https://bioconductor.org/packages/release/workflows/vignettes/RNAseq123/inst/doc/limmaWorkflow.html>

References

Law CW, Alhamdoosh M, Su S, Dong X, Tian L, Smyth GK, Ritchie ME. *RNA-seq analysis is easy as 1-2-3 with limma, Glimma and edgeR [version 3; peer review: 3 approved]*. F1000Research 2018, 5:1408 doi: [10.12688/f1000research.9005.3](https://doi.org/10.12688/f1000research.9005.3)

Sheridan, J.M., Ritchie, M.E., Best, S.A. et al. *A pooled shRNA screen for regulators of primary mammary stem and progenitor cells identifies roles for *Asap1* and *Prox1**. BMC Cancer 2015, 15:221 doi: [10.1186/s128850151187z](https://doi.org/10.1186/s128850151187z)

Examples

```
head(basal.vs.lp)
str(basal.vs.lp)
```

`basal.vs.ml`*basal.vs.ml from Bioconductor workflow RNAseq123*

Description

A subset of the object `basal.vs.ml` from Bioconductor workflow RNAseq123.

Usage

```
basal.vs.ml
```

Format

A data frame with 24 rows and 8 columns:

ENTREZID Entrez ID of mouse gene

SYMBOL Symbol of mouse gene

TXCHROM Chromosome location of mouse gene

logFC Log fold change

AveExpr Average expression level of the gene across all samples

t Moderated t-statistic

P.Value p-value

adj.P.Val Adjusted p-value

Source

<https://bioconductor.org/packages/release/workflows/vignettes/RNAseq123/inst/doc/limmaWorkflow.html>

References

Law CW, Alhamdoosh M, Su S, Dong X, Tian L, Smyth GK, Ritchie ME. *RNA-seq analysis is easy as 1-2-3 with limma, Glimma and edgeR [version 3; peer review: 3 approved]*. F1000Research 2018, 5:1408 doi: [10.12688/f1000research.9005.3](https://doi.org/10.12688/f1000research.9005.3)

Sheridan, J.M., Ritchie, M.E., Best, S.A. et al. *A pooled shRNA screen for regulators of primary mammary stem and progenitor cells identifies roles for *Asap1* and *Prox1**. BMC Cancer 2015, 15:221 doi: [10.1186/s128850151187z](https://doi.org/10.1186/s128850151187z)

Examples

```
head(basal.vs.ml)
str(basal.vs.ml)
```

`cam.BasalvsLP`*cam.BasalvsLP from Bioconductor workflow RNAseq123*

Description

A subset of the object `cam.BasalvsLP` from Bioconductor workflow RNAseq123.

Usage

```
cam.BasalvsLP
```

Format

A data frame with 4 rows and 4 columns:

NGenes Number of genes in each term

Direction Direction of the enrichment

PValue Nominal p-value

FDR Multiple-testing adjusted p-value

Source

<https://bioconductor.org/packages/release/workflows/vignettes/RNAseq123/inst/doc/limmaWorkflow.html>

References

Law CW, Alhamdoosh M, Su S, Dong X, Tian L, Smyth GK, Ritchie ME. *RNA-seq analysis is easy as 1-2-3 with limma, Glimma and edgeR [version 3; peer review: 3 approved]*. F1000Research 2018, 5:1408 doi: [10.12688/f1000research.9005.3](https://doi.org/10.12688/f1000research.9005.3)

Sheridan, J.M., Ritchie, M.E., Best, S.A. et al. *A pooled shRNA screen for regulators of primary mammary stem and progenitor cells identifies roles for *Asap1* and *Prox1**. BMC Cancer 2015, 15:221 doi: [10.1186/s128850151187z](https://doi.org/10.1186/s128850151187z)

Examples

```
head(cam.BasalvsLP)
str(cam.BasalvsLP)
```

`cam.BasalvsML`*cam.BasalvsML from Bioconductor workflow RNAseq123*

Description

A subset of the object `cam.BasalvsML` from Bioconductor workflow RNAseq123.

Usage

```
cam.BasalvsML
```

Format

A data frame with 4 rows and 4 columns:

NGenes Number of genes in each term

Direction Direction of the enrichment

PValue Nominal p-value

FDR Multiple-testing adjusted p-value

Source

<https://bioconductor.org/packages/release/workflows/vignettes/RNAseq123/inst/doc/limmaWorkflow.html>

References

Law CW, Alhamdoosh M, Su S, Dong X, Tian L, Smyth GK, Ritchie ME. *RNA-seq analysis is easy as 1-2-3 with limma, Glimma and edgeR [version 3; peer review: 3 approved]*. F1000Research 2018, 5:1408 doi: [10.12688/f1000research.9005.3](https://doi.org/10.12688/f1000research.9005.3)

Sheridan, J.M., Ritchie, M.E., Best, S.A. et al. *A pooled shRNA screen for regulators of primary mammary stem and progenitor cells identifies roles for *Asap1* and *Prox1**. BMC Cancer 2015, 15:221 doi: [10.1186/s128850151187z](https://doi.org/10.1186/s128850151187z)

Examples

```
head(cam.BasalvsML)
str(cam.BasalvsML)
```

createStudy	<i>Create a study</i>
-------------	-----------------------

Description

Create a new OmicNavigator study.

Usage

```
createStudy(  
  name,  
  description = name,  
  samples = list(),  
  features = list(),  
  models = list(),  
  assays = list(),  
  tests = list(),  
  annotations = list(),  
  results = list(),  
  enrichments = list(),  
  metaFeatures = list(),  
  plots = list(),  
  mapping = list(),  
  barcodes = list(),  
  reports = list(),  
  resultsLinkouts = list(),  
  enrichmentsLinkouts = list(),  
  metaFeaturesLinkouts = list(),  
  version = NULL,  
  maintainer = NULL,  
  maintainerEmail = NULL,  
  studyMeta = list()  
)
```

Arguments

name	Name of the study
description	Description of the study
samples	The metadata variables that describe the samples in the study. The input object is a named list of data frames (one per model). The first column of each data frame is used as the sampleID, so it must contain unique values. To share a data frame across multiple models, use the modelID "default".
features	The metadata variables that describe the features in the study. The input object is a list of data frames (one per model). The first column of each data frame is used as the featureID, so it must contain unique values. To share a data frame across multiple models, use the modelID "default". All columns will be coerced to character strings.

models	The models analyzed in the study. The input is a named list. The names correspond to the names of the models. The elements correspond to the descriptions of the models. Alternatively, instead of a single character string, you can provide a list of metadata fields about each model. The field "description" will be used to derive the tooltip displayed in the app.
assays	The assays from the study. The input object is a list of data frames (one per model). The row names should correspond to the featureIDs (addFeatures). The column names should correspond to the sampleIDs (addSamples). The data frame should only contain numeric values. To share a data frame across multiple models, use the modelID "default".
tests	The tests from the study. The input object is a list of lists. Each element of the top-level list is a model. The names should be the modelIDs. For each modelID, each element of the nested list is a test. The names should be the testIDs. The value should be a single character string describing the testID. To share tests across multiple models, use the modelID "default". Instead of a single character string, you can provide a list of metadata fields about each test. The field "description" will be used to derive the tooltip displayed in the app.
annotations	The annotations used for the enrichment analyses. The input is a nested list. The top-level list contains one entry per annotation database, e.g. reactome. The names correspond to the name of each annotation database. Each of these elements should be list of that contains more information about each annotation database. Specifically the sublist should contain 1) description, a character vector that describes the resource, 2) featureID, the name of the column in the features table that was used for the enrichment analysis, and 3) terms, a list of annotation terms. The names of terms sublist correspond to the name of the annotation terms. Each of the annotation terms should be a character vector of featureIDs.
results	The inference results from each model. The input is a nested named list. The names of the list correspond to the model names. Each element in the list should be a list of data frames with inference results, one for each test. In each data frame, the featureID must be in the first column, and all other columns must be numeric.
enrichments	The enrichment results from each model. The input is a nested named list. The names of the list correspond to the model names. Each list element should be a list of the annotation databases tested (addAnnotations). The names of the list correspond to the annotation databases. Each list element should be another list of tests (addTests). The names correspond to the tests performed. Each of these elements should be a data frame with enrichment results. Each table must contain the following columns: "termID", "description", "nominal" (the nominal statistics), and "adjusted" (the statistics after adjusting for multiple testing). Any additional columns are ignored.
metaFeatures	The metadata variables that describe the meta-features in the study. The input object is a list of data frames (one per model). The first column of each data frame is used as the featureID, so it must contain the same IDs as the corresponding features data frame (addFeatures). To share a data frame across multiple models, use the modelID "default". All columns will be coerced to character strings.

plots	Custom plotting functions for the study. The input object is a nested list. The first list corresponds to the modelID(s). The second list corresponds to the name(s) of the function(s) defined in the current R session. The third list provides metadata to describe each plot. The only required metadata element is <code>displayName</code> , which controls how the plot will be named in the app. You are encouraged to also specify the <code>plotType</code> , e.g. "singleFeature", "multiFeature", "multiTest", "multiModel". <code>PlotType</code> accepts vector of entries, whenever applicable, e.g., <code>plotType = c("multiFeature", "multiTest")</code> . If you do not specify the <code>plotType</code> , the plot will be assumed to be "singleFeature" and "singleTest". Optionally, if the plotting function requires external packages, these can be defined in the element packages. To share plots across multiple models, use the modelID "default".
mapping	Feature IDs from models. The input object is a list object with element names matching model names, and each element containing a vector with feature IDs per model. Features with same index position across models are considered found across models. For each model, the feature IDs must match the feature IDs from results object of the respective model.
barcodes	The metadata variables that describe the barcode plot. The input object is a list of lists (one per model). Each sublist must contain the element <code>statistic</code> , which is the column name in the results table to use to construct the barcode plot. Each sublist may additionally contain any of the following optional elements: 1) <code>absolute</code> - Should the statistic be converted to its absolute value (default is TRUE). 2) <code>logFoldChange</code> - The column name in the results table that contains the log fold change values. 3) <code>labelStat</code> - The x-axis label to describe the statistic. 4) <code>labelLow</code> - The left-side label to describe low values of the statistic. 5) <code>labelHigh</code> - The right-side label to describe high values of the statistic. 6) <code>featureDisplay</code> - The feature variable to use to label the barcode plot on hover. To share metadata across multiple models, use the modelID "default".
reports	The analysis report(s) that explain how the study results were generated. The input object is a list of character vectors (one per model). Each element should be either a URL or a path to a file on your computer. If it is a path to a file, this file will be included in the exported study package. To share a report across multiple models, use the modelID "default".
resultsLinkouts	The URL patterns that describe linkouts to external resources (see Details below). The input object is a nested named list. The names of the list correspond to the model names. Each element of the list is a named list of character vectors. The names of this nested list must correspond to the column names of the matching features table. To share linkouts across multiple models, use the modelID "default".
enrichmentsLinkouts	The URL patterns that describe linkouts to external resources (see Details below). The input object is a named list. The names of the list correspond to the annotation names. Each element of the list is a character vector of linkouts for that annotationID.
metaFeaturesLinkouts	The URL patterns that describe linkouts to external resources (see Details below). The input object is a nested named list. The names of the list correspond

exportStudy	<i>Export a study</i>
-------------	-----------------------

Description

Export a study

Usage

```
exportStudy(  
  study,  
  type = c("tarball", "package"),  
  path = NULL,  
  requireValid = TRUE  
)
```

Arguments

study	An OmicNavigator study
type	Export study as a package tarball ("tarball") or as a package directory ("package")
path	Optional file path to save the object
requireValid	Require that study is valid before exporting

Value

Invisibly returns the name of the tarball file ("tarball") or the path to the package directory ("package")

See Also

[validateStudy](#)

getAnnotations	<i>Get annotations from a study</i>
----------------	-------------------------------------

Description

Get annotations from a study

Usage

```
getAnnotations(study, annotationID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
annotationID	Filter by annotation
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument modelID):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]`.

If no data is available, an empty list is returned (`list()`).

getAssays	<i>Get assays from a study</i>
-----------	--------------------------------

Description

Get assays from a study

Usage

```
getAssays(study, modelID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument modelID):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]`.

If no data is available, an empty list is returned (`list()`).

getBarcodeData	<i>Get data for barcode and violin plots</i>
----------------	--

Description

Get data for barcode and violin plots

Usage

```
getBarcodeData(study, modelID, testID, annotationID, termID)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
testID	Filter by testID
annotationID	Filter by annotation
termID	Filter by termID

Value

A list with the following components:

data	Data frame with the differential statistics to plot
highest	(numeric) The largest differential statistic, rounded up to the next integer
labelStat	(character) The x-axis label to describe the differential statistic
labelLow	(character) The vertical axis label on the left to describe smaller values (default is "Low")
labelHigh	(character) The vertical axis label on the right to describe larger values (default is "High")

See Also

[addBarcodes](#), [getBarcodes](#)

getBarcodes *Get barcodes from a study*

Description

Get barcodes from a study

Usage

```
getBarcodes(study, modelID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument modelID):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[`.

If no data is available, an empty list is returned (`list()`).

getEnrichments *Get enrichments from a study*

Description

Get enrichments from a study

Usage

```
getEnrichments(  
  study,  
  modelID = NULL,  
  annotationID = NULL,  
  testID = NULL,  
  quiet = FALSE,  
  libraries = NULL  
)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
annotationID	Filter by annotation
testID	Filter by testID
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument `modelID`):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]`.

If no data is available, an empty list is returned (`list()`).

```
getEnrichmentsIntersection
      getEnrichmentsIntersection
```

Description

getEnrichmentsIntersection

Usage

```
getEnrichmentsIntersection(
  study,
  modelID,
  annotationID,
  mustTests,
  notTests,
  sigValue,
  operator,
  type
)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
annotationID	Filter by annotation
mustTests	The tests whose significant values must be included. (The intersection)
notTests	The tests whose significant values will be removed. (The difference)
sigValue	The significance levels for each column.
operator	The operators for each column.
type	Type of p-value ("nominal" or "adjusted")

Value

Returns a data frame with the enrichments, similar to [getEnrichmentsTable](#). Only rows that pass all the filters are included.

See Also

[getEnrichmentsTable](#)

getEnrichmentsLinkouts

Get enrichments table linkouts from a study

Description

Get enrichments table linkouts from a study

Usage

```
getEnrichmentsLinkouts(
  study,
  annotationID = NULL,
  quiet = FALSE,
  libraries = NULL
)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
annotationID	Filter by annotation
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then installed.packages will use the result of .libPaths .

Value

The object returned depends on the data available and any filters (e.g. the argument `modelID`):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]`.

If no data is available, an empty list is returned (`list()`).

`getEnrichmentsNetwork` *Get enrichments network from a study*

Description

Get enrichments network from a study

Usage

```
getEnrichmentsNetwork(study, modelID, annotationID, libraries = NULL)
```

Arguments

<code>study</code>	An OmicNavigator study. Either an object of class <code>onStudy</code> , or the name of an installed study package.
<code>modelID</code>	Filter by <code>modelID</code>
<code>annotationID</code>	Filter by annotation
<code>libraries</code>	The directories to search for installed study packages. If left as <code>NULL</code> (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

Returns a list with the following components:

<code>tests</code>	(character) Vector of testIDs
<code>nodes</code>	(data frame) The description of each annotation term (i.e. node). The nominal and adjusted p-values are in list-columns.
<code>links</code>	(list) The statistics for each pairwise overlap between the annotation terms (i.e. nodes)

getEnrichmentsTable *Get enrichments table from a study*

Description

Get enrichments table from a study

Usage

```
getEnrichmentsTable(  
  study,  
  modelID,  
  annotationID,  
  type = "nominal",  
  libraries = NULL  
)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
annotationID	Filter by annotation
type	Type of p-value ("nominal" or "adjusted")
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

A data frame of enrichments with the following columns:

termID	The unique ID for the annotation term
description	The description of the annotation term
...	One column for each of the enrichments

getEnrichmentsUpset *getEnrichmentsUpset*

Description

getEnrichmentsUpset

Usage

```
getEnrichmentsUpset(
  study,
  modelID,
  annotationID,
  sigValue,
  operator,
  type,
  tests = NULL
)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
annotationID	Filter by annotation
sigValue	The significance levels for each column.
operator	The operators for each column.
type	Type of p-value ("nominal" or "adjusted")
tests	Restrict UpSet plot to these tests

Value

No return value. This function is called for the side effect of creating an UpSet plot.

getFavicons *Get favicon URLs for table linkouts*

Description

To enhance the display of the linkouts in the app's tables, it can fetch the favicon URL for each website.

Usage

```
getFavicons(linkouts)
```

Arguments

linkouts Character vector or (potentially nested) list of character vectors containing the URLs for the table linkouts.

Value

The URLs to the favicons for each linkout. The output returned will always be the same class and structure as the input.

See Also

[getResultsLinkouts](#), [getEnrichmentsLinkouts](#)

Examples

```
getFavicons("https://reactome.org/content/detail/")
```

getFeatures

Get features from a study

Description

Get features from a study

Usage

```
getFeatures(study, modelID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.

modelID Filter by modelID

quiet Suppress messages (default: FALSE)

libraries The directories to search for installed study packages. If left as NULL (the default), then [installed.packages](#) will use the result of [.libPaths](#).

Value

A data frame (if modelID is specified) or a list of data frames. All the columns will be character strings, even if the values appear numeric.

getInstalledStudies *Get installed OmicNavigator studies*

Description

Get installed OmicNavigator studies

Usage

```
getInstalledStudies(libraries = NULL)
```

Arguments

`libraries` Character vector of library directories to search for study packages. If NULL, uses `.libPaths`.

Value

Returns a character vector of the installed OmicNavigator study packages

getLinkFeatures *Get the shared features in a network link*

Description

Get the shared features in a network link

Usage

```
getLinkFeatures(study, annotationID, termID1, termID2)
```

Arguments

`study` An OmicNavigator study. Only accepts name of installed study package.
`annotationID` Filter by annotation
`termID1, termID2` Linked terms to find overlapping features

Value

Returns a character vector with the features included in both termIDs (i.e. the intersection)

See Also

[getNodeFeatures](#)

getMapping	<i>Get mapping object from a study</i>
------------	--

Description

Get mapping object from a study

Usage

```
getMapping(study, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument modelID):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[`.

If no data is available, an empty list is returned (`list()`).

getMetaFeatures	<i>Get metaFeatures from a study</i>
-----------------	--------------------------------------

Description

Get metaFeatures from a study

Usage

```
getMetaFeatures(study, modelID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument `modelID`):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]`.

If no data is available, an empty list is returned (`list()`).

getMetaFeaturesLinkouts

Get metaFeatures table linkouts from a study

Description

Get metaFeatures table linkouts from a study

Usage

```
getMetaFeaturesLinkouts(study, modelID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

<code>study</code>	An OmicNavigator study. Either an object of class <code>onStudy</code> , or the name of an installed study package.
<code>modelID</code>	Filter by <code>modelID</code>
<code>quiet</code>	Suppress messages (default: <code>FALSE</code>)
<code>libraries</code>	The directories to search for installed study packages. If left as <code>NULL</code> (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument `modelID`):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]`.

If no data is available, an empty list is returned (`list()`).

getMetaFeaturesTable *Get metaFeatures for a given feature*

Description

Get metaFeatures for a given feature

Usage

```
getMetaFeaturesTable(study, modelID, featureID)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
featureID	Filter by featureID

Value

Returns a data frame with the metaFeatures for the provided featureID. If the featureID is not found in the metaFeatures table, the data frame will have zero rows.

See Also

[addMetaFeatures](#), [getMetaFeatures](#)

getModels *Get models from a study*

Description

Get models from a study

Usage

```
getModels(study, modelID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then installed.packages will use the result of .libPaths .

Value

The object returned depends on the data available and any filters (e.g. the argument `modelID`):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]`.

If no data is available, an empty list is returned (`list()`).

getNodeFeatures	<i>Get the features in a network node</i>
-----------------	---

Description

Get the features in a network node

Usage

```
getNodeFeatures(study, annotationID, termID, libraries = NULL)
```

Arguments

<code>study</code>	An OmicNavigator study. Only accepts name of installed study package.
<code>annotationID</code>	Filter by annotation
<code>termID</code>	Filter by termID
<code>libraries</code>	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

Returns a character vector with the features in the termID

See Also

[getLinkFeatures](#)

getOverlaps *Get overlaps from a study*

Description

Get overlaps from a study

Usage

```
getOverlaps(study, annotationID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
annotationID	Filter by annotation
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then installed.packages will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument modelID):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]]`.

If no data is available, an empty list is returned (`list()`).

getPackageVersion *Get version of OmicNavigator package*

Description

This is a convenience function for the app. It is easier to always call the OmicNavigator package functions via OpenCPU than to call the utils package for this one endpoint.

Usage

```
getPackageVersion()
```

Value

Returns a one-element character vector with the version of the currently installed OmicNavigator R package

getPlots	<i>Get plots from a study</i>
----------	-------------------------------

Description

Get plots from a study

Usage

```
getPlots(study, modelID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class <code>onStudy</code> , or the name of an installed study package.
modelID	Filter by modelID
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument `modelID`):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]`.

If no data is available, an empty list is returned (`list()`).

getPlottingData	<i>Get plotting data</i>
-----------------	--------------------------

Description

This function creates the input data that `plotStudy` passes to custom plotting functions added with `addPlots`. You can use it directly when you are interactively creating your custom plotting functions.

Usage

```
getPlottingData(study, modelID, featureID, testID = NULL, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
featureID	Filter by featureID
testID	Filter by testID
libraries	The directories to search for installed study packages. If left as NULL (the default), then installed.packages will use the result of .libPaths .

Value

Returns a list of 4 data frames:

assays	A data frame that contains the assay measurements, filtered to only include the row(s) corresponding to the input featureID(s) (see getAssays). If multiple featureIDs are requested, the rows are reordered to match the order of this input. The column order is unchanged.
samples	A data frame that contains the sample metadata for the given modelID (see getSamples). The rows are reordered to match the columns of the assays data frame.
features	A data frame that contains the feature metadata, filtered to only include the row(s) corresponding to the input featureID(s) (see getFeatures). If multiple featureIDs are requested, the rows are reordered to match the order of this input (and thus match the order of the assays data frame).
results	A data frame that contains the test results, filtered to only include the row(s) corresponding to the input featureID(s). If multiple featureIDs are requested, the rows are reordered to match the order of this input. The column order is unchanged. If multiple testIDs are provided, they are stored in a list object.

The data frame `results` is only returned if you pass a testID. By default the app will always pass the currently selected testID. To make `results` a list of data frames (one for each testID for the currently selected modelID), set the `plotType` to be "multiTest" when adding the plot with [addPlots](#).

See Also

[addPlots](#), [plotStudy](#)

getReportLink

Get link to report

Description

Get link to report

Usage

```
getReportLink(study, modelID)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID

Value

Returns a one-element character vector with either a path to a report file or a URL to a report web page. If no report is available for the modelID, an empty character vector is returned.

getReports	<i>Get reports from a study</i>
------------	---------------------------------

Description

Get reports from a study

Usage

```
getReports(study, modelID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument modelID):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]`.

If no data is available, an empty list is returned (`list()`).

getResults	<i>Get results from a study</i>
------------	---------------------------------

Description

Get results from a study

Usage

```
getResults(  
  study,  
  modelID = NULL,  
  testID = NULL,  
  quiet = FALSE,  
  libraries = NULL  
)
```

Arguments

study	An OmicNavigator study. Either an object of class <code>onStudy</code> , or the name of an installed study package.
modelID	Filter by modelID
testID	Filter by testID
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument `modelID`):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]`.

If no data is available, an empty list is returned (`list()`).

```
getResultsIntersection  
    getResultsIntersection
```

Description

getResultsIntersection

Usage

```
getResultsIntersection(  
    study,  
    modelID,  
    anchor,  
    mustTests,  
    notTests,  
    sigValue,  
    operator,  
    column  
)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
anchor	The primary test to filter from.
mustTests	The tests whose significant values must be included. (The intersection)
notTests	The tests whose significant values will be removed. (The difference)
sigValue	The significance levels for each column.
operator	The operators for each column.
column	The columns to be thresholded.

Value

Returns a data frame with the results, similar to [getResultsTable](#). Only rows that pass all the filters are included. The new column Set_Membership is a comma-separated field that includes the testIDs in which the featureID passed the filters.

See Also

[getResultsTable](#)

getResultsLinkouts *Get results table linkouts from a study*

Description

Get results table linkouts from a study

Usage

```
getResultsLinkouts(study, modelID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument modelID):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[]`.

If no data is available, an empty list is returned (`list()`).

getResultsTable *Get results table from a study*

Description

Get results table from a study

Usage

```
getResultsTable(study, modelID, testID, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
testID	Filter by testID
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

A data frame which includes the columns from the features table followed by the columns from the results table. All the columns from the features table will be character strings, even if the values appear numeric.

getResultsUpset	<i>getResultsUpset</i>
-----------------	------------------------

Description

getResultsUpset

Usage

```
getResultsUpset(study, modelID, sigValue, operator, column, legacy = FALSE)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
sigValue	The significance levels for each column.
operator	The operators for each column.
column	The columns to be thresholded.
legacy	Use legacy code (for testing purposes only)

Value

Invisibly returns the output from `upset`

getSamples	<i>Get samples from a study</i>
------------	---------------------------------

Description

Get samples from a study

Usage

```
getSamples(study, modelID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument modelID):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[]`.

If no data is available, an empty list is returned (`list()`).

getTests	<i>Get tests from a study</i>
----------	-------------------------------

Description

Get tests from a study

Usage

```
getTests(study, modelID = NULL, testID = NULL, quiet = FALSE, libraries = NULL)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID
testID	Filter by testID
quiet	Suppress messages (default: FALSE)
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

The object returned depends on the data available and any filters (e.g. the argument `modelID`):

If no filters are specified, then the object returned is a nested list, similar to the original input object.

If one or more filters are applied, then only a subset of the original nested list is returned. Technically, each filter applied is used to subset the original nested list using `[[]]`.

If no data is available, an empty list is returned (`list()`).

getUpsetCols

getUpsetCols

Description

Determine the common columns across all tests of a model that are available for filtering with UpSet.

Usage

```
getUpsetCols(study, modelID)
```

Arguments

study	An OmicNavigator study. Either an object of class onStudy, or the name of an installed study package.
modelID	Filter by modelID

Value

Returns a character vector with the names of the common columns

group	<i>group from Bioconductor workflow RNAseq123</i>
-------	---

Description

A subset of the object `group` from Bioconductor workflow RNAseq123.

Usage

```
group
```

Format

A factor with 3 levels:

Basal Basal cells

LP Luminal progenitor cells

ML Mature luminal cells

Source

<https://bioconductor.org/packages/release/workflows/vignettes/RNAseq123/inst/doc/limmaWorkflow.html>

References

Law CW, Alhamdoosh M, Su S, Dong X, Tian L, Smyth GK, Ritchie ME. [RNA-seq analysis is easy as 1-2-3 with limma, Glimma and edgeR \[version 3; peer review: 3 approved\]](#). F1000Research 2018, 5:1408 doi: [10.12688/f1000research.9005.3](https://doi.org/10.12688/f1000research.9005.3)

Sheridan, J.M., Ritchie, M.E., Best, S.A. et al. [A pooled shRNA screen for regulators of primary mammary stem and progenitor cells identifies roles for *Asap1* and *Prox1*](#). BMC Cancer 2015, 15:221 doi: [10.1186/s128850151187z](https://doi.org/10.1186/s128850151187z)

Examples

```
table(group)
str(group)
```

importStudy	<i>Import a study package</i>
-------------	-------------------------------

Description

Create an onStudy object by importing an installed study package

Usage

```
importStudy(study, libraries = NULL)
```

Arguments

study	Named of an installed OmicNavigator study
libraries	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Value

Returns the onStudy object imported from the OmicNavigator study package

installApp	<i>Install the OmicNavigator web app</i>
------------	--

Description

In order to run the OmicNavigator web app on your local machine, the app must be installed in the `www/` subdirectory of the R package. If you installed the release tarball from the GitHub Releases page, then you already have the app installed. If you installed directly from GitHub with `install_github`, or if you want to use a different version of the app, you can manually download and install the app.

Usage

```
installApp(version = NULL, overwrite = FALSE, lib.loc = NULL, ...)
```

Arguments

version	Version of the web app to install, e.g. "1.0.0"
overwrite	Should an existing installation of the app be overwritten?
lib.loc	a character vector with path names of R libraries. See 'Details' for the meaning of the default value of NULL.
...	Passed to <code>download.file</code> . If the download fails, you may need to adjust the download settings for your operating system. For example, to download with <code>wget</code> , pass the argument <code>method = "wget"</code> .

Value

A one-element character vector with the absolute path to the directory in which the app files were installed

<code>installStudy</code>	<i>Install a study as an R package</i>
---------------------------	--

Description

Install a study as an R package

Usage

```
installStudy(study, library = .libPaths()[1])
```

Arguments

<code>study</code>	An OmicNavigator study to install (class <code>onStudy</code>)
<code>library</code>	Directory to install package. Defaults to first directory returned by <code>.libPaths</code> .

Value

Invisibly returns the original `onStudy` object that was passed to the argument `study`

<code>lane</code>	<i>lane from Bioconductor workflow RNAseq123</i>
-------------------	--

Description

A subset of the object `lane` from Bioconductor workflow `RNAseq123`.

Usage

```
lane
```

Format

A factor with 3 levels:

L004 Sample sequenced on lane 4

L006 Sample sequenced on lane 6

L008 Sample sequenced on lane 8

Source

<https://bioconductor.org/packages/release/workflows/vignettes/RNAseq123/inst/doc/limmaWorkflow.html>

References

Law CW, Alhamdoosh M, Su S, Dong X, Tian L, Smyth GK, Ritchie ME. *RNA-seq analysis is easy as 1-2-3 with limma, Glimma and edgeR [version 3; peer review: 3 approved]*. F1000Research 2018, 5:1408 doi: [10.12688/f1000research.9005.3](https://doi.org/10.12688/f1000research.9005.3)

Sheridan, J.M., Ritchie, M.E., Best, S.A. et al. *A pooled shRNA screen for regulators of primary mammary stem and progenitor cells identifies roles for *Asap1* and *Prox1**. BMC Cancer 2015, 15:221 doi: [10.1186/s128850151187z](https://doi.org/10.1186/s128850151187z)

Examples

```
table(lane)
str(lane)
```

lcpm

lcpm from Bioconductor workflow RNAseq123

Description

A subset of the object lcpm from Bioconductor workflow RNAseq123.

Usage

```
lcpm
```

Format

A matrix with 24 rows and 9 columns

Source

<https://bioconductor.org/packages/release/workflows/vignettes/RNAseq123/inst/doc/limmaWorkflow.html>

References

Law CW, Alhamdoosh M, Su S, Dong X, Tian L, Smyth GK, Ritchie ME. *RNA-seq analysis is easy as 1-2-3 with limma, Glimma and edgeR [version 3; peer review: 3 approved]*. F1000Research 2018, 5:1408 doi: [10.12688/f1000research.9005.3](https://doi.org/10.12688/f1000research.9005.3)

Sheridan, J.M., Ritchie, M.E., Best, S.A. et al. *A pooled shRNA screen for regulators of primary mammary stem and progenitor cells identifies roles for *Asap1* and *Prox1**. BMC Cancer 2015, 15:221 doi: [10.1186/s128850151187z](https://doi.org/10.1186/s128850151187z)

Examples

```
head(lcpm)
str(lcpm)
```

<code>listStudies</code>	<i>List available studies and their metadata</i>
--------------------------	--

Description

List available studies and their metadata

Usage

```
listStudies(libraries = NULL)
```

Arguments

`libraries` The directories to search for installed study packages. If left as NULL (the default), then `installed.packages` will use the result of `.libPaths`.

Value

Returns a nested list with one element per installed OmicNavigator study package. Each study package entry has the following sublist components:

<code>name</code>	(character) Name of the study
<code>package</code>	(list) The fields from DESCRIPTION
<code>results</code>	(nested list) The testIDs available for each modelID
<code>enrichments</code>	(nested list) The annotationIDs available for each modelID
<code>plots</code>	(nested list) The plotIDs available for each modelID

Mm.c2

Mm.c2 from Bioconductor workflow RNAseq123

Description

A subset of the object Mm.c2 from Bioconductor workflow RNAseq123.

Usage

```
Mm.c2
```

Format

A list of 4 character vectors

Source

<https://bioconductor.org/packages/release/workflows/vignettes/RNAseq123/inst/doc/limmaWorkflow.html>

References

Law CW, Alhamdoosh M, Su S, Dong X, Tian L, Smyth GK, Ritchie ME. [RNA-seq analysis is easy as 1-2-3 with limma, Glimma and edgeR \[version 3; peer review: 3 approved\]](#). F1000Research 2018, 5:1408 doi: [10.12688/f1000research.9005.3](https://doi.org/10.12688/f1000research.9005.3)

Sheridan, J.M., Ritchie, M.E., Best, S.A. et al. [A pooled shRNA screen for regulators of primary mammary stem and progenitor cells identifies roles for *Asap1* and *Prox1*](#). BMC Cancer 2015, 15:221 doi: [10.1186/s128850151187z](https://doi.org/10.1186/s128850151187z)

Examples

```
Mm.c2[[1]]  
str(Mm.c2)
```

OmicNavigator

OmicNavigator

Description

Package options to control package-wide behavior are described below.

Details

The default prefix for OmicNavigator study packages is "ONstudy". If you would prefer to use a different prefix, you can change the package option `OmicNavigator.prefix`. For example, to use the prefix "OmicNavigatorStudy", you could add the following line to your `.Rprofile` file.

```
options(OmicNavigator.prefix = "OmicNavigatorStudy")
```

`plotStudy`*Plot a feature using a custom plotting function*

Description

Plot a feature using a custom plotting function

Usage

```
plotStudy(study, modelID, featureID, plotID, testID = NULL, libraries = NULL)
```

Arguments

<code>study</code>	An OmicNavigator study. Either an object of class <code>onStudy</code> , or the name of an installed study package.
<code>modelID</code>	Filter by modelID
<code>featureID</code>	Filter by featureID
<code>plotID</code>	Filter by plotID
<code>testID</code>	Filter by testID
<code>libraries</code>	The directories to search for installed study packages. If left as NULL (the default), then <code>installed.packages</code> will use the result of <code>.libPaths</code> .

Details

The arguments `study`, `modelID`, `featureID`, and `testID` are passed to the function `getPlottingData`, and the nested list returned by this function is passed as the first argument to your custom plotting function. By default, the app will pass a single `featureID` unless the `plotType` is "multiFeature". Similarly, the app will pass a single `testID` unless the `plotType` is "multiTest". You can specify the `plotType` when you add a plot with `addPlots`.

Value

This function is called for the side effect of creating a plot. However, it also invisibly returns the original `onStudy` object passed to `study`.

See Also

`addPlots`, `getPlottingData`

removeStudy	<i>Remove an installed study R package</i>
-------------	--

Description

Remove an installed study R package

Usage

```
removeStudy(study, library = .libPaths()[1])
```

Arguments

study	The name of the study or an onStudy object. Do not include the prefix of the installed package, e.g. ONstudy.
library	Directory where the study package is installed. Defaults to first directory returned by <code>.libPaths</code> .

Value

Invisibly returns the path of the removed study package

samplenames	<i>samplenames from Bioconductor workflow RNAseq123</i>
-------------	---

Description

A subset of the object `samplenames` from Bioconductor workflow RNAseq123.

Usage

```
samplenames
```

Format

A character vector containing the unique sample identifiers

Source

<https://bioconductor.org/packages/release/workflows/vignettes/RNAseq123/inst/doc/limmaWorkflow.html>

References

Law CW, Alhamdoosh M, Su S, Dong X, Tian L, Smyth GK, Ritchie ME. [RNA-seq analysis is easy as 1-2-3 with limma, Glimma and edgeR \[version 3; peer review: 3 approved\]](#). F1000Research 2018, 5:1408 doi: [10.12688/f1000research.9005.3](#)

Sheridan, J.M., Ritchie, M.E., Best, S.A. et al. [A pooled shRNA screen for regulators of primary mammary stem and progenitor cells identifies roles for *Asap1* and *Prox1*](#). BMC Cancer 2015, 15:221 doi: [10.1186/s128850151187z](#)

Examples

```
head(samplenames)
str(samplenames)
```

startApp	<i>Start app on local machine</i>
----------	-----------------------------------

Description

After you have installed at least one OmicNavigator study package with [installStudy](#), you can explore the results in the app. The function `startApp` starts a local instance of the app running on your current machine. It will automatically open the app in your default browser. For the best experience, use Google Chrome. From the dropdown menu, you will be able to select from any of the studies you have installed on your machine. When you are finished, you can stop the web server by returning to the R console and pressing the Esc key (Windows) or Ctrl-C (Linux, macOS).

Usage

```
startApp(...)
```

Arguments

... extra parameters passed to [ocpu_start_server](#)

Details

Note that the app can't be run from within RStudio Server.

The app requires some additional R packages to run. If you receive an error about a missing package, please install it with [install.packages](#). To ensure you have all the extra packages installed, you can run the command below:

```
install.packages(c("faviconPlease", "opencpu", "UpSetR"))
```

Value

No return value. This function is only called for the side effect of running a local instance of the app.

summary.onStudy	<i>Summarize elements of OmicNavigator study</i>
-----------------	--

Description

Displays a tree-like summary of the elements that have been added to an OmicNavigator study.

Usage

```
## S3 method for class 'onStudy'  
summary(object, elements = NULL, ...)
```

Arguments

object	OmicNavigator study object (class onStudy)
elements	Subset the output to only include specific elements of the study, e.g. c("results", "enrichments")
...	Currently unused

Value

Invisibly returns the original onStudy object

validateStudy	<i>Validate a study</i>
---------------	-------------------------

Description

Validate a study

Usage

```
validateStudy(study)
```

Arguments

study	An OmicNavigator study object
-------	-------------------------------

Value

For a valid study object, the logical value TRUE is invisibly returned. For an invalid study object, there is no return value because an error is thrown.

Index

* datasets

- basal.vs.lp, 19
- basal.vs.ml, 20
- cam.BasalvsLP, 21
- cam.BasalvsML, 22
- group, 52
- lane, 54
- lcpm, 55
- Mm.c2, 56
- samplenames, 59
- .libPaths, 28, 30–34, 36, 38–46, 48–51, 53, 54, 56, 58, 59
- [[, 28, 30, 31, 33, 38, 39, 41–43, 45, 46, 48, 50, 51

addAnnotations, 3, 6, 7, 24, 26

addAssays, 4, 26

addBarcodes, 5, 26, 29

addEnrichments, 6, 7, 26

addEnrichmentsLinkouts, 6, 26

addFeatures, 4, 8, 10, 16, 24, 26

addMapping, 8, 26

addMetaFeatures, 9, 10, 11, 26, 40

addMetaFeaturesLinkouts, 10, 26

addModels, 11, 26

addOverlaps, 12

addPlots, 13, 26, 43, 44, 58

addReports, 14, 26

addResults, 15, 26

addResultsLinkouts, 15, 26

addSamples, 4, 17, 24, 26

addTests, 6, 17, 24, 26

basal.vs.lp, 19

basal.vs.ml, 20

cam.BasalvsLP, 21

cam.BasalvsML, 22

createStudy, 4–10, 12–18, 23

download.file, 53

exportStudy, 26, 27

getAnnotations, 27

getAssays, 28, 44

getBarcodeData, 29

getBarcodes, 29, 30

getEnrichments, 30

getEnrichmentsIntersection, 31

getEnrichmentsLinkouts, 32, 36

getEnrichmentsNetwork, 33

getEnrichmentsTable, 32, 34

getEnrichmentsUpset, 35

getFavicons, 35

getFeatures, 36, 44

getInstalledStudies, 37

getLinkFeatures, 37, 41

getMapping, 38

getMetaFeatures, 38, 40

getMetaFeaturesLinkouts, 39

getMetaFeaturesTable, 40

getModels, 40

getNodeFeatures, 37, 41

getOverlaps, 42

getPackageVersion, 42

getPlots, 43

getPlottingData, 9, 14, 43, 58

getReportLink, 44

getReports, 45

getResults, 46

getResultsIntersection, 47

getResultsLinkouts, 36, 48

getResultsTable, 47, 48

getResultsUpset, 49

getSamples, 44, 50

getTests, 50

getUpsetCols, 51

group, 52

importStudy, 53

install.packages, 60

installApp, [53](#)
installed.packages, [28](#), [30–34](#), [36](#), [38–46](#),
[48–51](#), [53](#), [56](#), [58](#)
installStudy, [26](#), [54](#), [60](#)

lane, [54](#)
lcpm, [55](#)
listStudies, [56](#)

Mm.c2, [56](#)

ocpu_start_server, [60](#)
OmicNavigator, [57](#)

plotStudy, [9](#), [14](#), [43](#), [44](#), [58](#)

removeStudy, [59](#)

samplenames, [59](#)
startApp, [60](#)
summary.onStudy, [61](#)

upset, [49](#)

validateStudy, [27](#), [61](#)