

# Package ‘SWMPPrExtension’

October 13, 2021

**Type** Package

**Title** Functions for Analyzing and Plotting Estuary Monitoring Data

**Version** 2.1.0

**Maintainer** Dave Eslinger <dave.eslinger@noaa.gov>

**Description** Tools for performing routine analysis and plotting tasks with environmental data from the System Wide Monitoring Program of the National Estuarine Research Reserve System <<http://cdmo.baruch.sc.edu/>>. This package builds on the functionality of the SWMPPr package <<https://cran.r-project.org/package=SWMPPr>>, which is used to retrieve and organize the data. The combined set of tools address common challenges associated with continuous time series data for environmental decision making, and are intended for use in annual reporting activities.

References:

Beck, Marcus W. (2016) <ISSN 2073-

4859><<https://journal.r-project.org/archive/2016-1/beck.pdf>>

Rudis, Bob (2014) <<https://rud.is/b/2014/11/16/moving-the-earth-well-alaska-hawaii-with-r/>>.

United States Environmental Protection Agency (2015) <[https://cfpub.epa.gov/si/si\\_public\\_record\\_Report.cfm?Lab=OWOW&dirEntryId=327030](https://cfpub.epa.gov/si/si_public_record_Report.cfm?Lab=OWOW&dirEntryId=327030)>.

United States Environmental Protection Agency (2012) <<http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.646.1973&rep=rep1&type=pdf>>.

**BugReports** <https://github.com/NOAA-OCM/SWMPPrExtension/issues>

**License** CC0

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 4.0), SWMPPr

**Imports** EnvStats, RColorBrewer, broom, dplyr, flextable, ggplot2, ggthemes, grDevices, lubridate, magrittr, methods, officer, purrr, rlang, scales, sf, stats, tidyselect, tidyr, utils

**Suggests** ggmap

**RoxygenNote** 7.1.2

**NeedsCompilation** no

**Author** Julie Padilla [aut, ctb],  
 Marcus Beck [ctb],  
 Kimberly Cressman [ctb],  
 Dave Eslinger [cre, ctb],  
 Bob Rudis [ctb]

**Repository** CRAN

**Date/Publication** 2021-10-13 17:12:03 UTC

## R topics documented:

annual_range . . . . .	3
assign_season . . . . .	5
base_map . . . . .	6
cbm_spatial . . . . .	8
counties_4269 . . . . .	8
create_sk_flextable_list . . . . .	9
create_sk_national_ft_reserves . . . . .	10
create_sk_national_ft_results . . . . .	11
elkmmnut . . . . .	12
elksmwq . . . . .	13
elk_spatial . . . . .	13
ft_col_names . . . . .	14
generate_results_table . . . . .	15
generate_station_table . . . . .	15
geographic_unique_stations . . . . .	16
get_reserve . . . . .	17
get_shp_name . . . . .	18
get_sites . . . . .	18
get_site_code . . . . .	19
get_site_coordinates . . . . .	20
historical_daily_range . . . . .	20
historical_range . . . . .	22
import_local_nut . . . . .	24
lm_p_labs . . . . .	26
load_shp_file . . . . .	27
national_sk_map . . . . .	27
raw_boxplot . . . . .	29
remove_inf_and_nan . . . . .	30
reserve_locs . . . . .	31
res_custom_map . . . . .	32
res_custom_sk_map . . . . .	34
res_local_map . . . . .	36
res_national_map . . . . .	38
res_sk_map . . . . .	40
sampling_stations . . . . .	42
sampling_stations_backup . . . . .	43
seasonal_barplot . . . . .	43

<i>annual_range</i>	3
seasonal_boxplot . . . . .	45
seasonal_dot . . . . .	48
set_date_breaks . . . . .	50
set_date_breaks_minor . . . . .	51
set_date_break_labs . . . . .	51
sk_seasonal . . . . .	52
sk_tidy . . . . .	54
std_param_check . . . . .	54
summarise_handoff_files . . . . .	55
threshold_criteria_plot . . . . .	56
threshold_identification . . . . .	59
threshold_percentile_plot . . . . .	61
threshold_summary . . . . .	63
title_labeler . . . . .	66
update_sampling_stations . . . . .	66
us_4269 . . . . .	67
y_count_labeler . . . . .	68
y_labeler . . . . .	69
<b>Index</b>	<b>71</b>

---

<i>annual_range</i>	<i>Annual Range Timeseries</i>
---------------------	--------------------------------

---

## Description

Assess variability within each season for a single year

## Usage

```
annual_range(swmpr_in, ...)

## S3 method for class 'swmpr'
annual_range(
  swmpr_in,
  param = NULL,
  target_yr = NULL,
  criteria = NULL,
  free_y = FALSE,
  log_trans = FALSE,
  converted = FALSE,
  criteria_lab = "WQ Threshold",
  plot_title = FALSE,
  plot = TRUE,
  ...
)
```

**Arguments**

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See <a href="#">assign_season</a>
param	chr string of variable to plot
target_yr	numeric, the target year that should be compared against the historic range. If target year is not specified then the dot will not be plotted.
criteria	numeric, a numeric criteria that will be plotted as a horizontal line
free_y	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See <a href="#">y_labeler</a> for details.
criteria_lab	chr, label for the threshold criteria defined in <code>criteria</code> . Defaults to "WQ Threshold"
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE

**Details**

This function summarizes average daily values, average daily minimums/maximums, and absolute minimums/maximums across user-defined seasons for a target year (`target_yr`).

The user also has the option to add a threshold hold line using the `criteria` argument. Typically, this value is a water quality threshold, which is why `criteria_lab` defaults to 'WQ Threshold'. However, the user has the option to specify any other type of threshold they wish. when doing so, the value for `criteria_lab` should be changed accordingly.

**Value**

Returns a [ggplot](#) object

**Author(s)**

Julie Padilla

**See Also**

[ggplot](#), [assign\\_season](#), [y\\_labeler](#)

**Examples**

```
## get data, prep
data(elksmwq)
dat <- elksmwq
```

```

dat <- qaqc(elksmwq, qaqc_keep = c('0', '3', '5'))
do_plt <- annual_range(dat, param = 'do_mgl', target_yr = 2012)
do_plt <- annual_range(dat, param = 'do_mgl', target_yr = 2012, criteria = 2)

```

---

assign\_season

*Assign seasons to SWMP sampling data*


---

## Description

Assign seasons to SWMP sampling data on a monthly basis or user-defined seasonal basis

## Usage

```

assign_season(
  data,
  season_grps = NULL,
  season_names = NULL,
  season_start = NULL,
  abb = TRUE
)

```

## Arguments

data	a vector of POSIXct dates
season_grps	A list of seasons. Months (1-12) are assigned to different groups based on user preference. Defaults to 12 months, starting with January. Must assign a minimum of two seasons
season_names	A string vector of season names. The number of season names must match the length of the season list. A minimum of two seasons must be assigned (e.g., 'Wet', 'Dry'). Defaults to 12 months, starting with January. The number of season names must match the number of seasons
season_start	defaults to 12 months, starting with January
abb	logical, should abbreviations for month names be used? Defaults to TRUE

## Details

A helper function used by multiple data analyses to assign seasons to sampling data and to order the seasons. To assist with plotting, the seasons are assigned as factors. Seasons are assigned by first grouping the months into a list of `season_grps` and then specifying one name for each grouping using `season_names`. If `season_grps` is specified then `season_names` must also be defined. If neither argument is specified then the season assignments will default to monthly values. Using the `season_start` argument, the user can designate which season should be the first factor level. This assignment affects plot order for most functions. If `season_start` is not specified, then it will default to the first season in the list (January for monthly seasons and the first season in `season_names` for user-defined seasons).

**Value**

Returns a vector of ordered season factors.

**Author(s)**

Julie Padilla

**Examples**

```
data(elksmwq)
dat <- elksmwq

seas <- assign_season(dat$datetimestamp, abb = FALSE)
levels(seas)

seas <- assign_season(dat$datetimestamp, abb = TRUE)
levels(seas)

seas <- assign_season(dat$datetimestamp, season_start = 'Mar')
levels(seas)

seas <- assign_season(dat$datetimestamp, abb = FALSE, season_start = 'March')
levels(seas)

seas <- assign_season(dat$datetimestamp,
  season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12)),
  season_names = c('Winter', 'Spring', 'Summer', 'Fall'), season_start = 'Spring')
levels(seas)

seas <- assign_season(dat$datetimestamp, season_grps = list(c(10:12, 1:3), c(4:9)),
  season_names = c('Wet', 'Dry'))
levels(seas)
```

---

base\_map

*Create background map*

---

**Description**

Create a background map from a bounding box using Stamen Map tiles or a crude vector-based map.

**Usage**

```
base_map(
  bbox,
  bg_crs = 4326,
  vector_only = FALSE,
  maptype = "toner-lite",
  zoom = NULL,
  ...
)
```

**Arguments**

bbox	Bounding box vector.
bg_crs	EPSG code or st_crs object for the returned map.
vector_only	Logical, draw only a simple vector-based map.
maptype	Background map type from Stamen Maps ( <a href="http://maps.stamen.com/">http://maps.stamen.com/</a> ); one of c("terrain", "terrain-background", "terrain-labels", "terrain-lines", "toner", "toner-2010", "toner-2011", "toner-background", "toner-hybrid", "toner-labels", "toner-lines", "toner-lite", "watercolor").
zoom	Zoom level for the base map created when bg_map is not specified. An integer value, 5 - 15, with higher numbers providing more detail. If not provided, a zoom level is autoscaled based on bbox parameters.
...	Additional arguments to be passed to ggmap::get_stamenmap

**Details**

A helper, or stand-alone, function to create background map based on based on raster map tiles retrieved with ggmap::get\_stamenmap. If ggmap is unavailable, the function creates a basic map using county-level polygon files. This map is fairly crude and should be considered a placeholder.

**Value**

Returns a ggplot2 object.

**Author(s)**

Dave Eslinger

**Examples**

```
# Simple, low-zoom map for testing
bound_box <- c(-77.393, 38.277, -75.553, 39.741)
(x <- base_map(bound_box, zoom = 7))

# Default zoom map with terrain maptpe.
y <- base_map(bound_box, maptpe = 'terrain')
```

---

`cbm_spatial`*Spatial Data from Chesapeake Bay - Maryland*

---

**Description**

Shapefile for Chesapeake Bay - Maryland reserve boundary

**Usage**

```
data(cbm_spatial)
```

**Format**

A [SpatialPolygons](#) object

**Source**

[CDMO](#)

**References**

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>; accessed 08 October 2016

---

`counties_4269`*US County Map*

---

**Description**

US County boundaries from the US Census Bureau's MAF/TIGER geographic database in EPSG:4269, with all data except state FIPS codes and land area removed.

**Usage**

```
data('counties_4269')
```

**Format**

A `sf` `{DataFrame}` object

**Source**

[US Census Bureau](#)



## References

United States Census Bureau. Data accessed from the US Census Bureau website: <https://www2.census.gov/geo/tiger/GENZ>  
accessed 13 March 2020

---

create\_sk\_flextable\_list

*Create a List of Flextable Objects*

---

## Description

Create a list of flextable objects to display Seasonal Kendall results in the NERRS reserve level template

## Usage

```
create_sk_flextable_list(
  sk_result,
  stations,
  param,
  trend_col = c("#247BA0", "#A3DFFF", "#D9D9D9", "white"),
  font_col_default = "#444E65",
  font_sz_stn = 6,
  font_sz_result = 12,
  font_sz_head = 6,
  ht_head = 0.28,
  ht_body = 0.202,
  is_swmp = TRUE,
  stn_name = NULL,
  stn_abbrev = NULL,
  par_name = NULL
)
```

## Arguments

sk_result	a data.frame of reformatted results from <a href="#">sk_seasonal</a>
stations	chr, vector of stations to be displayed
param	chr, vector of parameters to be displayed
trend_col	chr, a four element vector that specifies colors for increasing, decreasing, no change, and insufficient data trends
font_col_default	chr, default color to be used for trend table
font_sz_stn	int, specify the font size of displayed station names
font_sz_result	int, specify the font size of the displayed results
font_sz_head	int, specify the font size of the table header row

ht_head	num, specify the cell height of the table body rows. Units for this parameter are in inches.
ht_body	num, specify the cell height of the table header row. Units for this parameter are in inches.
is_swmp	logical, are the station names and parameter names consistent with SWMP station and parameter names? If either of these conditions is false then this parameter should be set to FALSE and then the user should define stn_name, stn_abbrev, and par_name. default is TRUE.
stn_name	chr, a list of full station names that the user would like to add to the trend table (e.g., "Cat Point")
stn_abbrev	chr, a list of station abbreviations that the user would like to add to the trend table (e.g., "CP" as an abbreviation for Cat Point).
par_name	chr, a list of parameter names to be used if the names do not match standard CDMO parameters.

### Details

This function is intended for internal use with the NERRS reserve level reporting scripts. Using the results from the reserve level trend analysis, `create_sk_flextable_list` creates a list of two `flextable` objects to be displayed in the NERRS reserve level template. The first `flextable` in the list contains the two-letter station IDs for each station and the full location name of each station. The second table lists the seasonal kendall results and the names of the parameters of interest.

### Value

Returns a list of `flextable` objects

### Author(s)

Julie Padilla

---

`create_sk_national_ft_reserves`

*Create a Flextable Object of Reserve Names*

---

### Description

Create a `flextable` of reserve names for use with the NERRS national level template.

### Usage

```
create_sk_national_ft_reserves(
  sk_result,
  font_sz_stn = 8,
  font_sz_head = 8,
  ht_head = 0.75,
  ht_body = 0.2
)
```

**Arguments**

sk_result	a data.frame of reformatted results from <a href="#">sk_seasonal</a>
font_sz_stn	int, specify the font size of displayed station names
font_sz_head	int, specify the font size of the table header row
ht_head	num, specify the cell height of the table body rows. Units for this parameter are in inches.
ht_body	num, specify the cell height of the table header row. Units for this parameter are in inches.

**Details**

This function is intended for internal use with the NERRS national level reporting scripts. Using results from the reserve level trend analyses, `create_sk_national_ft_reserves` creates a `flextable` object of reserve names for display in the NERRS national level template.

**Value**

Returns a `flextable` object

**Author(s)**

Julie Padilla

---

`create_sk_national_ft_results`

*Create a Flextable Object of Seasonal Kendall Results*

---

**Description**

Create a flextable object to display Seasonal Kendall results for each reserve in the NERRS national level template

**Usage**

```
create_sk_national_ft_results(  
  sk_result,  
  param,  
  font_sz_result = 12,  
  font_sz_head = 8,  
  ht_head = 0.375,  
  ht_body = 0.2  
)
```

**Arguments**

sk_result	a <code>data.frame</code> of reformatted results generated by national Level template scripts from reserve level handoff files
param	chr, the name of the parameter that corresponds to the seasonal kendall results in sk_result
font_sz_result	int, specify the font size of the displayed results
font_sz_head	int, specify the font size of the table header row
ht_head	num, specify the cell height of the table body rows. Units for this parameter are in inches.
ht_body	num, specify the cell height of the table header row. Units for this parameter are in inches.

**Details**

This function is intended for internal use with the NERRS national level reporting scripts. Using results from the reserve level trend analyses, `create_sk_national_ft_results` creates a `flextable` object of seasonal kendall results to be displayed in the NERRS national level template.

**Value**

Returns a `flextable` object

**Author(s)**

Julie Padilla

---

elkmmnut

*Nutrient Data from Elkhorn Slough - North Marsh Station*

---

**Description**

Monthly nutrient data from Elkhorn Slough North Marsh station

**Usage**

```
data(elkmmnut)
```

**Format**

A `data.frame` object

**Source**

CDMO

**References**

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>; accessed 08 October 2016

---

elksmwq

*Water Quality Data from Elkhorn Slough - South Marsh Station*

---

**Description**

Water Quality data from Elkhorn Slough South Marsh station

**Usage**

`data(elksmwq)`

**Format**

A `data.frame` object

**Source**

CDMO

**References**

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>; accessed 08 October 2016

---

elk\_spatial

*Spatial Data from Elkhorn Slough*

---

**Description**

Shapefile for Elkhorn Slough reserve boundary

**Usage**

`data(elk_spatial)`

**Format**

A `SpatialPolygons` object

**Source**

CDMO

**References**

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program. Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>; accessed 08 October 2016

---

ft\_col\_names

*Convert Parameter Abbreviations*

---

**Description**

Convert SWMPr parameter abbreviations into formats appropriate for use with NERRS reserve level template [flextable](#)

**Usage**

```
ft_col_names(param)
```

**Arguments**

param            chr, vector of parameter abbreviations

**Details**

A helper function used internally by [create\\_sk\\_flextable\\_list](#) to label [flextable](#) columns in the trend table for the reserve level report.

**Value**

Returns a `data.frame` of user-specified results to be displayed

**Author(s)**

Julie Padilla

---

`generate_results_table`*Filter Reformatted Seasonal Kendall Results*

---

**Description**

Filters a dataframe of user-specified results for display in the NERRS reserve level report

**Usage**

```
generate_results_table(sk_result, stations, param)
```

**Arguments**

<code>sk_result</code>	a <code>data.frame</code> of reformatted seasonal kendall results from <a href="#">sk_seasonal</a> .
<code>stations</code>	<code>chr</code> , vector of station names included in <code>sk_result</code> that will be displayed in the NERRS reserve level report
<code>param</code>	<code>chr</code> , vector of parameters included in <code>sk_result</code> that will be displayed in the NERRS reserve level report

**Details**

A helper function used internally by [create\\_sk\\_flexable\\_list](#) to create a `data.frame` of user specified parameters to be displayed in the reserve level report.

**Value**

Returns a `data.frame` of user-specified results to be displayed

**Author(s)**

Julie Padilla

---

`generate_station_table`*Filter Reformatted Seasonal Kendall Results*

---

**Description**

Filters a dataframe of user-specified results for display in the NERRS reserve level report

**Usage**

```
generate_station_table(sk_result, stations)
```

**Arguments**

`sk_result` a `data.frame` of reformatted seasonal kendall results from [sk\\_seasonal](#).  
`stations` `chr`, vector of stations listed in `sk_result` that should be displayed in the NERRS reserve level report

**Details**

Used internally by [create\\_sk\\_flexable\\_list](#) to create a `data.frame` of user specified parameters to be displayed

**Value**

Returns a `data.frame` of user-specified results to be displayed

**Author(s)**

Julie Padilla

---

`geographic_unique_stations`

*Return a vector of geographically unique NERR Stations*

---

**Description**

Creates an alphabetically sorted, vector of geographically unique stations for mapping

**Usage**

```
geographic_unique_stations(nerr_site_id)
```

**Arguments**

`nerr_site_id` `chr` vector of valid NERR stations

**Details**

This function is intended for internal use with the NERRS reserve level reporting scripts and is used along with [res\\_local\\_map](#). It takes a vector of NERR site ids and only returns geographically unique locations.

**Value**

returns a vector of NERR stations

**Author(s)**

Julie Padilla



**Examples**

```
stns <- c('apacpnut', 'apacpwq', 'apadbnut', 'apadbwq', 'apaebmet',  
'apaebnut', 'apaebwq', 'apaesnut', 'apaeswq')  
  
geographic_unique_stations(stns)
```

---

get_reserve	<i>Identify NERRS reserve from metadata</i>
-------------	---

---

**Description**

Identify the NERRS reserve from metadata in the data file

**Usage**

```
get_reserve(data.file)
```

**Arguments**

data.file      location of data

**Details**

This function is intended for internal use with the NERRS reserve level reporting scripts. It determines the name of the full name of the NERRS reserve associated with the data in the user-specified data folder.

**Value**

Returns a character string of the full reserve name

**Author(s)**

Julie Padilla

---

get_shp_name	<i>Identify shapefile for NERRS reserve</i>
--------------	---

---

**Description**

Identify the shapefile name associated with the reserve in the data file

**Usage**

```
get_shp_name(gis.file.loc)
```

**Arguments**

```
gis.file.loc    path to gis file location
```

**Details**

This function is intended for internal use with the NERRS reserve level reporting scripts. It identifies the name of the shapefile associated with the NERRS reserve.

**Value**

Returns a character string of the shapefile for the reserve boundary

**Author(s)**

Julie Padilla

---

get_sites	<i>Identify NERRS reserve stations from metadata</i>
-----------	--

---

**Description**

Identify the NERRS reserve sampling stations based on the metadata in the data file

**Usage**

```
get_sites(  
  data.file,  
  type = c("wq", "nut", "met"),  
  active = TRUE,  
  primary = TRUE  
)
```

**Arguments**

data.file	location of data
type	chr string of data station type ('wq', 'nut', or 'met')
active	logical. Should inactive stations be excluded? Defaults to TRUE
primary	logical. Should non-primary stations be excluded? Defaults to TRUE

**Details**

This function is intended for internal use with the NERRS reserve level reporting scripts. It returns the sampling stations associated with the data in the user-specified data folder.

**Value**

Returns a character vector of reserve stations

**Author(s)**

Julie Padilla

---

get_site_code	<i>Return NERRS reserve site code based on data in the data file</i>
---------------	--

---

**Description**

Identify the 3-letter NERRS reserve code from metadata in the data file

**Usage**

```
get_site_code(data.file)
```

**Arguments**

data.file	data source location
-----------	----------------------

**Details**

This function is intended for internal use with the NERRS reserve level reporting scripts. It returns the 3-letter reserve code associated with the data in the user-specified data folder.

**Value**

Returns 3-letter, reserve site code as chr

**Author(s)**

Julie Padilla

---

`get_site_coordinates` *Identify NERRS sampling locations from metadata*

---

**Description**

Identify the latitude/longitude for sampling stations based on the metadata in the data file

**Usage**

```
get_site_coordinates(data.file, active = TRUE)
```

**Arguments**

<code>data.file</code>	location of data
<code>active</code>	logical. Only return active stations?

**Details**

This function is intended for internal use with the NERRS reserve level reporting scripts. It returns the names, station codes, and coordinates associated with the data in the user-specified data folder.

**Value**

Returns a dataframe of station ids, station names, lat/long

**Author(s)**

Julie Padilla

---

`historical_daily_range`  
*Historical Daily Range Timeseries*

---

**Description**

Compare daily averages for a target year to historical highs and lows

**Usage**

```
historical_daily_range(swmpr_in, ...)
```

```
## S3 method for class 'swmpr'
historical_daily_range(
  swmpr_in,
  param = NULL,
  hist_rng = NULL,
  target_yr = NULL,
  criteria = NULL,
  free_y = FALSE,
  log_trans = FALSE,
  converted = FALSE,
  criteria_lab = "WQ Threshold",
  plot_title = FALSE,
  plot = TRUE,
  ...
)
```

**Arguments**

swmpr_in	input swmpr object
...	not used
param	chr string of variable to plot
hist_rng	numeric vector, if historic range is not specified then the min/max values of the data set will be used.
target_yr	numeric, the target year that should be compared against the historic range. If target year is not specified then dot will not be plotted
criteria	numeric, a numeric criteria that will be plotted as a horizontal line
free_y	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See y_labeler for details.
criteria_lab	chr, label for the threshold criteria defined in criteria. Defaults to "WQ Threshold"
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE

**Details**

This function compares the average daily minimums/maximums and absolute daily minimums/maximums from a historical range to the average daily value from a target year. If `hist_rng` is not specified then the minimum and maximum years within the data set will be used. If `target_yr` is not specified then only the results for the `hist_rng` will be returned.

The user also has the option to add a threshold line using the `criteria` argument. Typically, this value is a water quality threshold, which is why `criteria_lab` defaults to 'WQ Threshold'. However, the user has the option to specify any other type of threshold they wish. when doing so, the value for `criteria_lab` should be changed accordingly.

**Value**

Returns a [ggplot](#) object

**Author(s)**

Julie Padilla, Kimberly Cressman

**See Also**

[ggplot](#), [y\\_labeler](#)

**Examples**

```
data(apacpwq)
dat <- apacpwq

dat <- qaqc(apacpwq, qaqc_keep = c('0', '3', '5'))
# with criteria
y <- historical_daily_range(dat, param = 'do_mgl', target_yr = 2013, criteria = 2)

# w/o criteria
z <- historical_daily_range(dat, param = 'do_mgl', target_yr = 2013)

# add a y label
zz <- z + labs(x = NULL, y = "Dissolved Oxygen (mg/L)")
```

---

historical\_range

*Historical Monthly/Seasonal Range Timeseries*

---

**Description**

Compare seasonal averages/minimums/maximums for a target year to historical seasonal averages/minimums/maximums

**Usage**

```
historical_range(swmp_r_in, ...)

## S3 method for class 'swmp_r'
historical_range(
  swmp_r_in,
  param = NULL,
  hist_rng = NULL,
  target_yr = NULL,
  criteria = NULL,
  free_y = FALSE,
  log_trans = FALSE,
  converted = FALSE,
  criteria_lab = "WQ Threshold",
  plot_title = FALSE,
  plot = TRUE,
  ...
)
```

**Arguments**

swmp_r_in	input swmp_r object
...	additional arguments passed to other methods. See <a href="#">assign_season</a>
param	chr string of variable to plot
hist_rng	numeric vector, if historic range is not specified then the min/max values of the data set will be used.
target_yr	numeric, the target year that should be compared against the historic range. If target year is not specified then dot will not be plotted
criteria	numeric, a numeric criteria that will be plotted as a horizontal line
free_y	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See <a href="#">y_labeler</a> for details.
criteria_lab	chr, label for the threshold criteria defined in criteria. Defaults to "WQ Threshold"
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE

**Details**

This function summarizes average daily values and average daily minimums/maximums across user-defined seasons for a target year (`target_yr`) and for a historical range (`hist_rng`). If `hist_rng` is not specified then the minimum and maximum years within the data set will be used. If `target_yr` is not specified then only the results for the `hist_rng` will be returned.

The user also has the option to add a threshold hold line using the `criteria` argument. Typically, this value is a water quality threshold, which is why `criteria_lab` defaults to 'WQ Threshold'. However, the user has the option to specify any other type of threshold they wish. when doing so, the value for `criteria_lab` should be changed accordingly.

### Value

Returns a [ggplot](#) object

### Author(s)

Julie Padilla, Kimberly Cressman

### See Also

[ggplot](#), [assign\\_season](#), [y\\_labeler](#)

### Examples

```
data(elksmwq)

dat <- qaqc(elksmwq, qaqc_keep = c('0', '3', '5'))
# with criteria
y <- historical_range(dat, param = 'do_mgl', target_yr = 2013, criteria = 2)

# w/o criteria
z <- historical_range(dat, param = 'do_mgl', target_yr = 2013)

# add a y label
zz <- z + labs(x = NULL, y = "Dissolved Oxygen (mg/L)")
```

---

import\_local\_nut

*Import local CDMO data*

---

### Description

Import local data that were obtained from the CDMO through the zip downloads feature

### Usage

```
import_local_nut(path, station_code, collMethd = c(1, 2), trace = FALSE)
```



### Arguments

path	chr string of full path to .csv files with raw data, can be a zipped or unzipped directory where the former must include the .zip extension
station_code	chr string of station to import, typically 7 or 8 characters including wq, nut, or met extensions, may include full name with year, excluding file extension
collMethd	chr string of nutrient data to subset. 1 indicates monthly, 2 indicates diel. Default is both diel and monthly data.
trace	logical indicating if progress is sent to console, default FALSE

### Details

The function is designed to import local data that were downloaded from the CDMO outside of R. This approach works best for larger data requests, specifically those from the zip downloads feature in the advanced query section of the CDMO. The function may also work using data from the data export system, but this feature has not been extensively tested. The downloaded data will be in a compressed folder that includes multiple .csv files by year for a given data type (e.g., apacpwq2002.csv, apacpwq2003.csv, apacpnut2002.csv, etc.). The import\_local function can be used to import files directly from the compressed folder or after the folder is decompressed. In the former case, the requested files are extracted to a temporary directory and then deleted after they are loaded into the current session. An example dataset is available online to illustrate the format of the data provided through the zip downloads feature. See the link below to access these data. All example datasets included with the package were derived from these raw data.

Occasionally, duplicate time stamps are present in the raw data. The function handles duplicate entries differently depending on the data type (water quality, weather, or nutrients). For water quality and nutrient data, duplicate time stamps are simply removed. Note that nutrient data often contain replicate samples with similar but not duplicated time stamps within a few minutes of each other. Replicates with unique time stamps are not removed but can be further processed using [rem\\_reps](#). Weather data prior to 2007 may contain duplicate time stamps at frequencies for 60 (hourly) and 144 (daily) averages, in addition to 15 minute frequencies. Duplicate values that correspond to the smallest value in the frequency column (15 minutes) are retained.

This function differs from [import\\_local](#) in that it allows for special handling of nutrient data. Using this function, the user can separate diel sampling data from low-tide sampling data using the collMthd argument.

Zip download request through CDMO: <http://cdmo.baruch.sc.edu/aqs/zips.cfm>

Example dataset: [https://s3.amazonaws.com/swmpexdata/zip\\_ex.zip](https://s3.amazonaws.com/swmpexdata/zip_ex.zip)

### Value

Returns a swmpr object with all parameters and QAQC columns for the station. The full date range in the raw data are also imported.

### Author(s)

Marcus Beck, Julie Padilla (additional of codecollMthd argument) maintainer: Julie Padilla

**See Also**

[all\\_params](#), [all\\_params\\_dtrng](#), [rem\\_reps](#), [single\\_param](#)

---

lm\_p\_labs

*P-Value labels for Plotting*

---

**Description**

Generate a dataframe of p-value labels based on p-values from linear regression

**Usage**

```
lm_p_labs(dat_in)
```

**Arguments**

`dat_in` `data.frame` with year, season, min, mean, max columns

**Details**

A helper function that returns a `data.frame` of p-value labels for use with the [seasonal\\_dot](#). P-values are taken from linear regression `lm`.

**Value**

Returns `data.frame` for use with [seasonal\\_dot](#)

**Author(s)**

Julie Padilla, Dave Eslinger

**See Also**

[lm](#)

---

load_shp_file	<i>Load and format shapefile for reserve level map</i>
---------------	--

---

### Description

Load and format shapefile for use with `res_local_map`. If polygons are dissolved, the only attribute returned will be a count of the number of grouped polygons, otherwise, all attributes are retained.

### Usage

```
load_shp_file(path, dissolve_boundaries = TRUE)
```

### Arguments

path	path to shapefile and name
dissolve_boundaries	logical, should reserve boundaries be dissolved? Defaults to TRUE

### Details

This function is intended for internal use with the NERRS reserve level reporting scripts. It loads a NERRS boundary shp file and dissolves unnecessary reserve boundaries. The resulting `sf` object is then used with [res\\_sk\\_map](#) and [res\\_local\\_map](#)

### Value

Returns a `sf` object

### Author(s)

Julie Padilla, Dave Eslinger

---

national_sk_map	<i>Reserve National Map with Seasonal Kendall Results</i>
-----------------	---

---

### Description

Create a base map for NERRS reserves in ggplot with seasonal kendall results

## Usage

```
national_sk_map(  
  incl = c("contig", "AK", "HI", "PR"),  
  highlight_states = NULL,  
  sk_reserves = NULL,  
  sk_results = NULL,  
  sk_fill_colors = c("#444E65", "#A3DFFF", "#247BA0", "#0a0a0a"),  
  agg_county = TRUE  
)
```

## Arguments

<code>incl</code>	chr vector to include AK, HI, and PR (case sensitive)
<code>highlight_states</code>	chr vector of state FIPS codes
<code>sk_reserves</code>	chr vector of 3 letter reserve codes that have seasonal kendall results
<code>sk_results</code>	chr vector of seasonal kendall results. Results can be 'inc', 'dec', 'insig', or 'insuff' which stand for 'increasing trend', 'decreasing trend', 'statistically insignificant trend', or 'insufficient data to detect trend'
<code>sk_fill_colors</code>	chr vector of colors used to fill seasonal kendall result markers
<code>agg_county</code>	logical, should counties be aggregated to the state-level? Defaults to TRUE

## Details

Create a base map of the US with options for including AK, HI, and PR. The user can choose which states and NERRS reserves to highlight. An early sp-based version of this function by Julie Padilla was developed, in part, from a blog post by Bob Rudis. The current sf-based version, by Dave Eslinger, uses an approach from the r-spatial tutorial by Mel Moreno and Mathieu Basille.

To ensure the proper plotting of results, the order of the results vector for `sk_results` should match the order of the reserves vector for `sk_reserves`.

## Value

Returns a [ggplot](#) object

## Author(s)

Julie Padilla, Dave Eslinger Maintainer: Dave Eslinger

## References

Rudis, Bob. 2014. "Moving The Earth (well, Alaska & Hawaii) With R". *rud.is* (blog). November 16, 2014. <https://rud.is/b/2014/11/16/moving-the-earth-well-alaska-hawaii-with-r/> Moreno, Mel, and Basille, Mathieu Basille. 2018. "Drawing beautiful maps programmatically with R, sf and ggplot2 — Part 3: Layouts" *r-spatial* (blog). October 25, 2018. <https://www.r-spatial.org/r/2018/10/25/ggplot2-sf-3.html>

**Examples**

```
##National map highlighting west coast states and NERRS (including AK)
nerr_states_west <- c('02', '06', '41', '53')

nerrs_codes <- c('pdb', 'sos', 'sfb', 'elk', 'tjr', 'kac')

nerrs_sk_results <- c('inc', 'inc', 'dec', 'insig', 'insuff', 'dec')

national_sk_map(highlight_states = nerr_states_west,
                sk_reserve = nerrs_codes, sk_results = nerrs_sk_results)
```

---

raw\_boxplot

*Boxplots of raw data by user-defined season for a target year*


---

**Description**

Boxplots of raw data by user-defined season for a target year

**Usage**

```
raw_boxplot(swmpr_in, ...)

## S3 method for class 'swmpr'
raw_boxplot(
  swmpr_in,
  param = NULL,
  target_yr = NULL,
  criteria = NULL,
  free_y = FALSE,
  log_trans = FALSE,
  converted = FALSE,
  plot_title = FALSE,
  ...
)
```

**Arguments**

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See <a href="#">assign_season</a> and <a href="#">y_labeler</a> .
param	chr string of variable to plot
target_yr	numeric, if target year is not specified then all data in the data frame will be used.
criteria	numeric, a numeric criteria that will be plotted as a horizontal line
free_y	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot

log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See y_labeler for details.
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE

### Details

This function produces boxplots of raw, unaggregated data by user-specified season for year of interest

### Value

A [ggplot](#) object

### Author(s)

Julie Padilla

### See Also

[ggplot](#), [assign\\_season](#), [y\\_labeler](#)

### Examples

```
## get data, prep
data(elksmwq)
dat <- elksmwq

dat <- qaqc(elksmwq, qaqc_keep = c('0', '3', '5'))
raw_boxplot(dat, param = 'do_mgl')
```

---

remove\_inf\_and\_nan      *Replace Inf/-Inf/NaN values*

---

### Description

Replace Inf, -Inf, and NaN in a matrix with NA

### Usage

```
remove_inf_and_nan(x)
```

**Arguments**

x                    input matrix

**Details**

This function replaces Inf, -Inf, and NaN in a matrix with NA. It is used internally by several functions.

**Value**

Returns a matrix object

**Author(s)**

Julie Padilla

---

reserve_locs	<i>NERRS Sampling Location Data Frame</i>
--------------	---

---

**Description**

Create a data.frame of selected NERRS locations for plotting with `res_national_map`

**Usage**

```
reserve_locs(incl = c("contig", "AK", "HI", "PR"), subset_reserve = NULL)
```

**Arguments**

incl                    Str vector to include AK, HI, and PR  
subset\_reserve        chr string of 3 letter reserve IDs to include as data points. To include He'eia use the reserve code 'HEA'.

**Details**

A helper function used to generate a data.frame of selected reserve locations for use with [res\\_national\\_map](#).

**Value**

Returns a data.frame for internal use with `res_national_map`

**Author(s)**

Julie Padilla, Dave Eslinger

---

res_custom_map	<i>Local Reserve Map for Custom Stations</i>
----------------	--

---

### Description

Create a stylized reserve-level map of custom station locations for use with the reserve level reporting template

### Usage

```
res_custom_map(
  stations,
  x_loc,
  y_loc,
  bbox,
  shp,
  station_labs = TRUE,
  station_col = NULL,
  lab_loc = NULL,
  bg_map = NULL,
  zoom = NULL,
  maptype = "toner-lite"
)
```

### Arguments

stations	chr string of the reserve stations to include in the map
x_loc	num vector of x coordinates for stations
y_loc	num vector of y coordinates for stations
bbox	a bounding box associated with the reserve. Must be in the format of c(X1, Y1, X2, Y2)
shp	sf data frame (preferred) or SpatialPolygons object
station_labs	logical, should stations be labeled? Defaults to TRUE
station_col	chr vector of colors used to color station points. Defaults to 'black'.
lab_loc	chr vector of 'R' and 'L', one letter for each station. if no lab_loc is specified then labels will default to the left.
bg_map	a georeferenced ggmap or ggplot object used as a background map, generally provided by a call to <code>base_map</code> . If bg_map is specified, maptype and zoom are ignored.
zoom	Zoom level for the base map created when bg_map is not specified. An integer value, 5 - 15, with higher numbers providing more detail. If not provided, a zoom level is autoscaled based on bbox parameters.
maptype	Background map type from Stamen Maps ( <a href="http://maps.stamen.com/">http://maps.stamen.com/</a> ); one of c("terrain", "terrain-background", "terrain-labels", "terrain-lines", "toner", "toner-2010", "toner-2011", "toner-background", "toner-hybrid", "toner-labels", "toner-lines", "toner-lite", "watercolor").



## Details

Creates a stylized, reserve-level base map. The user can specify the reserve and stations to plot. The user can also specify a bounding box. For multi-component reserves, the user should specify a bounding box that highlights the component of interest.

This function does not automatically detect conflicts between station labels. The `lab_loc` argument allows the user to specify "R" or "L" for each station to prevent labels from conflicting with each other.

This function is intended to be used with `mapview::mapshot` to generate a png for the reserve-level report.

## Value

returns a ggplot object

## Author(s)

Julie Padilla, Dave Eslinger

## Examples

```
### set plotting parameters
stns <- c('custom stn 1', 'custom stn 2')
x_coords <- c(-121.735281, -121.750369)
y_coords <- c(36.850377, 36.806667)
shp_fl <- elk_spatial
bounding_elk <- c(-121.8005, 36.7779, -121.6966, 36.8799)
lab_dir <- c('L', 'R')

### Low zoom and default mptype plot (for CRAN testing, not recommended)
# Lower zoom number gives coarser text and fewer features
(x_low <- res_custom_map(stations = stns, x_loc = x_coords, y_loc = y_coords,
                        bbox = bounding_elk, lab_loc = lab_dir, shp = shp_fl,
                        zoom = 10))

x_def <- res_custom_map(stations = stns, x_loc = x_coords, y_loc = y_coords,
                        bbox = bounding_elk, lab_loc = lab_dir, shp = shp_fl)

res_custom_map(stations = stns, x_loc = x_coords, y_loc = y_coords,
               bbox = bounding_elk, lab_loc = lab_dir,
               shp = shp_fl, station_col = c('red', 'green'))
```

---

res\_custom\_sk\_map      *Local Reserve Map With Seasonal Kendall Results for Custom Stations*

---

### Description

Create a stylized reserve-level map of seasonal kendall results from custom station locations for use with the reserve level reporting template

### Usage

```
res_custom_sk_map(
  stations,
  x_loc,
  y_loc,
  sk_result = NULL,
  bbox,
  shp,
  station_labs = TRUE,
  lab_loc = NULL,
  bg_map = NULL,
  zoom = NULL,
  maptype = "toner-lite"
)
```

### Arguments

stations	chr string of the reserve stations to include in the map
x_loc	num vector of x coordinates for stations. East longitudes must be negative.
y_loc	num vector of y coordinates for stations
sk_result	vector of values denoting direction and significance of seasonal kendall results. Result should be c('inc', 'dec', 'insig') for sig. negative, no sig. results, and sig. positive result
bbox	a bounding box associated with the reserve. Must be in the format of c(X1, Y1, X2, Y2)
shp	sf data frame (preferred) or SpatialPolygons object
station_labs	logical, should stations be labeled? Defaults to TRUE
lab_loc	chr vector of 'R' and 'L', one letter for each station. if no lab_loc is specified then labels will default to the left.
bg_map	a georeferenced ggmap or ggplot object used as a background map, generally provided by a call to <a href="#">base_map</a> . If bg_map is specified, maptype and zoom are ignored.
zoom	Zoom level for the base map created when bg_map is not specified. An integer value, 5 - 15, with higher numbers providing more detail. If not provided, a zoom level is autoscaled based on bbox parameters.

`maptype` Background map type from Stamen Maps (<http://maps.stamen.com/>); one of `c("terrain", "terrain-background", "terrain-labels", "terrain-lines", "toner", "toner-2010", "toner-2011", "toner-background", "toner-hybrid", "toner-labels", "toner-lines", "toner-lite", "watercolor")`.

### Details

Creates a stylized, reserve-level base map for displaying seasonal kendall results from `sk_seasonal`. The user can specify the reserve and stations to plot. The user can also specify a bounding box. For multi-component reserves, the user should specify a bounding box that highlights the component of interest.

To display seasonal trends, the user must specify `c('inc', 'dec', 'insig', 'insuff')` for each station listed in the `stations` argument.

### Value

returns a ggplot object

### Author(s)

Julie Padilla, Dave Eslinger

### Examples

```
### set plotting parameters
stns <- c('custom stn 1', 'custom stn 2')
x_coords <- c(-121.735281, -121.750369)
y_coords <- c(36.850377, 36.806667)
shp_fl <- elk_spatial
bounding_elk <- c(-121.8005, 36.7779, -121.6966, 36.8799)
lab_dir <- c('R', 'L')
trnds <- c('inc', 'dec')

### Low zoom and default maptype plot (for CRAN testing, not recommended)
# Lower zoom number gives coarser text and fewer features
(x_low <- res_custom_sk_map(stations = stns, x_loc = x_coords,
                           sk_result = trnds, y_loc = y_coords,
                           bbox = bounding_elk, lab_loc = lab_dir,
                           shp = shp_fl, zoom = 10))

### Default zoom and maptype plot
x_def <- res_custom_sk_map(stations = stns, x_loc = x_coords,
                           sk_result = trnds, y_loc = y_coords,
                           bbox = bounding_elk, lab_loc = lab_dir,
                           shp = shp_fl)

### Higher zoom number gives more details, but may not be visible
x_14 <- res_custom_sk_map(stations = stns, x_loc = x_coords,
                           sk_result = trnds, y_loc = y_coords,
                           bbox = bounding_elk, lab_loc = lab_dir,
                           shp = shp_fl, zoom = 14)
```

```

### Different maptypes may be used. All may not be available.
# Note that zoom and maptype interact, so some experimentation may be
# required.
x_terrain <- res_custom_sk_map(stations = stns, x_loc = x_coords,
                              sk_result = trnds, y_loc = y_coords,
                              bbox = bounding_elk, lab_loc = lab_dir,
                              shp = shp_fl, maptype = 'terrain')

```

---

res_local_map	<i>Local Reserve Map</i>
---------------	--------------------------

---

### Description

Create a stylized reserve-level map for use with the reserve level reporting template

### Usage

```

res_local_map(
  nerr_site_id,
  stations,
  bbox,
  shp,
  station_labs = TRUE,
  lab_loc = NULL,
  bg_map = NULL,
  zoom = NULL,
  maptype = "toner-lite"
)

```

### Arguments

nerr_site_id	chr string of the reserve to make, first three characters used by NERRS
stations	chr string of the reserve stations to include in the map
bbox	a bounding box associated with the reserve. Must be in the format of c(X1, Y1, X2, Y2)
shp	sf data frame (preferred) or SpatialPolygons object
station_labs	logical, should stations be labeled? Defaults to TRUE
lab_loc	chr vector of 'R' and 'L', one letter for each station. if no lab_loc is specified then labels will default to the left.
bg_map	a georeferenced ggmap or ggplot object used as a background map, generally provided by a call to <a href="#">base_map</a> . If bg_map is specified, maptype and zoom are ignored.

zoom	Zoom level for the base map created when bg_map is not specified. An integer value, 5 - 15, with higher numbers providing more detail. If not provided, a zoom level is autoscaled based on bbox parameters.
maptype	Background map type from Stamen Maps ( <a href="http://maps.stamen.com/">http://maps.stamen.com/</a> ); one of c("terrain", "terrain-background", "terrain-labels", "terrain-lines", "toner", "toner-2010", "toner-2011", "toner-background", "toner-hybrid", "toner-labels", "toner-lines", "toner-lite", "watercolor").

## Details

Creates a stylized, reserve-level base map. The user can specify the reserve and stations to plot. The user can also specify a bounding box. For multi-component reserves, the user should specify a bounding box that highlights the component of interest.

This function does not automatically detect conflicts between station labels. The lab\_loc argument allows the user to specify "R" or "L" for each station to prevent labels from conflicting with each other.

This function is intended to be used with mapview::mapshot to generate a png for the reserve-level report.

## Value

returns a ggplot object

## Author(s)

Julie Padilla, Dave Eslinger

## Examples

```
## a compact reserve
### set plotting parameters
stations <-
sampling_stations[(sampling_stations$NERR.Site.ID == 'elk'
  & sampling_stations$Status == 'Active'
  & sampling_stations$isSWMP == "P"), ]$Station.Code
to_match <- c('wq', 'met')
stns <- stations[grep(paste(to_match, collapse = '|'), stations)]
shp_fl <- elk_spatial
bounding_elk <- c(-121.8005, 36.7779, -121.6966, 36.8799)
lab_dir <- c('L', 'R', 'L', 'L', 'L')
labs <- c('ap', 'cw', 'nm', 'sm', 'vm')

### Low zoom and default maptype plot (for CRAN testing, not recommended)
# Lower zoom number gives coarser text and fewer features
(x_low <- res_local_map('elk', stations = stns, bbox = bounding_elk,
  lab_loc = lab_dir, shp = shp_fl,
  zoom = 10))

### Default zoom and maptype
```

```

x_def <- res_local_map('elk', stations = stns, bbox = bounding_elk,
                      lab_loc = lab_dir, shp = shp_fl,
                      zoom = 10)

### A multicomponent reserve (show two different bounding boxes)
# set plotting parameters
stations <- sampling_stations[(sampling_stations$NERR.Site.ID == 'cbm'
                               & sampling_stations$Status == 'Active'
                               & sampling_stations$isSWMP == "P"), ]$Station.Code
to_match <- c('wq', 'met')
stns <- stations[grep(paste(to_match, collapse = '|'), stations)]
shp_fl <- cbm_spatial
bounding_cbm_1 <- c(-77.393, 38.277, -75.553, 39.741)
bounding_cbm_2 <- c(-76.8, 38.7, -76.62, 38.85)
lab_dir <- c('L', 'R', 'L', 'L', 'L')
labs <- c('ap', 'cw', 'nm', 'sm', 'vm')

### plot
y <- res_local_map('cbm', stations = stns, bbox = bounding_cbm_1,
                  lab_loc = lab_dir, shp = shp_fl)

z <- res_local_map('cbm', stations = stns, bbox = bounding_cbm_2,
                  lab_loc = lab_dir, shp = shp_fl)

```

---

res\_national\_map

*Reserve National Map*


---

## Description

Create a base map for NERRS reserves in ggplot

## Usage

```

res_national_map(
  incl = c("contig", "AK", "HI", "PR"),
  highlight_states = NULL,
  highlight_reserves = NULL,
  agg_county = TRUE
)

```

## Arguments

`incl` chr vector to include AK, HI, and PR (case sensitive)  
`highlight_states` chr vector of state FIPS codes

highlight\_reserves  
chr vector of 3 letter reserve codes

agg\_county logical, should counties be aggregated to the state-level? Defaults to TRUE

### Details

Create a base map of the US with options for including AK, HI, and PR. The user can choose which states and NERRS reserves to highlight. An early sp-based version of this function by Julie Padilla was developed, in part, from a blog post by Bob Rudis. The current sf-based version, by Dave Eslinger, uses an approach from the r-spatial tutorial by Mel Moreno and Mathieu Basille.

### Value

Returns a `ggplot` object

### Author(s)

Julie Padilla, Dave Eslinger Maintainer: Dave Eslinger

### References

Rudis, Bob. 2014. "Moving The Earth (well, Alaska & Hawaii) With R". *rud.is* (blog). November 16, 2014. <https://rud.is/b/2014/11/16/moving-the-earth-well-alaska-hawaii-with-r/> Moreno, Mel, and Basille, Mathieu Basille. 2018. "Drawing beautiful maps programmatically with R, sf and ggplot2 — Part 3: Layouts" *r-spatial* (blog). October 25, 2018. <https://www.r-spatial.org/r/2018/10/25/ggplot2-sf-3.html>

### Examples

```
##National map highlighting states with NERRS
nerr_states <- c('01', '02', '06', '10', '12', '13', '15',
  '23', '24', '25', '27', '28', '33', '34', '36', '37', '39',
  '41', '44', '45', '48', '51', '53', '55', '72')

res_national_map(highlight_states = nerr_states)

#' ##Just the national map
res_national_map()

##National map highlighting west coast states and NERRS (including AK)
nerr_states_west <- c('02', '06', '41', '53')

nerrs_codes <- c('pdb', 'sos', 'sfb', 'elk', 'tjr', 'kac')

res_national_map(highlight_states = nerr_states_west, highlight_reserve = nerrs_codes)
```

res\_sk\_map

*Local Reserve Map With Seasonal Kendall Results***Description**

Create a stylized reserve-level map of seasonal kendall results for use with the reserve level reporting template

**Usage**

```
res_sk_map(
  nerr_site_id,
  stations,
  sk_result = NULL,
  bbox,
  shp,
  station_labs = TRUE,
  lab_loc = NULL,
  bg_map = NULL,
  zoom = NULL,
  maptype = "toner-lite"
)
```

**Arguments**

nerr_site_id	chr string of the reserve to make, first three characters used by NERRS
stations	chr string of the reserve stations to include in the map
sk_result	vector of values denoting direction and significance of seasonal kendall results. Result should be c('inc', 'dec', 'insig', 'insuff') for significant positive, significant negative, no significant results, and insufficient data to calculate result.
bbox	a bounding box associated with the reserve. Should be in the format of c(xmin, ymin, xmax, ymax).
shp	sf data frame (preferred) or SpatialPolygons object
station_labs	logical, should stations be labeled? Defaults to TRUE
lab_loc	chr vector of 'R' and 'L', one letter for each station. if no lab_loc is specified then labels will default to the left.
bg_map	a georeferenced ggmap or ggplot object used as a background map, generally provided by a call to <a href="#">base_map</a> . If bg_map is specified, maptype and zoom are ignored.
zoom	Zoom level for the base map created when bg_map is not specified. An integer value, 5 - 15, with higher numbers providing more detail. If not provided, a zoom level is autoscaled based on bbox parameters.



**mptype** Background map type from Stamen Maps (<http://maps.stamen.com/>); one of c("terrain", "terrain-background", "terrain-labels", "terrain-lines", "toner", "toner-2010", "toner-2011", "toner-background", "toner-hybrid", "toner-labels", "toner-lines", "toner-lite", "watercolor").

### Details

Creates a stylized, reserve-level base map for displaying seasonal kendall results from `sk_seasonal`. The user can specify the reserve and stations to plot. The user can also specify a bounding box. For multi-component reserves, the user should specify a bounding box that highlights the component of interest.

To display seasonal trends, the user must specify c('inc', 'dec', 'insig', 'insuff') for each station listed in the `stations` argument.

### Value

returns a ggplot object.

### Author(s)

Julie Padilla, Dave Eslinger

### Examples

```
## A compact reserve

### set plotting parameters
stations <- sampling_stations[(sampling_stations$NERR.Site.ID == 'elk'
  & sampling_stations$Status == 'Active'
  & sampling_stations$isSWMP == "P"), ]$Station.Code
to_match <- c('wq')
stns <- stations[grep(paste(to_match, collapse = '|'), stations)]
shp_fl <- elk_spatial
bounding_elk <- c(-121.8005, 36.7779, -121.6966, 36.8799)
trnds <- c('inc', 'dec', 'insuff', 'insig')

### Low zoom and default mptype plot (for CRAN testing, not recommended)
# Lower zoom number gives coarser text and fewer features
(x_low <- res_sk_map('elk', stations = stns, sk_result = trnds,
  bbox = bounding_elk, shp = shp_fl,
  zoom = 10))

### Default zoom and mptype
x_def <- res_sk_map('elk', stations = stns, sk_result = trnds,
  bbox = bounding_elk, shp = shp_fl)

### Higher zoom number gives more details, but those may not be visible
x_14 <- res_sk_map('elk', stations = stns, sk_result = trnds,
  bbox = bounding_elk, shp = shp_fl,
```

```

        zoom = 14)

### Different maptypes may be used.
x_terrain <- res_sk_map('elk', stations = stns, sk_result = trnds,
                      bbox = bounding_elk, shp = shp_fl,
                      matype = 'terrain')
### A multicomponent reserve (showing two different bounding boxes)

# set plotting parameters
stations <- sampling_stations[(sampling_stations$NERR.Site.ID == 'cbm'
                              & sampling_stations$Status == 'Active'
                              & sampling_stations$isSWMP == "P"), ]$Station.Code
to_match <- c('wq')
stns <- stations[grep(paste(to_match, collapse = '|'), stations)]
shp_fl <- cbm_spatial
bounding_cbm_1 <- c(-77.393, 38.277, -75.553, 39.741)
bounding_cbm_2 <- c(-76.8, 38.7, -76.62, 38.85)
trnds <- c('inc', 'insuff', 'dec', 'insig')

# plot
y <- res_sk_map('cbm', stations = stns, sk_result = trnds,
               bbox = bounding_cbm_1, shp = shp_fl)

z <- res_sk_map('cbm', stations = stns, sk_result = trnds,
               bbox = bounding_cbm_2, shp = shp_fl)

```

---

sampling\_stations      *Detailed NERRS site data*

---

## Description

Metadata on NERRS stations provided by the Central Data Management Office (CDMO) when data is downloaded

## Usage

```
data(sampling_stations)
```

## Format

A [data.frame](#) object

## Source

[CDMO](#)

**References**

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program.  
Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>;  
accessed 08 October 2016

---

sampling\_stations\_backup

*A Backup of Detailed NERRS site data*

---

**Description**

A backup of the current metadata on NERRS stations provided by the Central Data Management Office (CDMO) created when new data is loaded

**Usage**

```
data(sampling_stations_backup)
```

**Format**

A `data.frame` object

**Source**

CDMO

**References**

NOAA National Estuarine Research Reserve System (NERRS). System-wide Monitoring Program.  
Data accessed from the NOAA NERRS Centralized Data Management Office website: <http://www.nerrsdata.org/>;  
accessed 08 October 2016

---

seasonal\_barplot

*Cumulative Bar Plot*

---

**Description**

Cumulative bar plot over a historic range

**Usage**

```
seasonal_barplot(swmpr_in, ...)

## S3 method for class 'swmpr'
seasonal_barplot(
  swmpr_in,
  param = NULL,
  hist_rng = NULL,
  log_trans = FALSE,
  converted = FALSE,
  hist_avg = TRUE,
  bar_position = "stack",
  season_facet = FALSE,
  plot_title = FALSE,
  plot = TRUE,
  ...
)
```

**Arguments**

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See <a href="#">assign_season</a>
param	chr string of variable to plot
hist_rng	numeric vector, if historic range is not specified then the min/max values of the data set will be used.
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See <a href="#">y_labeler</a> for details.
hist_avg	logical, should a historical average be included? Defaults to TRUE.
bar_position	chr string, options available are stack or dodge. Defaults to stack
season_facet	logical, should plot be faceted by season? Defaults to FALSE.
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE

**Details**

This function uses barplots to summarize parameters that are best viewed on a cumulative basis (e.g., precipitation). Data are aggregated on a seasonal and annual basis.

There are two ways to make interannual comparisons: on an aggregate basis and on a seasonal basis. If the argument `season_facet = FALSE` then parameter totals from each season will be added together to compose one, multi-color bar. If `season_facet = TRUE` then parameter totals from each season separated into multiple plots for easier intra-season comparison across years.

**Value**

A [ggplot](#) object

**Author(s)**

Julie Padilla

**See Also**[ggplot](#), [assign\\_season](#), [y\\_labeler](#)**Examples**

```

data(apaebmet)
dat <- qaqc(apaebmet, qaqc_keep = c('0', '3', '5'))

x <- seasonal_barplot(dat, param = 'totprcp'
  , season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12))
  , season_names = c('Winter', 'Spring', 'Summer', 'Fall')
  , hist_avg = TRUE
  , converted = FALSE)

# return a table instead of a figure
y <- seasonal_barplot(dat, param = 'totprcp'
  , season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12))
  , season_names = c('Winter', 'Spring', 'Summer', 'Fall')
  , converted = FALSE
  , plot = FALSE)

## divide plot into seasonal facets
z <- seasonal_barplot(dat, param = 'totprcp'
  , season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12))
  , season_names = c('Winter', 'Spring', 'Summer', 'Fall')
  , season_facet = TRUE
  , hist_avg = TRUE
  , converted = FALSE)

## convert from mm to in
dat$totprcp <- dat$totprcp / 25.4

x1 <- seasonal_barplot(dat, param = 'totprcp'
  , season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12))
  , season_names = c('Winter', 'Spring', 'Summer', 'Fall')
  , hist_avg = TRUE
  , converted = TRUE)

```

---

seasonal\_boxplot

*Seasonal boxplots*


---

**Description**

Annual time series for year of interest on top of long-term percentiles

**Usage**

```
seasonal_boxplot(swmpr_in, ...)

## S3 method for class 'swmpr'
seasonal_boxplot(
  swmpr_in,
  param = NULL,
  hist_rng = NULL,
  target_yr = NULL,
  criteria = NULL,
  free_y = FALSE,
  log_trans = FALSE,
  converted = FALSE,
  criteria_lab = "WQ Threshold",
  stat_lab = "Average",
  plot_title = FALSE,
  plot = TRUE,
  FUN = function(x) mean(x, na.rm = TRUE),
  ...
)
```

**Arguments**

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See <a href="#">assign_season</a>
param	chr string of variable to plot
hist_rng	numeric vector, if historic range is not specified then the min/max values of the data set will be used.
target_yr	numeric, the target year that should be compared against the historic range. If target year is not specified then dot will not be plotted
criteria	numeric, a numeric criteria that will be plotted as a horizontal line
free_y	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See <a href="#">y_labeler</a> for details.
criteria_lab	chr, label for the threshold criteria defined in criteria. Defaults to "WQ Threshold"
stat_lab	chr, label for the summary statistic defined in FUN. Defaults to "Average"
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE
FUN	function used to aggregate daily SWMP data

## Details

This function uses boxplots to summarize statistics calculated on a daily basis across user-defined seasons for all years within the historic range (`hist_rng`). If `hist_rng` is not specified then the minimum and maximum years within the data set will be used. The summary statistics used to generate the boxplots are ggplot2 defaults: the center of the box is a median, and the lower/upper limits of the box are the 25-th and 75-th percentiles. The whiskers extend to the furthest data point within  $1.5 * \text{inter-quartile range (IQR)}$ . The dots beyond the whiskers are data points that are greater than  $1.5 * \text{IQR}$ . If the user selects a `target_yr`, then a median summary statistic value will be plotted as a point against the boxplots.

Using the `FUN` argument, the user can specify the daily summary statistic to use. Commonly used statistics are `min(x, na.rm = TRUE)`, `mean(x, na.rm = TRUE)`, and `max(x, na.rm = TRUE)`. After specifying `FUN`, the user should also specify `stat_lab`, which is used to construct appropriate legend labels.

The user also has the option to add a threshold hold line using the `criteria` argument. Typically, this value is a water quality threshold, which is why `criteria_lab` defaults to 'WQ Threshold'. However, the user has the option to specify any other type of threshold they wish. when doing so, the value for `criteria_lab` should be changed accordingly.

## Value

Returns a [ggplot](#) object or a `data.frame` if `plot = FALSE`

## Author(s)

Julie Padilla

## See Also

[ggplot](#), [assign\\_season](#)

## Examples

```
dat <- elksmwq
dat <- qaqc(dat, qaqc_keep = c('0', '3', '5'))

x <-
  seasonal_boxplot(dat, param = 'do_mgl')

y <-
  seasonal_boxplot(dat, param = 'do_mgl', target_yr = 2015,
    season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12)),
    season_names = c('Winter', 'Spring', 'Summer', 'Fall'),
    season_start = 'Spring')

z_min <-
  seasonal_boxplot(dat, param = 'do_mgl',
    stat_lab = 'Minimum', FUN = function(x) min(x, na.rm = TRUE))
```

```
z_max <-
  seasonal_boxplot(dat, param = 'do_mgl',
    stat_lab = 'Maximum', FUN = function(x) max(x, na.rm = TRUE))
```

---

seasonal\_dot

*Seasonal Dot Plot*


---

## Description

Plot average/min/max seasonal values faceted by season

## Usage

```
seasonal_dot(swmpr_in, ...)

## S3 method for class 'swmpr'
seasonal_dot(
  swmpr_in,
  param = NULL,
  lm_trend = FALSE,
  lm_lab = FALSE,
  free_y = FALSE,
  log_trans = FALSE,
  converted = FALSE,
  plot_title = FALSE,
  plot = TRUE,
  ...
)
```

## Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See <a href="#">assign_season</a>
param	chr string of variable to plot
lm_trend	logical, add linear trend line?
lm_lab	logical, add significance label? Statistically significant results will appear in bold.
free_y	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by ggplot
log_trans	logical, should y-axis be log? Defaults to FALSE
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See <code>y_labeler</code> for details.
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE



## Details

This function summarizes minimum, mean, and maximum values calculated on a seasonal basis to allow for easier intra-season comparisons over time.

`lm_trend = TRUE` adds a linear regression to the plot, and `lm_lab = TRUE` will add p-values from the linear regression to the plot. If the p-values are significant ( $p < 0.05$ ) then the text will appear in bold. `lm_lab` text is color coded to match with the corresponding dots.

## Value

Returns a [ggplot](#) object

## Author(s)

Julie Padilla, Dave Eslinger

## See Also

[ggplot](#), [assign\\_season](#), [y\\_labeler](#)

## Examples

```
dat_wq <- elkswmq
#dat_wq <- subset(dat_wq, subset = c('2010-01-01 0:00', '2017-01-01 0:00'))
dat_wq <- qaqc(dat_wq, qaqc_keep = c(0, 3, 5))

x <-
  seasonal_dot(dat_wq, param = 'do_mgl'
              , lm_trend = TRUE
              , lm_lab = TRUE
              , plot_title = TRUE)

y <-
  seasonal_dot(dat_wq, param = 'do_mgl'
              , lm_trend = FALSE
              , lm_lab = FALSE
              , plot_title = TRUE)

z <-
  seasonal_dot(dat_wq, param = 'do_mgl'
              , lm_trend = TRUE
              , lm_lab = FALSE
              , plot_title = TRUE)

dat_nut <- elkmmnut
dat_nut <- subset(dat_nut, subset = c('2007-01-01 0:00', '2017-01-01 0:00'))
dat_nut <- qaqc(dat_nut, qaqc_keep = c(0, 3, 5))

x1 <-
  seasonal_dot(dat_nut
```

```
      , param = 'chla_n'
      , season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12))
      , season_names = c('Winter', 'Spring', 'Summer', 'Fall')
      , season_start = 'Spring'
      , lm_trend = FALSE
      , lm_lab = FALSE
      , plot_title = TRUE)

y1 <-
  seasonal_dot(dat_nut, param = 'chla_n'
              , lm_trend = TRUE
              , lm_lab = FALSE
              , plot_title = TRUE)

z1 <-
  seasonal_dot(dat_nut, param = 'chla_n'
              , lm_trend = TRUE
              , lm_lab = TRUE
              , plot_title = TRUE)
```

---

set\_date\_breaks

*Set reasonable date breaks*

---

## Description

Select reasonable breaks for [scale\\_x\\_datetime](#)

## Usage

```
set_date_breaks(rng)
```

## Arguments

rng                    date range years

## Details

A helper function for easier date label setting

## Value

Returns a chr string for date\_breaks

## Author(s)

Julie Padilla

## See Also

[set\\_date\\_break\\_labs](#), [scale\\_x\\_datetime](#)

---

set\_date\_breaks\_minor *Select reasonable minor breaks for [scale\\_x\\_datetime](#)*

---

**Description**

Select reasonable minor breaks for [scale\\_x\\_datetime](#)

**Usage**

```
set_date_breaks_minor(rng)
```

**Arguments**

rng                    date range years

**Details**

A helper function for easier date label setting

**Value**

Returns a chr string for date\_breaks

**Author(s)**

Dave Eslinger, Julie Padilla

**See Also**

[set\\_date\\_break\\_labs](#), [scale\\_x\\_datetime](#)

---

set\_date\_break\_labs *Set reasonable date breaks labels*

---

**Description**

Select reasonable labels for breaks used in [scale\\_x\\_datetime](#)

**Usage**

```
set_date_break_labs(rng)
```

**Arguments**

rng                    date range years

**Details**

A helper function for easier date label setting

**Value**

Returns a chr string for date\_labels

**Author(s)**

Julie Padilla

**See Also**

[set\\_date\\_breaks](#), [scale\\_x\\_datetime](#)

---

 sk\_seasonal

*Seasonal Kendall Analysis for Seasonal Data*


---

**Description**

Non-parametric test for monotonic seasonal trends

**Usage**

```
sk_seasonal(swmpr_in, ...)

## S3 method for class 'swmpr'
sk_seasonal(
  swmpr_in,
  param = NULL,
  alpha = 0.05,
  data_min = 5,
  envStats_summary = FALSE,
  stat_lab = "Average",
  FUN = function(x) mean(x, na.rm = TRUE),
  ...
)
```

**Arguments**

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See <a href="#">assign_season</a>
param	chr string of variable to plot
alpha	num, alpha value to use to significance test. Defaults to 0.05.
data_min	num, the minimum number of observations required to perform the analysis. Defaults to 5

envStats_summary	logical, should the standard EnvStats::kendallSeasonalTrendTest be returned? Defaults to FALSE. See Details for more information.
stat_lab	chr, label for the summary statistic defined in FUN. Defaults to "Average".
FUN	function used to aggregate seasonal SWMP data.

## Details

This function performs a seasonal kendall test on seasonally aggregated values using [kendallSeasonalTrendTest](#).

Data are aggregated on a user-specified seasonal basis using the FUN argument. For example, using default settings, `sk_seasonal` would perform a seasonal kendall test on average monthly values. However, if the user set `FUN = min(x, na.rm = TRUE)` then a seasonal kendall would be performed on monthly minimum values.

If `EnvStats_summary = TRUE` then the detailed output summary from [kendallSeasonalTrendTest](#) will be returned. If `EnvStats_summary = FALSE` then an abbreviated summary will be returned in a `data.frame`. The abbreviated summary contains the station name, the type of statistic used to summarize the data on a seasonal basis (specified by `stat_lab`), and the following results from [kendallSeasonalTrendTest](#): tau, slope, p-value for the chi-square test, and the p-value for the trend test.

## Value

Returns a `data.frame` object or a summary from `EnvStats::kendallSeasonalTrendTest`

## Author(s)

Julie Padilla

## See Also

[assign\\_season](#), [y\\_labeler](#), [kendallSeasonalTrendTest](#)

## Examples

```
dat_wq <- elksmwq
dat_wq <- qaqc(dat_wq, qaqc_keep = c(0, 3, 5))

x <- sk_seasonal(dat_wq, param = 'temp')
```

---

sk_tidy	<i>Tidy Seasonal Kendall Results</i>
---------	--------------------------------------

---

**Description**

Tidy results from [kendallSeasonalTrendTest](#)

**Usage**

```
sk_tidy(data, station, param, stat, alpha = 0.05)
```

**Arguments**

data	a htest object produced by <a href="#">kendallSeasonalTrendTest</a>
station	chr string sampling station
param	chr string of variable to plot
stat	chr, label to be used for statistic used to group data
alpha	num, significance level. Defaults to 0.05

**Details**

A helper function used by [sk\\_seasonal](#) to return a table of tidied values.

**Value**

Returns a data.frame of results from [kendallSeasonalTrendTest](#)

**Author(s)**

Julie Padilla

---

std_param_check	<i>Standard Parameter Check</i>
-----------------	---------------------------------

---

**Description**

Determine if a parameter is one of the standard SWMP parameters

**Usage**

```
std_param_check(param)
```

**Arguments**

param	chr string of variable abbreviation
-------	-------------------------------------

**Details**

A helper function used internally by several plotting functions to determine if parameter has a standard y-axis label. To accommodate the needs of the reserve-level annual report, this function also recognizes dissolved organic phosphorus (DIP) and dissolved inorganic nitrogen (DIN) as standard parameters.

**Value**

Returns TRUE or FALSE

**Author(s)**

Julie Padilla

**Examples**

```
std_param_check('do_mgl')  
  
std_param_check('nitrogen')
```

---

summarise\_handoff\_files

*Summarise Hand-off Files from Reserve Level Reports*

---

**Description**

Summarise the seasonal kendall results from reserve level report hand-off files

**Usage**

```
summarise_handoff_files(path, param, res_region = NULL)
```

**Arguments**

path	chr string of full path to .csv handoff files
param	chr string of variable to summarise
res_region	a data.frame of look-up values that match 3-letter NERR site ids with regions

**Details**

This function is intended for use with the NERRS national level reporting scripts. It returns a data.frame that summarises the result of the reserve level seasonal kendall trend analyses found in the hand-off files generated by the reserve level reporting scripts. The summary groups reserves into regional classifications based on user-specified regions given in res\_region.

**Value**

Returns a `data.frame`

**Author(s)**

Julie Padilla

---

threshold\_criteria\_plot

*Water Quality Threshold Plot For Parameters With Criteria*

---

**Description**

Observed data compared against user-defined water quality thresholds

**Usage**

```
threshold_criteria_plot(swmpr_in, ...)

## S3 method for class 'swmpr'
threshold_criteria_plot(
  swmpr_in,
  param = NULL,
  rng = NULL,
  thresholds = NULL,
  threshold_labs = c("Good", "Fair", "Poor"),
  threshold_cols = c("#ABD9E9", "#FFFFCC", "#FEC596"),
  crit_threshold = NULL,
  log_trans = FALSE,
  monthly_smooth = FALSE,
  plot_title = FALSE,
  ...
)
```

**Arguments**

<code>swmpr_in</code>	input <code>swmpr</code> object
<code>...</code>	additional arguments passed to other methods. See <a href="#">y_labeler</a> .
<code>param</code>	chr string of the variable to plot
<code>rng</code>	num, years to include in the plot. This variable can either be one year (e.g., <code>rng = 2012</code> ), or two years (e.g. <code>rng = c(2012, 2016)</code> ), If range is not specified then the entire data set will be used.
<code>thresholds</code>	numeric vector, numeric criteria that will be plotted in the background
<code>threshold_labs</code>	chr vector of labels for categories created by <code>thresholds</code> .
<code>threshold_cols</code>	chr vector of color values for categories created by <code>thresholds</code> .



crit\_threshold num, value at which the critical threshold line should be plotted. Typically the same value used to establish the 'Poor' threshold.

log\_trans logical, should y-axis be log? Defaults to FALSE

monthly\_smooth logical, calculate a monthly average? Defaults to FALSE

plot\_title logical, should the station name be included as the plot title? Defaults to FALSE

### Details

This function visualizes exceedances of numeric criteria which are specified using thresholds. Suggested numeric criteria for several parameters (dissolved oxygen, dissolved inorganic phosphorus, dissolved inorganic nitrogen, and chlorophyll-a) can be found in the USEPA National Coastal Condition Report (2012).

If the parameter of interest does not have numeric criteria, then `threshold_percentile_plot` is recommended.

### Value

Returns a `ggplot` object

### Author(s)

Julie Padilla

### References

United States Environmental Protection Agency (USEPA). 2012. "National Coastal Condition Report IV." <http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.646.1973&rep=rep1&type=pdf>

### See Also

[ggplot.y\\_labeler](#)

### Examples

```
data(apacpwq)
dat_wq <- apacpwq

dat_wq <- qaqc(dat_wq, qaqc_keep = c(0, 3, 5))

## Due to the volume of instantaneous data, these plots are a bit slow
x <-
  threshold_criteria_plot(dat_wq, param = 'do_mg1'
    , rng = 2012
    , thresholds = c(2, 5)
    , threshold_labs = c('Poor', 'Fair', 'Good')
    , monthly_smooth = TRUE
    , threshold_cols = c('#FEC596', '#FFFFCC', '#ABD9E9'))

y <-
```

```

threshold_criteria_plot(dat_wq, param = 'do_mgl'
  , thresholds = c(2, 5)
  , threshold_labs = c('Poor', 'Fair', 'Good')
  , threshold_cols = c('#FEC596', '#FFFFCC', '#ABD9E9'))

z <-
  threshold_criteria_plot(dat_wq, param = 'do_mgl'
    , rng = 2012
    , thresholds = c(2, 5)
    , threshold_labs = c('Poor', 'Fair', 'Good')
    , threshold_cols = c('#FEC596', '#FFFFCC', '#ABD9E9')
    , monthly_smooth = TRUE)

## A few examples with only two thresholds
x1 <-
  threshold_criteria_plot(dat_wq, param = 'do_mgl'
    , rng = 2012
    , thresholds = c(2, 2)

    # A dummy blank (') value must be added as a threshold label
    , threshold_labs = c('Poor', '', 'Good')
    , threshold_cols = c('#FEC596', '#FFFFCC', '#ABD9E9')
    , monthly_smooth = TRUE)

y1 <-
  threshold_criteria_plot(dat_wq, param = 'do_mgl'
    , rng = 2012
    , thresholds = c(5, 5)

    # A dummy blank (') value must be added as a threshold label
    , threshold_labs = c('Poor', '', 'Good')
    , threshold_cols = c('#FEC596', '#FEC596', '#ABD9E9')
    , monthly_smooth = TRUE)

z1 <-
  threshold_criteria_plot(dat_wq, param = 'do_mgl'
    , rng = 2012
    , thresholds = c(2, 5)
    , threshold_labs = c('Poor', 'Good', 'Poor')
    , threshold_cols = c('#FEC596', '#ABD9E9', '#FEC596')
    , monthly_smooth = TRUE)

data(apacpnut)
dat_nut <- apacpnut

dat_nut <- qaqc(dat_nut, qaqc_keep = c(0, 3, 5))
dat_nut <- rem_reps(dat_nut)

x2 <-
  threshold_criteria_plot(dat_nut, param = 'chla_n'
    , thresholds = c(2, 5)
    , threshold_labs = c('Good', 'Fair', 'Poor'))

```

```

y2 <-
  threshold_criteria_plot(dat_nut, param = 'chla_n'
                        , rng = 2012
                        , thresholds = c(2, 5)
                        , threshold_labs = c('Good', 'Fair', 'Poor'))

## Nutrient plots are not capable of accidentally displaying any kind of smooth
z2 <-
  threshold_criteria_plot(dat_nut, param = 'chla_n'
                        , rng = 2012
                        , thresholds = c(2, 5)
                        , threshold_labs = c('Good', 'Fair', 'Poor')
                        , monthly_smooth = TRUE)

```

---

threshold\_identification

*Tabulate Threshold Exceedances*

---

### Description

Tabulate user-specified threshold exceedances

### Usage

```
threshold_identification(swmpr_in, ...)
```

```

## S3 method for class 'swmpr'
threshold_identification(
  swmpr_in,
  param,
  parameter_threshold,
  threshold_type,
  time_threshold = NULL,
  ...
)

```

### Arguments

swmpr_in	input swmpr object
...	arguments passed to other methods
param	vector of parameters to evaluate
parameter_threshold	vector of numerical thresholds to evaluate parameters against
threshold_type	vector of logical operators ('<', '>', '<=', '>=', '==', '!=')
time_threshold	The amount of time an event must last to be counted (in hours)

## Details

This function creates tabular summary of events when a user-specified threshold is exceeded.

Before using this function, the user must apply `setstep` to normalize the `datetime` time step.

For MET and WQ data, the user must specify `time_threshold`. This argument is the minimum duration that an event must last in order to be counted. For example, if `time_threshold = 2`, `param = "do_mgl"`, `parameter_threshold = 2`, and `threshold_type = "<"` then dissolved oxygen must be lower than 2 mg/L for more than two hours or the event will not be summarized in the final table. For NUT parameters, all exceedances are included in the tabular summary.

Recommended thresholds for chlorophyll-a, dissolved inorganic nitrogen, dissolved inorganic phosphorus, and dissolved oxygen can be found in the National Coastal Condition Assessment 2010 (USEPA 2016)

## Value

Returns a data frame of threshold exceedances by parameter

## Author(s)

Julie Padilla

## References

United States Environmental Protection Agency (USEPA). 2015. "National Coastal Condition Assessment 2010". EPA 841-R-15-006. [https://cfpub.epa.gov/si/si\\_public\\_record\\_Report.cfm?Lab=OWOW&dirEntryId=3270](https://cfpub.epa.gov/si/si_public_record_Report.cfm?Lab=OWOW&dirEntryId=3270)

## Examples

```
data("apacpwq")
wq <- apacpwq

dat_wq <- qaqc(wq, qaqc_keep = c(0, 3, 5))
dat_wq <- setstep(dat_wq)

wq_pars<- threshold_identification(dat_wq, param = c('do_mgl', 'ph', 'temp')
                                   , parameter_threshold = c(2, 5, 30)
                                   , threshold_type = c('<', '<', '>'), time_threshold = 2)

wq_par<- threshold_identification(dat_wq, param = c('do_mgl')
                                   , parameter_threshold = c(2)
                                   , threshold_type = c('<'), time_threshold = 2)

## time_threshold and setstep are not necessary for monthly parameters
data("apacpnut")
nut <- apacpnut

dat_nut <- qaqc(nut, qaqc_keep = c(0, 3, 5))

nut_pars <- threshold_identification(dat_nut, param = c('chla_n', 'po4f')
```

```

, parameter_threshold = c(10, 0.01)
, threshold_type = c('>', '>'))

nut_par <- threshold_identification(dat_nut, param = c('chla_n')
, parameter_threshold = c(10)
, threshold_type = c('>'))

nut_err <- threshold_identification(dat_nut, param = c('chla_n')
, parameter_threshold = c(30)
, threshold_type = c('>'))

```

---

threshold\_percentile\_plot

*Threshold Percentile Plot*


---

### Description

Observed data compared against user-defined percentiles

### Usage

```
threshold_percentile_plot(swmpr_in, ...)
```

```

## S3 method for class 'swmpr'
threshold_percentile_plot(
  swmpr_in,
  param = NULL,
  hist_rng = NULL,
  target_yr = NULL,
  percentiles = c(0.05, 0.95),
  free_y = FALSE,
  by_month = FALSE,
  log_trans = FALSE,
  converted = FALSE,
  plot_title = FALSE,
  ...
)

```

### Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods (not used for this function).
param	chr, variable to plot
hist_rng	num, years to include in the plot. This variable can either be one year (e.g., hist_rng = 2012), or two years (e.g. hist_rng = c(2012,2016)) , If range is not specified then the entire data set will be used.

<code>target_yr</code>	num, year of interest for plotting. If not specified, the entire data set will be plotted.
<code>percentiles</code>	num, percentiles to calculate (maximum: 2). Defaults to 5th and 95th percentiles.
<code>free_y</code>	logical, should the y-axis be free? Defaults to FALSE. If FALSE, defaults to zero, unless negative values are present. If TRUE, y-axis limits are selected by <code>ggplot</code>
<code>by_month</code>	logical. should percentiles be calculated on a monthly basis? Defaults to FALSE
<code>log_trans</code>	logical, should y-axis be log? Defaults to FALSE
<code>converted</code>	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See <code>y_labeler</code> for details.
<code>plot_title</code>	logical, should the station name be included as the plot title? Defaults to FALSE

### Details

This function provides an alternative to [threshold\\_criteria\\_plot](#). For parameters that may not have numeric threshold criteria, a percentile threshold can be used instead. For a one-tailed analysis, the 90-th percentile is recommended. For a two-tailed analysis, the 5-th and 95-th percentiles are recommended.

Using `by_month`, the user can specify whether the percentiles should be calculated on a monthly basis or by using the entire data set.

Recommended thresholds for chlorophyll-a, dissolved inorganic nitrogen, dissolved inorganic phosphorus, and dissolved oxygen can be found in the National Coastal Condition Assessment 2010 (USEPA 2016)

### Value

Returns a [ggplot](#) object

### Author(s)

Julie Padilla

### References

United States Environmental Protection Agency (USEPA). 2015. "National Coastal Condition Assessment 2010". EPA 841-R-15-006. [https://cfpub.epa.gov/si/si\\_public\\_record\\_Report.cfm?Lab=OWOW&dirEntryId=3270](https://cfpub.epa.gov/si/si_public_record_Report.cfm?Lab=OWOW&dirEntryId=3270)

### See Also

[ggplot](#)

### Examples

```
dat_wq <- qaqc(elksmwq, qaqc_keep = c(0, 3, 5))
dat_wq <- subset(dat_wq, subset = '2007-01-01 0:00', operator = '>=')

x <-
  threshold_percentile_plot(dat_wq, param = 'do_mgl')
```

```

, hist_rng = c(2013, 2014), by_month = FALSE)

y <-
  threshold_percentile_plot(dat_wq, param = 'do_mgl', percentiles = c(0.95)
    , hist_rng = c(2013, 2014), target_yr = 2014
    , by_month = FALSE)

x2 <-
  threshold_percentile_plot(dat_wq, param = 'do_mgl'
    , hist_rng = c(2013, 2014), by_month = TRUE)

y2 <-
  threshold_percentile_plot(dat_wq, param = 'do_mgl'
    , hist_rng = c(2013, 2014), by_month = TRUE
    , target_yr = 2014)

dat_nut <- qaqc(elkmmnut, qaqc_keep = c(0, 3, 5))
dat_nut <- subset(dat_nut, subset = '2007-01-01 0:00', operator = '>=')
dat_nut <- rem_reps(dat_nut)

x3 <-
  threshold_percentile_plot(dat_nut, param = 'chla_n'
    , hist_rng = c(2007, 2014), by_month = FALSE)

y3 <-
  threshold_percentile_plot(dat_nut, param = 'chla_n'
    , hist_rng = c(2007, 2014), by_month = FALSE
    , target_yr = 2016)

```

---

threshold\_summary      *Summary Plots for Threshold Identification*

---

## Description

Summary plots for threshold identification analysis

## Usage

```

threshold_summary(swmpr_in, ...)

## S3 method for class 'swmpr'
threshold_summary(
  swmpr_in,
  param = NULL,
  summary_type = c("month", "season", "year"),
  parameter_threshold = NULL,

```

```

threshold_type = NULL,
time_threshold = NULL,
converted = FALSE,
pal = "Set3",
plot_title = FALSE,
plot = TRUE,
label_y_axis = TRUE,
...
)

```

### Arguments

swmpr_in	input swmpr object
...	additional arguments passed to other methods. See <a href="#">assign_season</a> for more details.
param	chr string of variable to plot (one only)
summary_type	Choose from month, season, or year aggregation
parameter_threshold	vector of numerical thresholds to evaluate parameters against
threshold_type	vector of logical operators ('<', '>', '<=', '>=', '==', '!=')
time_threshold	The amount of time an event must last to be counted (in hours)
converted	logical, were the units converted from the original units used by CDMO? Defaults to FALSE. See <a href="#">y_labeler</a> for details.
pal	Select a palette for boxplot fill colors. See <a href="#">scale_fill_brewer</a> for more details.
plot_title	logical, should the station name be included as the plot title? Defaults to FALSE
plot	logical, should a plot be returned? Defaults to TRUE
label_y_axis	logical, include label for y-axis?

### Details

This function provides a graphical or tabular summary of the results from `threshold_identification`. The user can summarize results on a monthly, seasonal, or annual basis by specifying `summary_type = c('month', 'season', 'year')`. If `summary_type = 'season'`, then the user should also define `season`, `season_names`, and `season_start`, as required by `lcodeassign_season`. The user can specify 'month' for nutrient parameters, but this is not recommended and will produce a warning.

Recommended thresholds for chlorophyll-a, dissolved inorganic nitrogen, dissolved inorganic phosphorus, and dissolved oxygen can be found in the National Coastal Condition Assessment 2010 (USEPA 2016)

### Value

Returns a [ggplot](#) object (if `plot = TRUE`) or a dataframe (if `plot = FALSE`)

### Author(s)

Julie Padilla



## References

United States Environmental Protection Agency (USEPA). 2015. "National Coastal Condition Assessment 2010". EPA 841-R-15-006. [https://cfpub.epa.gov/si/si\\_public\\_record\\_Report.cfm?Lab=OWOW&dirEntryId=3270](https://cfpub.epa.gov/si/si_public_record_Report.cfm?Lab=OWOW&dirEntryId=3270)

## See Also

[assign\\_season](#), [ggplot](#), [threshold\\_identification](#), [scale\\_fill\\_brewer](#)

## Examples

```
## Water quality examples
data(apacpwq)
dat_wq <- qaqc(apacpwq, qaqc_keep = c(0, 3, 5))
dat_wq <- SWMPPr::setstep(dat_wq)

x <-
  threshold_summary(dat_wq, param = 'do_mgl', parameter_threshold = 2,
    , threshold_type = '<', time_threshold = 2, summary_type = 'month'
    , plot_title = TRUE)

y <-
  threshold_summary(dat_wq, param = 'do_mgl', parameter_threshold = 2,
    threshold_type = '<', time_threshold = 2, summary_type = 'season',
    season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12)),
    season_names = c('Winter', 'Spring', 'Summer', 'Fall'),
    season_start = 'Winter',
    plot_title = TRUE)

## Nutrient examples
dat_nut <- qaqc(apacpnut, qaqc_keep = c(0, 3, 5))

x <-
  threshold_summary(dat_nut, param = 'chla_n',
    parameter_threshold = 10,
    threshold_type = '>', summary_type = 'month',
    plot_title = TRUE)

y <-
  threshold_summary(dat_nut, param = 'chla_n', parameter_threshold = 10,
    threshold_type = '>', summary_type = 'season',
    season_grps = list(c(1,2,3), c(4,5,6), c(7,8,9), c(10, 11, 12)),
    season_names = c('Winter', 'Spring', 'Summer', 'Fall'),
    season_start = 'Winter', plot_title = TRUE)

z <-
  threshold_summary(dat_nut, param = 'chla_n', parameter_threshold = 10,
    threshold_type = '>', summary_type = 'year',
    plot_title = TRUE, plot = TRUE)
```

title\_labeler                    *Generate Plot Title Based on NERR Site ID*

---

**Description**

Generate a plot title based on SWMP station abbreviation

**Usage**

```
title_labeler(nerr_site_id)
```

**Arguments**

nerr\_site\_id    chr string of NERR site id

**Details**

A helper function used internally by several plotting functions to generate plot titles.

**Value**

Returns character vector

**Author(s)**

Julie Padilla

**Examples**

```
ttl <- title_labeler('elkapwq')
```

---

update\_samplng\_stations  
*Update reserve sampling stations*

---

**Description**

Script to modify the internal sampling\_sites.rda file for adding new reserves or for making changes to existing sampling station locations.

**Usage**

```
update_samplng_stations(  
  file_path = "inst/extdata",  
  file_name = "sampling_stations.csv"  
)
```

## Arguments

file_path	path to directory with new file
file_name	name of new csv file

## Details

This is a standalone function used to replace the internal SWMPExtension sampling sites data table used by the `get_sites.R` function. It reads a csv-formatted file of all NERRS SWMP stations that the user has downloaded from the CDMO SWMP station website: <https://cdmo.baruch.sc.edu/data/swmp-stations/>.

This downloaded csv-formatted file and its location are the only input arguments to `update_sampling_station()`. The current station information is loaded from `data/sampling_stations.rda`, a copy of which is written out as `data/sampling_stations_backup.rda`, and the new data file is read, formatted appropriately, and written out as `data/sampling_stations.rda`.

Note: This function need only be run when new reserves are added, stations are moved, etc.

## Value

Returns TRUE on a successful run, FALSE on a failure.

## Author(s)

Dave Eslinger

## Examples

```
# Provide a bad file name to get error message
x <- update_sampling_stations("data", "bad_file_name.csv")
print(x)

# Commented out example with a valid, but older, filename.
# WARNING! Don't actually run this example unless you have a
# more recent csv file that can be used to update the rda file.
# x <- update_sampling_stations("inst/extdata", "NERRS_sampling_stations.csv")
# print(x)
```

## Description

US state boundaries from the US Census Bureau's MAF/TIGER geographic database in EPSG:4269, with all data except state FIPS codes and land area removed.

**Usage**

```
data('us_4269')
```

**Format**

A sf[DataFrame] object

**Source**

US Census Bureau

**References**

United States Census Bureau. Data accessed from the US Census Bureau website: <https://www2.census.gov/geo/tiger/GENZ> accessed 13 March 2020

---

y_count_labeler	<i>Generate y-axis Label Based on SWMP Parameter Abbreviation</i>
-----------------	---

---

**Description**

Generate a y-axis label based on SWMP parameter abbreviation and threshold criteria

**Usage**

```
y_count_labeler(
  param,
  parameter_threshold,
  threshold_type,
  time_threshold = NULL,
  converted = FALSE
)
```

**Arguments**

param	chr string of variable abbreviation
parameter_threshold	vector of numerical thresholds to evaluate parameters against
threshold_type	vector of logical operators ('<', '>', '<=', '>=', '==', '!=')
time_threshold	The amount of time an event must last to be counted (in hours)
converted	logical, should the parameter label units be converted from metric to english? Defaults to FALSE. Currently available for temp, depth, cdepth, level, clevel, atemp, wspd, maxwspd, and totprcp

**Details**

A helper function used internally by several plotting functions to generate y-axis labels. This function does not convert sample results from metric to english. It only adjusts the units in the y-axis label.

**Value**

Returns character vector or an unevaluated expression

**Author(s)**

Julie Padilla

**Examples**

```
y_lab <- y_count_labeler(param = 'do_mgl', parameter_threshold = 2
, threshold_type = '<', time_threshold = 2, converted = FALSE)
```

---

y\_labeler

*Generate y-axis Label Based on SWMP Parameter Abbreviation*


---

**Description**

Generate a y-axis label based on SWMP parameter abbreviation

**Usage**

```
y_labeler(param, converted = FALSE)
```

**Arguments**

param	chr string of variable abbreviation
converted	logical, should the parameter label units be converted from metric to english? Defaults to FALSE. Currently available for temp, depth, cdepth, level, clevel, atemp, wspd, maxwspd, and totprcp

**Details**

A helper function used internally by several plotting functions to generate y-axis labels. This function does not convert sample results from metric to english. It only adjusts the units in the y-axis label.

**Value**

Returns character vector or an unevaluated expression

**Author(s)**

Julie Padilla

**Examples**

```
y_lab <- y_labeler('do_mgl')
```

# Index

- \* **Reporting**
  - create\_sk\_national\_ft\_results, 11
- \* **analyze**
  - annual\_range, 3
  - assign\_season, 5
  - base\_map, 6
  - historical\_daily\_range, 20
  - historical\_range, 22
  - national\_sk\_map, 27
  - raw\_boxplot, 29
  - res\_custom\_map, 32
  - res\_custom\_sk\_map, 34
  - res\_local\_map, 36
  - res\_national\_map, 38
  - res\_sk\_map, 40
  - seasonal\_barplot, 43
  - seasonal\_boxplot, 45
  - seasonal\_dot, 48
  - set\_date\_break\_labs, 51
  - sk\_seasonal, 52
  - threshold\_criteria\_plot, 56
  - threshold\_identification, 59
  - threshold\_percentile\_plot, 61
  - threshold\_summary, 63
- \* **data maintenance**
  - update\_sampling\_stations, 66
- \* **datasets**
  - cbm\_spatial, 8
  - counties\_4269, 8
  - elk\_spatial, 13
  - elkmmnut, 12
  - elksmwq, 13
  - sampling\_stations, 42
  - sampling\_stations\_backup, 43
  - us\_4269, 67
- \* **mapping**
  - geographic\_unique\_stations, 16
- \* **miscellaneous**
  - lm\_p\_labs, 26
  - remove\_inf\_and\_nan, 30
  - reserve\_locs, 31
  - set\_date\_breaks, 50
  - set\_date\_breaks\_minor, 51
  - sk\_tidy, 54
  - std\_param\_check, 54
  - title\_labeler, 66
  - y\_count\_labeler, 68
  - y\_labeler, 69
- \* **reporting**
  - create\_sk\_flextable\_list, 9
  - create\_sk\_national\_ft\_reserves, 10
  - ft\_col\_names, 14
  - generate\_results\_table, 15
  - generate\_station\_table, 15
  - get\_reserve, 17
  - get\_shp\_name, 18
  - get\_site\_code, 19
  - get\_site\_coordinates, 20
  - get\_sites, 18
  - load\_shp\_file, 27
  - summarise\_handoff\_files, 55
- \* **retrieve**
  - import\_local\_nut, 24
- all\_params, 26
- all\_params\_dtrng, 26
- annual\_range, 3
- assign\_season, 4, 5, 23, 24, 29, 30, 44–49, 52, 53, 64, 65
- base\_map, 6, 32, 34, 36, 40
- cbm\_spatial, 8
- counties\_4269, 8
- create\_sk\_flextable\_list, 9, 14–16
- create\_sk\_national\_ft\_reserves, 10
- create\_sk\_national\_ft\_results, 11
- data.frame, 12, 13, 42, 43

elk\_spatial, 13  
elkmmnut, 12  
elksmwq, 13

flextable, 10–12, 14  
ft\_col\_names, 14

generate\_results\_table, 15  
generate\_station\_table, 15  
geographic\_unique\_stations, 16  
get\_reserve, 17  
get\_shp\_name, 18  
get\_site\_code, 19  
get\_site\_coordinates, 20  
get\_sites, 18  
ggplot, 4, 22, 24, 28, 30, 39, 44, 45, 47, 49,  
57, 62, 64, 65

historical\_daily\_range, 20  
historical\_range, 22

import\_local, 25  
import\_local\_nut, 24

kendallSeasonalTrendTest, 53, 54

lm, 26  
lm\_p\_labs, 26  
load\_shp\_file, 27

national\_sk\_map, 27

raw\_boxplot, 29  
rem\_reps, 25, 26  
remove\_inf\_and\_nan, 30  
res\_custom\_map, 32  
res\_custom\_sk\_map, 34  
res\_local\_map, 16, 27, 36  
res\_national\_map, 31, 38  
res\_sk\_map, 27, 40  
reserve\_locs, 31

sampling\_stations, 42  
sampling\_stations\_backup, 43  
scale\_fill\_brewer, 64, 65  
scale\_x\_datetime, 50–52  
seasonal\_barplot, 43  
seasonal\_boxplot, 45  
seasonal\_dot, 26, 48  
set\_date\_break\_labs, 50, 51, 51

set\_date\_breaks, 50, 52  
set\_date\_breaks\_minor, 51  
setstep, 60  
sf, 27  
single\_param, 26  
sk\_seasonal, 9, 11, 15, 16, 35, 52, 54  
sk\_tidy, 54  
SpatialPolygons, 8, 13  
std\_param\_check, 54  
summarise\_handoff\_files, 55

threshold\_criteria\_plot, 56, 62  
threshold\_identification, 59, 65  
threshold\_percentile\_plot, 61  
threshold\_summary, 63  
title\_labeler, 66

update\_sampling\_stations, 66  
us\_4269, 67

y\_count\_labeler, 68  
y\_labeler, 4, 22, 24, 29, 30, 45, 49, 53, 56,  
57, 69