

# Package ‘fasstr’

October 21, 2021

**Title** Analyze, Summarize, and Visualize Daily Streamflow Data

**Version** 0.3.3

**Description** The Flow Analysis Summary Statistics Tool for R, 'fasstr', provides various functions to tidy and screen daily stream discharge data, calculate and visualize various summary statistics and metrics, and compute annual trending and volume frequency analyses. It features useful function arguments for filtering of and handling dates, customizing data and metrics, and the ability to pull daily data directly from the Water Survey of Canada hydrometric database (<<https://collaboration.cmc.ec.gc.ca/cmc/hydrometrics/www/>>).

**Depends** R (>= 3.3.0)

**License** Apache License 2.0

**URL** <https://bcgov.github.io/fasstr/>, <https://github.com/bcgov/fasstr>,  
<https://www2.gov.bc.ca/gov/content/environment/air-land-water/water>

**BugReports** <https://github.com/bcgov/fasstr/issues>

**Encoding** UTF-8

**Imports** dplyr (>= 0.8.1), e1071 (>= 1.7.0.1), fitdistrplus (>= 1.0.14), ggplot2 (>= 3.1.0), grDevices, openxlsx (>= 4.1.0), PearsonDS (>= 1.1), plyr (>= 1.8.4), purrr (>= 0.3.2), RcppRoll (>= 0.3.0), scales (>= 1.0.0), tidyhydat (>= 0.4.0), tidyr (>= 0.8.3), zyp (>= 0.10.1.1)

**Suggests** knitr, rmarkdown, testthat

**RoxygenNote** 7.1.2

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Jon Goetz [aut, cre] (<<https://orcid.org/0000-0002-4993-1119>>),  
Carl James Schwarz [aut],  
Robin Pike [ctb],  
Province of British Columbia [cph]

**Maintainer** Jon Goetz <jon.goetz@gov.bc.ca>

Repository CRAN

Date/Publication 2021-10-21 04:20:02 UTC

## R topics documented:

add_basin_area . . . . .	3
add_cumulative_volume . . . . .	4
add_cumulative_yield . . . . .	5
add_daily_volume . . . . .	7
add_daily_yield . . . . .	8
add_date_variables . . . . .	9
add_rolling_means . . . . .	10
add_seasons . . . . .	12
calc_all_annual_stats . . . . .	13
calc_annual_cumulative_stats . . . . .	17
calc_annual_flow_timing . . . . .	19
calc_annual_lowflows . . . . .	22
calc_annual_outside_normal . . . . .	24
calc_annual_peaks . . . . .	27
calc_annual_stats . . . . .	29
calc_daily_cumulative_stats . . . . .	32
calc_daily_stats . . . . .	34
calc_flow_percentile . . . . .	37
calc_longterm_daily_stats . . . . .	39
calc_longterm_mean . . . . .	42
calc_longterm_monthly_stats . . . . .	44
calc_longterm_percentile . . . . .	47
calc_monthly_cumulative_stats . . . . .	49
calc_monthly_stats . . . . .	52
compute_annual_frequencies . . . . .	55
compute_annual_trends . . . . .	58
compute_frequency_analysis . . . . .	61
compute_frequency_quantile . . . . .	64
compute_full_analysis . . . . .	66
compute_hydat_peak_frequencies . . . . .	69
fill_missing_dates . . . . .	71
plot_annual_cumulative_stats . . . . .	72
plot_annual_flow_timing . . . . .	75
plot_annual_lowflows . . . . .	77
plot_annual_means . . . . .	79
plot_annual_outside_normal . . . . .	81
plot_annual_stats . . . . .	83
plot_daily_cumulative_stats . . . . .	86
plot_daily_stats . . . . .	89
plot_data_screening . . . . .	92
plot_flow_data . . . . .	94
plot_flow_duration . . . . .	96

plot_longterm_daily_stats . . . . .	99
plot_longterm_monthly_stats . . . . .	102
plot_missing_dates . . . . .	105
plot_monthly_cumulative_stats . . . . .	107
plot_monthly_stats . . . . .	109
screen_flow_data . . . . .	112
write_flow_data . . . . .	114
write_full_analysis . . . . .	116
write_objects_list . . . . .	119
write_plots . . . . .	120
write_results . . . . .	122

<b>Index</b>	<b>123</b>
--------------	------------

---

add_basin_area	<i>Add a basin area column to daily flows</i>
----------------	---

---

## Description

Add a column of basin areas to a daily streamflow data set, in units of square kilometres.

## Usage

```
add_basin_area(data, groups = STATION_NUMBER, station_number, basin_area)
```

## Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
basin_area	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if groups is STATION_NUMBER with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations. (3) List each basin area for each group/station in groups (can override HYDAT value if listed) as such c("08NM116" = 795, "08NM242" = 10). If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.

**Value**

A tibble data frame of the original source data with an additional column:

```
Basin_Area_sqkm
      area of upstream drainage basin area, in square kilometres
```

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Add the HYDAT basin area to a data frame with station numbers
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
add_basin_area(data = flow_data)

# Add the HYDAT basin area to data from HYDAT
add_basin_area(station_number = "08NM116")

# Set a custom basin area
add_basin_area(station_number = "08NM116",
               basin_area = 800)

# Set multiple custom basin areas for multiple stations
add_basin_area(station_number = c("08NM116", "08NM242"),
               basin_area = c("08NM116" = 800, "08NM242" = 10))

}
```

---

add\_cumulative\_volume *Add a daily cumulative volumetric flows column to daily flows*

---

**Description**

Add a column of rolling daily cumulative volumetric flows on an annual basis to a daily streamflow data set. Adds the volumetric discharge from each day with the previous day(s) for each year, in units of cubic metres. The cumulative flows restart every year and are only calculated in years with complete data.

**Usage**

```
add_cumulative_volume(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  water_year_start = 1
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.

**Value**

A tibble data frame of the source data with an additional column:

Cumul\_Volume\_m3  
cumulative volumetric flows for each day for each year, in units of cubic metres

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Add a column based on water years starting in August
add_cumulative_volume(station_number = "08NM116",
                      water_year_start = 8)

}
```

---

add\_cumulative\_yield *Add a daily cumulative water yield column to daily flows*

---

**Description**

Add a column of rolling daily cumulative water yields on an annual basis to a daily streamflow data set. Adds the water yields from each day with the previous day(s) for each year, in units of millimetres. Converts cumulative discharge to a depth of water based on the upstream drainage basin area from `basin_area` argument. The cumulative flows restart every year and are only calculated in years with complete data.

**Usage**

```
add_cumulative_yield(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  basin_area,
  water_year_start = 1
)
```

**Arguments**

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in <code>data</code> that contains dates formatted YYYY-MM-DD. Only required if <code>dates</code> column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
<code>values</code>	Name of column in <code>data</code> that contains numeric flow values, in units of cubic metres per second. Only required if <code>values</code> column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
<code>groups</code>	Name of column in <code>data</code> that contains unique identifiers for different data sets, if applicable. Only required if <code>groups</code> column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.
<code>basin_area</code>	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if <code>groups</code> is <code>STATION_NUMBER</code> with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations. (3) List each basin area for each group/station in <code>groups</code> (can override HYDAT value if listed) as such <code>c("08NM116" = 795, "08NM242" = 10)</code> . If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.

water\_year\_start

Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.

### Value

A tibble data frame of the source data with an additional column:

Cumul\_Yield\_mm cumulative yield flows for each day for each year, in units of millimetres

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Add a column based on water years starting in August
add_cumulative_yield(station_number = "08NM116",
                    water_year_start = 8)

# Add a column based on water years starting in August with a custom basin area to calculate yield
add_cumulative_yield(station_number = "08NM116",
                    water_year_start = 8,
                    basin_area = 800)

}
```

---

add\_daily\_volume      *Add a daily volumetric flows column to daily flows*

---

### Description

Add a column of daily volumetric flows to a daily streamflow data set, in units of cubic metres. Converts the discharge to a volume.

### Usage

```
add_daily_volume(data, values = Value, station_number)
```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.

**Value**

A tibble data frame of the source data with an additional column:

Volume\_m3      daily total volumetric flow, in units of cubic metres

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Add a column of daily flow volumes
add_daily_volume(station_number = "08NM116")

}
```

---

add\_daily\_yield      *Add a daily volumetric water yield column to daily flows*

---

**Description**

Add a column of daily water yields to a daily streamflow data set, in units of millimetres. Converts the discharge to a depth of water based on the upstream drainage basin area.

**Usage**

```
add_daily_yield(
  data,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  basin_area
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.



station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
basin_area	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if groups is STATION_NUMBER with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations. (3) List each basin area for each group/station in groups (can override HYDAT value if listed) as such c("08NM116" = 795, "08NM242" = 10). If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.

### Value

A tibble data frame of the source data with an additional column:

Yield\_mm            daily water yield, in units of millimetres

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Add a column of yields based on HYDAT basin area
add_daily_yield(station_number = "08NM116")

# Add a column of yields based on a custom basin area
add_daily_yield(station_number = "08NM116",
                 basin_area = 800)

}
```

---

add\_date\_variables      *Add year, month, and day of year variable columns to daily flows*

---

### Description

Add columns of CalendarYear (YYYY), Month (MM), MonthName (e.g. 'Jan'), WaterYear (YYYY), and DayofYear (1-365 or 366; of WaterYear); to a data frame with a column of dates called 'Date'. Water years are designated by the year in which they end. For example, Water Year 1999 (starting Oct) is from 1 Oct 1998 (DayofYear 1) to 30 Sep 1999 (DayofYear 365)).

### Usage

```
add_date_variables(data, dates = Date, station_number, water_year_start = 1)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.

**Value**

A tibble data frame of the source data with additional columns:

CalendarYear	calendar year
Month	numeric month (1 to 12)
MonthName	month abbreviation (Jan-Dec)
WaterYear	year starting from the selected month start, water_year_start
DayofYear	day of the year from the selected month start (1-365 or 366)

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Add date variables using calendar years
add_date_variables(station_number = "08NM116")

# Add date variables using water years starting in August
add_date_variables(station_number = "08NM116",
                  water_year_start = 8)

}
```

---

add\_rolling\_means      *Add rolling n-day average column(s) to daily flows*

---

**Description**

Adds selected n-day rolling means to a daily streamflow data set. Based on selected n-days and alignment, the rolling mean for a given day is obtained by averaging the adjacent dates of daily mean values. For example, rolling days of '7' and 'right' alignment would obtain a mean of the given and previous 6 days of daily mean flow.

**Usage**

```
add_rolling_means(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = c(3, 7, 30),
  roll_align = "right"
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric values of the number of days to apply a rolling mean. Default c(3, 7, 30).
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.

**Value**

A data frame of the source data with an additional column(s):

QnDay                   rolling means of the n-day flow values of the designated date and adjacent dates, direction of mean specified by roll\_align

Default additional columns:

Q3Day                   rolling means of the 3-day flow values of the designated date and previous 2 days (roll\_align = "right")

Q7Day	rolling means of the 7-day flow values of the designated date and previous 6 days (roll_align = "right")
Q30Day	rolling means of the 30-day flow values of the designated date and previous 29 days (roll_align = "right")

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Add default 3, 7, and 30-day rolling mean columns, with "right" alignment
add_rolling_means(station_number = "08NM116")

# Add custom 5 and 10-day rolling mean columns
add_rolling_means(station_number = "08NM116",
                  roll_days = c(5,10))

# Add default 3, 7, and 30-day rolling mean columns, with "left" alignment
add_rolling_means(station_number = "08NM116",
                  roll_align = "left")

}
```

---

add\_seasons

*Add a column of seasons*

---

### Description

Adds a column of seasons identifiers to a data frame with a column of dates called 'Date'. The length of seasons, in months, is provided using the `seasons_length` argument. As seasons are grouped by months the length of the seasons must be divisible into 12 with one of the following season lengths: 1, 2, 3, 4, 6, or 12 months. The start of the first season coincides with the start month of each year; 'Jan-Jun' for 6-month seasons starting with calendar years or 'Dec-Feb' for 3-month seasons starting with water year starting in December.

### Usage

```
add_seasons(
  data,
  dates = Date,
  station_number,
  water_year_start = 1,
  seasons_length
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
seasons_length	Numeric value indicating the desired length of seasons in months, divisible into 12. Required.

**Value**

A tibble data frame of the source data with additional column:

Season	season identifier labelled by the start and end month of the season
--------	---

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Add a column with four annual seasons starting in January
add_seasons(station_number = "08NM116",
            seasons_length = 4)

# Add a column with two annual seasons (of 6 months length) starting in October
add_seasons(station_number = "08NM116",
            water_year_start = 10,
            seasons_length = 6)

}
```

**Description**

Calculates annual statistics from all annual `fasstr` functions from a daily streamflow data set. Data is ideally long-term and continuous with minimal missing/seasonal data as annual statistics are calculated. Calculates statistics from all values, unless specified. Returns a tibble with statistics. Data calculated using the following functions:

- `calc_annual_stats()`
- `calc_annual_lowflows()`
- `calc_annual_cumulative_stats()`
- `calc_annual_flow_timing()`
- `calc_annual_outside_normal()`
- `calc_monthly_stats()`

**Usage**

```
calc_all_annual_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  basin_area,
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  annual_percentiles = c(10, 90),
  monthly_percentiles = c(10, 20),
  stats_days = 1,
  stats_align = "right",
  lowflow_days = c(1, 3, 7, 30),
  lowflow_align = "right",
  timing_percent = c(25, 33, 50, 75),
  normal_percentiles = c(25, 75),
  transpose = FALSE,
  ignore_missing = FALSE
)
```

**Arguments**

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in <code>data</code> that contains dates formatted YYYY-MM-DD. Only required if <code>dates</code> column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.

values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
basin_area	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if groups is STATION_NUMBER with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations. (3) List each basin area for each group/station in groups (can override HYDAT value if listed) as such c("08NM116" = 795, "08NM242" = 10). If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
annual_percentiles	Numeric vector of percentiles to calculate annually. Set to NA if none required. Used for calc_annual_stats() function. Default c(10, 90).
monthly_percentiles	Numeric vector of percentiles to calculate monthly for each year. Set to NA if none required. Used for calc_monthly_stats() function. Default c(10, 20).
stats_days	Numeric vector of the number of days to apply a rolling mean on basic stats. Default c(1). Used for calc_annual_stats() and calc_monthly_stats() functions.
stats_align	Character string identifying the direction of the rolling mean on basic stats from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'. Used for calc_annual_stats(), calc_monthly_stats(), and calc_annual_outside_normal() functions.
lowflow_days	Numeric vector of the number of days to apply a rolling mean on low flow stats. Default c(1, 3, 7, 30). Used for calc_lowflow_stats() function.

<code>lowflow_align</code>	Character string identifying the direction of the rolling mean on low flow stats from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'. Used for <code>calc_lowflow_stats()</code> function.
<code>timing_percent</code>	Numeric vector of percents of annual total flows to determine dates. Used for <code>calc_annual_flow_timing()</code> function. Default <code>c(25, 33.3, 50, 75)</code> .
<code>normal_percentiles</code>	Numeric vector of two values, lower and upper percentiles, respectively indicating the limits of the normal range. Default <code>c(25, 75)</code> .
<code>transpose</code>	Logical value indicating whether to transpose rows and columns of results. Default FALSE.
<code>ignore_missing</code>	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.

### Value

A tibble data frame with column "Year" and then 107 (default) variables from the fasstr annual functions. See listed functions above for default variables. Transposing data creates a column of "Statistics" and subsequent columns for each year selected.

### See Also

[calc\\_annual\\_stats](#), [calc\\_annual\\_lowflows](#), [calc\\_annual\\_cumulative\\_stats](#), [calc\\_annual\\_flow\\_timing](#), [calc\\_monthly\\_stats](#), [calc\\_annual\\_outside\\_normal](#)

### Examples

```
## Not run:

# Working examples:

# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate all annual statistics from this package with default arguments
calc_all_annual_stats(station_number = "08NM116")

# Calculate all annual statistics from this package with default arguments
# with some default arguments shown to customize metrics
calc_all_annual_stats(station_number = "08NM116",
  annual_percentiles = c(10,90),
  monthly_percentiles = c(10,20),
  stats_days = 1,
  stats_align = "right",
  lowflow_days = c(1,3,7,30),
  lowflow_align = "right",
  timing_percent = c(25,33,50,75),
  normal_percentiles = c(25,75))
```



```

}

## End(Not run)

```

---

```

calc_annual_cumulative_stats
    Calculate annual (and seasonal) cumulative flows

```

---

### Description

Calculates annual and seasonal total flows, as volumetric discharge or water yields, from a daily streamflow data set. For water year and seasonal data, the year is identified by the year in which the year or season ends. Two-seasons and four-seasons per year are calculated, with each 6 and 3-month seasons starting with the first month of the year (Jan for calendar year, specified for water year). Each season is designated by the calendar or water year in which it occurs. Calculates statistics from all values from complete years, unless specified. Returns a tibble with statistics.

### Usage

```

calc_annual_cumulative_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  use_yield = FALSE,
  basin_area,
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  months = 1:12,
  include_seasons = FALSE,
  transpose = FALSE
)

```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.

values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.
use_yield	Logical value indicating whether to calculate area-based water yield, in mm, instead of volumetric discharge. Default FALSE.
basin_area	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if groups is STATION_NUMBER with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations. (3) List each basin area for each group/station in groups (can override HYDAT value if listed) as such <code>c("08NM116" = 795, "08NM242" = 10)</code> . If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
include_seasons	Logical value indication whether to include seasonal yields or volumetric discharges. Default TRUE.
transpose	Logical value indicating whether to transpose rows and columns of results. Default FALSE.

**Value**

A tibble data frame with the following columns, ending with '\_Volume\_m3' or '\_Yield\_mm' based on selection:

Year	calendar or water year selected
------	---------------------------------

Total\_\*            annual (or selected months) total flow, in m3 or mm

Default seasonal columns:

MMM-MMM\_\*        first of two season total flows, in m3 or mm

MMM-MMM\_\*        second of two season total flows, in m3 or mm

MMM-MMM\_\*        first of four season total flows, in m3 or mm

MMM-MMM\_\*        second of four season total flows, in m3 or mm

MMM-MMM\_\*        third of four season total flows, in m3 or mm

MMM-MMM\_\*        fourth of four season total flows, in m3 or mm

Transposing data creates a column of 'Statistics' and subsequent columns for each year selected.

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate annual total volumetric flow statistics
calc_annual_cumulative_stats(station_number = "08NM116")

# Calculate annual total yield statistics with default HYDAT basin area
calc_annual_cumulative_stats(station_number = "08NM116",
                             use_yield = TRUE)

# Calculate annual total yield statistics with a custom basin area
calc_annual_cumulative_stats(station_number = "08NM116",
                             use_yield = TRUE,
                             basin_area = 800)

}
```

---

calc\_annual\_flow\_timing

*Calculate annual timing of flows*

---

### Description

Calculates the timing (day of year and date) of portions of total annual flow of daily flow values from a daily streamflow data set. Calculates statistics from all values from complete years, unless specified. Returns a tibble with statistics.

**Usage**

```
calc_annual_flow_timing(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  percent_total = c(25, 33.3, 50, 75),
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  transpose = FALSE
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
percent_total	Numeric vector of percents of total annual flows to determine dates. Default c(25, 33.3, 50, 75).
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.

transpose Logical value indicating whether to transpose rows and columns of results. Default FALSE.

### Value

A tibble data frame with the following columns:

Year calendar or water year selected  
 DoY\_ 'n' pct\_TotalQ day of year for each n-percent of total volumetric discharge  
 Date\_ 'n' pct\_TotalQ date (YYYY-MM-DD) for each n-percent of total volumetric discharge

Default columns:

DoY\_25pct\_TotalQ day of year of 25-percent of total volumetric discharge  
 Date\_25pct\_TotalQ date (YYYY-MM-DD) of 25-percent of total volumetric discharge  
 DoY\_33.3pct\_TotalQ day of year of 33.3-percent of total volumetric discharge  
 Date\_33.3pct\_TotalQ date (YYYY-MM-DD) of 33.3-percent of total volumetric discharge  
 DoY\_50pct\_TotalQ day of year of 50-percent of total volumetric discharge  
 Date\_50pct\_TotalQ date (YYYY-MM-DD) of 50-percent of total volumetric discharge  
 DoY\_75pct\_TotalQ day of year of 75-percent of total volumetric discharge  
 Date\_75pct\_TotalQ date (YYYY-MM-DD) of 75-percent of total volumetric discharge

Transposing data creates a column of 'Statistics' (just DoY, not Date values) and subsequent columns for each year selected.

### References

- Barnett, T.P., Pierce, D.W., Hidalgo, H.G., Bonfils, C., Santer, B.D., Das, T., Bala, G., Wood, A.W., Nozawa, T., Mirin, A.A., Cayan, D.R., Dettinger, M.D., 2008. Human-Induced Changes in the Hydrology of the Western United States. *Science* 319, 1080-1083.

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate annual flow timings with default percent of annual totals
calc_annual_flow_timing(station_number = "08NM116")

# Calculate annual flow timings with custom percent of annual totals
```

```

calc_annual_flow_timing(station_number = "08NM116",
                        percent_total = 50)

}

```

---

calc\_annual\_lowflows *Calculate annual low flows and dates*

---

### Description

Calculates annual n-day minimum values, and the day of year and date of occurrence of daily flow values from a daily streamflow data set. Calculates statistics from all values, unless specified. Returns a tibble with statistics.

### Usage

```

calc_annual_lowflows(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = c(1, 3, 7, 30),
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  months = 1:12,
  transpose = FALSE,
  ignore_missing = FALSE
)

```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.

groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
transpose	Logical value indicating whether to transpose rows and columns of results. Default FALSE.
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.

### Value

A tibble data frame with the following columns:

Year	calendar or water year selected
Min_'n'_Day	annual minimum for each n-day rolling mean, direction of mean specified by roll_align
Min_'n'_Day_DoY	day of year for each annual minimum of n-day rolling mean
Min_'n'_Day_Date	date (YYYY-MM-DD) for each annual minimum of n-day rolling mean

Default columns:

Min_1_Day	annual 1-day mean minimum (roll_align = right)
-----------	--

Min\_1\_Day\_DoY day of year of annual 1-day mean minimum  
 Min\_1\_Day\_Date date (YYYY-MM-DD) of annual 1-day mean minimum  
 Min\_3\_Day annual 3-day mean minimum (roll\_align = right)  
 Min\_3\_Day\_DoY day of year of annual 3-day mean minimum  
 Min\_3\_Day\_Date date (YYYY-MM-DD) of annual 3-day mean minimum  
 Min\_7\_Day annual 7-day mean minimum (roll\_align = right)  
 Min\_7\_Day\_DoY day of year of annual 7-day mean minimum  
 Min\_7\_Day\_Date date (YYYY-MM-DD) of annual 7-day mean minimum  
 Min\_30\_Day annual 30-day mean minimum (roll\_align = right)  
 Min\_30\_Day\_DoY day of year of annual 30-day mean minimum  
 Min\_30\_Day\_Date date (YYYY-MM-DD) of annual 30-day mean minimum

Transposing data creates a column of 'Statistics' and subsequent columns for each year selected. 'Date' statistics not transposed.

### Examples

```

# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate annual 1, 3, 7, and 30-day (default) low flows with
# default alignment ('right')
calc_annual_lowflows(station_number = "08NM116")

# Calculate custom 3 and 7-day annual low flows with 'center' alignment
calc_annual_lowflows(station_number = "08NM116",
                     roll_days = c(3,7),
                     roll_align = "center")

}

```

---

calc\_annual\_outside\_normal

*Calculate annual days above and below normal*

---

### Description

Calculates the number of days per year outside of the 'normal' range (typically between 25 and 75th percentiles) for each day of the year. Upper and lower-range percentiles are calculated for each day of the year of from all years, and then each daily flow value for each year is compared. All days above or below the normal range are included. Analysis methodology is based on Environment and Climate Change Canada's [Water Quantity indicator](#) from the Canadian Environmental Sustainability Indicators. Calculates statistics from all values from complete years, unless specified. Returns a tibble with statistics.



**Usage**

```
calc_annual_outside_normal(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  normal_percentiles = c(25, 75),
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  months = 1:12,
  transpose = FALSE
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
normal_percentiles	Numeric vector of two values, lower and upper percentiles, respectively indicating the limits of the normal range. Default c(25, 75).
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.



---

calc_annual_peaks	<i>Calculate annual peak flows</i>
-------------------	------------------------------------

---

## Description

Calculates annual n-day minimum and maximum values, and the day of year and date of occurrence of daily flow values from a daily streamflow data set. Calculates statistics from all values, unless specified. Returns a tibble with statistics.

## Usage

```
calc_annual_peaks(  
  data,  
  dates = Date,  
  values = Value,  
  groups = STATION_NUMBER,  
  station_number,  
  roll_days = 1,  
  roll_align = "right",  
  water_year_start = 1,  
  start_year,  
  end_year,  
  exclude_years,  
  months = 1:12,  
  transpose = FALSE,  
  ignore_missing = FALSE  
)
```

## Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.

station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
transpose	Logical value indicating whether to transpose rows and columns of results. Default FALSE.
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.

### Value

A tibble data frame with the following columns:

Year	calendar or water year selected
Min_'n'_Day	annual minimum for selected n-day rolling mean, direction of mean specified by roll_align
Min_'n'_Day_DoY	day of year for selected annual minimum of n-day rolling mean
Min_'n'_Day_Date	date (YYYY-MM-DD) for selected annual minimum of n-day rolling mean
Max_'n'_Day	annual maximum for selected n-day rolling mean, direction of mean specified by roll_align
Max_'n'_Day_DoY	day of year for selected annual maximum of n-day rolling mean
Max_'n'_Day_Date	date (YYYY-MM-DD) for selected annual maximum of n-day rolling mean

Default columns:

Min\_1\_Day        annual 1-day mean minimum (roll\_align = right)  
 Min\_1\_Day\_DoY   day of year of annual 1-day mean minimum  
 Min\_1\_Day\_Date   date (YYYY-MM-DD) of annual 1-day mean minimum  
 Max\_1\_Day        annual 1-day mean maximum (roll\_align = right)  
 Max\_1\_Day\_DoY   day of year of annual 1-day mean maximum  
 Max\_1\_Day\_Date   date (YYYY-MM-DD) of annual 1-day mean maximum

Transposing data creates a column of 'Statistics' and subsequent columns for each year selected. 'Date' statistics not transposed.

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate annual 1-day (default) peak flow data with
# default alignment ('right')
calc_annual_peaks(station_number = "08NM116")

# Calculate custom 3-day peak flow data with 'center' alignment
calc_annual_peaks(station_number = "08NM116",
                  roll_days = 3,
                  roll_align = "center")

}
```

---

calc\_annual\_stats        *Calculate annual summary statistics*

---

### Description

Calculates means, medians, maximums, minimums, and percentiles for each year from all years of a daily streamflow data set. Calculates statistics from all values, unless specified. Returns a tibble with statistics.

### Usage

```
calc_annual_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = 1,
  roll_align = "right",
  percentiles = c(10, 90),
  water_year_start = 1,
```

```

    start_year,
    end_year,
    exclude_years,
    months = 1:12,
    transpose = FALSE,
    ignore_missing = FALSE
  )

```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
percentiles	Numeric vector of percentiles to calculate. Set to NA if none required. Default c(10,90).
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).

transpose	Logical value indicating whether to transpose rows and columns of results. Default FALSE.
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.

### Value

A tibble data frame with the following columns:

Year	calendar or water year selected
Mean	annual mean of all daily flows for a given year
Median	annual median of all daily flows for a given year
Maximum	annual maximum of all daily flows for a given year
Minimum	annual minimum of all daily flows for a given year
P'n'	each annual n-th percentile selected of all daily flows

Default percentile columns:

P10	annual 10th percentile of all daily flows for a given year
P90	annual 90th percentile of all daily flows for a given year

Transposing data creates a column of "Statistics" and subsequent columns for each year selected.

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate annual statistics from a data frame using the data argument
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
calc_annual_stats(data = flow_data)

# Calculate annual statistics using station_number argument
calc_annual_stats(station_number = "08NM116")

# Calculate annual statistics regardless if there
# is missing data for a given year
calc_annual_stats(station_number = "08NM116",
                  ignore_missing = TRUE)

# Calculate annual statistics for water years starting in October
calc_annual_stats(station_number = "08NM116",
                  water_year_start = 10)

# Calculate annual statistics filtered for custom years
calc_annual_stats(station_number = "08NM116",
                  start_year = 1981,
                  end_year = 2010,
```

```

        exclude_years = c(1991,1993:1995))

# Calculate annual statistics for 7-day flows for July-September
# months only, with 25 and 75th percentiles
calc_annual_stats(station_number = "08NM116",
                 roll_days = 7,
                 months = 7:9,
                 percentiles = c(25,75))
}

```

---

```
calc_daily_cumulative_stats
```

*Calculate cumulative daily flow statistics*

---

### Description

Calculate cumulative daily flow statistics for each day of the year of daily flow values from a daily streamflow data set. Defaults to volumetric cumulative flows, can use `use_yield` and `basin_area` to convert to area-based water yield. Calculates statistics from all values from all complete years, unless specified. Returns a tibble with statistics.

### Usage

```

calc_daily_cumulative_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  percentiles = c(5, 25, 75, 95),
  use_yield = FALSE,
  basin_area,
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  transpose = FALSE
)

```

### Arguments

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.



values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
percentiles	Numeric vector of percentiles to calculate. Set to NA if none required. Default c(5, 25, 75, 95).
use_yield	Logical value indicating whether to calculate area-based water yield, in mm, instead of volumetric discharge. Default FALSE.
basin_area	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if groups is STATION_NUMBER with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations. (3) List each basin area for each group/station in groups (can override HYDAT value if listed) as such c("08NM116" = 795, "08NM242" = 10). If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
transpose	Logical value indicating whether to transpose rows and columns of results. Default FALSE.

### Value

A data frame with the following columns, default units in cubic metres, millimetres if use\_yield and basin\_area provided:

Date	date (MMM-DD) of daily cumulative statistics
DayofYear	day of year of daily cumulative statistics
Mean	daily mean of all cumulative flows for a given day of the year
Median	daily mean of all cumulative flows for a given day of the year

Maximum	daily mean of all cumulative flows for a given day of the year
Minimum	daily mean of all cumulative flows for a given day of the year
P'n'	each daily n-th percentile selected of all cumulative flows for a given day of the year

Default percentile columns:

P5	daily 5th percentile of all cumulative flows for a given day of the year
P25	daily 25th percentile of all cumulative flows for a given day of the year
P75	daily 75th percentile of all cumulative flows for a given day of the year
P95	daily 95th percentile of all cumulative flows for a given day of the year

Transposing data creates a column of "Statistics" and subsequent columns for each year selected.

## Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate annual daily cumulative yield statistics
# with default HYDAT basin area
calc_daily_cumulative_stats(station_number = "08NM116",
                           use_yield = TRUE)

# Calculate annual daily cumulative yield statistics
# with custom basin area
calc_daily_cumulative_stats(station_number = "08NM116",
                           use_yield = TRUE,
                           basin_area = 800)

}
```

---

calc\_daily\_stats      *Calculate daily summary statistics*

---

## Description

Calculates means, medians, maximums, minimums, and percentiles for each day of the year of flow values from a daily streamflow data set. Can determine statistics of rolling mean days (e.g. 7-day flows) using the `roll_days` argument. Note that statistics are based on the numeric days of year (1-365) and not the date of year (Jan 1 - Dec 31). Calculates statistics from all values, unless specified. Returns a tibble with statistics.

**Usage**

```
calc_daily_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  percentiles = c(5, 25, 75, 95),
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  complete_years = FALSE,
  months = 1:12,
  transpose = FALSE,
  ignore_missing = FALSE
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
percentiles	Numeric vector of percentiles to calculate. Set to NA if none required. Default c(5, 25, 75, 95).
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.

water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
complete_years	Logical values indicating whether to include only years with complete data in analysis. Default FALSE.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
transpose	Logical value indicating whether to transpose rows and columns of results. Default FALSE.
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.

### Value

A tibble data frame with the following columns:

Date	date (MMM-DD) of daily statistics
DayofYear	day of year of daily statistics
Mean	daily mean of all flows for a given day of the year
Median	daily mean of all flows for a given day of the year
Maximum	daily mean of all flows for a given day of the year
Minimum	daily mean of all flows for a given day of the year
P'n'	each daily n-th percentile selected of all flows for a given day of the year

Default percentile columns:

P5	daily 5th percentile of all flows for a given day of the year
P25	daily 25th percentile of all flows for a given day of the year
P75	daily 75th percentile of all flows for a given day of the year
P95	daily 95th percentile of all flows for a given day of the year

Transposing data creates a column of "Statistics" and subsequent columns for each year selected.

## Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate daily statistics using station_number argument with defaults
calc_daily_stats(station_number = "08NM116",
                 start_year = 1980)

# Calculate daily statistics regardless if there is missing data for a given day of year
calc_daily_stats(station_number = "08NM116",
                 ignore_missing = TRUE)

# Calculate daily statistics using only years with no missing data
calc_daily_stats(station_number = "08NM116",
                 complete_years = TRUE)

# Calculate daily statistics for water years starting in October between 1980 and 2010
calc_daily_stats(station_number = "08NM116",
                 start_year = 1980,
                 end_year = 2010,
                 water_year_start = 10)

}
```

---

calc\_flow\_percentile *Calculate the percentile rank of a flow value*

---

## Description

Calculates the percentile rank of a discharge value compared to all flow values of a streamflow data set. Looks up the value in the distribution (`stats::ecdf()` function) of all daily discharge values from all years, unless specified. Returns a tibble with statistics.

## Usage

```
calc_flow_percentile(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = 1,
  roll_align = "right",
  flow_value,
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
```

```

    complete_years = FALSE,
    months = 1:12
  )

```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
flow_value	A numeric flow value of which to determine the percentile rank. Required.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
complete_years	Logical values indicating whether to include only years with complete data in analysis. Default FALSE.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).

### Value

A tibble data frame, or a single numeric value if no station number provided, of the percentile rank of a given flow value.

**Examples**

```

# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate the percentile rank of a 10-cms flow value from a full record
calc_flow_percentile(station_number = "08NM116",
                    flow_value = 10)

# Calculate the percentile rank of a 10-cms flow value from years with no missing data
calc_flow_percentile(station_number = "08NM116",
                    complete_years = TRUE,
                    flow_value = 10)

# Calculate the percentile rank of a 10-cms flow value for June from years with no missing data
calc_flow_percentile(station_number = "08NM116",
                    complete_years = TRUE,
                    months = 6,
                    flow_value = 10)

}

```

---

calc\_longterm\_daily\_stats

*Calculate long-term summary statistics from daily mean flows*

---

**Description**

Calculates the long-term mean, median, maximum, minimum, and percentiles of daily flow values for over all months and all data (Long-term) from a daily streamflow data set. Calculates statistics from all values, unless specified. Returns a tibble with statistics.

**Usage**

```

calc_longterm_daily_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  percentiles = c(10, 90),
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  months = 1:12,
  complete_years = FALSE,

```

```

include_longterm = TRUE,
custom_months,
custom_months_label,
transpose = FALSE,
ignore_missing = FALSE
)

```

## Arguments

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in <code>data</code> that contains dates formatted YYYY-MM-DD. Only required if <code>dates</code> column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
<code>values</code>	Name of column in <code>data</code> that contains numeric flow values, in units of cubic metres per second. Only required if <code>values</code> column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
<code>groups</code>	Name of column in <code>data</code> that contains unique identifiers for different data sets, if applicable. Only required if <code>groups</code> column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.
<code>percentiles</code>	Numeric vector of percentiles to calculate. Set to NA if none required. Default <code>c(10,90)</code> .
<code>roll_days</code>	Numeric value of the number of days to apply a rolling mean. Default 1.
<code>roll_align</code>	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.
<code>months</code>	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).



complete_years	Logical values indicating whether to include only years with complete data in analysis. Default FALSE.
include_longterm	Logical value indicating whether to include long-term calculation of all data. Default TRUE.
custom_months	Numeric vector of months to combine to summarize (ex. 6:8 for Jun-Aug). Adds results to the end of table. If wanting months that overlap calendar years (ex. Oct-Mar), choose water_year_start that begins before the first month listed. Leave blank for no custom month summary.
custom_months_label	Character string to label custom months. For example, if months = 7:9 you may choose "Summer" or "Jul-Sep". Default "Custom-Months".
transpose	Logical value indicating whether to transpose rows and columns of results. Default FALSE.
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.

### Value

A tibble data frame with the following columns:

Month	month of the year, included 'Long-term' for all months, and 'Custom-Months' if selected
Mean	mean of all daily data for a given month and long-term over all years
Median	median of all daily data for a given month and long-term over all years
Maximum	maximum of all daily data for a given month and long-term over all years
Minimum	minimum of all daily data for a given month and long-term over all years
P'n'	each n-th percentile selected for a given month and long-term over all years

Default percentile columns:

P10	annual 10th percentile selected for a given month and long-term over all years
P90	annual 90th percentile selected for a given month and long-term over all years

Transposing data creates a column of "Statistics" and subsequent columns for each year selected.

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate long-term statistics using data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
calc_longterm_daily_stats(data = flow_data,
                           start_year = 1980)
```

```

# Calculate long-term statistics using station_number argument with defaults
calc_longterm_daily_stats(station_number = "08NM116",
                          start_year = 1980)

# Calculate long-term statistics regardless if there is missing data for a given year
calc_longterm_daily_stats(station_number = "08NM116",
                          ignore_missing = TRUE)

# Calculate long-term statistics for water years starting in October
calc_longterm_daily_stats(station_number = "08NM116",
                          start_year = 1980,
                          water_year_start = 10)

# Calculate long-term statistics with custom years and percentiles
calc_longterm_daily_stats(station_number = "08NM116",
                          start_year = 1981,
                          end_year = 2010,
                          exclude_years = c(1991,1993:1995),
                          percentiles = c(25,75))

# Calculate long-term statistics and add custom stats for July-September
calc_longterm_daily_stats(station_number = "08NM116",
                          start_year = 1980,
                          custom_months = 7:9,
                          custom_months_label = "Summer")

}

```

---

calc\_longterm\_mean      *Calculate the long-term mean annual discharge*

---

### Description

Calculates the long-term mean annual discharge (MAD) from a daily streamflow data set. Calculates statistics from all values, unless specified. Returns a tibble with statistics.

### Usage

```

calc_longterm_mean(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,

```

```

    exclude_years,
    complete_years = FALSE,
    months = 1:12,
    percent_MAD,
    transpose = FALSE
  )

```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
complete_years	Logical values indicating whether to include only years with complete data in analysis. Default FALSE.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).

percent_MAD	Numeric vector of percents of long-term mean annual discharge to add to the table (ex. 20 for 20 percent MAD or c(5, 10, 20) for multiple portions of MAD). Leave blank for no values to be calculated.
transpose	Logical value indicating whether to transpose rows and columns of results. Default FALSE.

### Value

A tibble data frame of numeric values of a long-term mean (and percent of long-term mean if selected) of selected years and months.

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate the long-term mean annual discharge (MAD) using only years with no missing data
calc_longterm_mean(station_number = "08NM116",
                   complete_years = TRUE)

# Calculate the long-term MAD and 5, 10 and 20-percent MADs using only years with no missing data
calc_longterm_mean(station_number = "08NM116",
                   complete_years = TRUE,
                   percent_MAD = c(5,10,20))

}
```

---

```
calc_longterm_monthly_stats
```

*Calculate long-term summary statistics from annual monthly mean flows*

---

### Description

Calculates the long-term mean, median, maximum, minimum, and percentiles of annual monthly mean flow values for all months and all data (Long-term) from a daily streamflow data set. Calculates statistics from all values, unless specified. Returns a tibble with statistics.

### Usage

```
calc_longterm_monthly_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  percentiles = c(10, 90),
  roll_days = 1,
```

```

roll_align = "right",
water_year_start = 1,
start_year,
end_year,
exclude_years,
months = 1:12,
complete_years = FALSE,
include_annual = TRUE,
custom_months,
custom_months_label,
transpose = FALSE,
ignore_missing = FALSE
)

```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
percentiles	Numeric vector of percentiles to calculate. Set to NA if none required. Default c(10,90).
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.

end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
complete_years	Logical values indicating whether to include only years with complete data in analysis. Default FALSE.
include_annual	Logical value indicating whether to include annual calculation of all months. Default TRUE.
custom_months	Numeric vector of months to combine to summarize (ex. 6:8 for Jun-Aug). Adds results to the end of table. If wanting months that overlap calendar years (ex. Oct-Mar), choose water_year_start that begins before the first month listed. Leave blank for no custom month summary.
custom_months_label	Character string to label custom months. For example, if months = 7:9 you may choose "Summer" or "Jul-Sep". Default "Custom-Months".
transpose	Logical value indicating whether to transpose rows and columns of results. Default FALSE.
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.

### Value

A tibble data frame with the following columns:

Month	month of the year, included 'Annual' for all months, and 'Custom-Months' if selected
Mean	mean of all annual monthly means for a given month over all years
Median	median of all annual monthly means for a given month over all years
Maximum	maximum of all annual monthly means for a given month over all years
Minimum	minimum of all annual monthly means for a given month over all years
P'n'	each n-th percentile selected for annual monthly means for a given month over all years

Default percentile columns:

P10	annual 10th percentile selected for annual monthly means for a given month over all years
P90	annual 90th percentile selected for annual monthly means for a given month over all years

Transposing data creates a column of "Statistics" and subsequent columns for each year selected.

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate long-term monthly statistics using data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
calc_longterm_monthly_stats(data = flow_data,
                             start_year = 1980)

# Calculate long-term monthly statistics using station_number argument with defaults
calc_longterm_monthly_stats(station_number = "08NM116",
                             start_year = 1980)

# Calculate long-term monthly statistics regardless if there is missing data for a given year
calc_longterm_monthly_stats(station_number = "08NM116",
                             ignore_missing = TRUE)

# Calculate long-term monthly statistics for water years starting in October
calc_longterm_monthly_stats(station_number = "08NM116",
                             start_year = 1980,
                             water_year_start = 10)

# Calculate long-term monthly statistics with custom years
calc_longterm_monthly_stats(station_number = "08NM116",
                             start_year = 1981,
                             end_year = 2010,
                             exclude_years = c(1991,1993:1995))

# Calculate long-term monthly statistics and add custom stats for July-September
calc_longterm_monthly_stats(station_number = "08NM116",
                             start_year = 1980,
                             custom_months = 7:9,
                             custom_months_label = "Summer")

}
```

---

calc\_longterm\_percentile

*Calculate long-term percentiles*

---

**Description**

Calculates the long-term percentiles from a daily streamflow data set. Calculates statistics from all values, unless specified. Returns a tibble with statistics.

**Usage**

```
calc_longterm_percentile(  
  data,
```

```

dates = Date,
values = Value,
groups = STATION_NUMBER,
station_number,
percentiles,
roll_days = 1,
roll_align = "right",
water_year_start = 1,
start_year,
end_year,
exclude_years,
complete_years = FALSE,
months = 1:12,
transpose = FALSE
)

```

### Arguments

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in <code>data</code> that contains dates formatted YYYY-MM-DD. Only required if <code>dates</code> column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
<code>values</code>	Name of column in <code>data</code> that contains numeric flow values, in units of cubic metres per second. Only required if <code>values</code> column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
<code>groups</code>	Name of column in <code>data</code> that contains unique identifiers for different data sets, if applicable. Only required if <code>groups</code> column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.
<code>percentiles</code>	Numeric vector of percentiles (ex. <code>c(5, 10, 25, 75)</code> ) to calculate. Required.
<code>roll_days</code>	Numeric value of the number of days to apply a rolling mean. Default 1.
<code>roll_align</code>	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.



end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
complete_years	Logical values indicating whether to include only years with complete data in analysis. Default FALSE.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
transpose	Logical value indicating whether to transpose rows and columns of results. Default FALSE.

### Value

A tibble data frame of a long-term percentile of selected years and months.

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate the 20th percentile flow value from a flow record
calc_longterm_percentile(station_number = "08NM116",
                        percentile = 20)

# Calculate the 90th percentile flow value with custom years
calc_longterm_percentile(station_number = "08NM116",
                        start_year = 1980,
                        end_year = 2010,
                        percentile = 90)

}
```

---

calc\_monthly\_cumulative\_stats

*Calculate cumulative monthly flow statistics*

---

### Description

Calculate cumulative monthly flow statistics for each month of the year of daily flow values from a daily streamflow data set. Calculates statistics from all values from complete years, unless specified. Defaults to volumetric cumulative flows, can use use\_yield and basin\_area to convert to area-based water yield. Returns a tibble with statistics.

**Usage**

```
calc_monthly_cumulative_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  percentiles = c(5, 25, 75, 95),
  use_yield = FALSE,
  basin_area,
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  transpose = FALSE
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
percentiles	Numeric vector of percentiles to calculate. Set to NA if none required. Default c(5, 25, 75, 95).
use_yield	Logical value indicating whether to calculate area-based water yield, in mm, instead of volumetric discharge. Default FALSE.
basin_area	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if groups is STATION_NUMBER with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations.

(3) List each basin area for each group/station in groups (can override HYDAT value if listed) as such `c("08NM116" = 795, "08NM242" = 10)`. If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.

<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.
<code>transpose</code>	Logical value indicating whether to transpose rows and columns of results. Default FALSE.

### Value

A tibble data frame with the following columns, default units in cubic metres, or millimetres if `use_yield` and `basin_area` provided:

Month	month (MMM-DD) of cumulative statistics
Mean	monthly mean of all cumulative flows for a given month of the year
Median	monthly mean of all cumulative flows for a given month of the year
Maximum	monthly mean of all cumulative flows for a given month of the year
Minimum	monthly mean of all cumulative flows for a given month of the year
P'n'	each monthly n-th percentile selected of all cumulative flows for a given month of the year

Default percentile columns:

P5	monthly 5th percentile of all cumulative flows for a given month of the year
P25	monthly 25th percentile of all cumulative flows for a given month of the year
P75	monthly 75th percentile of all cumulative flows for a given month of the year
P95	monthly 95th percentile of all cumulative flows for a given month of the year

Transposing data creates a column of "Statistics" and subsequent columns for each year selected.

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate annual monthly cumulative volume statistics
calc_monthly_cumulative_stats(station_number = "08NM116")

# Calculate annual monthly cumulative volume statistics with default HYDAT basin area
calc_monthly_cumulative_stats(station_number = "08NM116",
```

```

        use_yield = TRUE)

# Calculate annual monthly cumulative volume statistics with custom basin area
calc_monthly_cumulative_stats(station_number = "08NM116",
                             use_yield = TRUE,
                             basin_area = 800)

}

```

---

calc\_monthly\_stats      *Calculate monthly summary statistics*

---

### Description

Calculates means, medians, maximums, minimums, and percentiles for each month of all years of flow values from a daily streamflow data set. Calculates statistics from all values, unless specified. Returns a tibble with statistics.

### Usage

```

calc_monthly_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  percentiles = c(10, 90),
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  months = 1:12,
  transpose = FALSE,
  spread = FALSE,
  ignore_missing = FALSE
)

```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.

values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
percentiles	Numeric vector of percentiles to calculate. Set to NA if none required. Default c(10,90).
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
transpose	Logical value indicating if each month statistic should be individual rows. Default FALSE.
spread	Logical value indicating if each month statistic should be the column name. Default FALSE.
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.

### Value

A tibble data frame with the following columns:

Year	calendar or water year selected
Month	month of the year
Mean	mean of all daily flows for a given month and year

Median	median of all daily flows for a given month and year
Maximum	maximum of all daily flows for a given month and year
Minimum	minimum of all daily flows for a given month and year
P'n'	each n-th percentile selected for a given month and year

Default percentile columns:

P10	10th percentile of all daily flows for a given month and year
P90	90th percentile of all daily flows for a given month and year

Transposing data creates a column of 'Statistics' for each month, labeled as 'Month-Statistic' (ex "Jan-Mean"), and subsequent columns for each year selected. Spreading data creates columns of Year and subsequent columns of Month-Statistics (ex 'Jan-Mean').

## Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate statistics using a data frame and data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
calc_monthly_stats(data = flow_data,
                   start_year = 1980)

# Calculate statistics using station_number argument with defaults
calc_monthly_stats(station_number = "08NM116",
                   start_year = 1980)

# Calculate statistics regardless if there is missing data for a given year
calc_monthly_stats(station_number = "08NM116",
                   ignore_missing = TRUE)

# Calculate statistics for water years starting in October
calc_monthly_stats(station_number = "08NM116",
                   start_year = 1980,
                   water_year_start = 10)

# Calculate statistics with custom years and percentiles
calc_monthly_stats(station_number = "08NM116",
                   start_year = 1981,
                   end_year = 2010,
                   exclude_years = c(1991,1993:1995),
                   percentiles = c(25,75))

}
```

---

 compute\_annual\_frequencies

*Perform an annual low or high-flow frequency analysis*


---

### Description

Performs a flow volume frequency analysis on annual statistics from a daily streamflow data set. Defaults to a low flow frequency analysis using annual minimums. Set `use_max = TRUE` for annual high flow frequency analyses. Calculates statistics from all values, unless specified. Function will calculate using all values in 'Values' column (no grouped analysis). Analysis methodology replicates that from **HEC-SSP**. Returns a list of tibbles and plots.

### Usage

```
compute_annual_frequencies(
  data,
  dates = Date,
  values = Value,
  station_number,
  roll_days = c(1, 3, 7, 30),
  roll_align = "right",
  use_max = FALSE,
  use_log = FALSE,
  prob_plot_position = c("weibull", "median", "hazen"),
  prob_scale_points = c(0.9999, 0.999, 0.99, 0.9, 0.5, 0.2, 0.1, 0.02, 0.01, 0.001,
    1e-04),
  fit_distr = c("PIII", "weibull"),
  fit_distr_method = ifelse(fit_distr == "PIII", "MOM", "MLE"),
  fit_quantiles = c(0.975, 0.99, 0.98, 0.95, 0.9, 0.8, 0.5, 0.2, 0.1, 0.05, 0.01),
  plot_curve = TRUE,
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  months = 1:12,
  ignore_missing = FALSE
)
```

### Arguments

<code>data</code>	A data frame of daily data that contains columns of dates and flow values. Groupings and the <code>groups</code> argument are not used for this function (i.e. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if <code>dates</code> column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.

<code>values</code>	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if <code>values</code> column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.
<code>roll_days</code>	Numeric value of the number of days to apply a rolling mean. Default 1.
<code>roll_align</code>	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
<code>use_max</code>	Logical value to indicate using maximums rather than the minimums for analysis. Default FALSE.
<code>use_log</code>	Logical value to indicate log-scale transforming of flow data before analysis. Default FALSE.
<code>prob_plot_position</code>	Character string indicating the plotting positions used in the frequency plots, one of 'weibull', 'median', or 'hazen'. Points are plotted against $(i-a)/(n+1-a-b)$ where $i$ is the rank of the value; $n$ is the sample size and $a$ and $b$ are defined as: ( $a=0$ , $b=0$ ) for Weibull plotting positions; ( $a=.2$ ; $b=.3$ ) for Median plotting positions; and ( $a=.5$ ; $b=.5$ ) for Hazen plotting positions. Default 'weibull'.
<code>prob_scale_points</code>	Numeric vector of probabilities to be plotted along the X axis in the frequency plot. Inverse of return period. Default <code>c(.9999, .999, .99, .9, .5, .2, .1, .02, .01, .001, .0001)</code> .
<code>fit_distr</code>	Character string identifying the distribution to fit annual data, one of 'PIII' (Log Pearson Type III) or 'weibull' (Weibull) distributions. Default 'PIII'.
<code>fit_distr_method</code>	Character string identifying the method used to fit the distribution, one of 'MOM' (method of moments) or 'MLE' (maximum likelihood estimation). Selected as 'MOM' if <code>fit_distr</code> ='PIII' (default) or 'MLE' if <code>fit_distr</code> ='weibull'.
<code>fit_quantiles</code>	Numeric vector of quantiles to be estimated from the fitted distribution. Default <code>c(.975, .99, .98, .95, .90, .80, .50, .20, .10, .05, .01)</code> .
<code>plot_curve</code>	Logical value to indicate plotting the computed curve on the probability plot. Default TRUE.
<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.
<code>months</code>	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).





```
## End(Not run)
```

---

```
compute_annual_trends Calculate prewhitened nonlinear annual trends on streamflow data
```

---

## Description

Calculates prewhitened nonlinear trends on annual streamflow data. Uses the `zyp` package to calculate trends. Review `zyp` for more information. Calculates statistics from all values, unless specified. Returns a list of tibbles and plots. All annual statistics calculated using the `calc_all_annual_stats()` function which uses the following `fasstr` functions:

- `calc_annual_stats()`
- `calc_annual_lowflows()`
- `calc_annual_cumulative_stats()`
- `calc_annual_flow_timing()`
- `calc_monthly_stats()`
- `calc_annual_outside_normal()`

## Usage

```
compute_annual_trends(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  zyp_method,
  basin_area,
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  annual_percentiles = c(10, 90),
  monthly_percentiles = c(10, 20),
  stats_days = 1,
  stats_align = "right",
  lowflow_days = c(1, 3, 7, 30),
  lowflow_align = "right",
  timing_percent = c(25, 33, 50, 75),
  normal_percentiles = c(25, 75),
  ignore_missing = FALSE,
  include_plots = TRUE,
  zyp_alpha
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
zyp_method	Character string identifying the prewhitened trend method to use from zyp, either 'zhang' or 'yuepilon'. 'zhang' is recommended over 'yuepilon' for hydrologic applications (Bürger 2017; Zhang and Zwiers 2004). Required.
basin_area	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if groups is STATION_NUMBER with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations. (3) List each basin area for each group/station in groups (can override HYDAT value if listed) as such c("08NM116" = 795, "08NM242" = 10). If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
annual_percentiles	Numeric vector of percentiles to calculate annually. Set to NA if none required. Used for calc_annual_stats() function. Default c(10, 90).
monthly_percentiles	Numeric vector of percentiles to calculate monthly for each year. Set to NA if none required. Used for calc_monthly_stats() function. Default c(10, 20).

stats_days	Numeric vector of the number of days to apply a rolling mean on basic stats. Default <code>c(1)</code> . Used for <code>calc_annual_stats()</code> and <code>calc_monthly_stats()</code> functions.
stats_align	Character string identifying the direction of the rolling mean on basic stats from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'. Used for <code>calc_annual_stats()</code> , <code>calc_monthly_stats()</code> , and <code>calc_annual_outside_normal()</code> functions.
lowflow_days	Numeric vector of the number of days to apply a rolling mean on low flow stats. Default <code>c(1, 3, 7, 30)</code> . Used for <code>calc_lowflow_stats()</code> function.
lowflow_align	Character string identifying the direction of the rolling mean on low flow stats from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'. Used for <code>calc_lowflow_stats()</code> function.
timing_percent	Numeric vector of percents of annual total flows to determine dates. Used for <code>calc_annual_flow_timing()</code> function. Default <code>c(25, 33.3, 50, 75)</code> .
normal_percentiles	Numeric vector of two values, lower and upper percentiles, respectively indicating the limits of the normal range. Default <code>c(25, 75)</code> .
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.
include_plots	Logical value indicating if annual trending plots should be included. Default TRUE.
zyp_alpha	Numeric value of the significance level (ex. $0.05$ ) of when to plot a trend line. Leave blank for no line.

## Value

A list of tibbles and optional plots from the trending analysis including:

`Annual_Trends_Data`

a tibble of the annual statistics used for trending

`Annual_Trends_Results`

a tibble of the results of the zyp trending analysis

`Annual_*`

each ggplot2 object for each annual trended statistic

## References

References:

- Büger, G. 2017. On trend detection. *Hydrological Processes* 31, 4039–4042. <https://doi.org/10.1002/hyp.11280>.
- Sen, P.K., 1968. Estimates of the Regression Coefficient Based on Kendall's Tau. *Journal of the American Statistical Association* Vol. 63, No. 324: 1379-1389.
- Wang, X.L. and Swail, V.R., 2001. Changes in extreme wave heights in northern hemisphere oceans and related atmospheric circulation regimes. *Journal of Climate*, 14: 2204-2221.

- Yue, S., P. Pilon, B. Phinney and G. Cavadias, 2002. The influence of autocorrelation on the ability to detect trend in hydrological series. *Hydrological Processes*, 16: 1807-1829.
- Zhang, X., Vincent, L.A., Hogg, W.D. and Niitsoo, A., 2000. Temperature and Precipitation Trends in Canada during the 20th Century. *Atmosphere-Ocean* 38(3): 395-429.
- Zhang, X., Zwiers, F.W., 2004. Comment on “Applicability of prewhitening to eliminate the influence of serial correlation on the Mann-Kendall test” by Sheng Yue and Chun Yuan Wang. *Water Resources Research* 40. <https://doi.org/10.1029/2003WR002073>.

### See Also

[zyp-package](#), [calc\\_all\\_annual\\_stats](#)

### Examples

```
## Not run:

# Working examples:

# Compute trends statistics using a data frame and data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
trends <- compute_annual_trends(data = flow_data,
                               zyp_method = "zhang")

# Compute trends statistics using station_number with defaults
trends <- compute_annual_trends(station_number = "08NM116",
                               zyp_method = "zhang")

# Compute trends statistics and plot a trend line if the significance is less than 0.05
trends <- compute_annual_trends(station_number = "08NM116",
                               zyp_method = "zhang",
                               zyp_alpha = 0.05)

# Compute trends statistics and do not plot the results
trends <- compute_annual_trends(station_number = "08NM116",
                               zyp_method = "zhang",
                               include_plots = FALSE)

## End(Not run)
```

---

compute\_frequency\_analysis

*Perform a custom volume frequency analysis*

---

### Description

Performs a volume frequency analysis on custom data. Defaults to ranking by minimums; use `use_max` for to rank by maximum flows. Calculates the statistics from events and flow values

provided. Columns of events (e.g. years), their values (minimums or maximums), and identifiers (low-flows, high-flows, etc.). Function will calculate using all values in the provided data (no grouped analysis). Analysis methodology replicates that from **HEC-SSP**. Returns a list of tibbles and plots.

### Usage

```
compute_frequency_analysis(
  data,
  events = Year,
  values = Value,
  measures = Measure,
  use_max = FALSE,
  use_log = FALSE,
  prob_plot_position = c("weibull", "median", "hazen"),
  prob_scale_points = c(0.9999, 0.999, 0.99, 0.9, 0.5, 0.2, 0.1, 0.02, 0.01, 0.001,
    1e-04),
  fit_distr = c("PIII", "weibull"),
  fit_distr_method = ifelse(fit_distr == "PIII", "MOM", "MLE"),
  fit_quantiles = c(0.975, 0.99, 0.98, 0.95, 0.9, 0.8, 0.5, 0.2, 0.1, 0.05, 0.01),
  plot_curve = TRUE
)
```

### Arguments

data	A data frame of data that contains columns of events, flow values, and measures (data type).
events	Column in data that contains event identifiers, typically year values. Default 'Year'.
values	Column in data that contains numeric flow values, in units of cubic metres per second. Default 'Value'.
measures	Column in data that contains measure identifiers (example data: '7-day low' or 'Annual Max'). Can have multiple measures (ex. '7-day low' and '30-day low') in column if multiple statistics are desired. Default 'Measure'.
use_max	Logical value to indicate using maximums rather than the minimums for analysis. Default FALSE.
use_log	Logical value to indicate log-scale transforming of flow data before analysis. Default FALSE.
prob_plot_position	Character string indicating the plotting positions used in the frequency plots, one of 'weibull', 'median', or 'hazen'. Points are plotted against $(i-a)/(n+1-a-b)$ where $i$ is the rank of the value; $n$ is the sample size and $a$ and $b$ are defined as: ( $a=0$ , $b=0$ ) for Weibull plotting positions; ( $a=.2$ ; $b=.3$ ) for Median plotting positions; and ( $a=.5$ ; $b=.5$ ) for Hazen plotting positions. Default 'weibull'.
prob_scale_points	Numeric vector of probabilities to be plotted along the X axis in the frequency plot. Inverse of return period. Default $c(.9999, .999, .99, .9, .5, .2, .1, .02, .01, .001, .0001)$ .



---

 compute\_frequency\_quantile

*Calculate an annual frequency analysis quantile*


---

### Description

Performs a volume frequency analysis on annual statistics from a daily streamflow data set and calculates a statistic based on the provided mean n-days and return period of the statistic, defaults to minimum flows. For example, to determine the 7Q10 of a data set, set the `roll_days` to 7 and the `return_period` to 10. Function will calculate using all values in 'Values' column (no grouped analysis), unless specified. Analysis methodology replicates that from [HEC-SSP](#). Returns a tibble with statistics.

### Usage

```
compute_frequency_quantile(
  data,
  dates = Date,
  values = Value,
  station_number,
  roll_days = NA,
  roll_align = "right",
  return_period = NA,
  use_max = FALSE,
  use_log = FALSE,
  fit_distr = c("PIII", "weibull"),
  fit_distr_method = ifelse(fit_distr == "PIII", "MOM", "MLE"),
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  months = 1:12,
  ignore_missing = FALSE
)
```

### Arguments

<code>data</code>	A data frame of data that contains columns of events, flow values, and measures (data type).
<code>dates</code>	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
<code>values</code>	Column in data that contains numeric flow values, in units of cubic metres per second. Default 'Value'.
<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT



	database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Required.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
return_period	Numeric vector of the estimated time interval, in years, between flow events of a similar size, inverse of probability, used to estimate the frequency statistic. Required.
use_max	Logical value to indicate using maximums rather than the minimums for analysis. Default FALSE.
use_log	Logical value to indicate log-scale transforming of flow data before analysis. Default FALSE.
fit_distr	Character string identifying the distribution to fit annual data, one of 'PIII' (Log Pearson Type III) or 'weibull' (Weibull) distributions. Default 'PIII'.
fit_distr_method	Character string identifying the method used to fit the distribution, one of 'MOM' (method of moments) or 'MLE' (maximum likelihood estimation). Selected as 'MOM' if fit_distr = 'PIII' (default) or 'MLE' if fit_distr = 'weibull'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.

**Value**

A numeric value of the frequency analysis quantile, given the roll\_days and return\_period.

**See Also**

[compute\\_frequency\\_analysis](#)

**Examples**

```
## Not run:

# Working example:

# Compute the annual 7-day flow value with a 1 in 10 year return interval
compute_frequency_quantile(station_number = "08NM116",
                           roll_days = 7,
                           return_period = 10)

## End(Not run)
```

---

compute\_full\_analysis *Compute a suite of tables and plots from various fasstr functions*

---

**Description**

Calculates tables and plots from a suite of statistics from fasstr functions. Calculates statistics from all values, unless specified. The statistics are grouped into 7 analysis groups (see `analyses` argument) which are stored in lists in the object. Due to the number of tables and plots to be made, this function may take several minutes to complete. If `ignore_missing = FALSE` (default) and there is missing data, some tables and plots may be empty and produce warnings. Use `ignore_missing = TRUE` to ignore the missing values or filter your data to complete years. Returns a list of tibbles and plots.

**Usage**

```
compute_full_analysis(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  analyses = 1:7,
  basin_area,
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  ignore_missing = FALSE,
  zyp_method = "zhang",
  zyp_alpha
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
analyses	Numeric vector of analyses to run (default is all (1:7)): <ul style="list-style-type: none"> <li>• 1: Screening</li> <li>• 2: Long-term</li> <li>• 3: Annual</li> <li>• 4: Monthly</li> <li>• 5: Daily</li> <li>• 6: Annual Trends</li> <li>• 7: Low-flow Frequencies</li> </ul>
basin_area	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: <ol style="list-style-type: none"> <li>(1) Leave blank if groups is STATION_NUMBER with HYDAT station numbers to extract basin areas from HYDAT.</li> <li>(2) A single numeric value to apply to all observations.</li> <li>(3) List each basin area for each group/station in groups (can override HYDAT value if listed) as such c("08NM116" = 795, "08NM242" = 10). If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.</li> </ol>
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.



---

 compute\_hydat\_peak\_frequencies

*Perform a frequency analysis on annual peak statistics from HYDAT*


---

## Description

Performs a volume frequency analysis on annual peak statistics (instantaneous minimums or maximums) extracted from HYDAT. Calculates statistics from all years, unless specified. The data argument is not available. Analysis methodology replicates that from **HEC-SSP**. Returns a list of tibbles and plots.

## Usage

```
compute_hydat_peak_frequencies(
  station_number,
  use_max = FALSE,
  use_log = FALSE,
  prob_plot_position = c("weibull", "median", "hazen"),
  prob_scale_points = c(0.9999, 0.999, 0.99, 0.9, 0.5, 0.2, 0.1, 0.02, 0.01, 0.001,
    1e-04),
  fit_distr = c("PIII", "weibull"),
  fit_distr_method = ifelse(fit_distr == "PIII", "MOM", "MLE"),
  fit_quantiles = c(0.975, 0.99, 0.98, 0.95, 0.9, 0.8, 0.5, 0.2, 0.1, 0.05, 0.01),
  start_year,
  end_year,
  exclude_years,
  plot_curve = TRUE
)
```

## Arguments

station_number	A character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract annual peak minimum or maximum instantaneous streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database.
use_max	Logical value to indicate using maximums rather than the minimums for analysis. Default FALSE.
use_log	Logical value to indicate log-scale transforming of flow data before analysis. Default FALSE.
prob_plot_position	Character string indicating the plotting positions used in the frequency plots, one of 'weibull', 'median', or 'hazen'. Points are plotted against $(i-a)/(n+1-a-b)$ where $i$ is the rank of the value; $n$ is the sample size and $a$ and $b$ are defined as: ( $a=0$ , $b=0$ ) for Weibull plotting positions; ( $a=.2$ ; $b=.3$ ) for Median plotting positions; and ( $a=.5$ ; $b=.5$ ) for Hazen plotting positions. Default 'weibull'.



```
# Compute an annual peak frequency analysis using default arguments (instantaneous highs)
results <- compute_hydat_peak_frequencies(station_number = "08NM116",
                                         start_year = 1980,
                                         end_year = 2010,
                                         use_max = TRUE)

## End(Not run)
```

---

fill\_missing\_dates      *Fills data gaps of missing dates*

---

### Description

Fills data gaps of missing dates of the data provided. Builds a continuous data set from the start date to the end date. Only missing dates are filled, columns not specified as dates or groups will be filled with NA. Will completely fill first and last years, unless specified using `fill_end_years = FALSE`.

### Usage

```
fill_missing_dates(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  water_year_start = 1,
  fill_end_years = TRUE
)
```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Not required as of fasstr 0.3.3 as all other columns are filled with NA.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.

**station\_number** Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.

**water\_year\_start** Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.

**fill\_end\_years** Logical value indicating whether to fill incomplete start and end years with rows of dates. If FALSE then only missing dates between the provided start and end dates will be filled. Default TRUE.

### Value

A tibble data frame of the source data with additional rows where missing dates existed.

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Fill missing dates with NA using calendar years
fill_missing_dates(station_number = "08NM116")

# Fill missing dates with NA using water years starting in August
fill_missing_dates(station_number = "08NM116",
                   water_year_start = 8)

}
```

---

plot\_annual\_cumulative\_stats

*Plot annual (and seasonal) cumulative flows*

---

### Description

Plots annual and seasonal (if include\_seasons = TRUE) total flows, volumetric discharge or water yields, from a daily streamflow data set. Calculates statistics from all values, unless specified. Data calculated from plot\_annual\_cumulative\_stats() function. For water year and seasonal data, the designated year is the year in which the year or season ends. Returns a list of plots.

### Usage

```
plot_annual_cumulative_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
```



```

    use_yield = FALSE,
    basin_area,
    water_year_start = 1,
    start_year,
    end_year,
    exclude_years,
    include_seasons = FALSE,
    log_discharge = FALSE,
    include_title = FALSE
  )

```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
use_yield	Logical value indicating whether to calculate area-based water yield, in mm, instead of volumetric discharge. Default FALSE.
basin_area	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if groups is STATION_NUMBER with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations. (3) List each basin area for each group/station in groups (can override HYDAT value if listed) as such c("08NM116" = 795, "08NM242" = 10). If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.

<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.
<code>include_seasons</code>	Logical value indication whether to include seasonal yields or volumetric discharges. Default TRUE.
<code>log_discharge</code>	Logical value to indicate plotting the discharge axis (Y-axis) on a logarithmic scale. Default FALSE.
<code>include_title</code>	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

**Value**

A list of ggplot2 objects with the following for each station provided:

<code>Annual_Total_Volume</code>	annual total volumetric discharge, in cubic metres
<code>Two_Seasons_Total_Volume</code>	if <code>include_seasons = TRUE</code> , two seasons total volumetric discharges, in cubic metres
<code>Four_Seasons_Total_Volume</code>	if <code>include_seasons = TRUE</code> , four seasons total volumetric discharges, in cubic metres

If `use_yield` argument is used the list will contain the following objects:

<code>Annual_Yield</code>	annual water yield, in millimetres
<code>Two_Seasons_Yield</code>	if <code>include_seasons = TRUE</code> , two seasons water yield, in millimetres
<code>Four_Seasons_Yield</code>	if <code>include_seasons = TRUE</code> , four seasons water yield, in millimetres

**See Also**

[calc\\_annual\\_cumulative\\_stats](#)

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot annual cumulative yield statistics with default HYDAT basin area
plot_annual_cumulative_stats(station_number = "08NM116",
                             use_yield = TRUE)

# Plot annual cumulative yield statistics with custom basin area
plot_annual_cumulative_stats(station_number = "08NM116",
                             use_yield = TRUE,
```

```

        basin_area = 800)
}

```

---

```
plot_annual_flow_timing
```

*Plot annual timing of flows*

---

### Description

Plots the timing (day of year and date) of portions of total annual flow of daily flow values from a daily streamflow data set. Calculates statistics from all values from complete years, unless specified. Data calculated using `calc_annual_flow_timing()` function. Returns a list of plots.

### Usage

```

plot_annual_flow_timing(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  percent_total = c(25, 33.3, 50, 75),
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  include_title = FALSE
)

```

### Arguments

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
<code>values</code>	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
<code>groups</code>	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.

<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
<code>percent_total</code>	Numeric vector of percents of total annual flows to determine dates. Default <code>c(25, 33.3, 50, 75)</code> .
<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.
<code>include_title</code>	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

**Value**

A list of ggplot2 objects with the following for each station provided:

`Annual_Flow_Timing`

a plot that contains each n-percent of total volumetric discharge

Default plots on each object:

`DoY_25pct_TotalQ`

day of year of 25-percent of total volumetric discharge

`DoY_33.3pct_TotalQ`

day of year of 33.3-percent of total volumetric discharge

`DoY_50pct_TotalQ`

day of year of 50-percent of total volumetric discharge

`DoY_75pct_TotalQ`

day of year of 75-percent of total volumetric discharge

**References**

- Barnett, T.P., Pierce, D.W., Hidalgo, H.G., Bonfils, C., Santer, B.D., Das, T., Bala, G., Wood, A.W., Nozawa, T., Mirin, A.A., Cayan, D.R., Dettinger, M.D., 2008. Human-Induced Clanges in the Hydrology of the Western United States. *Science* 319, 1080-1083.

**See Also**

[calc\\_annual\\_flow\\_timing](#)

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot annual flow timing statistics with default percent totals
plot_annual_flow_timing(station_number = "08NM116")

# Plot annual flow timing with custom percent totals
plot_annual_flow_timing(station_number = "08NM116",
                        percent_total = 50)

}
```

---

plot\_annual\_lowflows *Plot annual low flows and dates*

---

### Description

Plot annual n-day minimum values, and the day of year and date of occurrence of daily flow values from a daily streamflow data set. Calculates statistics from all values, unless specified. Data calculated from `calc_annual_lowflows()` function. Returns a list of plots.

### Usage

```
plot_annual_lowflows(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = c(1, 3, 7, 30),
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  months = 1:12,
  ignore_missing = FALSE,
  log_discharge = FALSE,
  include_title = FALSE
)
```

### Arguments

`data` Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using `station_number` argument.

<code>dates</code>	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if <code>dates</code> column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
<code>values</code>	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if <code>values</code> column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
<code>groups</code>	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if <code>groups</code> column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.
<code>roll_days</code>	Numeric value of the number of days to apply a rolling mean. Default 1.
<code>roll_align</code>	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.
<code>months</code>	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
<code>ignore_missing</code>	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.
<code>log_discharge</code>	Logical value to indicate plotting the discharge axis (Y-axis) on a logarithmic scale. Default FALSE.
<code>include_title</code>	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

### Value

A list of `ggplot2` objects with the following for each station provided:

`Annual_Minimums`

`ggplot2` object of annual minimums of selected n-day rolling means

```
Annual_Minimums_Days
  ggplot2 object of the day of years of annual minimums of selected n-day rolling
  means
```

### See Also

[calc\\_annual\\_lowflows](#)

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot annual 1, 3, 7, and 30-day (default) low flow statistics with default alignment
plot_annual_lowflows(station_number = "08NM116")

# Plot annual custom 3 and 7-day low flow statistics with "center" alignment
plot_annual_lowflows(station_number = "08NM116",
  roll_days = c(3,7),
  roll_align = "center")

}
```

---

plot\_annual\_means      *Plot annual means compared to the long-term mean*

---

### Description

Plot annual means using the long-term annual mean as the point of reference for annual means. Calculates statistics from all values, unless specified. Data calculated using `calc_annual_stats()` function. Returns a list of plots.

### Usage

```
plot_annual_means(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  months = 1:12,
  ignore_missing = FALSE,
  include_title = FALSE
)
```

**Arguments**

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
<code>values</code>	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
<code>groups</code>	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
<code>roll_days</code>	Numeric value of the number of days to apply a rolling mean. Default 1.
<code>roll_align</code>	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.
<code>months</code>	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
<code>ignore_missing</code>	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.
<code>include_title</code>	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

**Value**

A list of ggplot2 objects for with the following plots for each station provided:

`Annual_Means` a plot that contains annual means with the long-term mean as the x-axis intercept



**See Also**[calc\\_annual\\_stats](#)**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot annual means
plot_annual_means(station_number = "08NM116")

# Plot mean flows from July-September
plot_annual_means(station_number = "08NM116",
                  months = 7:9)

}
```

---

plot\_annual\_outside\_normal

*Plot annual days above and below normal*


---

**Description**

Plots the number of days per year outside of the 'normal' range (typically between 25 and 75th percentiles) for each day of the year. Upper and lower-range percentiles are calculated for each day of the year from all years, and then each daily flow value for each year is compared. All days above or below the normal range are included. Calculates statistics from all values from complete years, unless specified. Data calculated using `calc_annual_outside_normal()` function. Returns a list of plots.

**Usage**

```
plot_annual_outside_normal(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  normal_percentiles = c(25, 75),
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  months = 1:12,
  include_title = FALSE
)
```

**Arguments**

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
<code>values</code>	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
<code>groups</code>	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.
<code>normal_percentiles</code>	Numeric vector of two values, lower and upper percentiles, respectively indicating the limits of the normal range. Default <code>c(25, 75)</code> .
<code>roll_days</code>	Numeric value of the number of days to apply a rolling mean. Default 1.
<code>roll_align</code>	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.
<code>months</code>	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
<code>include_title</code>	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

**Value**

A list of `ggplot2` objects with the following for each station provided:

`Annual_Days_Outside_Normal`

a plot that contains the number of days outside normal

Default plots on each object:

Days\_Below\_Normal  
                                   number of days per year below the daily normal (default 25th percentile)

Days\_Above\_Normal  
                                   number of days per year above the daily normal (default 75th percentile)

Days\_Outside\_Normal  
                                   number of days per year below and above the daily normal (default 25/75th percentile)

### See Also

[calc\\_annual\\_outside\\_normal](#)

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot annual statistics with default limits of normal (25 and 75th percentiles)
plot_annual_outside_normal(station_number = "08NM116")

# Plot annual statistics with custom limits of normal
plot_annual_outside_normal(station_number = "08NM116",
                           normal_percentiles = c(10,90))

}
```

---

plot\_annual\_stats      *Plot annual summary statistics*

---

### Description

Plots means, medians, maximums, minimums, and percentiles for each year from all years of a daily streamflow data set. Calculates statistics from all values, unless specified. Data calculated using `calc_annual_stats()` function. Returns a list of plots.

### Usage

```
plot_annual_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  percentiles,
  roll_days = 1,
  roll_align = "right",
```

```

water_year_start = 1,
start_year,
end_year,
exclude_years,
months = 1:12,
ignore_missing = FALSE,
log_discharge = FALSE,
include_title = FALSE
)

```

### Arguments

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in <code>data</code> that contains dates formatted YYYY-MM-DD. Only required if <code>dates</code> column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
<code>values</code>	Name of column in <code>data</code> that contains numeric flow values, in units of cubic metres per second. Only required if <code>values</code> column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
<code>groups</code>	Name of column in <code>data</code> that contains unique identifiers for different data sets, if applicable. Only required if <code>groups</code> column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.
<code>percentiles</code>	Numeric vector of percentiles to calculate. Set to NA if none required. Default NA.
<code>roll_days</code>	Numeric value of the number of days to apply a rolling mean. Default 1.
<code>roll_align</code>	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.

months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.
log_discharge	Logical value to indicate plotting the discharge axis (Y-axis) on a logarithmic scale. Default FALSE.
include_title	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

### Value

A list of ggplot2 objects for with the following plots (percentile plots optional) for each station provided:

Annual\_Stats a plot that contains annual statistics

Default plots on each object:

Mean	annual mean of all daily flows
Median	annual median of all daily flows
Maximum	annual maximum of all daily flows
Minimum	annual minimum of all daily flows

### See Also

[calc\\_annual\\_stats](#)

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot annual statistics using a data frame and data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
plot_annual_stats(data = flow_data)

# Plot annual statistics using station_number argument with defaults
plot_annual_stats(station_number = "08NM116")

# Plot annual statistics regardless if there is missing data for a given year
plot_annual_stats(station_number = "08NM116",
                  ignore_missing = TRUE)

# Plot annual statistics for water years starting in October
plot_annual_stats(station_number = "08NM116",
                  water_year_start = 10)

# Plot annual statistics with custom years and percentiles
```

```

plot_annual_stats(station_number = "08NM116",
                  start_year = 1981,
                  end_year = 2010,
                  exclude_years = c(1991,1993:1995),
                  percentiles = c(25,75))

}

```

---

```
plot_daily_cumulative_stats
```

*Plot cumulative daily flow statistics*

---

### Description

Plot the daily cumulative mean, median, maximum, minimum, and 5, 25, 75, 95th percentiles for each day of the year from a daily streamflow data set. Calculates statistics from all values from complete, unless specified. Data calculated using `calc_daily_cumulative_stats()` function. Can plot individual years for comparison using the `add_year` argument. Defaults to volumetric cumulative flows, can use `use_yield` and `basin_area` to convert to water yield. Returns a list of plots.

### Usage

```

plot_daily_cumulative_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  use_yield = FALSE,
  basin_area,
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  log_discharge = FALSE,
  include_title = FALSE,
  add_year
)

```

### Arguments

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
-------------------	--

dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
use_yield	Logical value indicating whether to calculate area-based water yield, in mm, instead of volumetric discharge. Default FALSE.
basin_area	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if groups is STATION_NUMBER with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations. (3) List each basin area for each group/station in groups (can override HYDAT value if listed) as such c("08NM116" = 795, "08NM242" = 10). If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
log_discharge	Logical value to indicate plotting the discharge axis (Y-axis) on a logarithmic scale. Default FALSE.
include_title	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.
add_year	Numeric value indicating a year of daily flows to add to the daily statistics plot. Leave blank for no years.

### Value

A list of ggplot2 objects with the following for each station provided:

**Daily\_Cumulative\_Stats**

a plot that contains daily cumulative flow statistics

Default plots on each object:

Mean            daily cumulative mean

Median         daily cumulative median

Min-5 Percentile Range

a ribbon showing the range of data between the daily cumulative minimum and 5th percentile

5-25 Percentiles Range

a ribbon showing the range of data between the daily cumulative 5th and 25th percentiles

25-75 Percentiles Range

a ribbon showing the range of data between the daily cumulative 25th and 75th percentiles

75-95 Percentiles Range

a ribbon showing the range of data between the daily cumulative 75th and 95th percentiles

95 Percentile-Max Range

a ribbon showing the range of data between the daily cumulative 95th percentile and the maximum

'Year' Flows    (optional) the daily cumulative flows for the designated year

**See Also**

[calc\\_daily\\_cumulative\\_stats](#)

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot annual daily yield statistics with default HYDAT basin area
plot_daily_cumulative_stats(station_number = "08NM116",
                             use_yield = TRUE)

# Plot annual daily yield statistics with custom basin area
plot_daily_cumulative_stats(station_number = "08NM116",
                             use_yield = TRUE,
                             basin_area = 800)

}
```



---

plot\_daily\_stats      *Plot daily summary statistics*

---

## Description

Plots means, medians, maximums, minimums, and percentiles for each day of the year of flow values from a daily streamflow data set. Can determine statistics of rolling mean days (e.g. 7-day flows) using the `roll_days` argument. Calculates statistics from all values, unless specified. The Maximum-Minimum band can be removed using the `include_extremes` argument and the percentile bands can be customized using the `inner_percentiles` and `outer_percentiles` arguments. Data calculated using `calc_daily_stats()` function. Returns a list of plots.

## Usage

```
plot_daily_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  complete_years = FALSE,
  months = 1:12,
  ignore_missing = FALSE,
  include_extremes = TRUE,
  inner_percentiles = c(25, 75),
  outer_percentiles = c(5, 95),
  add_year,
  log_discharge = TRUE,
  include_title = FALSE
)
```

## Arguments

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if <code>dates</code> column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.

values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
complete_years	Logical values indicating whether to include only years with complete data in analysis. Default FALSE.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.
include_extremes	Logical value to indicate plotting a ribbon with the range of daily minimum and maximum flows. Default TRUE.
inner_percentiles	Numeric vector of two percentile values indicating the lower and upper limits of the inner percentiles ribbon for plotting. Default <code>c(25, 75)</code> , set to NULL for no inner ribbon.
outer_percentiles	Numeric vector of two percentile values indicating the lower and upper limits of the outer percentiles ribbon for plotting. Default <code>c(5, 95)</code> , set to NULL for no outer ribbon.
add_year	Numeric value indicating a year of daily flows to add to the daily statistics plot. Leave blank for no years.

log_discharge	Logical value to indicate plotting the discharge axis (Y-axis) on a logarithmic scale. Default FALSE.
include_title	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

### Value

A list of ggplot2 objects with the following for each station provided:

Daily\_Stats      a plot that contains daily flow statistics

Default plots on each object:

Mean              daily mean

Median            daily median

25-75 Percentiles

a ribbon showing the range of data between the daily 25th and 75th percentiles

5-95 Percentiles

a ribbon showing the range of data between the daily 5th and 95th percentiles

Minimum-Maximum

a ribbon showing the range of data between the daily minimum and maximums

'Year'

(on annual plots) the daily flows for the designated year

### See Also

[calc\\_daily\\_stats](#)

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot daily statistics using a data frame and data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
plot_daily_stats(data = flow_data,
                 start_year = 1980)

# Plot daily statistics using only years with no missing data
plot_daily_stats(station_number = "08NM116",
                 complete_years = TRUE)

# Plot daily statistics and add a specific year's daily flows
plot_daily_stats(station_number = "08NM116",
                 start_year = 1980,
                 add_year = 1985)

# Plot daily statistics for 7-day flows for July-September months only
plot_daily_stats(station_number = "08NM116",
                 start_year = 1980,
                 roll_days = 7,
```

```

        months = 7:9)
    }

```

---

plot\_data\_screening     *Plot annual summary statistics for data screening*

---

### Description

Plots the mean, median, maximum, minimum, standard deviation of annual flows. Calculates statistics from all values, unless specified. Data calculated using `screen_flow_data()` function. Returns a list of plots.

### Usage

```

plot_data_screening(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  months = 1:12,
  start_year,
  end_year,
  include_title = FALSE
)

```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.

station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
include_title	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

### Value

A list of ggplot2 objects with the following for each station provided:

Data\_Screening a plot that contains annual summary statistics for screening

Default plots on each object:

Minimum	annual minimum of all daily flows for a given year
Maximum	annual maximum of all daily flows for a given year
Mean	annual mean of all daily flows for a given year
StandardDeviation	annual 1 standard deviation of all daily flows for a given year

### See Also

[screen\\_flow\\_data](#)

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot screening statistics using a data frame and data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
plot_data_screening(data = flow_data)

# Plot screening statistics using station_number argument with defaults
```

```

plot_data_screening(station_number = "08NM116")

# Plot screening statistics for water years starting in October
plot_data_screening(station_number = "08NM116",
                    water_year_start = 10)

# Plot screening statistics for 7-day flows for July-September months only
plot_data_screening(station_number = "08NM116",
                    roll_days = 7,
                    months = 7:9)

}

```

---

plot_flow_data	<i>Plot a daily streamflow data set</i>
----------------	---

---

### Description

Plot the daily mean flow values from a streamflow data set. Plots daily discharge values from all years, unless specified. Can choose specific dates to start and end plotting. Can choose to plot out each year separately. Multiple groups/stations can be plotted if provided with the groups argument. Returns a list of plots.

### Usage

```

plot_flow_data(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  start_date,
  end_date,
  log_discharge = FALSE,
  plot_by_year = FALSE,
  one_plot = FALSE,
  include_title = FALSE
)

```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
start_date	Date (YYYY-MM-DD) of first date to consider for plotting. Leave blank if all years are required.
end_date	Date (YYYY-MM-DD) of last date to consider for plotting. Leave blank if all years are required.
log_discharge	Logical value to indicate plotting the discharge axis (Y-axis) on a logarithmic scale. Default TRUE.
plot_by_year	Logical value to indicate whether to plot each year of data individually. Default FALSE.
one_plot	Logical value to indicate whether to plot all groups/stations on one plot. Default FALSE.
include_title	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

**Value**

A ggplot2 object of daily flows from flow\_data or HYDAT flow data provided

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot data from a data frame and data argument
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
plot_flow_data(data = flow_data)

# Plot data directly from HYDAT
plot_flow_data(station_number = "08NM116")

# Plot statistics with custom years
plot_flow_data(station_number = "08NM116",
               start_year = 1981,
               end_year = 2010,
               exclude_years = c(1991,1993:1995))

# Plot data between specific dates
plot_flow_data(station_number = "08NM116",
               start_date = "1990-01-01",
               end_date = "1990-06-01")

# Plot data multiple groups on one plot
plot_flow_data(station_number = c("08NM241", "08NM242"),
               one_plot = TRUE)

}
```

---

plot\_flow\_duration      *Plot flow duration curves*

---

**Description**

Plots flow duration curves of flow data from a daily streamflow data set. Plots the percent time flows are equalled or exceeded. Calculates statistics from all values, unless specified. Data calculated using calc\_longterm\_stats() function then converted for plotting. Returns a list of plots.

**Usage**

```
plot_flow_duration(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
```



```

roll_days = 1,
roll_align = "right",
water_year_start = 1,
start_year,
end_year,
exclude_years,
complete_years = FALSE,
custom_months,
custom_months_label,
ignore_missing = FALSE,
months = 1:12,
include_longterm = TRUE,
log_discharge = TRUE,
include_title = FALSE
)

```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.

<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.
<code>complete_years</code>	Logical values indicating whether to include only years with complete data in analysis. Default FALSE.
<code>custom_months</code>	Numeric vector of months to combine to summarize (ex. 6:8 for Jun-Aug). Adds results to the end of table. If wanting months that overlap calendar years (ex. Oct-Mar), choose <code>water_year_start</code> that begins before the first month listed. Leave blank for no custom month summary.
<code>custom_months_label</code>	Character string to label custom months. For example, if <code>months = 7:9</code> you may choose "Summer" or "Jul-Sep". Default "Custom-Months".
<code>ignore_missing</code>	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.
<code>months</code>	Numeric vector of month curves to plot. NA if no months required. Default 1:12.
<code>include_longterm</code>	Logical value indicating whether to include long-term curve of all data. Default TRUE.
<code>log_discharge</code>	Logical value to indicate plotting the discharge axis (Y-axis) on a logarithmic scale. Default FALSE.
<code>include_title</code>	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

**Value**

A list of ggplot2 objects with the following for each station provided:

`Flow_Duration` a plot that contains flow duration curves for each month, long-term, and (option) customized months

**See Also**

[calc\\_longterm\\_daily\\_stats](#)

**Examples**

```
## Not run:

# Working examples:

# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot flow durations using a data frame and data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
plot_flow_duration(data = flow_data,
                  start_year = 1980)
```

```

# Plot flow durations using station_number argument with defaults
plot_flow_duration(station_number = "08NM116",
                  start_year = 1980)

# Plot flow durations and add custom stats for July-September
plot_flow_duration(station_number = "08NM116",
                  start_year = 1980,
                  custom_months = 7:9,
                  custom_months_label = "Summer")

}

## End(Not run)

```

---

plot\_longterm\_daily\_stats

*Plot long-term summary statistics from daily mean flows*

---

### Description

Plots the long-term mean, median, maximum, minimum, and percentiles of daily flow values for over all months and all data (Long-term) from a daily streamflow data set. Calculates statistics from all values, unless specified. The Maximum-Minimum band can be removed using the `include_extremes` argument and the percentile bands can be customized using the `inner_percentiles` and `outer_percentiles` arguments. Data calculated using the `calc_longterm_daily_stats()` function. Returns a list of plots.

### Usage

```

plot_longterm_daily_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  complete_years = FALSE,
  ignore_missing = FALSE,
  include_extremes = TRUE,
  inner_percentiles = c(25, 75),
  outer_percentiles = c(5, 95),
  add_year,

```

```

    log_discharge = TRUE,
    include_title = FALSE
  )

```

### Arguments

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
<code>values</code>	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
<code>groups</code>	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.
<code>roll_days</code>	Numeric value of the number of days to apply a rolling mean. Default 1.
<code>roll_align</code>	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.
<code>complete_years</code>	Logical values indicating whether to include only years with complete data in analysis. Default FALSE.
<code>ignore_missing</code>	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.
<code>include_extremes</code>	Logical value to indicate plotting a ribbon with the range of daily minimum and maximum flows. Default TRUE.

inner_percentiles	Numeric vector of two percentile values indicating the lower and upper limits of the inner percentiles ribbon for plotting. Default c(25, 75), set to NULL for no inner ribbon.
outer_percentiles	Numeric vector of two percentile values indicating the lower and upper limits of the outer percentiles ribbon for plotting. Default c(5, 95), set to NULL for no outer ribbon.
add_year	Numeric value indicating a year of daily flows to add to the daily statistics plot. Leave blank for no years.
log_discharge	Logical value to indicate plotting the discharge axis (Y-axis) on a logarithmic scale. Default FALSE.
include_title	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

**Value**

A list of ggplot2 objects with the following for each station provided:

Long-term\_Monthly\_Statistics  
a plot that contains long-term flow statistics

Default plots on each object:

Monthly Mean	mean of all annual monthly means for a given month over all years
Monthly Median	median of all annual monthly means for a given month over all years
25-75 Percentiles Range	a ribbon showing the range of data between the monthly 25th and 75th percentiles
5-95 Percentiles Range	a ribbon showing the range of data between the monthly 5th and 95th percentiles
Max-Min Range	a ribbon showing the range of data between the monthly minimum and maximums

**See Also**

[calc\\_longterm\\_daily\\_stats](#)

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot longterm daily statistics using data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
plot_longterm_daily_stats(data = flow_data,
                           start_year = 1980)

# Plot longterm daily statistics for water years starting in October
```

```

plot_longterm_daily_stats(station_number = "08NM116",
                          start_year = 1980,
                          end_year = 2010,
                          water_year_start = 10)

}

```

---

```
plot_longterm_monthly_stats
```

*Plot long-term summary statistics from annual monthly mean flows*

---

### Description

Plots the long-term mean, median, maximum, minimum, and percentiles of annual monthly mean flow values for all months and all data (Long-term) from a daily streamflow data set. Calculates statistics from all values, unless specified. The Maximum-Minimum band can be removed using the `include_extremes` argument and the percentile bands can be customized using the `inner_percentiles` and `outer_percentiles` arguments. Data calculated using the `calc_longterm_monthly_stats()` function. Returns a list of plots.

### Usage

```

plot_longterm_monthly_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  complete_years = FALSE,
  ignore_missing = FALSE,
  include_extremes = TRUE,
  inner_percentiles = c(25, 75),
  outer_percentiles = c(5, 95),
  add_year,
  log_discharge = TRUE,
  include_title = FALSE
)

```

### Arguments

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
-------------------	--

dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
complete_years	Logical values indicating whether to include only years with complete data in analysis. Default FALSE.
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.
include_extremes	Logical value to indicate plotting a ribbon with the range of daily minimum and maximum flows. Default TRUE.
inner_percentiles	Numeric vector of two percentile values indicating the lower and upper limits of the inner percentiles ribbon for plotting. Default c(25, 75), set to NULL for no inner ribbon.
outer_percentiles	Numeric vector of two percentile values indicating the lower and upper limits of the outer percentiles ribbon for plotting. Default c(5, 95), set to NULL for no outer ribbon.

<code>add_year</code>	Numeric value indicating a year of daily flows to add to the daily statistics plot. Leave blank for no years.
<code>log_discharge</code>	Logical value to indicate plotting the discharge axis (Y-axis) on a logarithmic scale. Default FALSE.
<code>include_title</code>	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

**Value**

A list of `ggplot2` objects with the following for each station provided:

`Long-term_Monthly_Statistics`  
a plot that contains long-term flow statistics

Default plots on each object:

`Monthly Mean` mean of all annual monthly means for a given month over all years  
`Monthly Median` median of all annual monthly means for a given month over all years  
`25-75 Percentiles Range`  
a ribbon showing the range of data between the monthly 25th and 75th percentiles  
`5-95 Percentiles Range`  
a ribbon showing the range of data between the monthly 5th and 95th percentiles  
`Max-Min Range` a ribbon showing the range of data between the monthly minimum and maximums

**See Also**

[calc\\_longterm\\_monthly\\_stats](#)

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot longterm monthly statistics using data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
plot_longterm_monthly_stats(data = flow_data,
                             start_year = 1980)

# Plot longterm monthly statistics using station_number argument with defaults
plot_longterm_monthly_stats(station_number = "08NM116",
                             start_year = 1980)

# Plot longterm monthly statistics and add a specific year's daily flows
plot_longterm_monthly_stats(station_number = "08NM116",
                             start_year = 1980,
                             add_year = 1985)

}
```



---

plot\_missing\_dates      *Plot annual and monthly missing dates*

---

### Description

Plots the number of missing data for each month of each year. Calculates statistics from all values, unless specified. Data calculated using `screen_flow_data()` function. Returns a list of plots.

### Usage

```
plot_missing_dates(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  months = 1:12,
  include_title = FALSE
)
```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.

<code>roll_days</code>	Numeric value of the number of days to apply a rolling mean. Default 1.
<code>roll_align</code>	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>months</code>	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
<code>include_title</code>	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

**Value**

A list of `ggplot2` objects with the following for each station provided:

`Missing_Dates` a plot that contains the number of missing dates for each year and month

**See Also**

[screen\\_flow\\_data](#)

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot missing dates using a data frame and data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
plot_missing_dates(data = flow_data)

# Plot missing dates using station_number argument with defaults
plot_missing_dates(station_number = "08NM116")

# Plot missing dates for water years starting in October
plot_missing_dates(station_number = "08NM116",
                  water_year_start = 9)

# Plot missing dates for 7-day flows for July-September months only
plot_missing_dates(station_number = "08NM116",
                  roll_days = 7,
                  months = 7:9)

}
```

---

 plot\_monthly\_cumulative\_stats

*Plot cumulative monthly flow statistics*


---

### Description

Plot the monthly cumulative mean, median, maximum, minimum, and 5, 25, 75, 95th percentiles for each month of the year from a daily streamflow data set. Calculates statistics from all values from complete years, unless specified. Data calculated using `calc_monthly_cumulative_stats()` function. Can plot individual years for comparison using the `add_year` argument. Defaults to volumetric cumulative flows, can use `use_yield` and `basin_area` to convert to water yield. Returns a list of plots.

### Usage

```
plot_monthly_cumulative_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  use_yield = FALSE,
  basin_area,
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  log_discharge = FALSE,
  include_title = FALSE,
  add_year
)
```

### Arguments

<code>data</code>	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using <code>station_number</code> argument.
<code>dates</code>	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if <code>dates</code> column name is not 'Date' (default). Leave blank if using <code>station_number</code> argument.
<code>values</code>	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if <code>values</code> column name is not 'Value' (default). Leave blank if using <code>station_number</code> argument.
<code>groups</code>	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if <code>groups</code> column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER'

	if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using <code>station_number</code> argument.
<code>station_number</code>	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires <code>tidyhydat</code> package and a HYDAT database. Leave blank if using <code>data</code> argument.
<code>use_yield</code>	Logical value indicating whether to calculate area-based water yield, in mm, instead of volumetric discharge. Default FALSE.
<code>basin_area</code>	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if <code>groups</code> is <code>STATION_NUMBER</code> with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations. (3) List each basin area for each group/station in <code>groups</code> (can override HYDAT value if listed) as such <code>c("08NM116" = 795, "08NM242" = 10)</code> . If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.
<code>water_year_start</code>	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
<code>start_year</code>	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
<code>end_year</code>	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
<code>exclude_years</code>	Numeric vector of years to exclude from analysis. Leave blank to include all years.
<code>log_discharge</code>	Logical value to indicate plotting the discharge axis (Y-axis) on a logarithmic scale. Default FALSE.
<code>include_title</code>	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.
<code>add_year</code>	Numeric value indicating a year of daily flows to add to the daily statistics plot. Leave blank for no years.

### Value

A list of `ggplot2` objects with the following for each station provided:

`Monthly_Cumulative_Stats`

a plot that contains monthly cumulative flow statistics

Default plots on each object:

Mean                    monthly cumulative mean

Median                 monthly cumulative median

Min-5 Percentile Range

a ribbon showing the range of data between the monthly cumulative minimum and 5th percentile

- 5-25 Percentiles Range  
a ribbon showing the range of data between the monthly cumulative 5th and 25th percentiles
- 25-75 Percentiles Range  
a ribbon showing the range of data between the monthly cumulative 25th and 75th percentiles
- 75-95 Percentiles Range  
a ribbon showing the range of data between the monthly cumulative 75th and 95th percentiles
- 95 Percentile-Max Range  
a ribbon showing the range of data between the monthly cumulative 95th percentile and the maximum
- 'Year' Flows (optional) the monthly cumulative flows for the designated year

### See Also

[calc\\_monthly\\_cumulative\\_stats](#)

### Examples

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot annual cumulative volume statistics
plot_monthly_cumulative_stats(station_number = "08NM116")

# Plot annual cumulative yield statistics with default HYDAT basin area
plot_monthly_cumulative_stats(station_number = "08NM116",
                              use_yield = TRUE)

# Plot annual cumulative yield statistics with custom basin area
plot_monthly_cumulative_stats(station_number = "08NM116",
                              use_yield = TRUE,
                              basin_area = 800)

}
```

---

plot\_monthly\_stats      *Plot monthly summary statistics*

---

### Description

Plots means, medians, maximums, minimums, and percentiles for each month of all years of flow values from a daily streamflow data set. Calculates statistics from all values, unless specified. Data calculated using the `calc_monthly_stats()` function. Produces a list containing a plot for each statistic. Returns a list of plots.

**Usage**

```
plot_monthly_stats(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  percentiles,
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  months = 1:12,
  ignore_missing = FALSE,
  log_discharge = FALSE,
  include_title = FALSE
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
percentiles	Numeric vector of percentiles to calculate. Set to NA if none required. Default NA.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.

water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.
log_discharge	Logical value to indicate plotting the discharge axis (Y-axis) on a logarithmic scale. Default FALSE.
include_title	Logical value to indicate adding the group/station number to the plot, if provided. Default FALSE.

**Value**

A list of ggplot2 objects for each monthly statistic for each station provided that contain:

## Monthly Mean Flows

mean of all daily flows for a given month and year

## Monthly Median Flows

median of all daily flows for a given month and year

## Monthly Maximum Flows

maximum of all daily flows for a given month and year

## Monthly Minimum Flows

minimum of all daily flows for a given month and year

## Monthly P'n' Flows

(optional) each n-th percentile selected for a given month and year

**See Also**

[calc\\_monthly\\_stats](#)

**Examples**

```
# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Plot monthly statistics using a data frame and data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
results <- plot_monthly_stats(data = flow_data,
```

```

        start_year = 1980,
        percentiles = 10)

# Plot monthly statistics for water years starting in October
results <- plot_monthly_stats(station_number = "08NM116",
                             start_year = 1980,
                             end_year = 2010,
                             water_year_start = 10,
                             percentiles = 10)

}

```

---

screen_flow_data	<i>Calculate annual summary and missing data statistics for screening data</i>
------------------	--

---

### Description

Calculates means, medians, maximums, minimums, standard deviations of annual flows and data availability and missing data statistics for each year and month of each year. Calculates the statistics from all daily discharge values from all years, unless specified. Returns a tibble with statistics.

### Usage

```

screen_flow_data(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  roll_days = 1,
  roll_align = "right",
  water_year_start = 1,
  start_year,
  end_year,
  months = 1:12,
  transpose = FALSE
)

```

### Arguments

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.



values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
roll_days	Numeric value of the number of days to apply a rolling mean. Default 1.
roll_align	Character string identifying the direction of the rolling mean from the specified date, either by the first ('left'), last ('right'), or middle ('center') day of the rolling n-day group of observations. Default 'right'.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
months	Numeric vector of months to include in analysis (e.g. 6:8 for Jun-Aug). Leave blank to summarize all months (default 1:12).
transpose	Logical value indicating whether to transpose rows and columns of results. Default FALSE.

### Value

A tibble data frame with the following columns:

Year	calendar or water year selected
n_days	number of days per year
n_Q	number of days per year with flow data
n_missing_Q	number of days per year with no flow data
Minimum	annual minimum of all daily flows for a given year
Maximum	annual maximum of all daily flows for a given year
Mean	annual mean of all daily flows for a given year
Median	annual median of all daily flows for a given year
StandardDeviation	annual 1 standard deviation of all daily flows for a given year

and the following monthly missing columns (order will depend on water\_year\_month):

```

Jan_missing_Q    number of Jan days per year with no flow data
Feb_missing_Q    number of Feb days per year with no flow data
Mar_missing_Q    number of Mar days per year with no flow data
Apr_missing_Q    number of Apr days per year with no flow data
May_missing_Q    number of May days per year with no flow data
Jun_missing_Q    number of Jun days per year with no flow data
Jul_missing_Q    number of Jul days per year with no flow data
Aug_missing_Q    number of Aug days per year with no flow data
Sep_missing_Q    number of Sep days per year with no flow data
Oct_missing_Q    number of Oct days per year with no flow data
Nov_missing_Q    number of Nov days per year with no flow data
Dec_missing_Q    number of Dec days per year with no flow data

```

Transposing data creates a column of "Statistics" and subsequent columns for each year selected.

### Examples

```

# Run if HYDAT database has been downloaded (using tidyhydat::download_hydat())
if (file.exists(tidyhydat::hy_downloaded_db())) {

# Calculate screening statistics using a data frame and data argument with defaults
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
screen_flow_data(data = flow_data)

# Calculate screening statistics using station_number argument with defaults
screen_flow_data(station_number = "08NM116")

# Calculate screening statistics for water years starting in October
screen_flow_data(station_number = "08NM116",
                 water_year_start = 9)

# Calculate screening statistics for 7-day flows for July-September months only
screen_flow_data(station_number = "08NM116",
                 roll_days = 7,
                 months = 7:9)

}

```

---

write\_flow\_data

*Write a streamflow dataset as a .xlsx, .xls, or .csv file*

---

### Description

Write a daily streamflow data set to a directory. Can fill missing dates or filter data by years or dates before writing using given arguments. List data frame or HYDAT station number to write its entirety. Can write as .xls, .xlsx, or .csv file types. Writing as Excel file type uses the writexl package.

**Usage**

```
write_flow_data(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  water_year_start = 1,
  start_year,
  end_year,
  start_date,
  end_date,
  file_name,
  fill_missing = FALSE,
  digits
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year of data to write. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year of data to write. Leave blank to use the last year of the source data.
start_date	Date (YYYY-MM-DD) of first date of data to write. Leave blank if all dates required.

end_date	Date (YYYY-MM-DD) of last date of data to write. Leave blank if all dates required.
file_name	Character string naming the output file. If none provided, a default file name (with .xlsx) is provided (see "Successfully created" message when using function for file name).
fill_missing	Logical value indicating whether to fill dates with missing flow data with NA. Default FALSE.
digits	Integer indicating the number of decimal places or significant digits used to round flow values. Use follows that of base::round() digits argument.

### Examples

```
## Not run:

# Working examples:

# Write data from a data frame
flow_data <- tidyhydat::hy_daily_flows(station_number = "08NM116")
write_flow_data(data = flow_data,
                file_name = "Mission_Creek_daily_flows.xlsx")

# Write data directly from HYDAT
write_flow_data(station_number = "08NM116",
                file_name = "Mission_Creek_daily_flows.xlsx")

# Write data directly from HYDAT and fill missing dates with NA
write_flow_data(station_number = "08NM116",
                file_name = "Mission_Creek_daily_flows.xlsx",
                fill_missing = TRUE)

## End(Not run)
```

---

write_full_analysis	<i>Write a suite of tables and plots from various fasstr functions into a directory</i>
---------------------	---

---

### Description

Calculates and writes tables and plots from a suite of statistics from *fasstr* functions into an Excel workbook, and accompanying plot files for certain analyses. Due to the number of tables and plots to be made, this function may take several minutes to complete. If `ignore_missing = FALSE` (default) and there is missing data, some tables and plots may be empty and produce warnings. Use `ignore_missing = TRUE` to ignore the missing values or filter your data to complete years. Calculates statistics from all values, unless specified. Returns a list of tibbles and plots, along with saving the Excel and image files in a directory.

**Usage**

```
write_full_analysis(
  data,
  dates = Date,
  values = Value,
  groups = STATION_NUMBER,
  station_number,
  analyses = 1:7,
  basin_area,
  water_year_start = 1,
  start_year,
  end_year,
  exclude_years,
  ignore_missing = FALSE,
  zyp_method = "zhang",
  zyp_alpha,
  file_name,
  plot_filetype = "pdf"
)
```

**Arguments**

data	Data frame of daily data that contains columns of dates, flow values, and (optional) groups (e.g. station numbers). Leave blank if using station_number argument.
dates	Name of column in data that contains dates formatted YYYY-MM-DD. Only required if dates column name is not 'Date' (default). Leave blank if using station_number argument.
values	Name of column in data that contains numeric flow values, in units of cubic metres per second. Only required if values column name is not 'Value' (default). Leave blank if using station_number argument.
groups	Name of column in data that contains unique identifiers for different data sets, if applicable. Only required if groups column name is not 'STATION_NUMBER'. Function will automatically group by a column named 'STATION_NUMBER' if present. Remove the 'STATION_NUMBER' column beforehand to remove this grouping. Leave blank if using station_number argument.
station_number	Character string vector of seven digit Water Survey of Canada station numbers (e.g. "08NM116") of which to extract daily streamflow data from a HYDAT database. Requires tidyhydat package and a HYDAT database. Leave blank if using data argument.
analyses	Numeric vector of analyses to run (default is all (1:7)): <ul style="list-style-type: none"> <li>• 1: Screening</li> <li>• 2: Long-term</li> <li>• 3: Annual</li> <li>• 4: Monthly</li> <li>• 5: Daily</li> </ul>

- 6: Annual Trends
- 7: Low-flow Frequencies

basin_area	Upstream drainage basin area, in square kilometres, to apply to observations. Three options: (1) Leave blank if groups is STATION_NUMBER with HYDAT station numbers to extract basin areas from HYDAT. (2) A single numeric value to apply to all observations. (3) List each basin area for each group/station in groups (can override HYDAT value if listed) as such c("08NM116" = 795, "08NM242" = 10). If group is not listed the HYDAT area will be applied if it exists, otherwise it will be NA.
water_year_start	Numeric value indicating the month (1 through 12) of the start of water year for analysis. Default 1.
start_year	Numeric value of the first year to consider for analysis. Leave blank to use the first year of the source data.
end_year	Numeric value of the last year to consider for analysis. Leave blank to use the last year of the source data.
exclude_years	Numeric vector of years to exclude from analysis. Leave blank to include all years.
ignore_missing	Logical value indicating whether dates with missing values should be included in the calculation. If TRUE then a statistic will be calculated regardless of missing dates. If FALSE then only those statistics from time periods with no missing dates will be returned. Default FALSE.
zyp_method	Character string identifying the prewhitened trend method to use from 'zyp', either 'zhang' or 'yuepilon'. 'zhang' is recommended over 'yuepilon' for hydrologic applications (see compute_annual_trends(); Bürger 2017; Zhang and Zwiers 2004). Only required if analysis group 6 is included. Default 'zhang'.
zyp_alpha	Numeric value of the significance level (ex. 0.05) of when to plot a trend line. Leave blank for no line.
file_name	Character string of the name of the Excel Workbook (and folder for plots if necessary) to create on drive to write all results.
plot_filetype	Image type to write. One of 'png', 'eps', 'ps', 'tex', 'pdf', 'jpeg', 'tiff', 'bmp', or 'svg'. If not 'pdf' then individual plots will be created instead of a combined PDF. Default 'pdf'.

### See Also

[compute\\_full\\_analysis](#), [screen\\_flow\\_data](#), [plot\\_data\\_screening](#), [plot\\_missing\\_dates](#), [calc\\_longterm\\_monthly](#), [plot\\_longterm\\_monthly\\_stats](#), [calc\\_longterm\\_daily\\_stats](#), [plot\\_longterm\\_daily\\_stats](#), [plot\\_flow\\_duration](#), [calc\\_annual\\_stats](#), [plot\\_annual\\_stats](#), [calc\\_annual\\_cumulative\\_stats](#), [plot\\_annual\\_cumulative\\_stats](#), [calc\\_annual\\_flow\\_timing](#), [plot\\_annual\\_flow\\_timing](#), [calc\\_annual\\_outside\\_normal](#), [plot\\_annual\\_outside\\_normal](#), [calc\\_annual\\_lowflows](#), [plot\\_annual\\_lowflows](#), [plot\\_annual\\_means](#), [calc\\_monthly\\_stats](#), [plot\\_monthly\\_stats](#), [calc\\_monthly\\_cumulative\\_stats](#), [plot\\_monthly\\_cumulative\\_stats](#), [calc\\_daily\\_stats](#), [plot\\_daily\\_stats](#), [calc\\_daily\\_cumulative\\_stats](#), [plot\\_daily\\_cumulative\\_stats](#), [compute\\_annual\\_trends](#), [compute\\_annual\\_frequencies](#), [write\\_flow\\_data](#), [write\\_plots](#)

## Examples

```
## Not run:

# Working examples:

# Save a full analysis with all the analyses
write_full_analysis(station_number = "08NM116",
                    file_name = "Mission Creek",
                    start_year = 1980,
                    end_year = 2010)

# Save a full analysis with only Annual and Daily analyses
write_full_analysis(station_number = "08NM116",
                    file_name = "Mission Creek",
                    start_year = 1980,
                    end_year = 2010,
                    analyses = c(3,5))

## End(Not run)
```

---

write_objects_list	<i>Write all data frames and plots from a list of objects into a directory</i>
--------------------	--

---

## Description

Write a list of tables (data frames) and plots (ggplots; as used by `fasstr`) into a directory. Objects that are not class "data.frame" or "gg" will not be saved. Each table and plot will be named by the object name in the list.

## Usage

```
write_objects_list(  
  list,  
  folder_name,  
  table_filetype,  
  plot_filetype,  
  width,  
  height,  
  units = "in",  
  dpi = 300  
)
```

## Arguments

list	List of data frames and plots to write to disk.
folder_name	Name of folder to create on disk (if it does not exist) to write each plot from list. If using <code>combined_pdf</code> argument, then it will be the name of the PDF document.

**table\_filetype** Table file type to write. One of 'csv', 'xls', or 'xlsx'.  
**plot\_filetype** Image type to write. One of 'png', 'eps', 'ps', 'tex', 'pdf', 'jpeg', 'tiff', 'bmp', or 'svg'. Image type will be overwritten if using combined\_pdf is used.  
**width** Numeric plot width in units. If not supplied, uses the size of current graphics device.  
**height** Numeric plot height in units. If not supplied, uses the size of current graphics device.  
**units** Character string plot height and width units, one of 'in', 'cm', or 'mm'. Default 'in'.  
**dpi** Numeric resolution of plots. Default 300.

### Examples

```

## Not run:

# Working examples:

# Example list of tables and plots to save
frequency <- compute_annual_frequencies(station_number = "08NM116")

# Write objects in a folder
write_objects_list(list = frequency,
                  folder_name = "Frequency Analysis",
                  table_filetype = "xlsx",
                  plot_filetype = "png")

## End(Not run)

```

---

write\_plots

*Write plots from a list into a directory or PDF document*

---

### Description

Write a list of plots (ggplots; as used by fasstr) into a directory or PDF document. When writing into a named directory each plot will be named by the plot name listed in the list; uses ggplot2::ggsave function. When writing into a PDF document (combined\_pdf == TRUE) the plot names will not appear; uses grDevices::pdf function.

### Usage

```

write_plots(
  plots,
  folder_name,
  plot_filetype,
  width,

```



```

    height,
    units = "in",
    dpi = 300,
    combined_pdf = FALSE
  )

```

### Arguments

plots	List of plots to write to disk.
folder_name	Name of folder to create on disk (if it does not exist) to write each plot from list. If using combined_pdf argument, then it will be the name of the PDF document.
plot_filetype	Image type to write. One of 'png', 'eps', 'ps', 'tex', 'pdf', 'jpeg', 'tiff', 'bmp', or 'svg'. Image type will be overwritten if using combined_pdf is used.
width	Numeric plot width in units. If not supplied, uses the size of current graphics device.
height	Numeric plot height in units. If not supplied, uses the size of current graphics device.
units	Character string plot height and width units, one of 'in', 'cm', or 'mm'. Default 'in'.
dpi	Numeric resolution of plots. Default 300.
combined_pdf	Logical value indicating whether to combine list of plots into one PDF document. Default FALSE.

### Examples

```

## Not run:

# Working examples:

# Example plots to save
plots <- plot_annual_lowflows(station_number = "08NM116")

# Write the plots as "png" files
write_plots(plots = plots,
            folder_name = "Low Flow Plots",
            plot_filetype = "png")

# Write the plots as a combined "pdf" document
write_plots(plots = plots,
            folder_name = "Low Flow Plots",
            combined_pdf = TRUE)

## End(Not run)

```

---

write_results	<i>Write a data frame as a .xlsx, .xls, or .csv file</i>
---------------	--

---

**Description**

Write a data frame to a directory with all numbers rounded to specified digits. Can write as .xls, .xlsx, or .csv file types. Writing as .xlsx or .xls uses the `writexl` package.

**Usage**

```
write_results(data, file_name, digits)
```

**Arguments**

<code>data</code>	Data frame to be written to a directory.
<code>file_name</code>	Character string naming the output file. Required.
<code>digits</code>	Integer indicating the number of decimal places or significant digits used to round flow values. Use follows that of <code>base::round()</code> <code>digits</code> argument.

**Examples**

```
## Not run:  
  
# Working examples:  
  
# Example data to write  
data_results <- calc_longterm_daily_stats(station_number = c("08HA002", "08HA011"),  
                                         start_year = 1971, end_year = 2000)  
  
# Write the data and round numbers to 1 decimal place  
write_results(data = data_results,  
             file_name = "Cowichan River Long-term Flows (1971-2000).xlsx",  
             digits = 1)  
  
## End(Not run)
```

# Index

add\_basin\_area, 3  
add\_cumulative\_volume, 4  
add\_cumulative\_yield, 5  
add\_daily\_volume, 7  
add\_daily\_yield, 8  
add\_date\_variables, 9  
add\_rolling\_means, 10  
add\_seasons, 12

calc\_all\_annual\_stats, 13, 61  
calc\_annual\_cumulative\_stats, 16, 17, 68, 74, 118  
calc\_annual\_flow\_timing, 16, 19, 68, 76, 118  
calc\_annual\_lowflows, 16, 22, 68, 79, 118  
calc\_annual\_outside\_normal, 16, 24, 68, 83, 118  
calc\_annual\_peaks, 27  
calc\_annual\_stats, 16, 29, 68, 81, 85, 118  
calc\_daily\_cumulative\_stats, 32, 68, 88, 118  
calc\_daily\_stats, 34, 68, 91, 118  
calc\_flow\_percentile, 37  
calc\_longterm\_daily\_stats, 39, 68, 98, 101, 118  
calc\_longterm\_mean, 42  
calc\_longterm\_monthly\_stats, 44, 68, 104, 118  
calc\_longterm\_percentile, 47  
calc\_monthly\_cumulative\_stats, 49, 68, 109, 118  
calc\_monthly\_stats, 16, 52, 68, 111, 118  
compute\_annual\_frequencies, 55, 68, 118  
compute\_annual\_trends, 58, 68, 118  
compute\_frequency\_analysis, 57, 61, 65, 70  
compute\_frequency\_quantile, 64  
compute\_full\_analysis, 66, 118  
compute\_hydat\_peak\_frequencies, 69

fill\_missing\_dates, 71

plot\_annual\_cumulative\_stats, 68, 72, 118  
plot\_annual\_flow\_timing, 68, 75, 118  
plot\_annual\_lowflows, 68, 77, 118  
plot\_annual\_means, 68, 79, 118  
plot\_annual\_outside\_normal, 68, 81, 118  
plot\_annual\_stats, 68, 83, 118  
plot\_daily\_cumulative\_stats, 68, 86, 118  
plot\_daily\_stats, 68, 89, 118  
plot\_data\_screening, 68, 92, 118  
plot\_flow\_data, 68, 94  
plot\_flow\_duration, 68, 96, 118  
plot\_longterm\_daily\_stats, 68, 99, 118  
plot\_longterm\_monthly\_stats, 68, 102, 118  
plot\_missing\_dates, 68, 105, 118  
plot\_monthly\_cumulative\_stats, 68, 107, 118  
plot\_monthly\_stats, 68, 109, 118

screen\_flow\_data, 68, 93, 106, 112, 118

write\_flow\_data, 68, 114, 118  
write\_full\_analysis, 116  
write\_objects\_list, 119  
write\_plots, 68, 118, 120  
write\_results, 122