

Package ‘healthyR’

August 20, 2021

Title Hospital Data Analysis Workflow Tools

Version 0.1.6

Description Hospital data analysis workflow tools, modeling, and automations. This library provides many useful tools to review common administrative hospital data. Some of these include average length of stay, readmission rates, average net pay amounts by service lines just to name a few. The aim is to provide a simple and consistent verb framework that takes the guesswork out of everything.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

URL <https://github.com/spsanderson/healthyR>

BugReports <https://github.com/spsanderson/healthyR/issues>

Imports magrittr, rlang ($\geq 0.1.2$), tibble, timetk, ggplot2, dplyr, lubridate, graphics, purrr, stringr, writexl, cowplot, scales, sqldf, tidyr, ggrepel, lifecycle, plotly

Suggests knitr, rmarkdown, roxygen2, pacman, healthyR.data, broom, tidyquant, uwot, cli, crayon, rstudioapi

VignetteBuilder knitr

Depends R (≥ 2.10)

NeedsCompilation no

Author Steven Sanderson [aut, cre],
Steven Sanderson [cph]

Maintainer Steven Sanderson <spsanderson@gmail.com>

Repository CRAN

Date/Publication 2021-08-20 16:40:02 UTC

R topics documented:

category_counts_tbl	2
diverging_bar_plt	3
diverging_lollipop_plt	5
dx_cc_mapping	6
gartner_magic_chart_plt	7
kmeans_mapped_tbl	8
kmeans_obj	9
kmeans_scree_data_tbl	10
kmeans_scree_plt	11
kmeans_tidy_tbl	13
kmeans_user_item_tbl	14
los_ra_index_plt	15
los_ra_index_summary_tbl	17
named_item_list	18
opt_bin	19
px_cc_mapping	20
save_to_excel	21
sql_left	22
sql_mid	22
sql_right	23
top_n_tbl	23
ts_alos_plt	24
ts_census_los_daily_tbl	26
ts_median_excess_plt	27
ts_plt	28
ts_readmit_rate_plt	30
ts_signature_tbl	31
umap_list	32
umap_plt	34
Index	36

category_counts_tbl *Counts by Category*

Description

Get the counts of a column by a particular grouping if supplied, otherwise just get counts of a column.

Usage

```
category_counts_tbl(.data, .count_col, .arrange_value = TRUE, ...)
```

Arguments

<code>.data</code>	The data.frame/tibble supplied.
<code>.count_col</code>	The column that has the values you want to count.
<code>.arrange_value</code>	Defaults to true, this will arrange the resulting tibble in descending order by <code>.count_col</code>
<code>...</code>	Place the values you want to pass in for grouping here.

Details

- Requires a data.frame/tibble.
- Requires a value column, a column that is going to be counted.

Author(s)

Steven P. Sanderson II, MPH

Examples

```
library(healthyR.data)
library(dplyr)

healthyR_data %>%
  category_counts_tbl(
    .count_col = payer_grouping
    , .arrange = TRUE
    , ip_op_flag
  )

healthyR_data %>%
  category_counts_tbl(
    .count_col = ip_op_flag
    , .arrange_value = TRUE
    , service_line
  )
```

diverging_bar_plt *Diverging Bar Chart*

Description

Diverging Bars is a bar chart that can handle both negative and positive values. This can be implemented by a smart tweak with `geom_bar()`. But the usage of `geom_bar()` can be quite confusing. That's because, it can be used to make a bar chart as well as a histogram. Let me explain.

By default, `geom_bar()` has the `stat` set to `count`. That means, when you provide just a continuous X variable (and no Y variable), it tries to make a histogram out of the data.

In order to make a bar chart create bars instead of histogram, you need to do two things. Set `stat = identity` and provide both `x` and `y` inside `aes()` where, `x` is either character or factor and `y` is numeric. In order to make sure you get diverging bars instead of just bars, make sure, your categorical variable has 2 categories that changes values at a certain threshold of the continuous variable. In below example, the `mpg` from `mtcars` data set is normalized by computing the z score. Those vehicles with `mpg` above zero are marked green and those below are marked red.

Usage

```
diverging_bar_plt(  
  .data,  
  .x_axis,  
  .y_axis,  
  .fill_col,  
  .plot_title = NULL,  
  .plot_subtitle = NULL,  
  .plot_caption = NULL,  
  .interactive = FALSE  
)
```

Arguments

<code>.data</code>	The data to pass to the function, must be a tibble/data.frame.
<code>.x_axis</code>	The data that is passed to the x-axis.
<code>.y_axis</code>	The data that is passed to the y-axis. This will also equal the parameter <code>label</code>
<code>.fill_col</code>	The column that will be used to fill the color of the bars.
<code>.plot_title</code>	Default is NULL
<code>.plot_subtitle</code>	Default is NULL
<code>.plot_caption</code>	Default is NULL
<code>.interactive</code>	Default is FALSE. TRUE returns a plotly plot

Details

This function takes only a few arguments and returns a `ggplot2` object.

Value

A plotly plot or a `ggplot2` static plot

Author(s)

Steven P. Sanderson II, MPH

Examples

```

suppressPackageStartupMessages(library(ggplot2))

data("mtcars")
mtcars$car_name <- rownames(mtcars)
mtcars$mpg_z <- round((mtcars$mpg - mean(mtcars$mpg))/sd(mtcars$mpg), 2)
mtcars$mpg_type <- ifelse(mtcars$mpg_z < 0, "below", "above")
mtcars <- mtcars[order(mtcars$mpg_z), ] # sort
mtcars$car_name <- factor(mtcars$car_name, levels = mtcars$car_name)

diverging_bar_plt(
  .data      = mtcars
  , .x_axis  = car_name
  , .y_axis  = mpg_z
  , .fill_col = mpg_type
  , .interactive = FALSE
)

```

diverging_lollipop_plt
Diverging Lollipop Chart

Description

This is a diverging lollipop function. Lollipop chart conveys the same information as bar chart and diverging bar. Except that it looks more modern. Instead of `geom_bar`, I use `geom_point` and `geom_segment` to get the lollipops right. Let's draw a lollipop using the same data I prepared in the previous example of diverging bars.

Usage

```

diverging_lollipop_plt(
  .data,
  .x_axis,
  .y_axis,
  .plot_title = NULL,
  .plot_subtitle = NULL,
  .plot_caption = NULL,
  .interactive = FALSE
)

```

Arguments

<code>.data</code>	The data to pass to the function, must be a tibble/data.frame.
<code>.x_axis</code>	The data that is passed to the x-axis. This will also be the x and xend parameters of the <code>geom_segment</code>

.y_axis The data that is passed to the y-axis. This will also equal the parameters of yend and label

.plot_title Default is NULL

.plot_subtitle Default is NULL

.plot_caption Default is NULL

.interactive Default is FALSE. TRUE returns a plotly plot

Details

This function takes only a few arguments and returns a ggplot2 object.

Value

A plotly plot or a ggplot2 static plot

Author(s)

Steven P. Sanderson II, MPH

Examples

```
suppressPackageStartupMessages(library(ggplot2))

data("mtcars")
mtcars$car_name <- rownames(mtcars)
mtcars$mpg_z <- round((mtcars$mpg - mean(mtcars$mpg))/sd(mtcars$mpg), 2)
mtcars$mpg_type <- ifelse(mtcars$mpg_z < 0, "below", "above")
mtcars <- mtcars[order(mtcars$mpg_z), ] # sort
mtcars$car_name <- factor(mtcars$car_name, levels = mtcars$car_name)

diverging_lollipop_plt(.data = mtcars, .x_axis = car_name
, .y_axis = mpg_z)
```

dx_cc_mapping

Diagnosis to Condition Code Mapping file

Description

A dataset containing the Diagnosis Code to AHRQ Condition Code Mapping that is used in helping to define service lines for inpatient discharges.

Usage

```
data(dx_cc_mapping)
```

Format

A data frame with 86852 rows and 5 variables

Details

- CC_Code. DX_1, DX_2, ..., DX_n
- CC_Desc. DX_1 = Conduction disorders, DX_n = description
- ICD_Ver_Flag. ICD Version 10 or 9
- ICDCode. ICD-9 ro ICD-10 Code
- Diagnosis. Long QT Syndrome

 gartner_magic_chart_plt

Gartner Magic Chart - Plotting of two continuous variables

Description

Plot a Gartner Magic Chart of two continuous variables

Usage

```
gartner_magic_chart_plt(
  .data,
  .x_col,
  .y_col,
  .y_lab,
  .x_lab,
  .plt_title,
  .tl_lbl,
  .tr_lbl,
  .br_lbl,
  .bl_lbl
)
```

Arguments

.data	The data set you want to plot
.x_col	The x-axis for the plot
.y_col	The y-axis for the plot
.y_lab	The y-axis label
.x_lab	The x-axis label
.plt_title	The title of the plot
.tl_lbl	The top left label
.tr_lbl	The top right label
.br_lbl	The bottom right label
.bl_lbl	The bottom left label

Details

- Supply a data frame with at least two continuous variables to plot against each other

Value

A ggplot plot

Author(s)

Steven P. Sanderson II, MPH

Examples

```
gartner_magic_chart_plt(
  .data = tibble::tibble(x = rnorm(100, 0, 1), y = rnorm(100,0,1))
  , .x_col = x
  , .y_col = y
  , .x_lab = "los"
  , .y_lab = "ra"
  , .plt_title = "tst"
  , .tr_lbl = "High RA-LOS"
  , .tl_lbl = "High RA"
  , .bl_lbl = "Leader"
  , .br_lbl = "High LOS"
)
```

kmeans_mapped_tbl *K-Means Mapper*

Description

Create a tibble that maps the [kmeans_obj\(\)](#) using [purrr::map\(\)](#) to create a nested data.frame/tibble that holds n centers. This tibble will be used to help create a scree plot.

Usage

```
kmeans_mapped_tbl(.data, .centers = 15)
```

Arguments

`.data` You must have a tibble in the working environment from the [kmeans_user_item_tbl\(\)](#)

`.centers` How many different centers do you want to try

Details

Takes in a single parameter of `.centers`. This is used to create the tibble and map the [kmeans_obj\(\)](#) function down the list creating a nested tibble.

Value

A nested tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Scree_plot

Examples

```
library(healthyR.data)
library(dplyr)

data_tbl <- healthyR_data%>%
  filter(ip_op_flag == "I") %>%
  filter(payer_grouping != "Medicare B") %>%
  filter(payer_grouping != "?") %>%
  select(service_line, payer_grouping) %>%
  mutate(record = 1) %>%
  as_tibble()

ui_tbl <- kmeans_user_item_tbl(
  .data = data_tbl
  , .row_input = service_line
  , .col_input = payer_grouping
  , .record_input = record
)

kmeans_mapped_tbl(ui_tbl)
```

kmeans_obj

K-Means Functions

Description

Takes the output of the `kmeans_user_item_tbl()` function and applies the k-means algorithm to it using `stats::kmeans()`

Usage

```
kmeans_obj(.data, .centers = 5)
```

Arguments

`.data` The data that gets passed from `kmeans_user_item_tbl()`
`.centers` How many initial centers to start with

Details

Uses the `stats::kmeans()` function and creates a wrapper around it.

Value

A stats k-means object

Author(s)

Steven P. Sanderson II, MPH

Examples

```
library(healthyR.data)
library(dplyr)

data_tbl <- healthyR_data%>%
  filter(ip_op_flag == "I") %>%
  filter(payer_grouping != "Medicare B") %>%
  filter(payer_grouping != "?") %>%
  select(service_line, payer_grouping) %>%
  mutate(record = 1) %>%
  as_tibble()

kmeans_user_item_tbl(
  .data = data_tbl
  , .row_input = service_line
  , .col_input = payer_grouping
  , .record_input = record
) %>%
  kmeans_obj()
```

kmeans_scree_data_tbl *K-Means Scree Plot Data Table*

Description

Take data from the `kmeans_mapped_tbl()` and unnest it into a tibble for inspection and for use in the `kmeans_scree_plt()` function.

Usage

```
kmeans_scree_data_tbl(.data)
```

Arguments

`.data` You must have a tibble in the working environment from the `kmeans_mapped_tbl()`

Details

Takes in a single parameter of `.data` from `kmeans_mapped_tbl()` and transforms it into a tibble that is used for `kmeans_scee_plt()`. It will show the values (tot.withinss) at each center.

Value

A nested tibble

Author(s)

Steven P. Sanderson II, MPH

Examples

```
library(healthyR.data)
library(dplyr)

data_tbl <- healthyR_data%>%
  filter(ip_op_flag == "I") %>%
  filter(payer_grouping != "Medicare B") %>%
  filter(payer_grouping != "?") %>%
  select(service_line, payer_grouping) %>%
  mutate(record = 1) %>%
  as_tibble()

ui_tbl <- kmeans_user_item_tbl(
  .data = data_tbl
  , .row_input = service_line
  , .col_input = payer_grouping
  , .record_input = record
)

kmm_tbl <- kmeans_mapped_tbl(ui_tbl)

kmeans_scee_data_tbl(kmm_tbl)
```

`kmeans_scee_plt`*K-Means Scree Plot*

Description

Create a scree-plot from the `kmeans_mapped_tbl()` function.

Usage

```
kmeans_scee_plt(.data)
```

Arguments

`.data` The data from the `kmeans_mapped_tbl()` function

Details

Outputs a scree-plot

Value

A `ggplot2` plot

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Scree_plot

Examples

```
library(healthyR.data)
library(dplyr)
library(tidyquant)

data_tbl <- healthyR_data%>%
  filter(ip_op_flag == "I") %>%
  filter(payer_grouping != "Medicare B") %>%
  filter(payer_grouping != "?") %>%
  select(service_line, payer_grouping) %>%
  mutate(record = 1) %>%
  as_tibble()

ui_tbl <- kmeans_user_item_tbl(
  .data      = data_tbl
  , .row_input = service_line
  , .col_input = payer_grouping
  , .record_input = record
)

kmm_tbl <- kmeans_mapped_tbl(ui_tbl)

kmeans_scree_plt(.data = kmm_tbl)
```

kmeans_tidy_tbl	<i>K-Means tidy Functions</i>
-----------------	-------------------------------

Description

K-Means tidy functions

Usage

```
kmeans_tidy_tbl(.kmeans_obj, .data, .tidy_type = "tidy")
```

Arguments

.kmeans_obj	A <code>stats::kmeans()</code> object
.data	The user item tibble created from <code>kmeans_user_item_tbl()</code>
.tidy_type	"tidy", "glance", or "augment"

Details

Takes in a k-means object and its associated user item tibble and then returns one of the items asked for. Either: `broom::tidy()`, `broom::glance()` or `broom::augment()`. The function defaults to `broom::tidy()`.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

Examples

```
library(healthyR.data)
library(dplyr)
library(broom)

data_tbl <- healthyR_data %>%
  filter(ip_op_flag == "I") %>%
  filter(payer_grouping != "Medicare B") %>%
  filter(payer_grouping != "?") %>%
  select(service_line, payer_grouping) %>%
  mutate(record = 1) %>%
  as_tibble()

uit_tbl <- kmeans_user_item_tbl(
  .data = data_tbl
  , .row_input = service_line
```

```
, .col_input = payer_grouping
, .record_input = record
)

km_obj <- kmeans_obj(uit_tbl)

kmeans_tidy_tbl(
  .kmeans_obj = km_obj
, .data = uit_tbl
, .tidy_type = "augment"
)

kmeans_tidy_tbl(
  .kmeans_obj = km_obj
, .data = uit_tbl
, .tidy_type = "glance"
)

kmeans_tidy_tbl(
  .kmeans_obj = km_obj
, .data = uit_tbl
, .tidy_type = "tidy"
) %>%
  glimpse()
```

kmeans_user_item_tbl *K-Means Functions*

Description

Takes in a data.frame/tibble and transforms it into an aggregated/normalized user-item tibble of proportions. The user will need to input the parameters for the rows/user and the columns/items.

Usage

```
kmeans_user_item_tbl(.data, .row_input, .col_input, .record_input)
```

Arguments

.data	The data that you want to transform
.row_input	The column that is going to be the row (user)
.col_input	The column that is going to be the column (item)
.record_input	The column that is going to be summed up for the aggregation and normalization process.

Details

This function should be used before using a k-mean model. This is commonly referred to as a user item matrix because "users" tend to be on the rows and "items" (e.g. orders) on the columns. You must supply a column that can be summed for the aggregation and normalization process to occur.

Value

A aggregated/normalized user item tibble

Author(s)

Steven P. Sanderson II, MPH

Examples

```
library(healthyR.data)
library(dplyr)

data_tbl <- healthyR_data%>%
  filter(ip_op_flag == "I") %>%
  filter(payer_grouping != "Medicare B") %>%
  filter(payer_grouping != "?") %>%
  select(service_line, payer_grouping) %>%
  mutate(record = 1) %>%
  as_tibble()

kmeans_user_item_tbl(
  .data = data_tbl
  , .row_input = service_line
  , .col_input = payer_grouping
  , .record_input = record
)
```

los_ra_index_plt

Plot LOS and Readmit Index with Variance

Description

Plot the index of the length of stay and readmit rate against each other along with the variance

Usage

```
los_ra_index_plt(.data)
```

Arguments

.data The data supplied from [los_ra_index_summary_tbl\(\)](#)

Details

- Expects a tibble
- Expects a Length of Stay and Readmit column, must be numeric
- Uses cowplot to stack plots

Value

A patchwork ggplot2 plot

Author(s)

Steven P. Sanderson II, MPH

Examples

```
suppressPackageStartupMessages(library(dplyr))

data_tbl <- tibble(
  "alos" = runif(186, 1, 20)
  , "elos" = runif(186, 1, 17)
  , "readmit_rate" = runif(186, 0, .25)
  , "readmit_rate_bench" = runif(186, 0, .2)
)

los_ra_index_summary_tbl(
  .data = data_tbl
  , .max_los = 15
  , .alos_col = alos
  , .elos_col = elos
  , .readmit_rate = readmit_rate
  , .readmit_bench = readmit_rate_bench
) %>%
  los_ra_index_plt()

los_ra_index_summary_tbl(
  .data = data_tbl
  , .max_los = 10
  , .alos_col = alos
  , .elos_col = elos
  , .readmit_rate = readmit_rate
  , .readmit_bench = readmit_rate_bench
) %>%
  los_ra_index_plt()
```

 los_ra_index_summary_tbl

Make LOS and Readmit Index Summary Tibble

Description

Create the length of stay and readmit index summary tibble

Usage

```
los_ra_index_summary_tbl(
  .data,
  .max_los = 15,
  .alos_col,
  .elos_col,
  .readmit_rate,
  .readmit_bench
)
```

Arguments

<code>.data</code>	The data you are going to analyze.
<code>.max_los</code>	You can give a maximum LOS value. Lets say you typically do not see los over 15 days, you would then set <code>.max_los</code> to 15 and all values greater than <code>.max_los</code> will be grouped to <code>.max_los</code>
<code>.alos_col</code>	The Average Length of Stay column
<code>.elos_col</code>	The Expected Length of Stay column
<code>.readmit_rate</code>	The Actual Readmit Rate column
<code>.readmit_bench</code>	The Expected Readmit Rate column

Details

- Expects a tibble
- Expects the following columns and there should only be these 4
 - Length Of Stay Actual - Should be an integer
 - Length Of Stacy Benchmark - Should be an integer
 - Readmit Rate Actual - Should be 0/1 for each record, 1 = readmitted, 0 did not.
 - Readmit Rate Benchmark - Should be a percentage from the benchmark file.
- This will add a column called visits that will be the count of records per length of stay from 1 to `.max_los`
- The `.max_los` param can be left blank and the function will default to 15. If this is not a good default and you don't know what it should be then set it to 75 percentile from the `stats::quantile()` function using the defaults, like so `.max_los = stats::quantile(data_tbl$alos)[[4]]`

- Uses all data to compute variance, if you want it for a particular time frame you will have to filter the data that goes into the .data argument. It is suggested to use `timetk::filter_by_time()`
- The index is computed as the excess of the length of stay or readmit rates over their respective expectations.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

Examples

```
suppressPackageStartupMessages(library(dplyr))
```

```
data_tbl <- tibble(
  "alos"           = runif(186, 1, 20)
  , "elos"         = runif(186, 1, 17)
  , "readmit_rate" = runif(186, 0, .25)
  , "readmit_bench" = runif(186, 0, .2)
)
```

```
los_ra_index_summary_tbl(
  .data = data_tbl
  , .max_los = 15
  , .alos_col = alos
  , .elos_col = elos
  , .readmit_rate = readmit_rate
  , .readmit_bench = readmit_bench
)
```

```
los_ra_index_summary_tbl(
  .data = data_tbl
  , .max_los = 10
  , .alos_col = alos
  , .elos_col = elos
  , .readmit_rate = readmit_rate
  , .readmit_bench = readmit_bench
)
```

named_item_list

Tibble to named list

Description

Takes in a data.frame/tibble and creates a named list from a supplied grouping variable. Can be used in conjunction with `save_to_excel()` to create a new sheet for each group of data.

Usage

```
named_item_list(.data, .group_col)
```

Arguments

.data	The data.frame/tibble.
.group_col	The column that contains the groupings.

Details

- Requires a data.frame/tibble and a grouping column.

Author(s)

Steven P. Sanderson II, MPH

Examples

```
library(healthyR.data)

df <- healthyR_data
df_list <- named_item_list(.data = df, .group_col = service_line)
df_list
```

opt_bin

Get the optimal binwidth for a histogram

Description

Gives the optimal binwidth for a histogram given a data set, it's value and the desired amount of bins

Usage

```
opt_bin(.data, .value_col, .iters = 30)
```

Arguments

.data	The data set in question
.value_col	The column that holds the values
.iters	How many times the cost function loop should run

Details

Modified from Hideaki Shimazaki Department of Physics, Kyoto University shimazaki at ton.scphys.kyoto-u.ac.jp Feel free to modify/distribute this program.

- Supply a data.frame/tibble with a value column. from this an optimal binwidth will be computed for the amount of binds desired

Value

A tibble of histogram breakpoints

Examples

```
suppressPackageStartupMessages(library(purrr))
suppressPackageStartupMessages(library(dplyr))

df_tbl <- rnorm(n = 1000, mean = 0, sd = 1)
df_tbl <- df_tbl %>%
  as_tibble() %>%
  set_names("value")

df_tbl %>%
  opt_bin(
    .value_col = value
    , .iters = 100
  )
```

px_cc_mapping

Procedure to Condition Code Mapping file

Description

A dataset containing the Procedure Code to AHRQ Condition Code Mapping that is used in helping to define service lines for inpatient discharges.

Usage

```
data(px_cc_mapping)
```

Format

A data frame with 79721 rows and 5 variables

Details

- CC_Code. PX_1, PX_2, ..., PX_n
- CC_Desc. PX_1 = Genitourinary incontinence procedures
- ICD_Ver_Flag. 10 or 9
- ICDCode. ICD-9 or ICD-10 Code
- Procedure. Inject Implant Urethra

save_to_excel	<i>Save a file to Excel</i>
---------------	-----------------------------

Description

Save a tibble/data.frame to an excel .xlsx file. The file will automatically with a save_dtime in the format of 20201109_132416 for November 11th, 2020 at 1:24:16PM.

Usage

```
save_to_excel(.data, .file_name)
```

Arguments

.data	The tibble/data.frame that you want to save as an .xlsx file.
.file_name	the name you want to give to the file.

Details

- Requires a tibble/data.frame to be passed to it.

Value

A saved excel file

Author(s)

Steven P. Sanderson II, MPH

sql_left	<i>Use SQL LEFT type function</i>
----------	-----------------------------------

Description

Perform an SQL LEFT() type function on a piece of text

Usage

```
sql_left(.text, .num_char)
```

Arguments

.text	A piece of text/string to be manipulated
.num_char	How many characters do you want to grab

Details

- You must supply data that you want to manipulate.

Examples

```
sql_left("text", 3)
```

sql_mid	<i>Use SQL MID type function</i>
---------	----------------------------------

Description

Perform an SQL SUBSTRING type function

Usage

```
sql_mid(.text, .start_num, .num_char)
```

Arguments

.text	A piece of text/string to be manipulated
.start_num	What place to start at
.num_char	How many characters do you want to grab

Details

- You must supply data that you want to manipulate.

Examples

```
sql_mid("this is some text", 6, 2)
```

sql_right	<i>Use SQL RIGHT type functions</i>
-----------	-------------------------------------

Description

Perform an SQL RIGHT type function

Usage

```
sql_right(.text, .num_char)
```

Arguments

.text	A piece of text/string to be manipulated
.num_char	How many characters do you want to grab

Details

- You must supply data that you want to manipulate.

Examples

```
sql_right("this is some more text", 3)
```

top_n_tbl	<i>Top N tibble</i>
-----------	---------------------

Description

Get a tibble returned with n records sorted either by descending order (default) or ascending order.

Usage

```
top_n_tbl(.data, .n_records, .arrange_value = TRUE, ...)
```

Arguments

`.data` The data you want to pass to the function
`.n_records` How many records you want returned
`.arrange_value` A boolean with TRUE as the default. TRUE sorts data in descending order
... The columns you want to pass to the function.

Details

- Requires a data.frame/tibble
- Requires at least one column to be chosen inside of the ...
- Will return the tibble in sorted order that is chosen with descending as the default

Author(s)

Steven P. Sanderson II, MPH

Examples

```
library(healthyR.data)

df <- healthyR_data

df_tbl <- top_n_tbl(
  .data = df
  , .n_records = 3
  , .arrange_value = TRUE
  , service_line
  , payer_grouping
)

print(df_tbl)
```

ts_alos_plt

Plot ALOS - Average Length of Stay

Description

Plot ALOS - Average Length of Stay

Usage

```
ts_alos_plt(.data, .date_col, .value_col, .by_grouping, .interactive)
```

Arguments

<code>.data</code>	The time series data you need to pass
<code>.date_col</code>	The date column
<code>.value_col</code>	The value column
<code>.by_grouping</code>	How you want the data summarized - "sec", "min", "hour", "day", "week", "month", "quarter" or "year"
<code>.interactive</code>	TRUE or FALSE. TRUE returns a plotly plot and FALSE returns a static ggplot2 plot

Details

- Expects a tibble with a date time column and a value column
- Uses `timetk` for underlying summarization and plot
- If `.by_grouping` is missing it will default to "day"
- A static `ggplot2` object is returned if the `.interactive` function is FALSE otherwise a plotly plot is returned.

Value

A `timetk` time series plot

Author(s)

Steven P. Sanderson II, MPH

Examples

```
library(healthyR)
library(healthyR.data)
library(timetk)
library(dplyr)
library(purrr)

# Make A Series of Dates ----
data_tbl <- healthyR_data

df_tbl <- data_tbl %>%
  filter(ip_op_flag == "I") %>%
  select(visit_end_date_time, length_of_stay) %>%
  summarise_by_time(
    .date_var = visit_end_date_time
    , .by      = "day"
    , visits  = mean(length_of_stay, na.rm = TRUE)
  ) %>%
  filter_by_time(
    .date_var      = visit_end_date_time
    , .start_date  = "2012"
    , .end_date    = "2019"
```

```

) %>%
  set_names("Date", "Values")

ts_alos_plt(
  .data = df_tbl
  , .date_col = Date
  , .value_col = Values
  , .by = "month"
  , .interactive = FALSE
)

```

ts_census_los_daily_tbl

Time Series - Census and LOS by Day

Description

Sometimes it is important to know what the census was on any given day, or what the average length of stay is on given day, including for those patients that are not yet discharged. This can be easily achieved. This will return one record for every account so the data will still need to be summarized.

This function can take a little bit of time to run while the join comparison runs.

Usage

```

ts_census_los_daily_tbl(
  .data,
  .keep_nulls_only = FALSE,
  .start_date_col,
  .end_date_col,
  .by_time = "day"
)

```

Arguments

<code>.data</code>	The data you want to pass to the function
<code>.keep_nulls_only</code>	A boolean that will keep only those records that have a NULL end date, meaning the patient is still admitted. The default is FALSE which brings back all records.
<code>.start_date_col</code>	The column containing the start date for the record
<code>.end_date_col</code>	The column containing the end date for the record.
<code>.by_time</code>	How you want the data presented, defaults to day and should remain that way unless you need more granular data.

Details

- Requires a dataset that has at least a start date column and an end date column
- Takes a single boolean parameter

Value

A tibble object

Author(s)

Steven P. Sanderson II, MPH

Examples

```
library(healthyR)
library(healthyR.data)
library(dplyr)

df <- healthyR_data

df_tbl <- df %>%
  filter(ip_op_flag == "I") %>%
  select(visit_start_date_time, visit_end_date_time) %>%
  timetk::filter_by_time(.date_var = visit_start_date_time, .start_date = "2020")

ts_census_los_daily_tbl(
  .data = df_tbl
  , .keep_nulls_only = FALSE
  , .start_date_col = visit_start_date_time
  , .end_date_col = visit_end_date_time
)
```

ts_median_excess_plt *Create a plot showing the excess of the median value*

Description

Plot out the excess +/- of the median value grouped by certain time parameters.

Usage

```
ts_median_excess_plt(
  .data,
  .date_col,
  .value_col,
  .x_axis,
  .ggplot_group_var,
  .years_back
)
```

Arguments

<code>.data</code>	The data that is being analyzed, data must be a tibble/data.frame.
<code>.date_col</code>	The column of the tibble that holds the date.
<code>.value_col</code>	The column that holds the value of interest.
<code>.x_axis</code>	What is the be the x-axis, day, week, etc.
<code>.ggplot_group_var</code>	The variable to group the ggplot on.
<code>.years_back</code>	How many yeas back do you want to go in order to compute the median value.

Details

- Supply data that you want to view and you will see the excess +/- of the median values over a specified time series tibble.

Value

A ggplot2 plot

Examples

```
suppressPackageStartupMessages(library(timetk))

ts_signature_tbl(
  .data      = m4_daily
  , .date_col = date
) %>%
ts_median_excess_plt(
  .date_col      = date
  , .value_col   = value
  , .x_axis      = week
  , .ggplot_group_var = year
  , .years_back  = 4
)
```

ts_plt

Time Series Plot

Description

This is a warpper function to the `timetk::plot_time_series()` function with a limited functionality parameter set. To see the full reference please visit the `timetk` package site.

Usage

```
ts_plt(  
  .data,  
  .date_col,  
  .value_col,  
  .color_col = NULL,  
  .facet_col = NULL,  
  .facet_ncol = NULL,  
  .interactive = FALSE  
)
```

Arguments

.data	The data to pass to the function, must be a tibble/data.frame.
.date_col	The column holding the date.
.value_col	The column holding the value.
.color_col	The column holding the variable for color.
.facet_col	The column holding the variable for faceting.
.facet_ncol	How many columns do you want.
.interactive	Return a plotly plot if set to TRUE and a static ggplot2 plot if set to FALSE. The default is FALSE.

Details

This function takes only a few of the arguments in the function and presets others while choosing the defaults on others. The smoother functionality is turned off.

Value

A plotly plot or a ggplot2 static plot

Author(s)

Steven P. Sanderson II, MPH

See Also

https://business-science.github.io/timetk/reference/plot_time_series.html

Examples

```
suppressPackageStartupMessages(library(dplyr))  
library(timetk)  
library(healthyR.data)  
  
healthyR.data::healthyR_data %>%  
  filter(ip_op_flag == "I") %>%  
  select(visit_end_date_time, service_line) %>%
```

```

filter_by_time(
  .date_var = visit_end_date_time
  , .start_date = "2020"
) %>%
group_by(service_line) %>%
summarize_by_time(
  .date_var = visit_end_date_time
  , .by = "month"
  , visits = n()
) %>%
ungroup() %>%
ts_plt(
  .date_col = visit_end_date_time
  , .value_col = visits
  , .color_col = service_line
)

```

ts_readmit_rate_plt *Plot Readmit Rate*

Description

Plot Readmit Rate

Usage

```
ts_readmit_rate_plt(.data, .date_col, .value_col, .by_grouping, .interactive)
```

Arguments

.data	The data you need to pass.
.date_col	The date column.
.value_col	The value column.
.by_grouping	How you want the data summarized - "sec", "min", "hour", "day", "week", "month", "quarter" or "year".
.interactive	TRUE or FALSE. TRUE returns a plotly plot and FALSE returns a static ggplot2 plot.

Details

- Expects a tibble with a date time column and a value column
- Uses timetk for underlying summarization and plot
- If .by_grouping is missing it will default to "day"

Value

A timetk time series plot that is interactive

Author(s)

Steven P. Sanderson II, MPH

Examples

```
set.seed(123)

suppressPackageStartupMessages(library(timetk))
suppressPackageStartupMessages(library(purrr))
suppressPackageStartupMessages(library(dplyr))

ts_tbl <- tk_make_timeseries(
  start = "2019-01-01"
  , by = "day"
  , length_out = "1 year 6 months"
)
values <- arima.sim(
  model = list(
    order = c(0, 1, 0)
    , n = 547
    , mean = 1
    , sd = 5
  )
)

df_tbl <- tibble(
  x = ts_tbl
  , y = values
) %>%
  set_names("Date", "Values")

ts_readmit_rate_plt(
  .data = df_tbl
  , .date_col = Date
  , .value_col = Values
  , .by = "month"
  , .interactive = FALSE
)
```

ts_signature_tbl *Make a Time Enhanced Tibble*

Description

Returns a tibble that adds the time series signature from the `timetk::tk_augment_timeseries_signature()` function. All added from a chosen date column defined by the `.date_col` parameter.

Usage

```
ts_signature_tbl(.data, .date_col, .pad_time = TRUE, ...)
```

Arguments

<code>.data</code>	The data that is being analyzed.
<code>.date_col</code>	The column that holds the date.
<code>.pad_time</code>	Boolean TRUE/FALSE. If TRUE then the <code>timetk::pad_by_time()</code> function is called and used on the data.frame before the modification. The default is TRUE.
<code>...</code>	Grouping variables to be used by <code>dplyr::group_by()</code> before using <code>timetk::pad_by_time()</code>

Details

- Supply data with a date column and this will add the year, month, week, week day and hour to the tibble. The original date column is kept.
- Returns a time-series signature tibble.
- You must know the data going into the function and if certain columns should be dropped or kept when using further functions

Value

A tibble

Examples

```
library(timetk)

ts_signature_tbl(
  .data      = m4_daily
  , .date_col = date
  , .pad_time = TRUE
  , id
)
```

umap_list

UMAP Projection

Description

Create a umap object from the `uwot::umap()` function.

Usage

```
umap_list(.data, .kmeans_map_tbl, .k_cluster = 5)
```

Arguments

<code>.data</code>	The data from the <code>kmeans_user_item_tbl()</code> function.
<code>.kmeans_map_tbl</code>	The data from the <code>kmeans_mapped_tbl()</code> .
<code>.k_cluster</code>	Pick the desired amount of clusters from your analysis of the scree plot.

Details

This takes in the user item table/matix that is produced by `kmeans_user_item_tbl()` function. This function uses the defaults of `uwot::umap()`.

Value

A list of tibbles and the umap object

Author(s)

Steven P. Sanderson II, MPH

See Also

- <https://cran.r-project.org/package=uwot> (CRAN)
- <https://github.com/jlmeville/uwot> (GitHub)
- <https://github.com/jlmeville/uwot> (arXiv paper)

Examples

```
library(healthyR.data)
library(healthyR)
library(dplyr)
library(broom)

data_tbl <- healthyR_data %>%
  filter(ip_op_flag == "I") %>%
  filter(payer_grouping != "Medicare B") %>%
  filter(payer_grouping != "?") %>%
  select(service_line, payer_grouping) %>%
  mutate(record = 1) %>%
  as_tibble()

uit_tbl <- kmeans_user_item_tbl(
  .data          = data_tbl
  , .row_input   = service_line
  , .col_input   = payer_grouping
  , .record_input = record
)

kmm_tbl <- kmeans_mapped_tbl(uit_tbl)

umap_list(.data = uit_tbl, kmm_tbl, 3)
```

`umap_plt`*UMAP and K-Means Cluster Visualization*

Description

Create a UMAP Projection plot.

Usage

```
umap_plt(.data, .point_size = 2, .label = TRUE)
```

Arguments

<code>.data</code>	The data from the <code>umap_list()</code> function.
<code>.point_size</code>	The desired size for the points of the plot.
<code>.label</code>	Should <code>ggrepel::geom_label_repel()</code> be used to display cluster user labels.

Details

This takes in `umap_kmeans_cluster_results_tbl` from the `umap_list()` function output.

Value

A `ggplot2` UMAP Projection with clusters represented by colors.

Author(s)

Steven P. Sanderson II, MPH

See Also

- <https://cran.r-project.org/package=uwot> (CRAN)
- <https://github.com/jlmelville/uwot> (GitHub)
- <https://github.com/jlmelville/uwot> (arXiv paper)

Examples

```
library(healthyR.data)
library(healthyR)
library(dplyr)
library(broom)
library(ggplot2)

data_tbl <- healthyR_data %>%
  filter(ip_op_flag == "I") %>%
  filter(payer_grouping != "Medicare B") %>%
  filter(payer_grouping != "?") %>%
  select(service_line, payer_grouping) %>%
```

```
mutate(record = 1) %>%
  as_tibble()

uit_tbl <- kmeans_user_item_tbl(
  .data      = data_tbl
  , .row_input = service_line
  , .col_input = payer_grouping
  , .record_input = record
)

kmm_tbl <- kmeans_mapped_tbl(uit_tbl)

ump_lst <- umap_list(.data = uit_tbl, kmm_tbl, 3)

umap_plt(.data = ump_lst, .point_size = 3)
```

Index

- * **datasets**
 - dx_cc_mapping, 6
 - px_cc_mapping, 20
- broom::augment(), 13
- broom::glance(), 13
- broom::tidy(), 13
- category_counts_tbl, 2
- diverging_bar_plt, 3
- diverging_lollipop_plt, 5
- dplyr::group_by(), 32
- dx_cc_mapping, 6
- gartner_magic_chart_plt, 7
- ggrepel::geom_label_repel(), 34
- kmeans_mapped_tbl, 8
- kmeans_mapped_tbl(), 10–12, 32
- kmeans_obj, 9
- kmeans_obj(), 8
- kmeans_scee_data_tbl, 10
- kmeans_scee_plt, 11
- kmeans_scee_plt(), 10, 11
- kmeans_tidy_tbl, 13
- kmeans_user_item_tbl, 14
- kmeans_user_item_tbl(), 8, 9, 13, 32, 33
- los_ra_index_plt, 15
- los_ra_index_summary_tbl, 17
- los_ra_index_summary_tbl(), 15
- named_item_list, 18
- opt_bin, 19
- purrr::map(), 8
- px_cc_mapping, 20
- save_to_excel, 21
- save_to_excel(), 18
- sql_left, 22
- sql_mid, 22
- sql_right, 23
- stats::kmeans(), 9, 10, 13
- stats::quantile(), 17
- timetk::filter_by_time(), 18
- timetk::pad_by_time(), 32
- timetk::plot_time_series(), 28
- timetk::tk_augment_timeseries_signature(), 31
- top_n_tbl, 23
- ts_alos_plt, 24
- ts_census_los_daily_tbl, 26
- ts_median_excess_plt, 27
- ts_plt, 28
- ts_readmit_rate_plt, 30
- ts_signature_tbl, 31
- umap_list, 32
- umap_list(), 34
- umap_plt, 34
- uwot::umap(), 32, 33