

Package ‘serp’

November 7, 2021

Type Package

Title Smooth Effects on Response Penalty for 'CLM'

Version 0.2.3

Description A regularization method for the cumulative link models. The 'smooth-effect-on-response penalty' ('SERP') provides flexible modelling of the ordinal model by enabling the smooth transition from the general cumulative link model to a coarser form of the same model. In other words, as the tuning parameter goes from zero to infinity, the subject-specific effects associated with each variable in the model tend to a unique global effect. The parameter estimates of the general cumulative model are mostly unidentifiable or at least only identifiable within a range of the entire parameter space. Thus, by maximizing a penalized rather than the usual non-penalized log-likelihood, this and other numerical problems common with the general model are to a large extent eliminated. Fitting is via a modified Newton's method. Several standard model performance and descriptive methods are also available. For more details on the penalty implemented here, see, 'Ugba (2021)' <[doi:10.21105/joss.03705](https://doi.org/10.21105/joss.03705)>, 'Ugba et al. (2021)' <[doi:10.3390/stats4030037](https://doi.org/10.3390/stats4030037)> and 'Tutz and Gertheiss (2016)' <[doi:10.1177/1471082X16642560](https://doi.org/10.1177/1471082X16642560)>.

License GPL-2 | file LICENSE

URL <https://github.com/ejikeugba/serp>

BugReports <https://github.com/ejikeugba/serp/issues>

Depends R (>= 3.2.0)

Imports ordinal (>= 2016-12-12), crayon, stats

Suggests covr, testthat, VGAM (>= 1.1-4)

Encoding UTF-8

LazyData True

RoxygenNote 7.1.1

NeedsCompilation no

Author Ejike R. Ugba [aut, cre, cph] (<<https://orcid.org/0000-0003-2572-0023>>)

Maintainer Ejike R. Ugba <ejike.ugba@outlook.com>

Repository CRAN

Date/Publication 2021-11-07 20:40:02 UTC

R topics documented:

AIC.serp	2
anova.serp	3
BIC.serp	4
coef.serp	5
confint.serp	5
errorMetrics	6
logLik.serp	7
predict.serp	8
print.errorMetrics	9
print.serp	10
print.summary.serp	10
serp	11
serp.control	15
summary.serp	17
vcov.serp	18
wine	18
Index	20

AIC.serp	<i>AIC for a fitted serp object</i>
----------	-------------------------------------

Description

Returns the akaike information criterion of a fitted object of class `serp`. For the penalized slope, the effective degrees of freedom (edf) is obtained from the trace of the generalized hat matrix which depends on the tuning parameter.

Usage

```
## S3 method for class 'serp'
AIC(object, ..., k = 2)
```

Arguments

<code>object</code>	An object of class <code>serp</code> .
<code>...</code>	additional arguments.
<code>k</code>	fixed value equal to 2.

Value

A single numeric value of the model AIC.

See Also

[serp](#), [BIC.serp](#), [coef.serp](#), [logLik.serp](#),

Examples

```
library(serp)
m <- serp(rating ~ temp + contact, slope = "parallel", link = "probit",
          data = wine)
AIC(m)
```

anova.serp

ANOVA method for a fitted serp object

Description

Provides a likelihood ratio test for comparing two or more serp objects. This does not currently support model(s) with penalized slope.

Usage

```
## S3 method for class 'serp'
anova(object, ..., test = c("Chisq", "none"))
```

Arguments

object	An object of class serp.
...	additional arguments.
test	type of test to be conducted.

Details

An ANOVA table with the following components on display:

Value

model	the respective model aliases.
slope	type of slope fitted, which may be any of, unparallel, parallel, or partial slope.
no.par	the no of parameters in the model.
AIC	the akaike information criterion.
logLik	the realized log-likelihood.
Test	the different pair(s) of test(s) conducted.
LR.stat	the computed Likelihood ratio statistic.
df	the degree of freedom.
Pr(chi)	the p-value of test statistic.

See Also

[serp](#), [confint.serp](#), [vcov.serp](#), [errorMetrics](#)

Examples

```
library(serp)
m1 <- serp(rating ~ temp + contact, slope = "parallel", link = "logit",
           data = wine)
m2 <- update(m1, ~ contact)
anova(m1, m2)
```

BIC.serp

BIC for a fitted serp object

Description

Returns the bayesian information criterion of a fitted object of class `serp`. For the penalized slopes, the effective degrees of freedom (edf) is obtained from the trace of the generalized hat matrix which depends on the tuning parameter.

Usage

```
## S3 method for class 'serp'
BIC(object, ...)
```

Arguments

`object` An object of class `serp`.
`...` additional arguments.

Value

A single numeric value of the model.

See Also

[serp](#), [AIC.serp](#), [coef.serp](#), [logLik.serp](#),

Examples

```
library(serp)
m <- serp(rating ~ temp + contact, slope = "parallel", link = "loglog",
          data = wine)
BIC(m)
```

coef.serp	<i>Coefficients for a fitted serp object</i>
-----------	--

Description

Returns the coefficients of a fitted object of class serp.

Usage

```
## S3 method for class 'serp'  
coef(object, ...)  
  
## S3 method for class 'serp'  
coefficients(object, ...)
```

Arguments

object	An object of class serp.
...	additional arguments.

Value

A vector of model coefficients.

See Also

[serp](#), [AIC.serp](#), [BIC.serp](#), [logLik.serp](#)

Examples

```
library(serp)  
m <- serp(rating ~ temp + contact, slope = "parallel", link = "loglog",  
          data = wine)  
coef(m)
```

confint.serp	<i>Confidence interval for a fitted serp object</i>
--------------	---

Description

Provides the confidence interval of estimates for an object of class serp.

Usage

```
## S3 method for class 'serp'  
confint(object, ..., parm, level = 0.95)
```

Arguments

object	An object of class <code>serp</code> .
...	additional arguments.
parm	unused argument.
level	significance level.

Value

A matrix of the the confidence intervals of fitted model.

See Also

[serp](#), [anova.serp](#), [vcov.serp](#), [errorMetrics](#)

Examples

```
library(serp)
m <- serp(rating ~ temp + contact, slope = "parallel", link = "logit",
          data = wine)
confint(m)
```

errorMetrics

Performance metrics for categorical response models

Description

Calculates the performance metrics of fitted binary and multi-categorical response models. Available measures include: brier score, logloss and misclassification error.

Usage

```
errorMetrics(
  actual,
  predicted,
  type= c("brier", "logloss", "misclass"),
  control = list())
```

Arguments

actual	vector of actual values observed
predicted	predicted probability matrix of a categorical model or a vector of fitted values for binary models.
type	specifies the type of error metrics.
control	A list of control parameters to replace default values returned by <code>serp</code> . <code>control</code> . 'misclass.thresh' resets the default misclassification error threshold, while 'minP' assigns a near-zero constant value to the predicted values beyond certain threshold, to forestall chances of numerical problems.

Details

A numeric value of the selected error type determining how good a categorical model compares to competing models.

Value

value	the value of error measure computed.
type	the error measure used: any of brier, logLoss or misclassification error.
threshold	the misclassification threshold.

See Also

[serp](#), [anova.serp](#), [confint.serp](#), [vcov.serp](#)

Examples

```
require(serp)

m1 <- serp(rating ~ temp + contact, slope = "parallel", link = "logit", data = wine)
errorMetrics(m1, type = "brier")

## objects of class other than \code{serp} require the actual
## observations with corresponding predicted values supplied.

set.seed(2)
n <- 50
y <- as.factor(rbinom(n, 1, 0.5))
m2 <- glm(y ~ rnorm(n), family = binomial())
ft <- m2$fitted.values

errorMetrics(actual=y, predicted=ft, type = "logloss")
errorMetrics(actual=y, predicted=ft, type = "misclass")

## Reset classification threshold
errorMetrics(actual=y, predicted=ft, type = "misclass",
control = list(misclass.thresh=0.4))
```

logLik.serp

Log-likelihood for a fitted serp object

Description

Returns the Log-likelihood for a fitted object of class `serp`.

Usage

```
## S3 method for class 'serp'
logLik(object, ...)
```

Arguments

```
object      An object of class serp.
...         additional arguments.
```

Value

A single numeric value of model log-likelihood

See Also

[serp](#), [AIC.serp](#), [BIC.serp](#), [coef.serp](#)

Examples

```
library(serp)
m <- serp(rating ~ temp + contact, slope = "parallel", link = "loglog",
          data = wine)
logLik(m)
```

predict.serp

Prediction from fitted serp model

Description

This function takes a fitted `serp` object produced by `serp()` and produces predicted values. Type of predictions returned include response, link and class. Prediction is also possible with new set of values having the same column names as in the original values used for the model fit.

Usage

```
## S3 method for class 'serp'
predict(object, type = c("link", "response", "class"), newdata = NULL, ...)
```

Arguments

```
object      An object of class serp.
type        could be any of these: response, link or terms.
newdata     fresh dataset with all relevant variables.
...         additional arguments.
```


Value

A vector of predicted classes with type equal to 'class' or a dataframe of predicted values for type equal to 'response' and 'link'.

See Also

[anova.serp](#), [summary.serp](#), [confint.serp](#), [vcov.serp](#), [errorMetrics](#)

Examples

```
library(serp)
m <- serp(rating ~ temp + contact, slope = "penalize",
          reverse = TRUE, link = "logit", tuneMethod = "user",
          lambda = 1, data = wine)

head(predict(m, type = "link"))
head(predict(m, type = "response"))
predict(m, type = "class")

n.wine <- wine[1:20,]
predict(m, newdata = n.wine, type = "class")
```

print.errorMetrics *Print method for an object of class errorMetrics*

Description

Prints out a vector of calculated error value of fitted model.

Usage

```
## S3 method for class 'errorMetrics'
print(x, ...)
```

Arguments

x An object of class errorMetrics.
... additional arguments.

Value

No return value

See Also

[errorMetrics](#)

print.serp

Print method for a fitted serp object

Description

Prints out a vector of coefficients of the fitted model with some additional goodness-of-fit measures.

Usage

```
## S3 method for class 'serp'  
print(x, ...)
```

Arguments

x	An object of class serp.
...	additional arguments.

Value

No return value

See Also

[serp](#), [print.summary.serp](#)

print.summary.serp

Print method for an object of class summary.serp

Description

Prints out the information supplied via `summary.serp` method.

Usage

```
## S3 method for class 'summary.serp'  
print(x, ...)
```

Arguments

x	An object of class <code>summary.serp</code> .
...	additional arguments.

Value

No return value

See Also

[serp](#), [print.serp](#)

 serp

Smooth Effects on Response Penalty for CLM

Description

Fits cumulative link models (CLMs) with the smooth-effect-on-response penalty (SERP) via a modified Newton-Raphson algorithm. SERP enables the regularization of the parameter space between the general and the restricted cumulative models, with a resultant shrinkage of all subject-specific effects to global effects. The Akaike information criterion (`aic`), K-fold cross validation (`cv`), among other tuning approaches, provide the means of arriving at an optimal tuning parameter in a situation where a user-supplied tuning value is not available. The `slope` argument allows for the selection of a penalized, unparallel, parallel, or partial slope.

Usage

```
serp(
  formula,
  link = c("logit", "probit", "loglog", "cloglog", "cauchit"),
  slope = c("penalize", "parallel", "unparallel", "partial"),
  tuneMethod = c("aic", "cv", "finite", "user"),
  reverse = FALSE,
  lambdaGrid = NULL,
  cvMetric = c("brier", "logloss", "misclass"),
  gridType = c("discrete", "fine"),
  globalEff = NULL,
  data,
  subset,
  weights = NULL,
  weight.type = c("analytic", "frequency"),
  na.action = NULL,
  lambda = NULL,
  contrasts = NULL,
  control = list(),
  ...)
```

Arguments

<code>formula</code>	regression formula of the form: response ~ predictors. The response should be a factor (ordered).
<code>link</code>	sets the link function for the cumulative link model including: <code>logit</code> , <code>probit</code> , <code>complementary log-log</code> , <code>cloglog</code> , <code>cauchit</code> .
<code>slope</code>	selects the form of coefficients used in the model, with <code>penalize</code> denoting the penalized coefficients, <code>unparallel</code> , <code>parallel</code> and <code>partial</code> denoting the unpenalized non-parallel, parallel and semi-parallel coefficients respectively.

tuneMethod	sets the method of choosing an optimal shrinkage parameter, including: <code>aic</code> , <code>cv</code> , <code>finite</code> and <code>user</code> . i.e., the lambda value along parameter shrinkage path at which the fit's AIC or the k-fold cross-validated test error is minimal. The finite tuning is used to obtain the model along parameter shrinkage for which the log-Likelihood exist (is finite). The 'user' tuning supports a user-supplied lambda value.
reverse	false by default, when true the sign of the linear predictor is reversed.
lambdaGrid	optional user-supplied lambda grid for the <code>aic</code> , and <code>cv</code> tuning methods, when the discrete <code>gridType</code> is chosen. Negative range of values are not allowed. A short lambda grid could increase computation time assuming large number of predictors and cases in the model.
cvMetric	sets the performance metric for the <code>cv</code> tuning, with the brier score used by default.
gridType	chooses if a discrete or a continuous lambda grid should be used to select the optimal tuning parameter. The former is used by default and could be adjusted as desired in <code>serp.control</code> . The latter is on the range (0, <code>maxPen</code>). A user-supplied grid is also possible, which automatically overrides the internal grid.
globalEff	specifies variable(s) to be assigned global effects during penalization or when <code>slope</code> is set to <code>partial</code> . Variables are specified as a formula with an empty left hand side, for instance, <code>globalEff = ~predictors</code> .
data	optional dataframe explaining the variables used in the formula.
subset	specifies which subset of the rows of the data should be used for fit. All observations are used by default.
weights	optional case weights in fitting. Negative weights are not allowed. Defaults to 1.
weight.type	chooses between analytic and frequency weights with the former used by default. The latter should be used when weights are mere case counts used to compress the data set.
na.action	a function to filter missing data.
lambda	a user-supplied single numeric value for the tuning parameter when using the user tuning method. Negative values are not allowed.
contrasts	a list of contrasts to be used for some or all of the factors appearing as variables in the model formula.
control	A list of fit control parameters to replace default values returned by <code>serp.control</code> . Values not set assume default values.
...	additional arguments.

Details

The `serp` function fits the cumulative link model (CLM) with smooth-effect-on-response penalty (SERP). The cumulative model developed by McCullagh (1980) is probably most frequently used ordinal model. When motivated by an underlying latent variable, a simple form of the model is expressed as follows:

$$P(Y \leq r|x) = F(\delta_{0r} + x^T \delta)$$

where x is a vector of covariates, δ a vector of regression parameters and F a continuous distribution function. This model assumes that the effect of x does not depend on the category. However, with this assumption relaxed, one obtains the following general cumulative model:

$$P(Y \leq r|x) = F(\delta_{0r} + x^T \delta_r),$$

where $r=1, \dots, k-1$. This model, however, has the stochastic ordering property, which implies that $P(Y \leq r-1|x) < P(Y \leq r|x)$ holds for all x and all categories r . Such assumption is often problematic, resulting in unstable likelihoods with ill-conditioned parameter space during the iterative procedure.

SERP offers a means of arriving at stable estimates of the general model. It provides a form of regularization that is based on minimizing the penalized log-likelihood:

$$l_p(\delta) = l(\delta) - J_\lambda(\delta)$$

where $l(\delta)$, is the log-likelihood of the general cumulative model and $J_\lambda(\delta) = \lambda J(\delta)$ the penalty function weighted by the turning parameter λ . Assuming an ordered categorical outcome $Y \in \{1, \dots, k\}$, and considering that the corresponding parameters $\delta_{1j}, \dots, \delta_{k-1,j}$ vary smoothly over the categories, the following penalty (Tutz and Gertheiss, 2016),

$$J_\lambda(\delta) = \sum_{j=1}^p \sum_{r=1}^{k-2} (\delta_{r+1,j} - \delta_{rj})^2$$

enables the smoothing of response categories such that all category-specific effects associated with the response turn towards a common global effect. SERP could also be applied to a semi-parallel model with only the category-specific part of the model penalized. See, Ugba (2021), Ugba et al. (2021) for further details and application in empirical studies.

An object of class `serp` with the components listed below, depending on the type of slope modeled. Other summary methods include: `summary`, `coef`, `predict`, `vcov`, `anova`, `errorMetrics`, etc.

Value

<code>aic</code>	the akaike information criterion, with effective degrees of freedom obtained from the trace of the generalized hat matrix depending on the tuning parameter.
<code>bic</code>	the bayesian information criterion, with effective degrees of freedom obtained from the trace of the generalized hat matrix depending on the tuning parameter.
<code>call</code>	the matched call.
<code>coef</code>	a vector of coefficients of the fitted model.
<code>converged</code>	a character vector of fit convergence status.
<code>contrasts</code>	(where relevant) the contrasts used in the model.
<code>control</code>	list of control parameters from <code>serp.control</code> .
<code>cvMetric</code>	the performance metric used for cv tuning.
<code>deviance</code>	the residual deviance.

edf	the (effective) number of degrees of freedom used by the model
fitted.values	the fitted probabilities.
globalEff	variable(s) in model treated as global effect(s)
gradient	a column vector of gradients for the coefficients at the model convergence.
Hessian	the hessian matrix for the coefficients at the model convergence.
iter	number of interactions before convergence or non-convergence.
lambda	a user-supplied single numeric value for the user tuning tuning method.
lambdaGrid	a numeric vector of lambda values used to determine the optimum tuning parameter.
logLik	the realized log-likelihood at the model convergence.
link	character vector indicating the link function of the fit.
message	character vector stating the type of convergence obtained
misc	a list to hold miscellaneous fit information.
model	model.frame having variables from formula.
na.action	(where relevant) information on the treatment of NAs.
nobs	the number of observations.
nrFold	the number of k-fold cross validation for the cv tuning method. Default to k = 5.
rdf	the residual degrees of freedom
reverse	a logical vector indicating the the direction of the cumulative probabilities. Default to $P(Y \leq r)$.
slope	a character vector indicating the type of slope parameters fitted. Default to penalize.
Terms	the terms structure describing the model.
testError	numeric value of the cross-validated test error at which the optimal tuning parameter emerged.
tuneMethod	a character vector specifying the method for choosing an optimal shrinkage parameter.
value	numeric value of AIC or logLik obtained at the optimal tuning parameter when using <code>aic</code> or <code>finite</code> tuning methods respectively.
ylev	the number of the response levels.

References

- Ugba, E. R. (2021). `serp`: An R package for smoothing in ordinal regression *Journal of Open Source Software*, 6(66), 3705. <https://doi.org/10.21105/joss.03705>
- Ugba, E. R., Mörlein, D. and Gertheiss, J. (2021). Smoothing in Ordinal Regression: An Application to Sensory Data. *Stats*, 4, 616–633. <https://doi.org/10.3390/stats4030037>
- Tutz, G. and Gertheiss, J. (2016). Regularized Regression for Categorical Data (With Discussion and Rejoinder). *Statistical Modelling*, 16, pp. 161-260. <https://doi.org/10.1177/1471082X16642560>
- McCullagh, P. (1980). Regression Models for Ordinal Data. *Journal of the Royal Statistical Society. Series B (Methodological)*, 42, pp. 109-142. <https://doi.org/10.1111/j.2517-6161.1980.tb01109.x>

See Also

[anova.serp](#), [summary.serp](#), [predict.serp](#), [confint.serp](#), [vcov.serp](#), [errorMetrics](#)

Examples

```
require(serp)
## The unpenalized non-proportional odds model returns unbounded estimates, hence,
## not fully identifiable.
f1 <- serp(rating ~ temp + contact, slope = "unparallel",
          reverse = TRUE, link = "logit", data = wine)
coef(f1)

## The penalized non-proportional odds model with a user-supplied lambda gives
## a fully identified model with bounded estimates. A suitable tuning criterion
## could as well be used to select lambda (e.g., aic, cv)
f2 <- serp(rating ~ temp + contact, slope = "penalize",
          link = "logit", reverse = TRUE, tuneMethod = "user",
          lambda = 1e1, data = wine)
coef(f2)

## A penalized partial proportional odds model with one variable set to
## global effect is also possible.
f3 <- serp(rating ~ temp + contact, slope = "penalize",
          reverse = TRUE, link = "logit", tuneMethod = "user",
          lambda = 2e1, globalEff = ~ temp, data = wine)
coef(f3)

## The unpenalized proportional odds model with constrained estimates. Using a
## very strong lambda in f2 will result in estimates equal to estimates in f4.
f4 <- serp(rating ~ temp + contact, slope = "parallel",
          reverse = FALSE, link = "logit", data = wine)
summary(f4)
```

serp.control

Control parameters for a fitted serp object

Description

Default control parameters for 'serp' fit. User-supplied control parameters could be specified in the main function.

Usage

```
serp.control(
  maxits = 5e01,
  eps = 1e-07,
  maxpen = 1e07,
```

```

trace = 0L,
maxAdjIter = 5e0,
max.half.iter = 1e01,
relTol = 1e-03,
nrFold = 5e0,
cv.seed = 1e01,
grid.length = 5e01,
misclass.thresh = 5e-01,
minP = .Machine$double.eps,
...)
```

Arguments

<code>maxits</code>	the maximum number of Newton's iterations. Default to 100.
<code>eps</code>	threshold value during optimization at which the iteration routine terminates. In other words, when the reported change in the log-likelihood goes below this threshold, convergence is achieved.
<code>maxpen</code>	the upper end point of the interval from zero to be searched for a tuning parameter.
<code>trace</code>	prints the Newton's fitting process at each iteration step.If 0 (default) no information is printed, if 1, 2 or 3 different shades of information are printed.
<code>maxAdjIter</code>	the maximum allowable number of Newton step adjustment to forestall an early optimization failure. Defaults to 5.
<code>max.half.iter</code>	the maximum number of iteration step-halfings. Defaults to 10.
<code>relTol</code>	relative convergence tolerance, defaults to 1e-03. checks relative changes in the parameter estimates between Newton iterations.
<code>nrFold</code>	the number of k-fold cross validation for the CV tuning method. Default to k = 5.
<code>cv.seed</code>	single numeric value to change the random seed in CV tuning.
<code>grid.length</code>	the length of the discrete lambda grid for the penalty method.
<code>misclass.thresh</code>	to reset the classification threshold in <code>errorMetrics</code> when type is 'misclass'.
<code>minP</code>	A near zero minimum value the fitted probabilities are allowed to get during iteration to prevent numerical instability .
<code>...</code>	additional arguments.

Value

a list of control parameters.

See Also

[serp](#)

Examples

```
library(serp)
serp(rating ~ contact, slope = "parallel", link = "logit",
     control = list(maxits = 2e01, eps=1e-05, trace = 2),
     data = wine)
```

summary.serp

Summary method for a fitted serp object.

Description

This function summarizes the result of a fitted serp object in a dataframe.

Usage

```
## S3 method for class 'serp'
summary(object, ...)
```

Arguments

object	An object of class serp.
...	Not used. Additional summary arguments.

Details

an object of class summary.serp. A list (depending on the type of slope used) of all model components defined in the [serp](#), function with additional components listed below.

Value

coefficients	the matrix of coefficients, standard errors, z-values and p-values.
null.deviance	the deviance for the intercept only model.
null.logLik	the log-likelihood for the intercept only model.
penalty	list of penalization information obtained with slope set to "penalize".
expcoefs	the exponentiated coefficients.

See Also

[anova.serp](#), [predict.serp](#), [confint.serp](#), [vcov.serp](#), [errorMetrics](#)

Examples

```
library(serp)
m <- serp(rating ~ temp + contact, slope = "penalize",
         reverse = TRUE, link = "logit", tuneMethod = "user",
         lambda = 0, data = wine)
summary(m)
```

vcov.serp	<i>Variance covariance matrix for a fitted serp object</i>
-----------	--

Description

Provides the Variance covariance matrix of an object of class `serp`.

Usage

```
## S3 method for class 'serp'  
vcov(object, ...)
```

Arguments

<code>object</code>	An object of class <code>serp</code> .
<code>...</code>	additional arguments.

Value

A variance covariance matrix of a fitted model.

See Also

[serp](#)
[serp](#), [anova.serp](#), [confint.serp](#), [errorMetrics](#)

Examples

```
library(serp)  
m <- serp(rating ~ temp + contact, slope = "parallel", link = "logit",  
          data = serp:wine)  
vcov(m)
```

wine	<i>Bitterness of wine dataset</i>
------	-----------------------------------

Description

The wine dataset adopted from Randall(1989), represents the outcome of a factorial experiment on factors determining the bitterness of wine. Two treatment factors (temperature and contact) with two levels each are provided, with the rating of wine taken on a continuous scale in the interval from 0 (none) to 100 (intense). These were subsequently grouped into five ordered categories ranging from 1 = 'least bitter' to 5 = 'most bitter'. Altogether, nine different judges assessed wine from two bottles and out of the four treatment conditions, making a total of 72 observations.

Usage

wine

Format

A data frame with 72 rows and 6 variables:

Value

response	scorings of wine bitterness on a 0—100 continuous scale.
rating	ordered factor with 5 levels; a grouped version of response.
contact	factor with two levels ("no" and "yes").
temp	temperature: factor with two levels.
judge	factor with nine levels.
bottle	factor with eight levels.

Source

Taken from Randall (1989).

References

Randall, J (1989). The analysis of sensory data by generalized linear model. *Biometrical Journal*, 31, 781–793. <https://doi.org/10.1002/bimj.4710310703>

Examples

```
## Not run:  
str(wine)  
head(wine)  
  
## End(Not run)
```

Index

* dataset

wine, 18

AIC.serp, 2, 4, 5, 8

anova.serp, 3, 6, 7, 9, 15, 17, 18

BIC.serp, 3, 4, 5, 8

coef.serp, 3, 4, 5, 8

coefficients.serp (coef.serp), 5

confint.serp, 4, 5, 7, 9, 15, 17, 18

errorMetrics, 4, 6, 6, 9, 15, 17, 18

logLik.serp, 3–5, 7

predict.serp, 8, 15, 17

print.errorMetrics, 9

print.serp, 10, 11

print.summary.serp, 10, 10

serp, 3–8, 10, 11, 11, 16–18

serp.control, 15

summary.serp, 9, 15, 17

vcov.serp, 4, 6, 7, 9, 15, 17, 18

wine, 18